
FED. SUP CLASS
5305



NOMINAL SIZE	D		2 (.086)	4 (.112)	6 (.138)	8 (.164)
THREADS PER INCH			64NF	48NF	40NF	36NF
BODY DIAMETER	D_e	Max	.0860	.1120	.1380	.1640
		Min	.0733	.0954	.1184	.1424
HEAD DIAMETER	A	Max	.167	.219	.270	.322
		Min	.155	.205	.256	.306
HEAD HEIGHT	H	Max	.053	.068	.082	.096
		Min	.045	.058	.072	.085
SLOT WIDTH	J	Max	.031	.039	.048	.054
		Min	.023	.031	.039	.045
SLOT DEPTH	T	Max	.033	.041	.050	.058
		Min	.023	.030	.038	.043
RADIUS ON HEAD	R_1	Nom	.035	.042	.046	.052
RADIUS UNDER HEAD	R	Max	.011	.015	.018	.020

LENGTH	L	Tolerance	Dash Number	Dash Number	Dash Number	Dash Number
THREADS SHALL EXTEND TO WITHIN 2 THREADS OF THE BEARING SURFACE OF THE HEAD, OR CLOSER IF PRACTICABLE.	1/8	+0 -1/32	1	11	24	39
	3/16		2	12	25	40
	1/4		3	13	26	41
	5/16		4	14	27	42
	3/8		5	15	28	43
	7/16		6	16	29	44
	1/2		7	17	30	45
	5/8		8	18	31	46
	3/4		9	19	32	47
	7/8		10	20	33	48
	1			21	34	49
	1-1/4	+0 -1/16		22	35	50
	1-1/2			23	36	51
	1-3/4				37	52
	2				38	53
Minimum Complete Thread Length of 1-3/4.	2-1/4	+0 -3/32				54
	2-1/2					55
	2-3/4					56
	3					57

Ⓐ CANCELLED
SEE SHEET 2

MATERIAL: Corrosion Resisting Steel, Specification QQ-S-763, 70,000 PSI minimum tensile strength, minimum elongation 16% in 2 inches.

FINISH: Passivated by immersion for a period of 20 minutes in a solution containing 15% (by weight) of nitric acid at a temperature of 70°F ± 5°, followed by a thorough rinse in hot water.

THREADS: The threads shall be in accordance with Screw-Thread Standards for Federal Services Handbook H-28.

NOTES: (1) Referenced documents of issue in effect on date of invitation for bids shall apply.
(2) In case of conflict with any referenced document, this standard will govern.
(3) The MS part number consists of the MS sheet number, plus the dash number. Example: MS 35234-1.
(4) All dimensions in inches.

Ⓐ For changes, see sheets 1 and 2.

APPROVED FEB 9, 1954 REVISED Ⓐ 12 DEC 63

NOTICE.—When Government drawings, specifications, or other data are used for any purpose other than in connection with a definitely related Government procurement operation, the United States Government thereby incurs no responsibility, nor any obligation whatsoever; and the fact that the Government may have formulated, furnished, or in any way supplied the said drawings, specifications, or other data is not to be regarded by implication or otherwise as in any manner licensing the holder or any other person or corporation, or conveying any rights or permission to manufacture, use, or sell any patented invention that may in any way be related thereto.

This military standard is approved by the Department of Defense and is mandatory on all activities. Selection for all new engineering and design applications and for repetitive use shall be made from this document.

P.A.	WC	TITLE	MILITARY STANDARD
Other Cust	Ships MOAMA	SCREW, MACHINE, PAN HEAD, SLOTTED, CORROSION RESISTING STEEL, PASSIVATED, NF-2A AND UNF-2A	MS 35234
PROCUREMENT SPECIFICATION FF-S-92		SUPERSEDES:	SHEET 1 OF 2

DD FORM 672-1 (Continued) PREVIOUS EDITIONS OF THIS FORM ARE OBSOLETE

Source: https://assist.dla.mil -- Downloaded: 20260-23117:12Z
Check the source to verify that this is the current version before use.

FED. SUP CLASS
5305

NOMINAL SIZE	D		10 (.190)	1/4	5/16	3/8
THREADS PER INCH			32NF	28UNF	24UNF	24UNF
BODY DIAMETER	D_e	Max	.1900	.2500	.3125	.3750
		Min	.1658	.2225	.2806	.3430
HEAD DIAMETER	A	Max	.373	.492	.615	.740
		Min	.357	.473	.594	.716
HEAD HEIGHT	H	Max	.110	.144	.178	.212
		Min	.099	.130	.162	.195
SLOT WIDTH	J	Max	.060	.075	.084	.094
		Min	.050	.064	.072	.081
SLOT DEPTH	T	Max	.067	.087	.109	.130
		Min	.050	.070	.092	.113
RADIUS ON HEAD	R_1	Nom	.061	.087	.099	.143
RADIUS UNDER HEAD	R	Max	.023	.026	.031	.031
LENGTH	L	Tolerance	Dash Number	Dash Number	Dash Number	Dash Number
THREADS SHALL EXTEND TO WITHIN 2 THREADS OF THE BEARING SURFACE OF THE HEAD, OR CLOSER IF PRACTICABLE.	1/8	+0 -1/32	58	Ⓐ CANCELLED SEE NOTE		
	3/16		59			
	1/4		60	76		
	5/16		61	77	92	
	3/8		62	78	93	
	7/16		63	79	94	107
	1/2		64	80	95	108
	5/8		65	81	96	109
	3/4		66	82	97	110
	7/8		67	83	98	111
	1		68	84	99	112
	1-1/4	+0 -1/16	69	85	100	113
	1-1/2		70	86	101	114
	1-3/4		71	87	102	115
	2		72	88	103	116
Minimum Complete Thread Length of 1-3/4.	2-1/4	+0 -3/32	73	89	104	117
	2-1/2		74	90	105	118
	2-3/4		75	91	106	119
	3					

NOTE: For illustration, material, finish, and other pertinent data, see sheet 1.

Ⓐ CANCELLED AFTER 12 Dec 63 USE MS51958 . INTERCHANGEABILITY RELATIONSHIP - MS51958 can replace the cancelled screws of the same size. The cancelled MS35234 cannot always replace MS51958 and should be used until existing stock is depleted. Then use only the superseding MS screws of the same size for design and replacement.

APPROVED FEB 9, 1954 REVISED Ⓐ FOR CHANGES SEE SHEETS 1 AND 2

NOTICE—When Government drawings, specifications, or other data are used for any purpose other than in connection with a definitely related Government procurement operation, the United States Government thereby incurs no responsibility, nor any obligation whatsoever; and the fact that the Government may have formulated, furnished, or in any way supplied the said drawings, specifications, or other data is not to be regarded by implication or otherwise as in any manner licensing the holder or any other person or corporation, or conveying any rights or permission to manufacture, use, or sell any patented invention that may in any way be related thereto.

This military standard is approved by the Department of Defense and is mandatory on all activities. Selection for all new engineering and design applications and for repetitive use shall be made from this document.

P.A. WC	TITLE	MILITARY STANDARD
Other Cust Ships MOAMA	SCREW, MACHINE, PAN HEAD, SLOTTED, CORROSION RESISTING STEEL, PASSIVATED, NF-2A AND UNF-2A	MS 35234
PROCUREMENT SPECIFICATION FF-S-92	SUPERSEDES:	SHEET 2 OF

DD FORM SEP 67 672-1 (Continuation) Previous editions of this form are obsolete.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T17:12Z
Check the source to verify that this is the current version before use.