

FED. SUP CLASS
4730





DETAIL OF BODY

DASH NO.	TUBE O.D.	A PIPE THREADS NPTF	B	C	D	E	F	G	H	J	K	L	M
1	1/8	1/8	5/16-24UNF-2A	7/32	3/32	.135 .139	13/64	1/8	9/32	3/16	7/16	7/8	1-3/16
2	3/16	1/8	3/8-24UNF-2A	7/32	1/8	.196 .200	1/4	5/32	9/32	3/16	7/16	7/8	1-7/32
3	1/4	1/8	1/2-20UNF-2A	21/64	13/64	.261 .265	19/64	13/64	13/32	3/16	1/2	1	1-13/32
4	5/16	1/8	9/16-18UNF-2A	21/64	13/64	.324 .328	19/64	13/64	13/32	3/16	5/8	1	1-3/8
5	1/4	1/4	1/2-20UNF-2A	21/64	13/64	.261 .265	19/64	13/64	13/32	13/64	5/8	1-5/32	1-9/16
6	5/16	1/4	9/16-18UNF-2A	21/64	13/64	.324 .328	19/64	13/64	13/32	13/64	5/8	1-1/4	1-5/8
7	3/8	1/4	5/8-18UNF-2A	23/64	9/32	.386 .390	19/64	13/64	7/16	9/32	11/16	1-1/4	1-11/16
8	1/2	1/4	3/4-16UNF-2A	11/32	27/64	.514 .518	5/16	13/64	7/16	9/32	3/4	1-1/4	1-25/32
9	1/2	3/8	3/4-16UNF-2A	11/32	27/64	.514 .518	5/16	13/64	7/16	27/64	3/4	1-1/4	1-25/32
10	5/8	3/8	15/16-16UN-2A	23/64	1/2	.641 .645	11/32	15/64	15/32	13/32	15/16	1-11/32	1-7/8
11	3/8	1/2	5/8-18UNF-2A	23/64	9/32	.386 .390	19/64	13/64	7/16	1/2	7/8	1-19/32	2-1/32
12	5/8	1/2	15/16-16UN-2A	23/64	1/2	.641 .645	11/32	15/64	15/32	1/2	15/16	1-5/8	2-5/32
13	3/4	1/2	1-1/16-16UN-2A	23/64	21/32	.766 .770	11/32	13/64	15/32	1/2	1-1/8	1-39/64	2-13/64
14	3/4	3/4	1-1/16-16UN-2A	23/64	21/32	.776 .770	11/32	13/64	15/32	21/32	1-1/8	1-5/8	2-7/32
15	7/8	3/4	1-3/16-16UN-2A	23/64	23/32	.891 .895	11/32	13/64	15/32	21/32	1-1/4	1-5/8	2-7/32
16	1	3/4	1-5/16-16UN-2A	23/64	7/8	1.016 1.020	13/32	13/64	15/32	21/32	1-3/8	1-5/8	2-7/32
17	7/8	1	1-3/16-16UN-2A	23/64	23/32	.891 .895	11/32	13/64	15/32	23/32	1-3/8	1-13/16	2-13/32
18	1	1	1-5/16-16UN-2A	23/64	7/8	1.016 1.020	13/32	13/64	15/32	7/8	1-3/8	1-13/16	2-13/32
19	1-1/4	1	1-5/8-16UN-2A	7/16	1-3/32	1.270 1.274	13/32	13/64	35/64	29/32	1-5/8	1-7/8	2-9/16
20	1-1/4	1-1/4	1-5/8-16UN-2A	7/16	1-3/32	1.270 1.274	13/32	13/64	35/64	1-3/32	1-11/32	1-29/32	2-17/32
21	1-1/2	1-1/2	1-7/8-16UN-2A	15/32	1-11/32	1.520 1.524	31/64	13/64	35/64	1-11/32	2	2	2-11/16

Ⓔ **INACTIVE** FOR NEW DESIGN. USE FOR MAINTENANCE PURPOSES ONLY. FOR NEW DESIGN USE MS51819.

APPROVED 24 APR 62 REVISED (A) 29 DEC 67 (B) 10 OCT 74 (C) 5 FEB 75 (D) 15 MAY 77 (E) 26 FEB 82

This military standard is approved for use by the US Army Tank-Automotive Command, Department of the Army, and is available for use by all Departments and Agencies of the Department of Defense.

P.A. ARMY-AT Other Cust	TITLE ADAPTERS, STRAIGHT, PIPE TO TUBE - SAFETY SLEEVE COMPRESSION TYPE, MALE PIPE END	MILITARY STANDARD MS39206(AT)
PROCUREMENT SPECIFICATION NONE	SUPERSEDES	SHEET 1 OF 2

DD FORM 672-1 (Limited coordination) PREVIOUS EDITIONS OF THIS FORM ARE OBSOLETE 4730-A219

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T17:48Z
Check the source to verify that this is the current version before use.

FED. SUP CLASS
4730

MATERIAL: STEEL, IN ACCORDANCE WITH FEDERAL STANDARD NO. 66, AISI-C-1112, C-1113, C-1117, C-1118 OR C-1137.

FINISH: CADMIUM PLATED, SPECIFICATION QQ-P-416, TYPE II, CLASS 3.

TOLERANCE: UNLESS OTHERWISE SPECIFIED, DECIMALS ± .005, FRACTIONS ± 1/64, DEGREES ± 2°.

THREADS: THE THREADS SHALL BE IN ACCORDANCE WITH MIL-STD-H28/2/8.

DIMENSIONS: UNLESS OTHERWISE SPECIFIED, DIMENSIONS ARE IN INCHES.

PART NUMBER: THE PART NUMBER CONSISTS OF MS NUMBER PLUS THE DASH NUMBER, EXAMPLE: MS 39206-1.
THE PART NUMBER COVERS THE COMPLETE ITEM (WITH NUT AND SLEEVE).

NOTES: 1. REFERENCED DOCUMENTS SHALL BE OF THE ISSUE IN EFFECT ON DATE OF INVITATIONS FOR BID.

2. THIS ILLUSTRATION IS FOR IDENTIFICATION AND IS NOT INTENDED TO RESTRICT DESIGNS OR SHAPES NOT DIMENSIONED.

INACTIVE—SEE SHEET 1.

APPROVED 24 APRIL 1962 REVISED

P.A. Other Cust	TITLE ADAPTERS, STRAIGHT, PIPE TO TUBE - SAFETY SLEEVE COMPRESSION TYPE, MALE PIPE END	MILITARY STANDARD MS39206(AT)
PROCUREMENT SPECIFICATION NONE	SUPERSEDES	SHEET 2 OF 2

DD FORM 1 SEP 67 672-1 (LIMITED COORDINATION)

PREVIOUS EDITIONS OF THIS FORM ARE OBSOLETE

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T17:48Z
Check the source to verify that this is the current version before use.

NOTICE
OF VALIDATION

MS39206E(AT)
NOTICE 1
17 September 1987

MILITARY SPECIFICATION

ADAPTERS, STRAIGHT, PIPE TO TUBE-SAFETY SLEEVE COMPRESSION TYPE, MALE PIPE END

MS39206E(AT), dated 26 February 1982, has been reviewed and determined to be valid for maintenance purposes only.

Custodian:
Army-AT

Preparing activity:
Army - AT

FSC 4730

AMSC N/A

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 202610-23T17:48Z
Check the source to verify that this is the current version before use.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T17:48Z
Check the source to verify that this is the current version before use.