INCH-POUND
MIL-M-38510/172B
AMENDMENT 2
23 APRIL 1999
SUPERSEDING
AMENDMENT 1
31 AUGUST 1988

MILITARY SPECIFICATION

MICROCIRCUITS, DIGITAL, CMOS, AND-OR-INVERT, EXCLUSIVE-OR, EXCLUSIVE-NOR GATES, MONOLITHIC SILICON, POSITIVE LOGIC

Inactive for new design after 9 August 1996

This amendment forms a part of MIL-M-38510/172B, dated 30 April 1984, and is approved for use by all Departments and Agencies of the Department of Defense.

PAGE 1

1.2.3, add new case outline as follows:

"T F-2A (14-lead, .390" x .260" x .115"), flat package".

PAGE 4

4.4.1, add new paragraph as follows:

"f. Subgroups 9 and 11 shall be measured only for initial qualification and after process or design changes which may affect dynamic performance."

PAGE 6

* TABLE I, output high (source) current test, (I_{OH2}), device type 03, under the conditions column; Delete "Any one input = V_{SS}" and substitute "Any one input = V_{DD}".

PAGE 7

* TABLE I, input leakage current test, (I_{IH}), max limits column, device type 01, delete "45" and substitute "100"; (I_{IL}), max limits column, device type 01, delete "-45" and substitute "-100".

* TABLE I, transition times, low to high test, symbol column; Delete "t_{TLL}" and substitute "t_{TLH}".

PAGE 8

TABLE II, Line no. 8, class B device, table III subgroups: Delete "1*2,3,9" and substitute "1*,2,3,9,10,11". Also, Line no. 12: Delete in its entirety.

FSC 5962

AMSC N/A
DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T13:43Z
Check the source to verify that this is the current version before use.

PAGE 9

FIGURE 1: Delete “Cases A, C, D, X, and Y” and substitute “Cases A, C, D, T, X, and Y” (4 places).

PAGE 11

FIGURE 3, note 3: first sentence, delete and substitute the following: “Except for V_{DD} and V_{SS}, terminals shall be connected through resistors which value is 2 kΩ to 47 kΩ.”

PAGE 12

FIGURE 4, note 1: first sentence, delete and substitute the following: “Except for V_{DD} and V_{SS}, terminals shall be connected through resistors which value is 2 kΩ to 47 kΩ.”

PAGE 14

FIGURE 5: input waveform: Delete “$t_{TLH(1)}$” and $t_{THL(1)}$” and substitute “t_r” and “t_f” respectively. Also, under Dynamic test waveforms notes: Delete “$t_{THL(1)}$” = $t_{TLH(1)}$ = 20 ±2 ns” and substitute “$t_r + t_f \leq 20$ ns”.

PAGES 15 THROUGH 34

TABLE III, case outline column: Delete “A, C, D, X, Y” and substitute “A, C, D, T, X, Y”.

PAGE 26

* TABLE III, test number 73, subgroup 1, max limit column: Delete “8” and substitute “800”.

* TABLE III, test numbers 74 through 81: subgroup 1, max limit column: Delete “1” and substitute “100”; subgroup 2, max limit column: Delete “45” and substitute “100”.

* TABLE III, test number 82, subgroup 1, max limit column: Delete “-8” and substitute “-800”.

* TABLE III, test numbers 83 through 90, subgroup 1, max limit column: Delete “-1” and substitute “-100”; subgroup 2, max limit column: Delete “-45” and substitute “-100”.

PAGE 35

4.4.3c: Delete in its entirety.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T13:43Z
Check the source to verify that this is the current version before use.

The margins of this amendment are marked with an asterisk to indicate where changes (additions, modifications, corrections, deletions) from the previous amendment were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous amendment.

CONCLUDING MATERIAL

Custodians:
Army - CR
Navy - EC
Air Force - 11
NASA – NA
DLA - CC

Preparing activity:
DLA - CC

Review activities:
Navy - AS, CG, MC, OS, SH
Army - AR, MI, SM
Air Force - 19, 99

(Project 5962-1844)

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T13:43Z
Check the source to verify that this is the current version before use.