MIL-C-22770H(OS)
17 August 1977
Superseding
MIL-C-22770G(OS)
25 January 1974

MILITARY SPECIFICATION

COILS, WIRE

This specification is approved for use by the Naval Sea Systems Command(OS), Department of the Navy, and is available for use by all Departments and Agencies of the Department of Defense.

1. SCOPE AND CLASSIFICATION

1.1 Scope. This specification establishes the requirements for wire coils. The wire coils are hollow core self-supporting coils which are layer wound with a continuous unspliced length of insulated singe-conductor wire, and so packaged as to achieve mechanical protection under the environmental conditions specified herein. The wire coils are designed to permit axial payout of the wire from the center of the coil at rates up to the maximum specified.

1.2 Classification. The wire coils shall be of the following types, as specified by the contract or purchase order (see 6.2):

Type	Use	Coil Documentation	Shipping Condition
I	Submarine (10K yds)	Dwg 3014059 (DL 3014059)	Dwg 3014055
IIa	Torpedo Mk 37	Dwg 2194170 (LD 539996)	Dwg 2643987
IIb	Torpedo Mk 37	Dwg 3245474 (PL 3245474)	Dwg 2643987
IIIa	Submarine (3K yds)	Dwg 2194168 (LD 539997)	Dwg 2643986
IIIb	Submarine (3K yds)	Dwg 3245473 (PL 3245473)	Dwg 2643986

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: Commanding Officer, Naval Ordnance Station, Standardization Division (Code 611), Indian Head, MD 20640 by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

FSC 1355

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T13:56Z
Check the source to verify that this is the current version before use.

2. APPLICABLE DOCUMENTS

2.1 Issues of documents. The following documents of the issue in effect on the date of invitation for bids or request for proposal form a part of this specification to the extent specified herein.

SPECIFICATIONS

Military

MIL-P-116	Preservation, Methods of
MIL-S-901	Shockproof Equipment, Class HI (High-Impact), Shipboard Application, Tests for (Navy)
MIL-P-15011	Pallets, Material Handling, Wood, Post Construction, 4 way entry
MIL-T-18404	Torpedoes, Environmental Requirements, General Specification for
MIL-E-22403	Environmental Requirements and Tests (For Torpedo Mark 45 Mod 0 and Mod 1 Components and Assemblies)
MIL-E-82590	Environmental Requirements and Tests (For Torpedo Mark 37 Componenets and Accessories)

Federal

NN-P-71	Pallets, Material Handling, Wood, Stringer Construction, 2-Way and 4-Way (partial)
QQ-S-781	Strapping, Steel, Flat and Seals

STANDARDS

Military

MIL-STD-129	Marking for Shipment and Storage
MIL-STD-167	Mechanical Vibration of Shipboard Equipment
MIL-STD-1320/1	Truckloading of Hazardous Materials-Palletized Loads - Single Row Pattern

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T13:56Z
Check the source to verify that this is the current version before use.

MIL-STD-1320/2	Truckloading of Hazardous Materials Palletized Loads - Double Row Pattern
MIL-STD-1325/100	Railcar Loading of Hazardous Materials Typical Carloading Procedures for Palletized Unit Loads

DRAWINGS

Naval Sea Systems Command (Code Ident 10001)

Dwg 439819	48 x 48 Wood pallet Mk 1 Mod 0
LD 539996	Coil, Wire, and all Parts, Subassemblies, and Documents Listed thereon
LD 539997	Coil, Wire, and all Parts, Subassemblies, and Documents Listed thereon
LD 1874055	Test Equipment Type III
Dwg 1874070	Indicator, Continuity
Dwg 1874073	Fixture, Test
Dwg 1874074	Fixture, Test
Dwg 2194168	Coil, Wire, Submarine, Shipboard
Dwg 2194170	Coil, Wire, Torpedo
Dwg 2643986	Shipping Condition, Coil, Wire (Shipboard)
Dwg 2643987	Shipping Condition, Coil, Wire (Torpedo)
Dwg 2882731	Test Fixture Assembly (Shock and Vibration)
Dwg 3014055	Shipping Condition, Coil, Wire (Shipboard)
Dwg 3014059	Coil, Wire, Submarine Shipboard
DL 3014059	Coil, Wire, Submarine Shipboard
Dwg 3029892	Test Equipment
Dwg 3245473	Coil, Wire, Submarine Shipboard
PL 3245473	Coil, Wire, Submarine Shipboard

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T13:56Z
Check the source to verify that this is the current version before use.

Dwg 3245474	Coil, Wire, Torpedo
PL 3245474	Coil, Wire, Torpedo
Dwg 3245921	Test Equipment Type II

(Copies of specifications, standards, drawings, and publications required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer).

3. REQUIREMENTS

3.1 General requirements

3.1.1 Preproduction samples. Unless otherwise specified in the contract or order, preproduction samples of the wire coil shall be manufactured using the methods and procedures proposed for the production. The sample will be tested as specified in Section 4 herein and is for the purpose of determining, prior to production, that the contractor's production methods are capable of yielding items that comply with the technical requirements of the contract (see 4.3.1).

3.1.2 Materials. All materials and purchased parts entering into the final assembly of the wire coil shall conform to the detailed requirements indicated on the applicable drawings and specifications.

3.1.3 Finishes, coatings, and construction. Finishes, coatings, and construction for the wire coil shall be in accordance with the applicable drawings, specifications, and publications.

3.1.4 Marking. Consecutive serial numbers shall be assigned for all units of each type of wire coil procured under this specification. Requests for serial numbers for each type shall be directed to the Naval Underwater Systems Center, Newport, Rhode Island 02840.

3.1.5 Conflicting requirements. In the event of conflict between the documents referenced herein and the contents of this specification, the contents of this specification shall apply.

3.2 Definitions

3.2.1 Test axes. The vibration and shock test axes for Wire Coil Types II and III are the longitudinal axis and any pair of perpendicular transverse axes. The test axes for Wire Coil Type I are defined by the test fixture.

3.3 Performance requirements and product characteristics. The wire coils shall meet the following performance requirements and product characteristics:

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T13:56Z
Check the source to verify that this is the current version before use.

3.3.1 Dimensions. The dimensions of the wire coil shall conform to the applicable drawings indicated below.

Type I	Dwg 3014059
Type II	Dwgs 2194170, 3245474
Type III	Dwgs 2194168, 3245473

3.3.2 Electrical continuity. The resistance of the conductor of the wire shall be no greater than the following values when corrected to 20 degrees C (68 degrees F):

Type I	850 ohms
Type II	1300 ohms
Type III	290 ohms

3.3.3 Insulation resistance. The wire coils shall have a minimum insulation resistance as follows:

Type I	500 megohms
Type II	400 megohms
Type III	1800 megohms

3.3.3.1 Wire Coil Types I, II, and III shall show no loss of continuity at any increment of hydrostatic pressure from zero to 525 psig and return to zero psig..

3.3.4 Payout characteristics. The wire coil shall pay out at the following speeds without damage to the conductor or insulation:

Type I	40 feet per second
Type IIa	40 feet per second
Type IIb	40 feet per second
Type IIIa, IIIb	20 feet per second

3.3.4.1 Wire breakage. The wire coil shall pay out lengths of wire equal to at least 90 percent of the nominal wire lengths specified by the applicable drawings of 3.3.1 without damage to the conductor or insulator. The wire shall break in such a manner that no tension is exerted on the free-standing end of the wire.

3.4 Environmental requirements. The wire shall meet the performance requirements and product characteristics of this specification during and after any of the environmental conditions specified as follows:

3.4.1 Vibration. The wire coil shall meet the following vibration requirements:

Types I and IIIa, IIIb	Environmental vibration (Type I) requirements of MIL-STD-167 (SHIPS)
Types IIa, IIb	Vibration requirements of MIL-E-82590 (Vibration, nonoperating and Vibration, operating)

Source: https://assist.dla.mil -- Downloaded: 202640-19T13:56Z
Check the source to verify that this is the currentversion before use.

3.4.2 Shock. The wire coil shall meet the following shock requirements:

Types I and IIIa, IIIb	Shock requirements for light weight equipment as specified by MIL-S-901, Grade A, Class I, Type B
Types IIa, IIb	Shock requirements of MIL-E-22403 modified to 30g ± 5g peak magnitude.

3.4.3 Acceleration. Wire Coil Types IIa and IIb shall withstand an acceleration of 15 g for a period of 0.2 seconds along the longitudinal axis without degradation of performance. There is no acceleration requirement for Wire Coil Types I and IIIa, IIIb.

3.4.4 Temperature, nonoperating. The wire coils shall withstand temperatures between minus 65 degrees F and plus 160 degrees F (minus 54 degrees C and plus 71 degrees C) without degradation of performance.

3.4.5 Temperature, operating condition. The wire coils shall be capable of operating over the temperature range of plus 30 degrees F to plus 95 degrees F (minus 1 degree C to plus 35 degrees C).

3.4.6 Marine environment. The wire coils shall withstand immersion in seawater or in a 2 percent saline solution without degradation of performance.

3.4.7 Tropical environment. The wire coil shall withstand the tropical environments specified in MIL-T-18404 without degradation of performance.

3.5 Workmanship. Wire coils, including all parts, shall be constructed and finished in a manner to ensure compliance with all requirements of this specification. Particular attention shall be paid to freedom of parts from burrs and sharp edges.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract, the contractor is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein. unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.2 Classification of inspections. Inspection of the wire coils shall be classified as follows:

(a) Preproduction inspection (paragraph 4.6)

(b) Periodic production inspection (paragraph 4.6)

(c) Quality conformance inspection (paragraph 4.7)

4.3 Sampling

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T13:56Z
Check the source to verify that this is the current version before use.

4.3.1 Preproduction sample. A preproduction sample of each type of wire coil specified in the contract or order shall consist of the following quantities:

Types I, IIb, IIIb	6
Types IIa and IIIa	6 of each, as applicable

Acceptance of the preproduction sample shall be based on no defects in the sample. Further production of the wire coils by the supplier prior to the approval of the preproduction sample shall be at the supplier's risk.

4.3.2 Periodic production sampling. Periodic production samples shall be selected from units that have satisfactorily passed the quality conformance inspections of 4.7. Periodic production sampling shall be as follows:

Step 1 - Upon the initiation of production, randomly select one unit from every 10 units. Upon satisfactory acceptance of samples selected from three consecutive groups of 10, shift to Step 2.

Step 2 - Randomly select one unit from every 25 units. Continue with Step 2 for the balance of the contract or until a defective unit is found or until a significant change in manufacturing methods or materials is introduced (see 4.3.2.2).

4.3.2.1 Defective unit. When a defective unit is found in any test sample, acceptance of all units on hand of similar type from the lot in which the defect is found shall be withheld. Return to Step 1 on the production from the winding maching which produced the defective sample when test results exhibit a failure. Acceptance of any lots produced in the intervening period is dependent on the test results of the periodic production samples for these lots.

4.3.2.2 Production change. Whenever a significant change in manufacturing, materials, or methods is introduced which destroys the homogeneity of the production run, return to Step 1 and proceed as indicated. Examples of significant changes in manufacturing, materials, or methods are as follows:

(a) Procurement of wire from a different vendor.

(b) Use of a different winding machine (whether or not it is considered "identical").

(c) Interruption of the production line for more than two weeks.

(d) Use of a winding machine operator who has not produced at least three satisfactory coils within the preceding six months.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T13:56Z
Check the source to verify that this is the current version before use.

4.3.3 Lot size. All units of a single lot shall be made to the same design, with the same material and manufacturing techniques, and shall be part of one continuous production run. A lot is also considered to be units of similar type manufactured on the same winding machine during a homogeneous production run.

4.3.4 Quality conformance sampling. Each wire coil delivered shall be subjected to quality conformance testing (100 percent inspection). Defective units shall be rejected.

4.4 Test conditions. Unless otherwise specified, the wire coil shall be subjected to tests under the following conditions:

4.4.1 Temperature. Plus 65 degrees F (plus 18 degrees C) to plus 95 degrees F (plus 35 degrees C).

4.4.2 Altitude. Normal ground atmospheric pressure.

4.4.3 Vibration. None.

4.4.4 Humidity. Room ambient 95 percent relative maximum.

4.5 Test equipment. The following items of test equipment are required to perform the tests set forth in this specification:

4.5.1 Payout equipment. The equipment for testing the payout capability of the wire coil shall conform to the following drawings:

Type I	Dwgs 1874070, 1874055
Type IIa, IIb	Dwgs 1874070, 3245921
Type IIIa, IIIb	Dwgs 1874055, 1874070, 3029892

These equipments shall provide the following features:

(a) Wire payout speeds to 40 feet per second.

(b) Insulation resistance during payout.

(c) Wire continuity during payout.

(d) Specific payout tube geometry.

In addition , the test equipment shall provide for soaking the wire coil in water during payout over a temperature range of plus 30 degrees F to plus 95 degrees F.

4.5.2 Pressure vessel. The pressure vessel shall be capable of subjecting any wire coil covered by this specification to a hydrostatic pressure of 550 pound per square inch gage (psig), and shall be equipped with a pressure gage to read pressure to an accuracy of 3 percent. Packing glands or a similar feature shall be provided for bringing leads outside of the vessel for measuring insulation resistance.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T13:56Z
Check the source to verify that this is the current version before use.

4.5.3 Ohmmeter capable of measuring wire resistance over the range of 0-2000 ohms with an accuracy of 3 percent.

4.5.4 Megohmmeter capable of measuring insulation resistance at 500 volts dc over the range of 0-2000 megohms with an accuracy of 3 percent.

4.6 Preproduction inspection and periodic production inspection. The preproduction and periodic production samples, after satisfactorily passing the quality conformance inspections detailed in 4.7, shall be subjected to the following tests and examinations:

4.6.1 Test series. Periodic production test samples selected in accordance with 4.3.2 shall be subjected to the test series of Table I in rotation. That is, the sample from the first lot shall be tested against Test Series I, the sample from the second lot shall be tested against Test Series II, and so forth. Coils from each winding machine shall be subjected to all test series in rotation.

TABLE I

Test Series I

Sequence	Test	Reference Paragraph
1	Vibration	4.6.2.1
2	Shock	4.6.2.2
3	Acceleration	4.6.2.3
4	Temperature, operating (low)	4.6.2.5.1

Test Series II

Sequence	Test	Reference Paragraph
1	Temperature, trans & storage (low)	4.6.2.4.1
2	Temperature, trans & storage (high)	4.6.2.4.2
3	Temperature, operating (high)	4.6.2.5.2

Test Series III

Sequence	Test	Reference Paragraph
1	Payout	4.6.2.8

Test Series IV

Sequence	Test	Reference Paragraph
1	Marine environment	4.6.2.6
2	Payout	4.6.2.8

Source: https://assist.dla.mil -- Downloaded: 20261O-19T13:56Z
Check the source to verify that this is the current version before use.

TABLE I (continued)

Test Series V

Sequence	Test	Reference Paragraph
1	Tropical environment	4.6.2.7
2	Payout	4.6.2.8

Test Series VI

Sequence	Test	Reference Paragraph
1	Hydrostatic pressure	4.6.2.9
2	Payout	4.6.2.8

4.6.2 Test procedure.

4.6.2.1 Vibration. The wire coil shall be mounted and tested in accordance with the following tabulation:

Dispenser	Mounting Fixture	Vibration Tests
Type I Type IIIa, IIIb	Drawing 2882731 Drawing 1874074	Environmental Vibration (Type I) tests of MIL-STD-167
Type IIa, IIb	Drawing 1874073	Vibration tests of MIL-E-82590 (Vibration, nonoperating and Vibration, operating)

4.6.2.2 Shock. The wire coil shall be mounted in accordance with 4.6.2.1 and tested in accordance with the following tabulation:

Dispenser	Shock Tests
Type I Type IIIa, IIIb	Shock tests for lightweight equipment as specified by MIL-S-901, Grade A, Class I, Type B
Type IIa, IIb	Shock tests of MIL-E-22403, modified to 30g ± 5g peak magnitude

4.6.2.3 Acceleration. Wire Coil Types IIa and IIb shall be mounted as specified in 4.6.2.1. When mounted on a suitable acceleration device, the wire coil shall be subjected to the acceleration specified in 3.4.3.

4.6.2.4 Temperature, nonoperating.

4.6.2.4.1 Low temperature. The wire coil shall be stored at minus 60 degrees F plus or minus 5 degrees F (minus 51.1 degrees C plus or minus 2.5 degrees C) for a period of 48 hours minimum to 56 hours maximum and then allowed to return to room ambient temperature.

Source: https://assist.dla.mil -- Downloaded: 202610-19T13:56Z
Check the source to verify that this is the current version before use.

4.6.2.4.2 High temperature. The wire coil shall be stored at plus 155 degrees F plus or minus 5 degrees F (plus 68 degrees C plus or minus 2.5 degrees C) for a period of 48 hours minimum to 56 hours maximum and then allowed to return to room ambient temperature.

4.6.2.5 Temperature, operating.

4.6.2.5.1 Low temperature. The wire coils shall be mounted in the wire payout equipment specified in 4.5 and immersed in seawater or a 2 percent saline solution maintained at a temperature of plus 32 degrees F plus or minus 2 degrees F (0 degrees C plus or minus 1 degree C) for at least 24 hours. (The water shall not be frozen). While still immersed, the wire coil shall be subjected to the continuity, insulation resistance, and payout tests of 4.7.1.2, 4.7.1.3, and 4.6.2.8.

4.6.2.5.2 High temperature. The wire coil shall be tested as in 4.6.2.5.1, except that the water temperature shall be maintained at plus 90 degrees F plus or minus 5 degrees F (plus 35 degrees C plus or minus 2.5 degrees C).

4.6.2.6 Marine environment. The wire coils shall be immersed in natural seawater, or a 2 percent saline solution at room temperature, for 18 plus or minus 2 hours and removed for a period of 6 plus or minus 1 hours. This constitutes one cycle. The sequence shall be repeated for 30 cycles. At the conclusion of this procedure, the coil shall be examined for damage and obscured markings.

4.6.2.7 Tropical environment. The wire coil shall be subjected to the tropical environment specified in 3.4.7. At the conclusion of this procedure, the coil shall be examined for damage and obscured markings.

4.6.2.8 Payout. The wire coil shall be mounted in the applicable payout equipment of 4.5.1 and the receptacle of the payout equipment shall be filled with seawater to completely immerse the wire coil. During payout the wire shall be monitored continuously, using the equipment of 4.5.1.

4.6.2.9 Insulation resistance under pressure. Wire Coil Types I, II, and III, as required by 4.6.1, shall be tested using a megohmmeter in accordance with 4.5.4. The wire coil shall be submerged in tap water containing a 0.5 percent solution of wetting agent, such as Aerosol, in the pressure vessel of 4.5.2 and pressurized from zero to 525 plus or minus 25 psig in less than 10 minutes. The coil shall be kept at this pressure for at least 30 minutes. At the conclusion of this 30 minute period, and while still under pressure, the insulation resistance shall be measured between the wire center conductor, joined at the standing and payout ends, and the pressure vessel. Reduce the pressure to 0 psig and, while the coil is still submerged, again check the insulation resistance. The wire coil shall be continuously monitored (using the ohmmeter of 4.5.3) for any loss of continuity during the entire cycle of increase and decrease of hydrostatic pressure.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T13:56Z
Check the source to verify that this is the current version before use.

4.7 Quality conformance inspection. Each wire coil delivered under contract shall be subjected to the following tests and examinations. Failure to meet any requirement specified herein shall be considered cause for rejection.

4.7.1 Test procedures.

4.7.1.1 Physical dimensions. Each wire coil shall be checked to determine its physical dimensions.

4.7.1.2 Electrical continuity. Measure the resistance of the wire coil with an ohmmeter in accordance with 4.5.3 and 3.3.2.

4.7.1.3 Insulation resistance in air. Wire Coil Types I, IIb, and IIIb shall be tested using the megohmmeter of 4.5.4 in accordance with 3.3.3. The insulation resistance shall be measured dry at atmospheric pressure between the wire center conductor joined at the standing and payout ends, and the electrically conductive material extruded onto the wire.

4.7.1.4 Packaging and marking. Examine the packaged wire coil to ensure compliance with preservation, packaging, packing, and marking requirements of Section 5.

5. PACKAGING

5.1 Preservation-packaging. Preservation-packaging shall be as specified herein.

5.1.1 Cleaning. Coils shall be cleaned in accordance with MIL-P-116, process C-1.

5.1.1.1 Drying. Coils shall be dried in accordance with MIL-P-116.

5.1.1.2 Preservation application. Preservative shall not be used unless otherwise specified.

5.1.1.3 Unit packaging. Unless otherwise specified (see 6.2) wire coil shall be packaged in accordance with MIL-P-116 using method III.

5.2.1 Packing. Unless otherwise specified, Type I wire coil shall be individually packed in accordance with drawing 3014055, Type IIa, IIb in accordance with drawing 2643987 and Type IIIa, IIIb in accordance with drawing 2643986. All wire leads shall be maintained in the configuration prescribed in 3.3.4.1 without damage to the coil.

5.3 Palletization.

5.3.1 Type I. Twenty seven shipping containers packed as described in 5.2.1 shall be stacked on a pallet fabricated in accordance with MIL-P-15011 or NN-P-71 with "X" dimension of 40" and a "Y" dimension of 48".

Source: https://assist.dla.mil -- Downloaded: 202640-19T13:56Z
Check the source to verify that this is the currentversion before use.

Six 3/4 by 0.020 inch flat steel straps in accordance with QQ-S-781, type I, finish A shall be used to secure packs to pallet. The palletizing pattern shall consist of three rows of three shipping containers stacked two layers high.

5.3.1.1 Type IIa, IIb. Eighteen shipping containers packed as described in 5.2.1 shall be stacked two layers high on a pallet fabricated in accordance with drawing 439819 with an "X" dimension of 48 inches and a "Y" dimension of 48 inches. Six 3/4 by 0.020 inch flat steel straps in accordance with QQ-S-781, type I, finish A shall be used to secure packs to pallet. The palletizing pattern shall consist of three rows of three shipping containers stacked two layers high.

5.3.1.2 Type IIIa, IIIb. Fourty eight shipping containers packed as described in 5.2.1 shall be stacked on a pallet fabricated in accordance with drawing 439819 with an "X" dimension of 48 inches and a "Y" dimension of 48 inches". Eight 3/4 by 0.020 inch flat steel straps in accordance with QQ-S-781, type I, finish A shall be used to secure packs to pallets. The palletizing pattern shall consist of four rows of four shipping containers stacked three layers high.

5.3.2 Pallet size. Pallet quantities less than 40 cubic feet need not be palletized. Palletized loads shall be uniform in size and quantities to the greatest extent practicable.

5.4 Marking. Each container shall be marked with the serial or lot number of the unit it contains. In addition to special marking indicated on drawing or required by contract, unit packages, palletized loads and unpalletized loads shall be marked in accordance with MIL-STD-129 (see 6.2).

5.5 Loading.

5.5.1 Railcar. Palletized unit loads as described in 5.3.1, 5.3.1.1 and 5.3.1.2 shall be loaded and secured in accordance with MIL-STD-1325/100.

5.5.2 Truck or trailer. Palletized unit loads as described in 5.3.1, 5.3.1.1 and 5.3.1.2 shall be loaded and secured in accordance with MIL-STD-1320/1 or MIL-STD-1320/2 depending on the number of palletized loads to be loaded.

6. NOTES AND CONCLUDING MATERIAL

6.1 Intended use. The wire coils are intended for use with various Marks and Mods of torpedoes and torpedo-related equipment.

6.2 Ordering data.

6.2.1 Procurement requirements. The contract or order should specify the following:

(a) The specific title, number, and date of this specification.

(b) The type coil required (see 1.2).

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T13:56Z
Check the source to verify that this is the current version before use.

(c) Exceptions to this specification, applicable drawings, and other documents.

(d) Serial numbers to be used.

(e) That all additional samples required because of failure of any unit(s) to pass prescribed periodic production inspections shall be provided and inspected at the expense of the supplier.

(f) The quantity of coils required. Insofar as possible, the contract should be in even multiples of the palletized unit load quantity. Shipping destinations should be similarly tailored.

6.2.2 Changes from previous issue. Asterisks are not used in this revision to identify changes with respect to the previous issue, due to the extensiveness of the changes.

Custodian
Navy - OS

Preparing Activity
Navy - OS

Project No. 1355-N389

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T13:56Z
Check the source to verify that this is the current version before use.

FOLD

POSTAGE AND FEES PAID
DoD 316

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

Commanding Officer
Naval Ordnance Station (611)
Standardization Division
Indian Head, MD 20640

FOLD

Source: https://assist.dla.mil -- Downloaded: 202640-19T13:56Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

INSTRUCTIONS: This form is provided to solicit beneficial comments which may improve this document and enhance its use. DoD contractors, government activities, manufacturers, vendors, or other prospective users of the document are invited to submit comments to the government. Fold on lines on reverse side, staple in corner, and send to preparing activity. Attach any pertinent data which may be of use in improving this document. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity. A response will be provided to the submitter, when name and address is provided, within 30 days indicating that the 1426 was received and when any appropriate action on it will be completed.

NOTE: This form shall not be used to submit requests for waivers, deviations or clarification of specification requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements.

DOCUMENT IDENTIFIER *(Number)* AND TITLE

MIL-C-22770H(OS), Coils, Wire

NAME OF ORGANIZATION AND ADDRESS OF SUBMITTER

☐ VENDOR ☐ USER ☐ MANUFACTURER

1. ☐ HAS ANY PART OF THE DOCUMENT CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE? ☐ IS ANY PART OF IT TOO RIGID, RESTRICTIVE, LOOSE OR AMBIGUOUS? PLEASE EXPLAIN BELOW.

A. GIVE PARAGRAPH NUMBER AND WORDING

B. RECOMMENDED WORDING CHANGE

C. REASON FOR RECOMMENDED CHANGE(S)

2. REMARKS

SUBMITTED BY *(Printed or typed name and address — Optional)*

TELEPHONE NO.

DATE

DD FORM 1 OCT 76 1426

EDITION OF 1 JAN 72 WILL BE USED UNTIL EXHAUSTED.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T13:56Z
Check the source to verify that this is the current version before use.