MILITARY SPECIFICATION

LAUNCHER, WEAPONS, AIRBORNE AND ASSOCIATED EQUIPMENT
GENERAL SPECIFICATION FOR

This amendment forms a part of Military Specification MIL-L-22769A(AS), dated 15 January 1962, and is approved for use by the Naval Air Systems Command, Department of the Navy, and is available for use by all Departments and Agencies of the Department of Defense.

PAGE 1

In upper right hand corner, delete "(WEP)" and substitute: "(AS)".

Under title, delete preamble in its entirety and substitute: "This specification is approved for use by the Naval Air Systems Command, Department of the Navy, and is available for use by all Departments and Agencies of the Department of Defense."

2.1 under SPECIFICATIONS, add "DOD-D-1000 Drawings, Engineering and Associated Lists."

add "MIL-C-5015 Connectors, Electrical, Circular Threaded, AN Type, General Specification for."

delete "MIL-P-7936" and its title.

PAGE 2

2.1, under SPECIFICATIONS, delete "MIL-R-22973" and its title.
delete "MIL-R-23094" and its title.
delete "MIL-D-70327" and its title.

2.1, under STANDARDS, add "MIL-STD-794 Parts and Equipment, Procedures for Packaging of."

add "MIL-STD-875 Type Designation System for Aeronautical and Support Equipment."

add "MIL-STD-889 Dissimilar Metals."

delete "MS25245" and its title.

delete "MS33586" and its title.

2.1, delete "PUBLICATIONS", "AIR FORCE - NAVY Aeronautical Bulletin" and "No. 440" and "Type Designation System for Aeronautical and Support Equipment."

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T13:56Z
Check the source to verify that this is the current version before use.

FSC 10GP

PAGE 3

3.1.1, last line, delete "by Drawing MS33586" and substitute "in MIL-STD-889."

3.2.1.2 delete "Input power connections - Electrical input power connections shall be in accordance with Drawing MS25245" and substitute "Input power connector - Unless otherwise specified, the electrical input power connector shall be in accordance with MIL-C-5015."

PAGE 6

3.7, line 4, delete "ANA Bulletin No. 440" and substitute "MIL-STD-875."

3.8, last line, delete "Specification MIL-D-70327" and substitute "DOD-D-1000."

PAGE 9

4.5.2, delete first sentence in its entirety and substitute "Unless otherwise specified, sampling tests shall be performed at a temperature of 25° +5°C (68°F to 86°F) and at an input voltage within the range specified for the launching equipment."

PAGE 10

4.6.4, delete last sentence in its entirety and substitute "Unless otherwise specified, total operating life test shall be performed at a temperature of 25° +5°C (68°F to 86°F) and at an input voltage within the range specified for the launching equipment."

PAGE 11

5.1, line 3, delete "Specification MIL-P-7936" and subsitute "MIL-STD-794."

PAGE 13

6.5.3, delete "6.5.3 Mean-Time-Between-Failures" and paragraph in its entirety.

Preparing activity
Navy - AS
(Project No. 10GP-N003)

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T13:56Z
Check the source to verify that this is the current version before use.