MIL-P-22798(CG)
AMENDMENT 2
20 February 1962
SUPERSEDING
AMENDMENT 1
21 April 1961

MILITARY SPECIFICATION

PUMP, CENTRIFUGAL, GASOLINE-ENGINE-DRIVEN, 60 G.P.M.

This amendment forms a part of Military Specification MIL-P-22798(CG), 10 January 1961.

Page 1, under the specification symbol and approval date, add the following supersession data:

"Superseding
U. S. C. G. ENE P. D. # 26-58
16 December 1957"

Page 1, above the title, delete the word "PROPOSED".

Page 2, paragraph 3.7.2: Delete and substitute:

"3.7.2 Suction and discharge connections.- The suction inlet connection shall have a 2-1/2 inch male Navy Standard hose thread, 7-1/2 threads per inch. The discharge outlet shall have a bronze ball-type discharge valve with a 1-1/2 inch male Navy Standard hose thread on the discharge end, 11-1/2 threads per inch."

Page 2, paragraph 3.7.5: Delete and substitute:

"3.7.5 Shaft seal.- The pump casing shall contain an oversize stuffing box fitted with a split bronze packing gland to take up the packing."

Preparing Activity:
U.S. Coast Guard

FSC 4320

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T13:59Z
Check the source to verify that this is the current version before use.

In accordance with the following procedures to determine its performance capabilities