2 April 1976

MILITARY SPECIFICATION

SEALING MACHINES, ELECTRICAL IMPULSE

(JAW TYPE)

This amendment forms a part of Military Specification MIL-S-22783C, dated 31 March 1972 and is approved for use by all Departments and Agencies of the Department of Defense.

PAGE 6

3.5.11, line 5, after "timer,": Delete "cooling timer,".

PAGE 10

4.2, lines 5 and 6: Delete "preproduction sample." Substitute, "first article."

PAGE 12

4.3.5: Delete and substitute:

"4.3.5 End item testing. Each sample sealing machine shall be tested as specified in 4.4.1 through 4.4.6 and failure of a test shall be recorded as a defect. The inspection level shall be II with an AQL of 4.0, expressed in terms of defects per hundred units. When applicable, one representative production unit shall be tested as specified in 4.4.7 and failure of the test shall be cause for rejection of all units produced."

PAGE 13

4.4.1, subpara b: Delete ", cooling timer,".

PAGE 14

4.4.7, line 2: Delete and substitute "is required, the sealing machine".

Custodians:

Army - GL
Navy - SA
Air Force - 84

Preparing activity:

Army - GL

Project No. 3540-0118

Review activities:

Army - WC, SM

FSC 3540

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T13:58Z
Check the source to verify that this is the current version before use.