MIL-S-22805A

20 October 1969

SUPERSEDING
MIL-S-22805(Wep)
17 January 1961

MILITARY SPECIFICATION

SPRAY KIT, SELF PRESSURIZED

This specification is mandatory for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 This specification covers the requirements for a disposable kit which utilizes a container pressurized with a liquified gas to atomize a product contained in a separate jar (see 6.1).

2. APPLICABLE DOCUMENTS

2.1 The following documents of the issue in effect on date of invitation for bids or request for proposal, form a part of the specification to the extent specified herein:

SPECIFICATIONS

Federal

BB-F-1421	Fluorocarbon Refrigerant
PPP-B-576	Boxes, Wood, Cleated, Veneer, Paper Overlaid
PPP-B-591	Boxes, Fiberboard, Wood-Cleated
PPP-B-601	Boxes, Wood, Cleated-Plywood
PPP-B-621	Boxes, Wood, Nailed and Lock-Corner
PPP-B-636	Box, Fiberboard
PPP-B-665	Boxes, Paperboard, Metal Stayed (Including Stay Material)

Military

MIL-L-19537	Lacquer, Acrylic-Nitrocellulose, Gloss (for Aircraft Use)
MIL-T-19544	Thinner, Acrylic-Nitrocellulose Lacquer

FSC 4940

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T14:00Z
Check the source to verify that this is the current version before use.

STANDARDS

Federal

Fed. Test Method Standard No. 141	Paint, Varnish, Lacquer, and Related Materials, Methods of Inspection, Sampling and Testing

Military

MIL-STD-105	Sampling Procedures and Tables for Inspection by Attributes
MIL-STD-129	Marking for Shipment and Storage

(Copies of specifications, standards, drawings, and publications required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

2.2 Other publications - The following document forms a part of this specification to the extent specified herein. Unless otherwise indicated, the issue in effect on date of invitation for bids or request for proposal shall apply:

Code of Federal Regulations

49 CFR 171-178	Department of Transportation (DOT) Regulations for the Transportation of Explosives and Other Dangerous Articles by Land and Water

(Application for copies should be addressed to the Superintendent of Documents, U.S. Government Printing Office, Washington, D. C. 20402.)

3. REQUIREMENTS

3.1 First article inspection - The spray kit furnished under this specification shall be a product which has been tested and passed the first article inspection specified herein (see 4.3).

3.2 Spray kit - The kit shall consist of 2 spray devices, 10 propellant cans, 4 product jars provided with lids, and 20 dip tubes cut to proper length.

3.3 Spray unit - The spray unit shall consist of a spray device, a propellant can, a jar and a dip tube. The spray unit shall be designed so that no component will become detached during handling or operation. The finished product shall be in compliance with the applicable Department of Transportation Regulations.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T14:00Z
Check the source to verify that this is the current version before use.

3.3.1 Spray device - The spray device shall consist of a housing or bridgelike piece which serves to unitize a propellent can power supply, a product jar, a dip tube, a spray nozzle, and a trigger or activating mechanism. The spray device shall be a rigid structure which shall prevent relative movement of the propellent can, jar and spray head during handling and operation. The spray device shall be designed so that no component part will become detached during handling or operation.

3.3.1.1 Spray nozzle - The spray nozzle shall consist of a product delivery orifice and a propellent delivery orifice firmly secured to the housing or bridge portion. The spray nozzle shall be an external mixing type and must be designed so that the positioning of the orifices will not be disturbed during handling, use, or cleaning, and shall be of corrosion and solvent resistant construction. The product delivery portion shall be designed so that the dip tube can be securely fixed to it and allow not less than 1/4 inch exposure for attachment.

3.3.1.2 Activating mechanism - The activating mechanism shall be designed for convenient operation, requiring only one hand to hold and operate the unit. The activating mechanism shall be readily operated by finger pressure. A movement of the finger in activating the mechanism shall be not greater than 1/4 inch to activate the valve.

3.3.2 Propellent can - The pressurized can shall have a cylindrical shaped body with a concave bottom complying with the Department of Transportation Regulations, Sections 173.306 and 178.33 (see 6.3). The bottom of the can shall be double-seamed and compound lined. The can shall be free of foreign matter and shall be provided with a valve for dispensing the propellent. The can shall be pressurized with 15 ounces net weight of propellent No. 12 (dichlorodifluoromethane) conforming with BB-F-1421. A snap fitted rigid plastic or metal cover for the valve cup shall be provided to protect the valve from damage or accidental functioning during transportation or storage where parts of the valve mechanism extend above the valve cup. The can shall have an exterior coating to prevent corrosion.

3.3.2.1 Valve - The valve shall be centrally located on the valve cup and shall be capable of being operated by the activating mechanism. The valve shall be a spray type valve through which the vapor phase propellent shall be delivered.

3.3.3 Product jar - The jar shall be a minimum of 4 fluid ounce capacity and a maximum of 8 fluid ounce capacity and be graduated with permanent and durable markings of 1/2 ounce increments. The jar and lid shall be shatter resistant when tested in accordance with 4.6.6. The product jar shall conform to the jar clarity test of 4.6.5. A lid shall be provided for each product jar capable of effecting a solvent-proof seal.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T14:00Z
Check the source to verify that this is the current version before use.

3.3.4 Dip tube - The dip tube shall be solvent- and crack-resistant material of such length as to come to within 1/8 to 1/4 inch of the bottom of the jar in final assembly.

3.4 Interchangeability within kit components - The components of the spray kit shall comply to the applicable requirements of this specification, and shall be interchangeable with like components of the kit and like components of other kits procured under the same contract.

3.5 Physical properties - The spray unit, or the components thereof, shall conform to the requirements in Table I, when tested as specified herein and in the sequence listed.

TABLE I

PHYSICAL PROPERTIES

TESTS	REQUIREMENTS	TEST PARAGRAPH
Fluorinated hydrocarbon content	15 ozs.(min)	4.6.2
Solvent resistance	No apparent deterioration	4.6.3
Fatigue	No deleterious effects	4.6.4
Jar clarity	Sufficiently transparent to display liquid content level	4.6.5
Jar breakage	Shatter resistant, no scattering of jar fragments	4.6.6
Valve operation	Opens and closes freely; no leakage	4.6.7
Dip tube pressure	Vacuum 2.65 inches of mercury (min) or minus 1.3 psig (min)	4.6.8
Delivery rate Propellent Product	 3.75 gms (min) 8.25 gms (max) 6.75 gms (min)	 4.6.9.1 4.6.9.2
Spraying efficiency	1.4 min	4.6.9.3
Spraying properties	1-1/2 inches width (min) uniform coating	4.6.10
Continuous discharge	No loss of spray	4.6.11

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T14:00Z
Check the source to verify that this is the current version before use.

TABLE I (Continued)

TESTS	REQUIREMENTS	TEST PARAGRAPH
Leakage		
Static	No leakage	4.6.12.1
Dynamic	No leakage	4.6.12.2
Propellent pressure	70 psig (min)	4.6.13

3.6 Workmanship - All details of workmanship shall be in accordance with standard commercial practice.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection - Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or order, the supplier may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements. Inspection records of the examinations and tests shall be kept complete and available to the Government as specified in the contract or order.

4.2 Classification of inspections - The inspection requirements specified herein are classified as follows:

(a) First article inspection (see 4.3).

(b) Quality conformance inspection (see 4.4).

4.3 First article inspection - The first article inspection shall be performed by a Government laboratory and shall comprise testing of the first article samples and a review of the certifications and reports accompanying the first article inspection samples. First article inspection shall consist of all the tests of this specification (see 4.3.1). Tests shall be performed in the sequence listed in Table I.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T14:00Z
Check the source to verify that this is the current version before use.

4.3.1 First article samples - The first article inspection sample shall consist of three complete spray kits whose components have been manufactured and assembled under actual production conditions. As soon as practicable after the award of the contract or order, and prior to submission of spray kits for acceptance under contract, the contractor shall furnish first article inspection samples within the time specified (see 6.2). Each first article inspection sample shall be accompanied by a certification of compliance to this specification and a report giving a description of the product submitted. Delivery of the items contracted for shall not be made until the first article tests are completed and the items found acceptable. The samples, certifications, and reports shall be forwarded to the Naval Air Development Center, Attention: Director, Aero Materials Department, Johnsville, Warminster, Pennsylvania 18974. The samples shall be plainly identified by securely attached durable tags or labels marked with the following information:

Sample for First Article Inspection
SPRAY KIT, SELF PRESSURIZED
Plants where components are manufactured
Name of manufacturer or contractor
Contract or order number
Submitted by (Name) (Date) for First Article Inspection in accordance with the requirements of Specification MIL-S-22805A under (reference applicable contract number)

4.3.2 Resubmittal of first article samples - In the event that first article samples fail to comply with the requirements of this specification, resubmittal may be made when changes, such as design or production, have been made to correct the defects. Evidence of the corrective action shall be forwarded to the testing officer (see 4.3.1) before retests will be conducted.

4.4 Quality conformance inspection - Quality conformance inspection shall consist of an examination for quality control methods used by the manufacturer, an examination for conformance to the packaging, packing, and marking requirements, and examining and testing the quality conformance samples (see 4.4.1) for all of the requirements of this specification. Tests shall be performed in the sequence listed in Table I.

4.4.1 Quality conformance samples - Quality conformance inspection samples shall be taken from each lot. Each propellent can procured shall have passed the Department of Transportation immersion test (see 6.3). Quality conformance test samples shall be subjected to all tests and examinations of this specification (see 4.1).

4.4.1.1 Inspection lot - A lot shall consist of products made under essentially the same conditions and presented for acceptance at the same time. A spray unit shall be the base unit for determining lot sizes.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T14:00Z
Check the source to verify that this is the current version before use.

4.4.1.2 Sample for tests - A sample for the quality conformance tests shall be selected in accordance with MIL-STD-105, Inspection Level S-2, with acceptable quality level (AQL) 1.5 percent defective.

4.4.1.3 Sampling for visual inspection - The sample unit shall be a spray unit. Sufficient units shall be selected at random in accordance with Inspection Level S-2, of MIL-STD-105 with AQL as specified for respective defects.

4.5 Visual and dimensional examinations - Visual and dimensional examinations shall be in accordance with the following classification of defects:

4.5.1 Spray kit -

Quantity of components not as specified.

4.5.2 Defects in spray device -

Corrosion of parts
Warped or cracked
Spray nozzle missing

4.5.3 Defects in propellent can -

Markings as specified in 5.3.2 missing
Precautionary marking as in 5.3.2.1 missing
External coating missing
Corrosion
Bottom not concave
Can not filled

4.5.4 Defects in product jar -

Not of proper capacity
Jar cracked or broken
Graduation markings missing or illegible

4.5.5 Defects in dip tubes -

Cracked
Not cut to proper length
Do not fit product delivery spray nozzle

4.5.6 Packaging, packing, and marking - The lot size for this examination shall be expressed as a shipping container. The Inspection Level shall be S-3.

Defects

Not marked as specified in 5.3.1
Integrity of unit package not maintained

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T14:00Z
Check the source to verify that this is the current version before use.

Not marked in accordance with Department of Transportation Regulations
Precautionary markings of 5.3.1.1 missing

4.5.7 Source of material used for inspection - The same spray kits may be used in the visual examination of 4.5 to 4.5.6 and quality conformance testing of 4.4.1.

4.5.8 Acceptable quality levels (AQL's) - The acceptable quality levels expressed in percent defectives shall be as follows:

For defects listed in 4.5.3 - 1.0 percent defective

For defects listed in 4.5.1, 4.5.2, 4.5.4, 4.5.5 and 4.5.6 -4.0 percent defective

4.6 Test methods -

4.6.1 Test conditions - Unless otherwise specified, the physical tests required in this specification shall be made under atmospheric pressure and at a temperature of 73 ±3.5°F. All samples shall be exposed at the above conditions for 2 hours prior to the start of testing. Three separate units of test shall be subjected to each applicable test in this specification. When the test yields an arithmetic or numerical result each unit tested shall be tested in triplicate, with the exception of the Fluorinated hydrocarbon content test which cannot be repeated on any one unit. The arithmetic average of the tests shall be the reported result. Where possible fresh propellent containers shall be used for each test, otherwise propellent containers must be conditioned for at least 1/2 hour between tests.

4.6.1.1 Test product - The test sample to be prepared for determining the efficiency of the spray unit shall be a lacquer conforming to MIL-L-19537 (white) diluted with thinner conforming to MIL-T-19544 to a viscosity of 15 ±2 seconds when tested in accordance with Fed. Test Method Std. No. 141, Method 4282, using a No. 4 Ford cup. The test samples shall be prepared fresh in small batches.

4.6.2 Fluorinated hydrocarbon content - The propellent can shall be weighed. The top of the can shall be pierced with a can piercing device and the can allowed to stand at room temperature for one hour. The container shall be reweighed and weight differential shall be considered as the weight of the contents. Fresh propellent cans must be used for this test.

4.6.3 Solvent resistance - Each spray device, dip tube, jar and lid shall be submerged separately in a mixture of equal parts of toluene, xylene, lacquer thinner (MIL-T-19544), and mineral spirits for a period of 72 hours. There shall be no apparent deterioration.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T14:00Z
Check the source to verify that this is the current version before use.

4.6.4 Fatigue test - The component parts of the spray device shall be assembled and disassembled 5 times. The screw on parts shall be tightened until slippage occurs or until a reading of 20 inch pounds of torque is reached during each assembling. If during subsequent tests any part becomes loose or disassembled during handling and operation this shall be considered cause for rejection. The units used for this test shall then be subjected to the tests of valve operation, dip tube pressure, product delivery rate, propellent delivery rate, spraying properties, continuous discharge, static leakage and dynamic leakage.

4.6.5 Jar clarity - Two ounces of water shall be added to the jar, and the jar illuminated with 50 ±10 foot candles of diffused light. The liquid level shall be visible when viewed from the side of the jar closest to the light source.

4.6.6 Jar breakage - The jar shall be filled with 2 ounces of water, closed with the lid and dropped from a height of 4 feet onto a concrete deck. Evidence of jar or lid fragments on the deck shall be considered as failure. Fragments that do not separate from the jar body or are contained within the jar shall not be considered as failure.

4.6.7 Valve operation - The spray unit assembled with propellent can shall be manually operated without evidence of excessive finger pressure. The valve shall close immediately upon release. The valve shall be successively operated 30 times as prescribed above after which it shall be examined for leakage by submersion for 5 minutes in water treated and maintained as in 4.5.12.1. The emission of a series of bubbles from any point on the spray unit shall be considered as evidence of leakage.

4.6.8 Dip tube pressure - The spray unit, assembled except for jar, shall be operated with a vacuum gage connected to the free end of the dip tube. The maximum vacuum attained within the first 10 seconds of operation shall be recorded as the dip tube vacuum.

4.6.9 Delivery rate -

4.6.9.1 Propellent - The delivery rate of the propellent shall be determined with the spray unit assembled with or without a jar. The unit shall be weighed to the nearest 0.01gm. The valve shall be operated in the fully opened position for 15 ±0.2 seconds. The unit shall then be reweighed and the loss in weight taken as the delivery rate.

4.6.9.2 Product - The spray unit fully assembled with jar filled with the test product specified in 4.6.1.1 shall be weighed. The valve shall be actuated to cause the maximum delivery of propellent for 15 ±0.2 seconds. The unit shall then be reweighed. The product delivery rate shall be taken as the loss in weight minus the reported average propellent discharge rate that was determined in 4.6.9.1 for that unit.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T14:00Z
Check the source to verify that this is the current version before use.

4.6.9.3 Spraying efficiency - The spraying efficiency will be the product delivery rate divided by the propellent delivery rate.

4.6.10 Spraying properties - The spray unit assembled with propellent can and with jar filled with the product specified in 4.6.1.1 shall be used in this test. A 4- by 12-inch steel panel fabricated, prepared, and cleaned in accordance with Method No. 2011 of Federal Test Method Standard No. 141 shall be set at an angle of 15 degrees from the vertical. The spray unit shall be held vertical at a distance of 8 inches from the panel with the valve open. The spray unit shall be moved from one edge of the panel to the other, making only one pass over the panel at the rate of 10 inches per second. The panel shall then be laid in a horizontal position to dry for 15 minutes, and then examined for compliance with the requirements. The coating on the panel shall be a smooth, unbroken strip at least 1-1/2 inches wide. Overspray in either side of the strip shall not be considered detrimental.

4.6.11 Continuous discharge - The spray unit assembled with a loaded propellent can and jar filled with the product specified in 4.6.1.1 shall be continuously operated for at least one minute. Sputtering or loss of the spray during this period shall be cause for rejection.

4.6.12 Leakage -

4.6.12.1 Static - The spray unit assembled with a loaded propellent can shall be completely submerged for 1 minute in a water-wetting agent solution maintained at 73 ±3.5°F after which it shall be observed for a period of five minutes. The emission of bubbles from any part of the spray unit during the observation period shall be considered as evidence of leakage.

4.6.12.2 Dynamic - The spray unit assembled as for the "Static test" shall be submerged with only the spray head extending out of the water treated and maintained as in 4.6.12.1. The partially submerged spray unit shall be operated continuously for one minute. The emission of bubbles from any part of the spray unit shall be considered as evidence of leakage.

4.6.13 Propellent can pressure - The can pressure shall be measured by means of a standard test gage fitted with a suitable adapter.

5. PREPARATION FOR DELIVERY

5.1 Packaging - The levels of packaging shall be specified in the contract or order (see 6.2). Containers or method of shipment shall comply with Department of Transportation Regulations or other carrier regulations applicable to the mode of transportation.

5.1.1 Level A - The component parts of the spray kit , consisting of 2 spray devices, 10 propellent cans, 4 product jars with lid , and 20 dip tubes cut to length, shall be unit packaged in a suitable box conforming to

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T14:00Z
Check the source to verify that this is the current version before use.

PPP-B-636 or PPP-B-665. The interior of the box shall be suitably partitioned to form compartments. Components shall be snugly packed in their compartments to prevent shifting. Provisions shall be made to provide valve protection against discharge or damage, where necessary.

5.1.2 Level C - The spray kits shall be packaged in a manner which will afford adequate protection against corrosion, deterioration, and damage during shipment from the supply source to the first receiving activity. The supplier's commercial practice will be acceptable when it fulfills the above requirements.

5.2 Packing - The levels of packing shall be as specified in the contract or order (see 6.2). Containers or method of shipment shall comply with Department of Transportation Regulations, or other carrier regulations applicable to the mode of transportation. The gross weight shall be within the weight limitations specified in the applicable box specification.

5.2.1 Level A - Spray kits packaged as specified in 5.1.1 shall be packed in overseas type exterior containers conforming to PPP-B-576, PPP-B-591, PPP-B-621, PPP-B-601, or PPP-B-636, Class 2, Grade 3, and to the appendixes thereto. For Army procurement containers conforming to PPP-B-576, PPP-B-591, and PPP-B-636 shall not be used.

5.2.2 Level B - Spray kits packaged as specified in 5.1.1 shall be packed in domestic type containers of Level A. For Army procurement containers conforming to domestic type fiberboard shall not be used.

5.2.3 Level C - Spray kits shall be packed in a manner to ensure safe delivery and acceptance at destination.

5.3 Marking -

5.3.1 Packages and shipping containers shall be marked in accordance with MIL-STD-129 and Department of Transportation Regulations, and with the following information:

Title, number, and date of this specification
Contract or order
Name of contractor (if different from manufacturer)
Date of manufacture (loading date of propellent can)

5.3.1.1 Precautionary marking - Packages and shipping containers shall be marked as follows:

WARNING

Contents in pressurized containers.
Do not store in temperatures above 120°F.
Keep away from direct sunlight, radiators,
stoves, hot water, and other heat sources.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T14:00Z
Check the source to verify that this is the current version before use.

5.3.2 Propellent can - The propellent cans shall be durably and legibly marked on the main panel of the body by lithographing or silk screening with a noncorrosive, petroleum-resistant, waterproof marking which will not smear or rub off. Each can shall be marked with the manufacturer's name and instructions for assembly, operation of the spray unit, and cleaning of the spray nozzle and the following:

Contents nonflammable and nontoxic
Contains propellent (dichlorodifluoromethane) only
Net weight 15 ounces

5.3.2.1 Precautionary markings on propellent can shall be as follows:

CAUTION: If contents in product jar is toxic or flammable spray only in a well-ventilated room; keep away from any open flame. Observe all cautions and notices on bulk product packages.

WARNING: Propellent is under 70 pounds pressure at 70°F. Do not expose to high temperatures. Do not store at temperatures exceeding 120°F. Keep away from direct sunlight, radiators, stoves, hot water, and other heat. Do not puncture or incinerate can.

6. NOTES

6.1 Intended use - The spray kit described in this specification is intended for use where small quantities of materials are required in the maintenance of missiles, aircraft, rockets, and their components. These kits may also be utilized in fleet operating and maintenance squadrons, especially where stocking and storage space is limited. These kits may be used for spray application of light and medium viscosity materials. Such materials as enamels, primers, rust-preventives, lacquers, acrylic cleaners, and defogging compounds, may be applied by the spray units described herein.

6.2 Ordering data - Requisitions, contracts, and orders should specify the following:

(a) Title, number, and date of this specification.
(b) Quantity
(c) Levels of packaging and packing
(d) Specify time for delivery of first article samples (4.3.1).

6.3 It is to be noted that Section 173.306 of the Department of Transportation Regulations specifies that each completed metal container filled for shipment must be heated until content reaches a minimum temperature of 130°F without evidence of leakage, distortion, or other defects.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T14:00Z
Check the source to verify that this is the current version before use.

6.4 It is understood that the spray units or components thereof supplied for acceptance under contract shall be identical in every respect to the first article samples inspected and found satisfactory. Any unapproved changes from the first article samples shall constitute cause for rejection.

Custodians:
Army - WC
Navy - AS
Air Force - 82

Review activities:
Army - WC, SM
Navy - OS
Air Force -

User activities:
Army - AV, EL
Navy - YD, SH
Air Force -

Preparing activity:
Navy - AS
(DOD Project No. 4940-0175)

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T14:00Z
Check the source to verify that this is the current version before use.

SPECIFICATION ANALYSIS SHEET

Form Approved
Budget Bureau No. 119-R004

INSTRUCTIONS

This sheet is to be filled out by personnel either Government or contractor, involved in the use of the specification in procurement of products for ultimate use by the Department of Defense. This sheet is provided for obtaining information on the use of this specification which will insure that suitable products can be procured with a minimum amount of delay and at the least cost. Comments and the return of this form will be appreciated. Fold on lines on reverse side, staple in corner, and send to preparing activity (as indicated on reverse hereof).

SPECIFICATION

MIL-S-22805A SPRAY KIT, SELF PRESSURIZED

ORGANIZATION (Of submitter)	CITY AND STATE

CONTRACT NO.	QUANTITY OF ITEMS PROCURED	DOLLAR AMOUNT
		$

MATERIAL PROCURED UNDER A

☐ DIRECT GOVERNMENT CONTRACT ☐ SUBCONTRACT

1. HAS ANY PART OF THE SPECIFICATION CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE?

A. GIVE PARAGRAPH NUMBER AND WORDING.

B. RECOMMENDATIONS FOR CORRECTING THE DEFICIENCIES.

2. COMMENTS ON ANY SPECIFICATION REQUIREMENT CONSIDERED TOO RIGID

3. IS THE SPECIFICATION RESTRICTIVE?

☐ YES ☐ NO IF "YES", IN WHAT WAY?

4. REMARKS (Attach any pertinent data which may be of use in improving this specification. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity)

SUBMITTED BY (Printed or typed name and activity)	DATE

DD FORM 1426 REPLACES NAVSHIPS FORM 4863, WHICH IS OBSOLETE C-0570

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T14:00Z
Check the source to verify that this is the current version before use.

FOLD

DEPARTMENT OF THE NAVY
Naval Air Engineering Center
Philadelphia, Pennsylvania 19112

POSTAGE AND FEES PAID
NAVY DEPARTMENT

OFFICIAL BUSINESS

Weapons Engineering Standardization Office (Code X)
Naval Air Engineering Center
Philadelphia, Pennsylvania 19112

FOLD

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T14:00Z
Check the source to verify that this is the current version before use.