INCH-POUND

MIL-S-22805B
31 March 1993

SUPERSEDING
MIL-S-22805A
20 October 1969

MILITARY SPECIFICATION

SPRAY KIT, SELF PRESSURIZED

This specification is approved for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification covers the requirements for disposable self-pressurized kits which utilize a propellant can pressurized with a liquified gas to atomize a product contained in a separate but attached jar (see 6.1).

1.2 Classification. The disposable kits shall be classified as follows (see 6.2d):

1.2.1 Types.

Type I - Non-flammable propellant unit.
Type II - Flammable propellant unit

1.2.2 Classes. Type I shall be available in the following classes.

Class 22 - Hydrochlorofluorocarbon (HCFC) propellant
Class 134A - Hydrofluorocarbon (HFC) propellant

2. APPLICABLE DOCUMENTS

2.1 Government documents.

Beneficial comments, (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: Commanding Officer, Naval Air Warfare Center Aircraft Division Lakehurst, Code SR3 Lakehurst, NJ 08733-5100, by using the Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

AMSC N/A FSC 4940

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T14:00Z
Check the source to verify that this is the current version before use.

2.1.1 Specifications and standards. The following specifications and standards form a part of this specification to the extent specified herein. Unless otherwise specified, the issues of these documents are those listed in the issue of the Department of Defense Index of Specifications and Standards (DODISS) and supplement thereto, cited in the solicitation (see 6.2b).

SPECIFICATIONS

FEDERAL

BB-F-1421	Fluorocarbon Refrigerants
TT-T-266	Thinner, Dope and Lacquer (Cellulose-Nitrate)
PPP-B-576	Boxes, Wood, Cleated, Veneer, Paper Overlaid
PPP-B-591	Boxes, Fiberboard, Wood-Cleated
PPP-B-601	Boxes, Wood, Cleated-Plywood
PPP-B-621	Boxes, Wood, Nailed and Lock-Corner
PPP-B-636	Boxes, Shipping, Fiberboard
PPP-B-665	Boxes, Paperboard, Metal Edged and Components

MILITARY

MIL-L-19537	Lacquer, Acrylic-Nitrocellulose, Gloss (for Aircraft Use)

STANDARDS

FEDERAL

FED-STD-141	Paint, Varnish, Lacquer, and Related Materials, Methods of Inspection, Sampling and Testing

MILITARY

MIL-STD-105	Sampling Procedures and Tables for Inspection by Attributes
MIL-STD-129	Marking for Shipment and Storage

(Unless otherwise indicated, copies of federal and military specifications, standards, and handbooks are available from the Standardization Documents Order Desk, Building 4D, 700 Robbins Avenue, Philadelphia, PA 19111-5094.)

2.1.2 Other Government documents and drawings. The following other Government documents and drawings form a part of this specification to the extent specified herein. Unless otherwise specified, the issues shall be those in effect on the date of the solicitation.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T14:00Z
Check the source to verify that this is the current version before use.

DEPARTMENT OF TRANSPORTATION

CFR 49 Code of Federal Regulations, Title 49 - Transportation

(Application for copies should be addressed to the Superintendent of Documents, U.S. Government Printing Office, Washington, DC 20402.)

2.2 Order of precedence. In the event of a conflict between the text of this document and the references cited herein (except for related associated detail specifications, specification sheets, or MS standards), the text of this document takes precedence. Nothing in this document, however, supersedes applicable laws and regulations unless a specific exemption has been obtained.

3 REQUIREMENTS

3.1 First article. The spray kit furnished under this specification shall be a product which has been subjected to the first article inspection (see 6.3) in accordance with 4.3.

3.1.1 Type I propellant.

3.1.1.1 Class 22. The propellant for Type I, Class 22 shall consist of hydrochlorofluorocarbons or a blend containing hydrochlorofluorocarbons. Class 22 blends shall contain no chlorinated solvents or fully halogenated solvents. Class 22 hydroclorofluorocarbons shall be in accordance with BB-F-1421.

3.1.1.2 Class 134A. The propellant for Type I, Class 134A shall consist of hydrofluorocarbons or a blend containing hydrofluorocarbons. Class 134A blends shall contain no chlorinated solvents, hydrochlorofluorocarbons or fully halogenated chlorofluorocarbons.

3.1.2 Type II propellant. The propellant for Type II shall consist of a hydrocarbon solvent blend.

3.2 Spray kit. The kit shall consist of 4 spray devices, 10 propellant cans, 4 product jars provided with lids, and 20 dip tubes cut to proper length.

3.3 Spray unit. The spray unit shall consist of a spray device, a propellant can, a jar and a dip tube. The spray unit shall be designed so that no component will become detached during handling or operation. The finished product shall be in compliance with all applicable Department of Transportation Regulations.

3.3.1 Spray device. The spray device shall consist of a housing or bridgelike piece which serves to unitize a propellant can power supply, a product jar, a dip tube, a spray nozzle, and a trigger or activating mechanism. The spray device shall be a rigid structure which shall prevent relative movement of

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T14:00Z
Check the source to verify that this is the current version before use.

the propellant can, jar and spray head during handling and operation. The spray device shall be designed so that no component part will become detached during handling or operation.

3.3.1.1 Spray nozzle. The spray nozzle shall consist of a product delivery orifice and a propellant delivery orifice firmly secured to the housing or bridge portion. The spray nozzle shall be an external mixing type and must be designed so that the positioning of the orifices will not be disturbed during handling, use, or cleaning, and shall be of corrosion and solvent resistant construction. The product delivery portion shall be designed so that the dip tube can be securely fixed to it and allow not less than 1/4 inch exposure for attachment.

3.3.1.2 Activating mechanism. The activating mechanism shall be designed for convenient operation, requiring only one hand to hold and operate the unit. The activating mechanism shall be readily operated by finger pressure. A movement of the finger in activating the mechanism shall be not greater than 1/4 inch to activate the valve.

3.3.2 Propellant can. The size of the propellant can shall be 211 x 413 mm and shall comply with specification DOT.2Q of part 178 of CFR 49. The can shall be free of foreign matter and shall be provided with a valve for dispensing the propellant. The can shall have an exterior coating to prevent corrosion.

3.3.2.1 Type I propellant charge. The propellant charge for Type I, Class 22 shall be 340 grams of material or blend described in 3.1.1.1. The propellant charge for Type I, Class 134A shall be 330 grams of material or blend described in 3.1.1.2.

3.3.2.2 Type II propellant charge. The propellant charge to Type II shall be 184 grams of the solvent blend described in 3.1.2.

3.3.2.3 Valve. The valve shall be centrally located on the valve cup and shall be capable of being operated by the activating mechanism. The valve shall be a spray type valve through which the vapor phase propellant shall be delivered.

3.3.2.4 Valve cover. A snap fitted rigid plastic or metal cover for the valve cup shall be provided to protect the valve from damage or accidental functioning during transportation or storage where parts of the valve mechanism extend above the valve cup.

3.3.3 Product jar. The jar shall be a minimum of 4 fluid ounce capacity and a maximum of 8 fluid ounce capacity and be graduated with permanent and durable markings of 1/2 ounce increments. The jar and lid shall be shatter resistant plastic when tested in accordance with 4.6.5. The product jar shall conform to the jar clarity test of 4.6.4. A lid shall be provided for each product jar capable of effecting a solvent-proof seal.

3.3.4 Dip tube. The dip tube shall be solvent and crack-resistant material and shall be of such length as to come to within 1/8 to 1/4 inch of the bottom of the jar in final assembly.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T14:00Z
Check the source to verify that this is the current version before use.

3.4 Interchangeability within kit components. The components of the spray kit shall comply to the applicable requirements of this specification, and shall be interchangeable with like components of the kit and like components of other kits procured under the same contract.

3.5 Physical properties. The spray unit, or the components thereof, shall conform to the requirements in Table I, when tested as specified herein and in the sequence listed.

TABLE I. Physical properties

TESTS	REQUIREMENTS	TEST PARAGRAPH
Propellant Content, min Type I, Class 22 Type I, Class 134A Type II	 340 grams 330 grams 184 grams	4.6.1
Solvent resistance	No apparent deterioration	4.6.2
Fatigue	No deleterious effects	4.6.3
Jar clarity	Sufficiently transparent to display liquid content level	4.6.4
Jar breakage	Shatter resistant, no scattering of jar fragments	4.6.5
Valve operation	Opens and closes freely; no leakage	4.6.6
Dip tube pressure	Vacuum 2.65 inches of mercury (min) or minus 1.3 psig (min)	4.6.7
Delivery rate Propellant Product	 3.75 gms 8.25 gms 8.0 gms (min)	 4.6.8.1 4.6.8.2
Spraying efficiency	1.4 min	4.6.8.3
Spraying properties	1-1/2 inches width (min) uniform coating	4.6.9
Continuous discharge	No loss of spray	4.6.10
Leakage Static Dynamic	 No leakage No leakage	 4.6.11.1 4.6.11.2
Propellant pressure	59 to 70 psig	4.6.12

Source: https://assist.dla.mil -- Downloaded: 202610-19T14:00Z
Check the source to verify that this is the current version before use.

3.6 Workmanship. All details of workmanship shall be in accordance with standard commercial practice.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the contractor is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to ensure supplies and services conform to prescribed requirements.

4.1.1 Responsibility for compliance. All items shall meet all requirements of sections 3 and 5. The inspection set forth in this specification shall become a part of the contractor's overall inspection system or quality program. The absence of any inspection requirements in the specification shall not relieve the contractor of the responsibility of ensuring that all products or supplies submitted to the Government for acceptance comply with all requirements of the contract. Sampling inspection, as part of manufacturing operations, is an acceptable practice to ascertain conformance to requirements, however, this does not authorize submission of known defective material, either indicated or actual, nor does it commit the Government to acceptance of defective material.

4.2 Classification of inspection. The examination and testing of the kits shall be classified as follows:

a. First article inspection (see 4.3).

b. Quality conformance inspection (see 4.4).

4.3 First article inspection. First article inspection shall consist of the examinations and tests specified in Table I.

4.3.1 First article test samples. First article test samples shall consist of three (3) complete spray kits whose components have been manufactured and assembled for filling the contract. Samples shall be forwarded to, and tested at a laboratory approved by the Naval Air Warfare Center Aircraft Division Warminster for conducting first article inspection tests. Information on approved test laboratories may be obtained from the Commanding Officer, Naval Air Warfare Center Aircraft Division Warminster, P.O. Box 5152, Code 6062, Warminster, PA 18974-0591. Samples shall be plainly identified by securely attached durable tags marked with the following information:

Samples for First Article Inspection

Source: https://assist.dla.mil -- Downloaded: 202610-19T14:00Z
Check the source to verify that this is the current version before use.

SPRAY KIT, SELF PRESSURIZED.
Plants where components are manufactured.
Name of manufacturer or contractor.
Contract or order number.
Submitted by (Name) (Date) for First Article
Inspection in accordance with the requirements of
Specification MIL-S-22805B under (reference applicable
contract number).

4.3.2 First article sample and inspection for a subsequent contract. If a contractor has previously furnished the kit in accordance with the requirements of this specification and his product has been found to be satisfactory, the requirement for a first article sample and its submittal for any subsequent contract or order may be waived at the discretion of the Naval Air Warfare Center Aircraft Division Warminster.

4.4 Quality conformance Inspection.

4.4.1 Lot formation. An inspection lot shall consist of the total number of kits assembled for delivery under essentially the same conditions and presented for inspection at the same time.

4.4.1.1 Certification. The contractor shall certify that each charged propellant can delivered under contract has passed the Department of Transportation immersions test (see 6.7).

4.4.2 Sampling.

4.4.2.1 Visual and dimensional examination. A random sample of kits shall be selected from each lot in accordance with Inspection Level S-2 of MIL-STD-105. The sample unit shall be one kit. The samples selected shall be examined as specified in Table II.

4.4.2.2 Tests. A random sample of kits to be tested shall be selected from each lot in accordance with Inspection Level S-2 of MIL-STD-105. The sample unit shall be one complete kit. The samples shall be tested to the requirements of Table I. There shall be no defects.

4.4.2.3 Packaging inspection. An examination shall be made to determine that packaging and marking comply with the requirements of Section 5 of this specification. Defects shall be scored in accordance with Table III. The sample unit for this examination shall be one shipping container fully prepared for delivery, except that it need not be sealed. Shipping containers fully prepared for delivery shall be examined for closure defects. The lot size shall be the number of shipping containers in the end item inspection lot. The samples for this examination shall be selected at random in accordance with MIL-STD-105, Inspection Level S-2 and an AQL of 4.0 Defects Per Hundred Units.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T14:00Z
Check the source to verify that this is the current version before use.

TABLE II. Visual and dimensional examination

EXAMINATION	DEFECT	AQL 1/
Spray kit	Quantity of components not as specified	2.5
Spray device	Corrosion of parts; warped or cracked; spray nozzle missing	2.5
Propellant cans	Markings as specified in 5.3.2 missing Precautionary marking as in 5.3.2.1 missing External coating missing Corrosion Bottom not concave Can not filled	1.0
Product jar	Not of proper capacity Jar cracked or broken Graduation markings missing or illegible	2.5
Dip tube	Cracked Not cut to proper length Do not fit product delivery spray nozzle	2.5

1/ MIL-STD-105, Acceptable Quality Level; percent defective

4.5 Testing variables.

4.5.1 Test conditions. Unless otherwise specified, the physical tests required in this specification shall be made under atmospheric pressure and at a temperature of 73° ±3.5°F. All samples shall be exposed at the above conditions for 2 hours prior to the start of testing. Three separate units of test shall be subjected to each applicable test in this specification. When the test yields an arithmetic or numerical result each unit tested shall be tested in triplicate, with the exception of the fluorinated hydrocarbon content test which cannot be repeated on any one unit. The arithmetic average of the tests shall be the reported result. Where possible fresh propellant containers shall be used for each test, otherwise propellant containers must be conditioned for at least 1/2 hour between tests.

4.5.2 Test solution. The test spray solution to be prepared for determining the efficiency of the spray unit shall be a lacquer conforming to MIL-L-19537 (white) diluted with thinner conforming to TT-T-266 to a viscosity of 15 ± 2 seconds when tested in accordance with FED-STD-141, Method 4282, using a No. 4 Ford cup. The test samples shall be prepared fresh in small batches.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T14:00Z
Check the source to verify that this is the current version before use.

TABLE III. Packaging inspection

Examine	Defect
Packaging	Container not as specified; closure not accomplished by specified or required methods or materials. Puncture, break, leakage of contents. Non-conforming components, component missing, damaged or otherwise defective. Bulged or distorted container.
Markings	Data omitted, illegible, incorrect, incomplete, or not in accordance with contract requirements. Markings not in accordance with Department of Transportation Regulations.

4.5.3 Interchangeability. Visual conformance to 3.4 shall be noted during all inspection and test procedures requiring assembly/disassembly of the kit.

4.6 Test methods.

4.6.1 Propellant content. The propellant can shall be weighed. The top of the can shall be pierced with a can piercing device and the can allowed to stand at room temperature for one hour. The container shall be reweighed and weigh differential shall be considered as the weight of the contents. Fresh propellant cans must be used for this test.

4.6.2 Solvent resistance. Each spray device, dip tube, jar and lid shall be submerged separately in a mixture of equal parts of toluene, xylene, lacquer thinner (TT-T-266) and mineral spirits for a period of 72 hours. There shall be no apparent deterioration.

4.6.3 Fatigue test. The component parts of the spray device shall be assembled and disassembled 25 times. The screw on parts shall be tightened until slippage occurs or until a reading of 20 inch pounds of torque is reached during each assembling. If during subsequent tests any part becomes loose or disassembled during handling and operation this shall be considered cause for rejection. The units used for this test shall then be subjected to the tests of valve operation, dip tube pressure, product delivery rate, propellant delivery rate, spraying properties, continuous discharge, static leakage and dynamic leakage.

4.6.4 Jar clarity. Two ounces of water shall be added to the jar, and the jar illuminated with 50 ±10 foot candles of diffused light. The liquid level shall be visible when viewed from the side of the jar closest to the light source.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T14:00Z
Check the source to verify that this is the current version before use.

4.6.5 Jar breakage. The jar shall be filled with 2 ounces of water, closed with the lid and dropped from a height of 4 feet onto a concrete deck. Evidence of jar or lid fragments on the deck shall be considered as failure. Fragments that do not separate from the jar body or are contained within the jar shall not be considered as failure.

4.6.6 Valve operation. The spray unit assembled with propellant can shall be manually operated without evidence of excessive finger pressure. The valve shall close immediately upon release. The valve shall be successively operated 30 times as prescribed above after which it shall be examined for leakage by submersion for 5 minutes in water treated and maintained as in 4.6.11.1. The emission of a series of bubbles from any point on the spray unit shall be considered as evidence of leakage.

4.6.7 Dip tube pressure. The spray unit, assembled except for jar, shall be operated with a vacuum gage connected to the free end of the dip tube. The maximum vacuum attained within the first 10 seconds of operation shall be recorded as the dip tube vacuum.

4.6.8 Delivery rate.

4.6.8.1 Propellant. The delivery rate of the propellant shall be determined with the spray unit assembled with or without a jar. The unit shall be weighed to the nearest 0.01 gm. The valve shall be operated in the fully opened position for 15 ±0.2 seconds. The unit shall then be reweighed and the loss in weight taken as the delivery rate.

4.6.8.2 Product. The spray unit fully assembled with jar filled with the test solution specified in 4.5.2 shall be weighed. The valve shall be actuated to cause the maximum delivery of propellant for 15 ± 0.2 seconds. The unit shall then be reweighed. The product delivery rate shall be taken as the loss in weight minus the reported average propellant discharge rate that was determined in 4.6.8.1 for that unit.

4.6.8.3 Spraying efficiency. The spraying efficiency will be the product delivery rate divided by the propellant delivery rate.

4.6.9 Spraying properties. The spray unit assembled with propellant can and with jar filled with the test solution specified in 4.5.2 shall be used in this test. A 4 by 12 inch steel panel fabricated, prepared, and cleaned in accordance with Method No. 2011 of FED-STD-141 shall be set at an angle of 15 degrees from the vertical. The spray unit shall be held vertical at a distance of 8 inches from the panel with the valve open. The spray unit shall be moved from one edge of the panel to the other, making only one pass over the panel at the rate of 10 inches per second. The panel shall then be laid in a horizontal position to dry for 15 minutes, and then examined for compliance with the requirements. The coating on the panel shall be a smooth, unbroken strip at least 1-1/2 inches wide. Overspray in either side of the strip shall not be considered detrimental.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T14:00Z
Check the source to verify that this is the current version before use.

4.6.10 Continuous discharge. The spray unit assembled with a loaded propellant can and jar filled with the test solution specified in 4.5.2 shall be continuously operated for at least one minute. Sputtering or loss of the spray during this period shall be cause for rejection.

4.6.11 Leakage.

4.6.11.1 Static. The spray unit assembled with a loaded propellant can shall be completely submerged for 1 minute in a water-wetting agent solution maintained at 73° ± 3.5°F after which it shall be observed for a period of five minutes. The emission of bubbles from any part of the spray unit during the observation period shall be considered as evidence of leakage.

4.6.11.2 Dynamic. The spray unit assembled as for the "Static test" shall be submerged with only the spray head extending out of the water treated and maintained as in 4.6.11.1. The partially submerged spray unit shall be operated continuously for one minute. The emission of bubbles from any part of the spray unit shall be considered as evidence of leakage.

4.6.12 Propellant can pressure. The can pressure shall be measured by means of a standard test gage fitted with a suitable adapter.

5. PACKAGING

5.1 Preservation. Preservation shall be Level A or C as specified in the contract or order (see 6.2).

5.1.1 Level A. The component parts of the spray kit, consisting of 2 spray devices, 10 propellant cans, 4 product jars with lid, and 20 dip tubes cut to length, shall be unit packaged in a suitable box conforming to PPP-B-636 or PPP-B-665. The interior of the box shall be suitably partitioned to form compartments. Components shall be snugly packed in their compartments to prevent shifting. Provisions shall be made to provide valve protection against discharge or damage, where necessary.

5.1.2 Level C. The spray kit shall be packaged in a manner which will afford adequate protection against corrosion, deterioration, and damage during shipment from the supply source to the first receiving activity. The supplier's commercial practice will be acceptable when it fulfills the above requirements.

5.2 Packing. Packing shall be Level A, B or C as specified in the contract or order (see 6.2). Containers or method of shipment shall comply with Department of Transportation Regulations, or other carrier regulations applicable to the mode of transportation. The gross weight shall be within the weight limitations specified in the applicable box specification.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T14:00Z
Check the source to verify that this is the current version before use.

5.2.1 Level A. Spray kits packaged as specified in 5.1.1 shall be packed in overseas type exterior containers conforming to PPP-B-621 or PPP-B-601, and the appendixes thereto.

5.2.2 Level B. Spray kits packaged as specified in 5.1.1 shall be packed in domestic type containers conforming to PPP-B-576, PPP-B-591, PPP-B-621, PPP-B-601 or PPP-B-636, Class 2, Grade 3 and the appendixes thereto. For Army procurement containers conforming to domestic type fiberboard shall not be used.

5.2.3 Level C. Spray kits shall be packed in a manner to ensure safe delivery and acceptance at destination.

5.3 Marking.

5.3.1 Packages and shipping containers. Packages and shipping containers shall be marked in accordance with MIL-STD-129 and Department of Transportation Regulations, and shall include the following information:

Title, number, and date of this specification
Contract or order
Name of contractor (if different from manufacturer)
Date of manufacture (loading date of propellant can)

5.3.1.1 Precautionary marking. Packages and shipping containers shall be marked as follows:

WARNING

Contents in pressurized containers.
Do not store in temperatures above 120°F.
Keep away from direct sunlight, radiators,
stoves, hot water, and other heat sources.

5.3.1.2 Type II propellants. Packages and shipping containers shall be marked with the following:

WARNING: FLAMMABLE
Contents of pressurized
container is flammable

5.3.2 Propellant can. The propellant cans shall be durably and legibly marked on the main panel of the body by lithographing or silk screening with a noncorrosive, petroleum-resistant, waterproof marking which will not smear or rub off. Each can shall be marked with the manufacturer's name and instructions for assembly, operation of the spray unit, and cleaning of the spray nozzle and the following:

Source: https://assist.dla.mil -- Downloaded: 20260-19T14:00Z
Check the source to verify that this is the current version before use.

5.3.2.1 Type I.

TYPE I PROPELLANT
CONTENTS NOT FLAMMABLE
CONTAINS (For Class 22 - hydrofluorocarbons;
For Class 134A - Hydrofluorocarbons)
Net weight - (For Class 22 - 340 grams;
For Class 134A - 330 grams)

5.3.2.2 Type II.

TYPE II PROPELLANT
CONTENTS FLAMMABLE
CONTAINS: Hydrocarbon solvents
NET WEIGHT 184 grams

5.3.2.3 Precautionary markings. Precautionary markings on propellant can shall be as follows:

CAUTION: If contents in product jar is toxic or flammable, spray only in a well-ventilated room; keep away from any open flame. Observe all cautions and notices on bulk product packages.

WARNING: Propellant is under 69 pounds pressure at 70° F. Do not expose to high temperatures. Do not store at temperatures exceeding 120°F. Keep away from direct sunlight, radiators, stoves, hot water, and other heat. Do not puncture or incinerate can.

6. NOTES

(This section contains information of a general or explanatory nature that may be helpful, but is not mandatory.)

6.1 Intended use. The spray kit described in this specification is intended for use where small quantities of materials are required in the maintenance of missiles, aircraft, rockets, and their components. These kits may also be utilized in fleet operating and maintenance squadrons, especially where stocking and storage space is limited. These kits may be used for spray application of light and medium viscosity materials. Such materials as enamels, primers, rust-preventives, lacquers, acrylic cleaners, and defogging compounds, may be applied by the spray units described herein.

6.2 Acquisition requirements. Acquisition documents must specify the following:

a. Title, number, and date of this specification.

Source: https://assist.dla.mil -- Downloaded: 202610-19T14:00Z
Check the source to verify that this is the current version before use.

b. Issue of DODISS to be cited in the solicitation and if required, the specific issue of individual documents referenced (see 2.1.1).

c. Number of kits required (see 3.2).

d. Type and class (if applicable) of propellant (see 1.2).

e. Selection of applicable level of preservation and packaging (see 5.1 and 5.2).

f. Labeling of other special marking required (see 5.3).

g. Whether first article inspection is required.

6.3 First article. When first article inspection is required, the contracting officer should provide specific guidance to offerors whether the item(s) should be a preproduction sample, a first article sample, a first production item, a sample selected from the first production items, a standard production item from the contractor's current inventory, and the number of items to be tested as specified in 4.3.1. The contracting officer should also include specific instructions in acquisition documents regarding arrangements for examinations, approval of first article test results, and disposition of first articles. Invitations for bids should provide that the Government reserves the right to waive the requirement for samples for first article inspection to those bidders offering a product which has been previously acquired or tested by the Government, and that bidders offering such products, who wish to rely on such production or test, must furnish evidence with the bid that prior Government approval is presently appropriate for the pending contract. Bidders should not submit alternate bids unless specifically requested to do so in the solicitation.

6.4 Product retest after failure. In the case of failure of the sample or samples submitted, consideration will be given to the request of the manufacturer for additional tests only after it has been clearly shown that changes have been made in the product which the Government considers sufficient to warrant additional tests, and a new designation is given the material by the manufacturer.

6.5 Consideration of data requirements. The following data requirements should be considered when this specification is applied on a contract. The applicable Data Item Descriptions (DID's) should be reviewed in conjunction with the specific acquisition to ensure that only essential data are requested/provided and that the DID's are tailored to reflect the requirements of the specific acquisition. To ensure correct contractual application of the data requirements, a Contract Data Requirements List (DD Form 1423) must be prepared to obtain the data, except where DOD FAR Supplement 27.475-1 exempts the requirement for a DOD Form 1423.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T14:00Z
Check the source to verify that this is the current version before use.

Reference Paragraph	DID Number	DID Title	Suggested Tailoring
4.4.1.1	DI-NDTI-80809A	Test/Inspection Report	

The above DID's were those cleared as of the date of this solicitation. The current issue of DOD 5010.12-L, Acquisition Management Systems and Data Requirements Control List (AMSDL), must be researched to ensure that only current, cleared DID's are cited on the DD Form 1423.

6.6 Definitive specification part number. The specification part number is a definitive part number which will be formulated to identify each type and class, item covered by this specification. The part number will be formulated by selecting from the requirements to options available in this specification as follows:

M22805 - X - X

- X (last): Class 22 or 134A (For Type I only; use numeric "0" for Type II)
- X (middle): Type (1 for Type I; 2 - for Type II)
- M22805: Military specification

Example: Type I, Class 22 shall be identified as M22805-1-22. Type II shall be identified as M22805-2-0.

6.7 DOT immersion test. It is to be noted that section 173.306 of the Department of Transportation Regulations specifies that each completed metal container filled for shipment must be heated until contents reach a minimum temperature of 130°F without evidence of leakage, distortion, or other defects.

6.8 Subject term (key word) listing.

Dip tube
HCFC propellant
HFC propellant
Hydrocarbon propellant
Pressurized containers
Propellant can
Spray nozzle

6.9 Changes from previous issue. Asterisks are not used in this revision to identify changes with respect to the previous issue due to the extensiveness of the changes.

Source: https://assist.dla.mil -- Downloaded: 202610-19T14:00Z
Check the source to verify that this is the current version before use.

Custodians:
Army - AL
Navy - AS
Air Force - 99

Review Activities:
Navy - OS
Air Force - 82
DLA - CS

User Activities:
Army - AV, ER
Navy - YD, SH

Preparing Activity:
Navy - AS

(Project No. 4940-0651)

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T14:00Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

INSTRUCTIONS

1. The preparing activity must complete blocks 1, 2, 3, and 8. In block 1, both the document number and revision letter should be given.
2. The submitter of this form must complete blocks 4, 5, 6, and 7.
3. The preparing activity must provide a reply within 30 days from receipt of the form.

NOTE: This form may not be used to request copies of documents, nor to request waivers, or clarification of requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements.

I RECOMMEND A CHANGE:	1. DOCUMENT NUMBER MIL-S-22805B	2. DOCUMENT DATE (YYMMDD) 93/03/31

3. DOCUMENT TITLE
SPRAY KIT, SELF PRESSURIZED

4. NATURE OF CHANGE (Identify paragraph number and include proposed rewrite, if possible. Attach extra sheets as needed.)

5. REASON FOR RECOMMENDATION

6. SUBMITTER

a. NAME (Last, First, Middle Initial)	b. ORGANIZATION	
c. ADDRESS (Include Zip Code)	d. TELEPHONE (Include Area Code) (1) Commercial (2) AUTOVON (If applicable)	7. DATE SUBMITTED (YYMMDD)

8. PREPARING ACTIVITY

a. NAME COMMANDING OFFICER, NAVAL AIR WARFARE CENTER AIRCRAFT DIVISION LAKEHURST SYSTEMS REQUIREMENTS DEPARTMENT	b. TELEPHONE (Include Area Code) (1) Commercial: (908) 323-7488 (2) AUTOVON: 624-7488
c. ADDRESS (Include Zip Code) CODE SR3 LAKEHURST, NJ 08733-5100	IF YOU DO NOT RECEIVE A REPLY WITHIN 45 DAYS, CONTACT: Defense Quality and Standardization Office 5203 Leesburg Pike, Suite 1403, Falls Church, VA 22041-3466 Telephone (703) 756-2340 AUTOVON 289-2340

Source: https://assist.dla.mil -- Downloaded: 20261019T14:00Z
Check the source to verify that this is the current version before use.