INCH-POUND

MIL-T-22821/1B
28 November 1990
SUPERSEDING
MIL-T-22821/1A
15 August 1968

MILITARY SPECIFICATION SHEET

TACHOMETER GENERATOR, TYPE 15IH4A (HEAT COMPENSATED)

This specification is approved for use by all Departments and Agencies of the Department of Defense. The requirements for acquiring the Tachometer Generators described herein shall consist of this specification sheet and the issue of the following specification listed in that issue of the Department of Defense Index of Specifications and Standards cited in the solicitation: MIL-T-22821.

TABLE I. Requirements.

Requirement	Value	Unit	Tolerance
Frequency:			
Heater winding, test	400	Hz	± 5%
Energizing winding, test	400	Hz	± 1%
Voltage:			
Heater winding, test	115	volts	± 1%
Energizing winding, test	115	volts	± 1%
Current:			
Heater winding	260	milliamps	maximum
Energizing winding	86	milliamps	maximum
Power:			
Heater winding	30	watts	maximum
Energizing winding	6.5	watts	maximum
In-phase speed sensitive TR	0.07170	ratio	± 2.5%
Phase shift	0	degrees	± 45 minutes
In-phase linearity	0.5	percent	———
In-phase axis error	± 8	millivolts	maximum
Zero speed output voltages:			
Total rms	13	millivolts	maximum
Fundamental rms	10	millivolts	maximum
Voltage sensitivity (energizing winding)			
Linearity (115 V ± 10% range)	0.5	percent	maximum
In-phase TR at 115 V ± 10%	< or = to 1%	———	maximum

AMSC - N/A

FSC 6680

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T14:04Z
Check the source to verify that this is the current version before use.

TABLE I. Requirements - Continued.

Requirement	Value	Unit	Tolerance
Normal operating temperature	-55 to 100	degrees C	maximum
Speed range	0 to 3600	rpm	-------
Calibration speed	3000	rpm	-------
Standard load	open circuit	-------	-------
Temperature sensitivity: (-55 to 100 degree C max. range)			
Linearity (in-phase)	0.5	percent	maximum
In-phase TR (23 ± 2°C)	< or = 2 ± 7%	-------	maximum
Warm-up time (at 23 degrees)	8.0	minutes	maximum
Temperature rise	100	degrees	maximum
Rotor moment of inertia	2.1	gm-cm^2	maximum
Radial play	0.0008	inches	maximum
End play	0.0010-0.0035	inches	min.-max.
Weight	9.4	ounces	maximum

TABLE II. Part identifying number variant characteristics.

Part identifying number 1/	Shaft Style	Termination	G
M22821/1-01A	Splined	Terminal Board	2.687

1/Part identifying number M22821/1-01A shall be the NATO standard.

1/The suffix letter following the numerical dash number corresponds to the latest modification letter in the type designation.

TABLE III. Part identifying number cross references. 1/

SUPERSEDED PART NUMBERS	NEW PART IDENTIFYING NUMBERS
BUORD Drawing 675061	
BUORD MK 12 Mod 0	M22821/1-01A

1/All line items shown in Table III refer to equivalent and interchangeable tachometer generators of the same type designation modification. Part number changes do not affect form, fit or function of the tachometer generators listed therein.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T14:04Z
Check the source to verify that this is the current version before use.

Custodians:
Army - AR
Navy - AS

Review Activities:
Air Force - 99
DLA - ES, GS

User Activities:
Navy - MC, CG

Preparing Activity:
Navy - AS

(Project 6680-0218-01)

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T14:04Z
Check the source to verify that this is the current version before use.