INCH-POUND

MIL-T-22821/2C
28 November 1990
SUPERSEDING
MIL-T-22821/2B
7 May 1971

MILITARY SPECIFICATION SHEET

TACHOMETER GENERATOR, TYPE 15RG4A

This specification is approved for use by all Departments and Agencies of the Department of Defense. The requirements for acquiring the Tachometer Generators described herein shall consist of this specification sheet and the issue of the following specification listed in that issue of the Department of Defense Index of Specifications and Standards (DODISS) cited in the solicitation: MIL-T-22821.

TABLE I. Requirements.

Requirement	Value	Unit	Tolerance
Frequency:			
Energizing winding, test	400	Hz	± 1%
Energizing winding, range	400	Hz	± 5%
Voltage:			
Energizing winding, test	115	volts	± 1%
Energizing winding, range	115	volts	± 10%
Current:			
Energizing winding	0.09	amps	maximum
Power:			
Energizing winding	5.4	watts	maximum
Power factor:			
Energizing winding	0.64	——	± 0.1
Impedance:			
Energizing winding	1575	ohms	minimum
Output winding	3400	ohms	minimum
In-phase speed sensitive T.R. (at 3000 rpm)	0.0829	——	± 2.5%
Phase shift (at 3000 rpm)	7.0 (lag)	degrees	± 1.5
In-phase linearity	± 0.8	percent	——
In-phase axis error	0.010	volts	maximum
Zero speed output voltage:			
Total	0.015	volts	maximum
Fundamental	0.010	volts	maximum
Normal operating temperature	23.0	degrees C	± 5

AMSC - N/A

FSC 6680

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T14:04Z
Check the source to verify that this is the current version before use.

TABLE I. Requirements - Continued.

Requirement	Value	Unit	Tolerance
Speed range	0-3600	rpm	———
Calibration speed	3000	rpm	———
Standard load	open circuit	———	———
Temperature rise	75	degrees C	maximum
Rotor moment of inertia	2.1	gm-cm^2	maximum
Radial play	0.0008	inches	maximum
End play	0.0010-0.0045	inches	min.-max.
Weight	7.5	ounces	maximum

TABLE II. Part identifying number variant characteristics.

Part identifying number 1/	Shaft Style	Termination	G
M22821/2-01A	Splined	Terminal Board	2.069

1/Part identifying number M22821/2-01A shall be the NATO standard.

1/The suffix letter following the numerical dash number corresponds to the latest modification letter in the type designation.

TABLE III. Part identifying number cross references. 1/

SUPERSEDED PART NUMBERS	NEW PART IDENTIFYING NUMBERS
BUORD Drawing 979431	
BUORD MK 1 Mod 1	M22821/2-01A

1/All line items shown in Table III refer to equivalent and interchangeable tachometer generators of the same type designation modification. Part number changes do not affect form, fit or function of the tachometer generators listed therein.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T14:04Z
Check the source to verify that this is the current version before use.

Custodians:
Army - AR
Navy - AS

Review Activities:
Air Force - 99
DLA - ES, GS

User Activities:
Navy - MC, OG

Preparing Activity:
Navy - AS

(Project 6680-0218-02)

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T14:04Z
Check the source to verify that this is the current version before use.