INCH-POUND


MIL-PRF-39012/13C
16 July 2016
SUPERSEDING
MIL-C-39012/13B
18 September 1977

PERFORMANCE SPECIFICATION SHEET

CONNECTORS, COAXIAL, RADIO FREQUENCY, SERIES C (UNCABLED-RECEPTACLE, FEMALE, JAM NUT MOUNTED, FRONT MOUNTED, PRESSURIZED, CLASS 2)

This specification is approved for use by all Departments and Agencies of the Department of Defense.

The complete requirements for procuring the connectors described herein shall consist of this document and the latest issue of Specification MIL-PRF-39012.



INCHES	MM	INCHES	MM	INCHES	MM
.022	.56	.375	9.52	.590	14.99
.045	1.14	.380	9.65	.600	15.24
.094	2.39	.385	9.78	.650	16.51
.119	3.02	.495	12.57	.830	21.08
.153	3.89	.505	12.83	.846	21.49
.156	3.96	.508	12.90	1.231	31.27
.158	4.01	.570	14.48	1.281	32.54


NOTES:
1. Dimensions are in inches. Metric equivalents are given for general information only.
2. All undimensioned pictorial configurations are for reference purposes only.
3. Full threads to within .063 (1.60 mm) of shoulder; 1 ½ maximum uneven threads to shoulder.
4. Orientation of bayonet studs and mounting flats shall be within 3” of that shown.

FIGURE 1. General configuration.

AMSC N/A

FSC 5935

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T16:43Z
Check the source to verify that this is the current version before use.



INCHES	MM	INCHES	MM
.005	.13	.313	7.95
.007	.18	.332	8.43
.088	2.24	.338	8.59
.098	2.49	.374	9.50
.100	2.54	.411	10.44
.119	3.02	.415	10.54
.124	3.15	.440	11.18
.190	4.83	.450	11.43
.272	6.91	.485	12.32
.273	6.93	.495	12.57
.300	7.62	.530	13.46
.303	7.70	.540	13.72
.307	7.80	.590	14.99
.309	7.85	.600	15.24

NOTES:
1. Dimensions are in inches.
2. Metric equivalents are given for general information only and are based upon 1.00 inch = 25.4 mm.
3. All undimensioned pictorial configurations are for reference purposes only.

FIGURE 2. Mating dimensions for female terminations.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T16:43Z
Check the source to verify that this is the current version before use.

TABLE I. Group qualification.

Group	Submission and qualification of the following connector	Qualifies the following connector
I	M39012/13-0001	M39012/13-0001

ENGINEERING DATA:

Nominal impedance: 50 ohms.

Frequency range: 0 to 11,000 MHz.

Voltage rating: 1,000 volts rms maximum working voltage at sea level. 250 volts rms maximum at 70,000 feet.

Temperature rating: -65°C to +165°C.

REQUIREMENTS:

Dimensions and configuration: See figure 1.

Force to engage and disengage:
Longitudinal force – 4 ½ lbs maximum.
Torque – 4 inch pounds maximum.

Coupling proof torque: Not applicable.

Inspection conditions: Coupling torque not applicable.

Mating characteristics:
See figure 2 for dimensions.
Center contact (female):
Oversize test pin - .098 diameter minimum (non-closed entry contacts only).
Insertion depth - .125 minimum.
Number of insertions – 1.

Insertion force test – Steel test pin dia .092 minimum.
Test pin finish – 16 microinches.
Insertion force – 2 lbs maximum.

Withdrawal force test: Steel test pin dia .090 maximum.
Withdrawal force – 2 ounces minimum.
Test pin finish – 16 microinches.

Hermetic seal: Not applicable.

Leakage (pressurized connectors):
Connectors shall be mounted in mounting hole shown on figure 1 with mating end capped. Test applicable to mounting seal only. Air pressure – 30 psi. Duration – 30 seconds minimum, 2 minutes maximum.

Insulation resistance: MIL-STD-202-302, test condition B. 5,000 megohms minimum.

Center contact retention: 6 lbs minimum axial force.

Corrosion (salt spray): MIL-STD-202-101, test condition B.

Voltage standing wave ratio (VSWR): Not applicable.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T16:43Z
Check the source to verify that this is the current version before use.

Swept frequency VSWR test setup: Not applicable.

Connector durability:
500 cycles at 12 cycles/minute maximum.
The connector shall meet mating characteristics and force to engage and disengage requirements.

Contact resistance: In milliohms maximum.

	Initial	After environment
Center contact	1.0	1.5
Outer contact	.15	Not applicable

Dielectric withstanding voltage: MIL-STD-202-301. 3,000 volts rms at sea level.

Vibration, high frequency: MIL-STD-202-204, test condition B.

Shock: MIL-STD-202-213, test condition I.

Temperature cycling: MIL-STD-202-107, test condition B, except test high temperature shall be +200°C.

Thermal shock: Not applicable.

Moisture resistance: MIL-STD-202-106. No measurements at high humidity. Insulation resistance shall be at least 200 megohms within 5 minutes after removal from humidity.

Corona level:
Altitude – 70,000 feet.
Voltage – 750 volts rms minimum.

RF high potential withstanding voltage:
Voltage and frequency – 2,500 volts rms at 5 to 7.5 MHz.
Leakage current – Not applicable.

Cable retention force: Not applicable.

Coupling mechanism retention force: Not applicable.

RF leakage: Not applicable.

Insertion loss: Not applicable.

Part number: M39012/13-0001.

TABLE II. Cross reference of part numbers.

Part number	Substitute for part number or type designation 1/
M39012/13-0001	UG-706/U

1/ The superseded part number or the type designation is for cross-reference only. The part number M39012/13-XXXX shall be used in all cases for marking and identifying the connector.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T16:43Z
Check the source to verify that this is the current version before use.

Changes from previous issues. Marginal notations are not used in this revision to identify changes with respect to the previous issue due to the extent of the changes.

Referenced documents. In addition to MIL-PRF-39012, this document references the following:

MIL-STD-202-101
MIL-STD-202-106
MIL-STD-202-107
MIL-STD-202-204
MIL-STD-202-213
MIL-STD-202-301
MIL-STD-202-302

CONCLUDING MATERIAL

Custodians:
Army – CR
Navy – EC
Air Force – 85
DLA – CC

Preparing activity:
DLA – CC

(Project 5935-2016-086)

Review activities:
Army – AM, AT, CR4, MI
Navy – AS, MC, OS, SH
Air Force – 19, 99

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at https://assist.dla.mil.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T16:43Z
Check the source to verify that this is the current version before use.