INCH-POUND


MIL-PRF-39012/16H
w/AMENDMENT 2
03 January 2017
SUPERSEDING
MIL-PRF-39012/16H
w/AMENDMENT 1
20 April 2009

PERFORMANCE SPECIFICATION SHEET

CONNECTORS, PLUGS, ELECTRICAL, COAXIAL RADIO FREQUENCY, (SERIES BNC (CABLED), PIN CONTACT, CLASS 2)

This specification is approved for use by all Departments and Agencies of the Department of Defense.


The requirements for acquiring the product described herein shall consist of this specification sheet and MIL-PRF-39012.



NOTES:
1. Dimensions are in inches. Metric equivalents are given for information only.
2. For dimension A, see tables I and III.
3. Dimension .593 inch (15.06 mm) is the largest overall diameter of the connector.
4. Wrench flats are to accommodate standard wrench opening in accordance with FED-STD-H28, appendix 10.
5. All undimensioned pictorial representations are for reference purposes only.
6. Dimension A defines the maximum length of the connector when assembled to the appropriate cable.
7. Series BNC, pin contact interface in accordance with MIL-STD-348.

FIGURE 1. General configuration.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T16:43Z
Check the source to verify that this is the current version before use.



Inches	mm
.002	0.05
.010	0.20
.015	0.38
.036	0.91
.077	1.96
.267	6.78

NOTES:
1. Dimensions are in inches. Metric equivalents are given for information only.
2. In the mated condition, the longitudinal force of the spring of the coupling mechanism shall exceed the pressure exerted bed the sealing gasket by an amount necessary to insure butting of the outer contacts at the reference plane.
3. Chamfer is optional.

FIGURE 2. Category D captivation detail.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T16:43Z
Check the source to verify that this is the current version before use.

TABLE I. Dash numbers, cross reference, and dimensions.

Part or Identifying Number (PIN) 1/ M39012/16-	Applicable cable 2/ M17/	Dimensions	Inches (millimeters) maximum #
Category A – Field serviceable (no special tools required) 3/			
X101 (superseding –X111 4/)	Cable group VI 60-RG142 5/ 128-RG400 6/	A	1.250 (31.75)
X102 (Superseding –0118 4/)	Cable group VII 110-RG302 5/ 6/ 7/		
X103	Cable group IV 54-RG122 6/		
X220	Cable group II 113-RG316 5/ 6/		
X225 Cable group X	Cable group X 127-RG393 5/ 6/	A	1.739 (44.17)
Category C – field replaceable (MIL-DTL-22520 crimp tool) See note next to applicable cable for crimp die 3/ 8/			
X013	Cable group VIA 9/ 111-RG305 5/ 6/	A	1.500 (38.10)
X014	Cable group VIB 9/ 60-RG142 5/ 128-RG400 6/		
X015 (Superseding –X220 4/)	Cable group VIIA 10/ 110-RG302 5/ 6/ 7/		

See notes at end of table.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T16:43Z
Check the source to verify that this is the current version before use.

TABLE I. Dash numbers, cross reference, and dimensions – Continued.

PIN 1/ M39012/16-	Applicable cable 2/ M17/	Dimensions	Inches (millimeters) maximum #
Category C – field replaceable (MIL-DTL-22520 crimp tool) See note next to applicable cable for crimp die 3/ 8/			
X016	Cable group IV 11/ 54-RG122 6/	A	1.500 (38.10)
X017	Cable group VIIB 10/ 90-RG71 6/ 7/		
X222	Cable group IIA 12/ 113-RG316 5/ 6/ 12/		
Category D – Field replaceable – Defined piece part 3/ 8/ 13/			
X501	Cable group IV 54-RG122 6/	A	1.500 (38.10)
X502	Cable group V 95-RG180 5/ 6/ 7/		
X503 Cable group VIB	Cable group VIB 60-RG142 5/ 128-RG400 6/		
X504	Cable group VIA 111-RG303 5/ 6/		


1/ For cross-reference of dash number to superseded PIN or designation, see table IV.
2/ The latest version of each cable shall be applicable.
3/ These connectors have captivated center contacts.
4/ The superseded PIN is **NOT** acceptable for Government use.
5/ Cable to be used for the +200°C temperature cycling tests. This cable can be used for tests with the approval of the Qualifying Activity.
6/ Cable to be used when performing test requiring cable except as in 5/ and 7/.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T16:43Z
Check the source to verify that this is the current version before use.

TABLE I. Dash numbers, cross reference, and dimensions – Continued.

7/ These are not 50-ohm cables; therefore, when attached to the specified connectors, VSWR, RF, leakage and insertion toss are not applicable.
8/ These connectors are assembled using the applicable crimp tool, to the specified cables stripped as shown on figure 4.
9/ M22520/5-19 closure B or MS22520/5-05 closure A.
M22520/5-11 closure A.
M22520/5-57 closure A.
10/ M22520/5-19 closure A or M22520/5-07 closure A.
M22520/5-13 closure A.
M22520/5-59 closure A.
11/ M22520/5-41 closure B or M22520/5-05 closure B.
M22520/5-09 closure A.
12/ M22520/5-35 closure B or M22520/5-03 closure A.
13/ Complete connector assembly shall consist of a body, center contact, ferrule and assembly instructions.
Dimensions are in inches. Metric equivalents are given for information only.
X Denotes connector body plating material option. The only plating options allowable are Silver or Nickel over brass in accordance with MIL-PRF-39012. Only connectors of the same materials shall be mated to avoid dissimilar metal problems. **CAUTION: A NICKEL PLATED BODY IS NOT FOR USE IN APPLICATIONS WHERE PASSIVE INTERMODULATION GENERATION (PIM) MAY BE A CONCERN (http://amphenolrf.com/simple/PIM%20Paper.pdf).** Silver is the preferred plating.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T16:43Z
Check the source to verify that this is the current version before use.



CENTER CONTACT


Inches	mm	Inches	mm	Inches	mm	Inches	mm
.001	0.03	.033	0.84	.145	3.68	.220	5.59
,002	0.05	.035	0.89	.175	4.45	.230	5.84
.003	0.08	.040	1.02	.183	4.65	.235	5.97
.005	0.13	.043	1.09	.206	5.23	.245	6.22
.015	0.38	.067	1.70	.210	5.33	.250	6.35
.017	0.43	.083	2.11	.212	5.38	.478	12.14
						.500	12.70

Dash no.	Contact no. 1/	A +0.001 -0.002	B	Basic crimp tool 2/	Crimp die or positioner	Crimp tensile pounds min. (N)	Color band □	Color band ○
X501	16 – 12	0.033	.005 +.003 -.000 x 45°	M22520/1-01	M22520/1-12	10 lbs (44.48)	Orn	Yellow
X502	16 – 11	0.017	.005 +.003 .- 000 x 30°			6 lbs (26.69)	Blue	
X503 X504	16 – 10	0.043	.005 +.003 -.000 x 45°	M22520/1-01	M22520/1-12	20 lbs (88.96)	Red	

1/ Contact numbers and ferrule numbers are for identification only.
2/ Class 2 tool may be used by OEM (see MIL-DTL-22520).

FIGURE 3. Contact and ferrule dimensions for category D only.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T16:43Z
Check the source to verify that this is the current version before use.



CRIMP FERRULE


Dash number	Ferrule number 1/	A ± 0.003	B ± 0.003	Basic crimp tool 2/	Crimp die or positioner M22520/5
X501 X502	16-50	0.212	0.175	M22520/5-01	-9 Closure A -5 or –41 Closure B
X503	16-51	0.250	0.220		-5, -11, -57 Closure A or –19 Closure B
X504	16-52	0.245	0.206		

1/ Contact numbers and ferrule numbers are for identification only.
2/ Class 2 tool may be used by OEM (see MIL-DTL-22520).

NOTES:
1. Dimensions are in inches. Metric equivalents are given for information only.
2. Crimp tensile test shall be in accordance with SAE-AS39029.
3. Copyright notice: ALL information disclosed in these specification sheets which is or may be copyright is reproduced herein with the express permission of the copyright owner.
4. .003 inch maximum break.
5. Color bands shall be positioned so that no coloring material enters the inspection hole.

FIGURE 3. Contact and ferrule dimensions for category D only – Continued.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T16:43Z
Check the source to verify that this is the current version before use.



Inches	mm
.146	3.71
.166	4.22
.333	8.46
.353	8.97
.427	10.85
.447	11.35
.593	15.06

NOTES:
1. Dimensions are in inches. Metric equivalents are given for information only.

FIGURE 4. Cable stripping dimensions for field replaceable connectors.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T16:43Z
Check the source to verify that this is the current version before use.

ENGINEERING DATA:

Nominal Impedance: 50 ohms.

Frequency range: 0 to 4 GHz.

Voltage rating:

500 volts rms, maximum working voltage at see level.

125 volts rms, maximum at 70,000 feet (4.437 kPa).

Temperature rating; -65°C to +165°C.

REQUIREMENTS:

Design and configurations: See figures 1, 2, 3, and 4.

Force to engage and disengage:

Longitudinal force: 3 pounds (13.34 N), maximum.

Torque: 2.5 inch-pounds (.28 Nm), maximum.

Coupling proof torque: Not applicable.

Inspection conditions: Coupling torque not applicable.

Mating characteristics;

In accordance with MIL-STD-348 and figure 2.

Outer contact:

Test ring ID: .319 inch (8.10 mm) maximum, 16 microinch (0.406 µm) finish.

Insertion force: 5 pounds (22.24 N), maximum when inserted a minimum of .093 inch (2.36 mm).

Contacts with slotted members: Shall contact a .324 inch (8.23 mm), minimum diameter ring within .031 inch (0.79 mm) of their tip ends.

Hermetic seal: Not applicable.

Leakage (pressurized connectors): Not applicable.

Insulation resistance: MIL-STD-202-302, test condition B, 5,000 megohms, minimum.

Center contact retention: 6 pounds (26.69 N) minimum axial force. Applicable to captivated-center-contact connectors only.

Corrosion (salt spray): MIL-STD-202-101, test condition B.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T16:43Z
Check the source to verify that this is the current version before use.

Voltage standing wave ratio (VSWR): From .5 to 4 GHz, or approximately 80 percent of upper cutoff frequency of the cable, whichever is lower; 1.30, maximum.

Swept frequency VSWR test setup:

Item 6: VSWR shall be less than 1.015 + .005 F (F in GHz).

Item 16: VSVR shall be less than 1.015 + .005 F (F in GHz).

Second step of VSWR checkout procedure: VSWR shall be less then 1.045 + .019 F (F in GHz).

Group B inspection; VSWR shall be less than 1.1 +.01 F (F in GHz}.

Qualification and group C inspection: VSWR shall not exceed 1.15.

Connector durability: 500 cycles minimum, at 12 cycles per minute, maximum. The connector shall meet the mating characteristics and force to engage and disengage requirements.

Initial: 5 pounds (22.24 N), maximum.

Final: 5 pounds (22.24 N) maximum; 1 pound (4.45 N), minimum.

Contact resistance: In milliohms, maximum:

	Initial	After environment
Center contact	1.5	2.0
Outer contact (silver)	.2	Not applicable
Outer contact (nickel)	.4	Not applicable
Braid to body	.1	Not applicable

Dielectric withstanding voltage: MIL-STD-202-301, 1,500 volts rms, minimum at sea level.

Vibration, high frequency: MIL-STD-202-204, test condition B. No discontinuity permitted.

Shock: MIL-STD-202-213, test condition G.

Thermal shock: MIL-STD-202-107, test condition B, except test high temperature shall be +85°C. High temperature shall be at +200°C for connectors using +200'C cables (see tables I and III).

Moisture resistance: MIL-STD-202-106. No measurements at high humidity. Insulation resistance shall be at least 200 megohms within 5 minutes after removal from humidity.

Corona Level:

Voltage: 375 volts rms, minimum.

Altitude: 70,000 feet (4.437 kPa).

RF high potential withstanding voltage:

Voltage and frequency: 1,000 volts rms at a frequency from 5 to 7.5 MHz.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T16:43Z
Check the source to verify that this is the current version before use.

Leakage current: Not applicable.

Cable retention force:

Noncrimp assemblies: 40 pounds (177.93 N), minimum.

Crimp assemblies:

10 pounds (44.48 N), minimum for cables .155 - .189 inch (3.94 mm – 4.80 mm) OD.

20 pounds (88.96 N), minimum for cables .190 - .229 inch (4.83 mm – 5.82 mm) OD.

30 pounds (133.45 N), minimum for cables .230 -.249 inch (5.84 mm – 6.32 mm) OD.

40 pounds (177.93 N), minimum for cables .250 inch (6.35 mm) OD and larger.

Coupling mechanism retention force: 100 pounds (444.82 N), minimum.

RF Leakage: -55 dB minimum, tested at a frequency between 2 and 3 GHz.

Insertion loss:

.2 dB maximum tested at 3 GHz.

PIN: M39012/16 (dash number from table I or “B” number from table III).

Group qualification: See table II.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T16:43Z
Check the source to verify that this is the current version before use.

TABLE II. Group qualification. 1/

Group	Submission and qualification of 2/ 3/ any of the following connectors	Qualifies the following connectors
I	M39012/16 -X101 -X103 -X111 -X118 -X220 -X225	M39012/16 -X101 -X102 -X103 -X111 -X118 -X220 -X225
II	-X102	-X102
III	B0004 B0005 B0006 B0007 B0009 B0019	B0004 B0005 B0006 B0007 B0008 B0009 B0012 B0019
IV	B0008 B0012	B0008 B0012
V	-X013 -X014 -X016 -X020 -X222	-X013 -X014 -X015 -X016 -X017 -X020 -X222
VI	-X015 -X017	-X015 -X017
VII	-X501 -X503 -X504	-X501 -X502 -X503 -X504
VIII	-X502	-X502

1/ If a connector manufacturer produces a connector which meets all the requirements for two or more connector PIN's (within the same series), the manufacturer may receive qualification approval for two or more connector PIN's qualifying the one connector. It is not necessary that such connectors be in the same group. Each connector, however, must be marked with its own appropriate PIN. For group qualification, the connectors must be of similar design and be of the same materials and plating.

2/ For qualification retention, where more then one part is listed in a group in this column, data may be supplied on any of those parts in order to retain qualification for those parts in the corresponding right hand column. The part does not necessarily have to be the part initially qualified.

3/ Qualification by similarity may be given for the like styles of currently qualified TNC series connectors with the approval of the qualifying and preparing activity. Similarity will include, cable accommodation, materials and plating, assembly procedures and crimp tools/dies, as a minimum.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T16:43Z
Check the source to verify that this is the current version before use.

TABLE III. Category B – Non-field replaceable (special tools may be required).

.

Not for Air Force, Army, or Navy use. For OEM use only.

Dash number 1/ 2/ 3/	Applicable cable M17/ #	Dimensions	Inches (millimeters) maximum #
M39012/16B0004	28-RG058*	A	1.500 (38.10)
M39012/16B0005	84-RG223*		
M39012/16B0006	111-RG303*		
M39012/16B0007	60-RG142*@		
M39012/16B0008	29-RG59*^ 30-RG062 ^ 97-RG210 ^		
M39012/16B0009	54-RG122*		
M39012/16B0012	90-RG71*^		
M39012/16B0019	110-RG302^ * @		

1/ For cross-reference of dash number to superseded PIN or type designation, see table IV.
2/ For maintenance replacements for category B, see table V.
3/ Inactive for new design.
The latest version of each cable shall be applicable.
* Cable to be used when performing tests requiring cable except as in notes @ and ^.
@ Cable to be used for the +200°C temperature cycling tests. This cable can be used for tests with the approval of the Qualifying Activity.
^ These are not 50 ohm cables; therefore, when attached to the specified connectors, VSWR, RF leakage, and Insertion loss are not applicable.
Dimensions are in inches. Metric equivalents are given for information only.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T16:43Z
Check the source to verify that this is the current version before use.

TABLE IV. Cross-reference of PIN.

Preferred PIN M39012/16	Substitute for PIN or type designation 1/ 2/
-0101	UG-88/U, M39012/16-0001
-0102	UG-260/U, M39012/16-0002, M39012/16-0018, m39012/16-0118
-0103	UB-1033/U, M39012/16-0003
B0004	M23329/3-01, M39012/16-0004
B0005	M23329/3-02, M39012/16-0005
B0006	M23329/3-03, M39012/16-0006
B0007	M23229/3-04, M39012/16-0007
B0008	M23329/3-05, M39012/16-0008
B0009	M23329/3-06, M39012/16-0009
-0111	M39012/16-0011
B0012	M39012/16-0012
-0013	
-0014	
-0015	
-0016	
-0017	
B0019	M39012/16-0019
-0020	
-0501	
-0502	
-0503	
-0504	
-0225	UG-959/U

1/ The superseded PIN or the type designation is for cross-reference only. Where a superseded PIN or type designation is not given, none was assigned or will be assigned. The PIN M39012/16-XXXX shall be used in all cases for marking and identifying the connector.

2/ The basic type designation includes all letter versions of the specified number, e.g. UG-18/U includes UG-18 A/U, UG-18 B/U, etc.

TABLE V. Maintenance replacements for category B.

Category B number* Inactive for new design	Category C dash number	Category A dash number	Category D dash number
B0004	0013	0101	0504
B0005	0014	0101	---
B0006	0013	0111	---
B0007	0014	0101	0503
B0008	0015	0102	---
B0009	0016	0103	0501
B0012	0017	0102	---
B0019	0020	0118	---

* Category B connectors are for original installation only. They will not be stocked or acquired by the Government.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T16:43Z
Check the source to verify that this is the current version before use.

Amendment notations. The margins of this specification are marked with vertical lines to indicate modifications generated by this amendment. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations.

Referenced documents. In addition to MIL-PRF-39012, this document references the following:

FED-STD-H28
MIL-STD-202-101
MIL-STD-202-106
MIL-STD-202-107
MIL-STD-202-204
MIL-STD-202-213
MIL-STD-202-301
MIL-STD-202-302
MIL-STD-348
MIL-DTL-22520
SAE-AS39029

CONCLUDING MATERIAL

Custodians:
Army - CR
Navy - EC
Air Force – 85
NASA – NA
DLA - CC

Review activities:
Army: - AR, AT, EA, MI
Navy - AS, MC, OS, SH
Air Force - 19, 99

Preparing activity:
DLA-CC

(Project 5935-2016-219)

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at https://assist.dla.mil.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T16:43Z
Check the source to verify that this is the current version before use.