MILITARY SPECIFICATION SHEET

CONNECTORS, COAXIAL, RADIO FREQUENCY
(SERIES N (UNCABLED) - RECEPTACLES - JAM NUT AND
FLANGE MOUNTED, SOCKET CONTACT, CLASS 2)

This amendment forms a part of Military Specification Sheet MIL-C-39012/4C, dated 26 April 1974, and is approved for use by all Departments and Agencies of the Department of Defense.

PAGE 1

FIGURE 1, dash number 0001: Delete ".250 MAX PNL" and substitute ".045 MIN .250 MAX PNL"; and following ".625-24 UNEF-2A", add "(SEE NOTE 7)". Make these same changes on dash number 0003.

FIGURE 1, dash number 0002: Delete ".110 MAX PNL" and substitute ".045 MIN .110 MAX PNL".

PAGE 2

* FIGURE 1, continued: At top of page, delete NOTES 1 through 5. At bottom of page add the following notes:

"7. Full threads to within .063 (1.60 mm) of shoulder; 1 1/2 max uneven threads to shoulder.

8. There shall be a solid barrier in the socket between the pin entry and the solder pocket to prevent solder wicking."

PAGE 3

FIGURE 2, dash number 0003: Delete "PANEL .080 TO .250" and substitute "PANEL .045 TO .250"; and following ".625-24 UNEF-2A", add "(SEE NOTE 4)".

FIGURE 2, NOTES: Add:

"4. Full threads to within .063 (1.60 mm) of shoulder; 1 1/2 max uneven threads to shoulder."

NOTE: The margin of this amendment is marked with an asterisk to indicate where the change from the previous amendment was made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous amendment.

Custodians:
Army - CR
Navy - EC
Air Force - 85

Review activities:
Army - MI
Navy - SH
Air Force - 11, 17, 99
DLA - ES

User activities:
Army - AM, AT, ME
Navy - AS, MC, OS
Air Force - 19

Preparing activity:
Army - CR

Agent:
DLA - ES

(Project 5935-3075-3)

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T16:39Z
Check the source to verify that this is the current version before use.