
INCH-POUND
MIL-PRF-39012/8E
16 January 2015
SUPERSEDING
MIL-PRF-39012/8D
3 October 1986

PERFORMANCE SPECIFICATION SHEET

CONNECTORS, RECEPTACLE, ELECTRICAL, COAXIAL, RADIO FREQUENCY, (SERIES C (CABLED), FEMALE, FLANGE MOUNTED, REAR MOUNTED, CLASS 2)

This specification is approved for use by all Departments and Agencies of the Department of Defense.

The requirements for acquiring the product described herein shall consist of this specification sheet and MIL-PRF-39012.



Inches	mm
.075	1.91
.095	2.41
.188	4.78
.356	9.04
.362	9.19
.497	12.62
.503	12.78
.620	15.75
.630	16.00
.679	17.25
.701	17.81
.714	18.14
.722	18.34
.995	25.27
1.005	25.53

NOTES:
1. Dimensions are in inches.
2. Metric equivalents are given for information only.
3. For dimensions A and B, see tables I and III.
4. Receptacle recommended for component part use on panels with a .090 (2.29mm) maximum thickness.
5. Wrench flats to accommodate standard wrench in accordance with FED-STD-H28.
6. Dimension A defines the maximum length of the connector when assembled to the appropriate cable.
7. All undimensioned pictorial configurations are for reference purposes only.
8. Bayonet studs and edges of flange shall be within 3 inches (7.62cm) of orientation shown.
9. Series C, socket contact interface, in accordance with MIL-STD-348.

FIGURE 1. General Configuration.


Source: https://assist.dla.mil -- Downloaded: 2026-10-21T16:41Z
Check the source to verify that this is the current version before use.

TABLE I. Dash numbers, cross-reference, and dimensions.

Dash Number 4/	Applicable cable M17/ 6/	Typical mating connector M39012/ (optional hardware) 1/	Dimensions	Inches 13/ (millimeters) maximum
CATEGORY A – FIELD SERVICEABLE (NO SPECIAL TOOLS REQUIRED)				
0001 5/	65-RG165 74-RG213 75-RG214 7/ RG-225/U 8/	6-0002 10-0001	A	1.531 (38.89)
0002 5/	73-RG212 7/ 112-RG304	6-0001		
0009 Canceled	74-RG215 10/	6-0013 10-0005	A	2.218 (56.34)
0015	65-RG165 74-RG213 75-RG214 7/ RG-225/U 8/	6-0005	A	1.531 (38.89)
0016 2/	73-RG212 7/ 112-RG304	6-0014		
0017 2/	74-RG215 10/	6-0019	A	2.218 (56.34)
0018 2/	92-RG115 8/	6-0020 10-0009	A	1.531 (38.89)
CATEGORY C – FIELD REPLACEABLE (MIL-DTL-22520 CRIMP TOOL) SEE NOTE NEXT TO APPLICABLE CABLE FOR CRIMP DIE 2/ 3/				
0010	74-RG213 7/ 12/ 65-RG165 7/ 8/ 12/	6-0028 10-0006	A	2.000 (50.80)
0011	75-RG214 7/ 12/	6-0029 10-0007		
0012	RG-225/U 7/ 8/ 12/	6-0030 10-0008		
0013	73-RG212 7/ 11/ 112-RG304 11/	6-0027		
0014	6-RG11 8/ 12/	6-0031		
0024	92-RG115 9/	6-0032		

1/ Optional hardware numbers are in parentheses.
2/ These connectors have captivated center contacts.
3/ Category C connectors are assembled, using the applicable crimp tool, per MIL-DTL-22520 to the specified cable stripped as shown on figure 2.
4/ For cross reference of dash number to superseded Part or Identifying Number (PIN) or type designation, see table IV.
5/ Inactive for new design. Not for Air Force or Navy use.
6/ The RG cables are specified with the basic number. The latest version of each cable shall be applicable..
7/ Cable to be used when performing tests requiring cable except as in 8/ and 9/.
8/ Cable to be used for the +200°C temperature cycling tests.
9/ These are not 50 ohm cables; therefore, when attached to the specified connectors, VSWR, RF leakage and insertion loss are not applicable.
10/ Armored cable.
11/ M22520/5-35 closure A or M22520/5-55 closure A.
12/ M22520/5-61.
13/ Dimensions are in inches. Metric equivalents are given for information only.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T16:41Z
Check the source to verify that this is the current version before use.



Inches	mm
.187	4.75
.396	10.06
.416	10.57
.490	12.45
.510	12.95
.677	17.20
.697	17.70

NOTES:
1. Dimensions are in inches.
2. Metric equivalents are given for information only.

FIGURE 2. Recommended cable stripping dimensions for category C connectors.

ENGINEERING INFORMATION:

Nominal impedance: 50 ohms.

Frequency range: 0 to 11 GHz.

Voltage rating: 1,000 volts rms maximum working voltage at sea level.
250 volts rms maximum at 70,000 feet (4.437 kPa).

Temperature rating: -65°C to +165°C.

REQUIREMENTS:

Dimensions and configuration: See figure 1 and MIL-STD-348.

Force to engage and disengage:

Longitudinal force: 4 1/2 pounds, maximum.

Torque: 4 inch-pounds, maximum (.45 Nm).

Coupling proof torque: Not applicable.

Inspection conditions: Coupling torque not applicable.

Mating characteristics: See MIL-STD-348.

Center contact (female):

Oversize test pin: .098 inch (2.49 mm) diameter, minimum (non-closed entry contacts only).

Insertion depth: .125 inch (3.17 mm), minimum.

Number of insertions: 1

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T16:41Z
Check the source to verify that this is the current version before use.

Insertion force test:

Steel test pin diameter: .092 inch (2.34 mm), minimum.

Test pin finish: 16 microinches (0.406 µm).

Insertion force: 2 pounds (8.90 N), maximum.

Withdrawal force test:

Steel test pin diameter: .090 inch (2.29 mm), maximum.

Withdrawal force: 2 ounce (.56 N), minimum.

Test pin finish: 16 microinches (0.406 µm).

Hermetic seal: Not applicable.

Leakage (pressurized connectors): Not applicable.

Insulation resistance: In accordance with MIL-STD-202, method 302, condition B, 5,000 mega ohms minimum.

Center contact retention: 6 pounds (26.69 N), minimum axial force.

Corrosion (salt spray): In accordance with MIL-STD-202, method 101, condition B.

Voltage standing wave ratio (VSWR): From 500 MHz to 11 GHz, or approximately 80 percent of the upper cutoff frequency of the cable, whichever is lower; 1.35, maximum.

Swept frequency VSWR setup:

Item 6: VSWR shall be less than 1.015 +.005F (F in GHz).

Item 16: VSWR shall be less than 1.015 +.005F (F in GHz).

Second step of VSWR checkout procedure: VSWR shall be less than 1.045 +.015F (F in GHz).

Group B inspection: VSWR shall be less than 1.10 +.01F (F in GHz).

Qualification and group C inspection: VSWR shall not exceed 1.15.

Connector durability: 500 cycles, minimum at 12 cycles per minute, maximum. The connector shall meet mating characteristics and force to engage and disengage requirements.

Contact resistance: In milliohms, maximum:

	Initial	After environment
Center contact:	1.0	1.5
Outer contact:	.35	Not applicable
Braid to body:	.05	Not applicable

Dielectric withstanding voltage at sea level: In accordance with MIL-STD-202, method 301. 3,000 volts rms minimum at sea level.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T16:41Z
Check the source to verify that this is the current version before use.

Vibration, high frequency: In accordance with MIL-STD-202, method 204, test condition B.

Shock: In accordance with MIL-STD-202, method 213, test condition I.

Thermal shock: In accordance with MIL-STD-202, method 107, test condition B, except test high temperature shall be +85°C. High temperature shall be +200°C for connectors using +200°C cables (see tables I and III).

Moisture resistance: In accordance with MIL-STD-202, method 106. No measurements at high humidity. Insulation resistance shall be at least 200 megohms within 5 minutes after removal from humidity.

Corona level:

Voltage: 750 volts rms, minimum.

Altitude: 70,000 feet.

RF high potential withstanding voltage:

Voltage and frequency: 2,500 volts rms tested at a frequency from 5 to 7.5 MHz.

Leakage current: Not applicable.

Cable retention force:

Non-crimp assemblies: 75 pounds (333.62 N), minimum.

Crimp assemblies:

50 lbs. (222.41 N) minimum for cables .155 -.189 inch (3.94 – 4.80 mm) OD.
60 lbs. (266.90 N) minimum for cables .190 - .229 inch (4.83 – 5.82 mm) OD.
75 lbs. (333.62 N) minimum for cables .230 - .249 inch (5.84 – 6.32 mm) OD.
90 lbs. (400.34 N) minimum for cables .250 inch (6.35 mm) OD and larger.

Coupling mechanism retention force: Not applicable.

RF leakage: -55 dB minimum, tested at frequency between 2 and 3 GHz.

RF insertion loss:

.15 dB maximum at 9 GHz.

.05 $\sqrt{F\ (GHz)}$ dB maximum tested at 3 and 6 GHz.

Part or Identifying Number (PIN): M39012/8- (dash number from table I or B number from table III).

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T16:41Z
Check the source to verify that this is the current version before use.

Group qualification: See table II.

TABLE II. Group qualification. 1/

Group	Submission and qualification of any of the following connectors.	Qualifies the following Connectors
I	M39012/8 -0001	M39012/8 -0001 -0002 -0009
II	-0015	-0015 -0016 -0017 -0018
III	B0019	B0019 B0020 B0021 B0022 B0023
IV	-0010	-0010 -0011 -0012 -0013 -0014 -0024

1/ If a connector manufacturer produces a connector which meets all the requirements for two or more connector PIN's (within the same series), the manufacturer may receive qualification approval for two or more connector PIN's by qualifying the one connector. It is not necessary that such connectors be in the same group. Each connector, however, must be marked with its own appropriate PIN. For group qualification, the connectors must be of similar design and be of the same materials and plating.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T16:41Z
Check the source to verify that this is the current version before use.

TABLE III. Category B – non-field replaceable (special tools may be required).

Not for Air Force, Army, or Navy use. For OEM use only.

PIN 2/ 3/ M39012/8	Applicable Cable M17/ 4/	Typical mating connector M39012/ (optional hardware) 1/	Dimensions	Inches 8/ (millimeters) maximum
B0019	74-RG213 5/ 65-RG165	6-0022	A	2.000 (50.80)
B0020	75-RG214	6-0023		
B0021	RG-225/U 5/ 6/	6-0024		
B0022	73-RG212 5/ RG-304/U	6-0021		
B0023	92-RG115 6/	6-0026		

1/ Optional hardware numbers are in parentheses.
2/ These connectors have captivated center contacts.
3/ For cross-reference of PIN to superseded PIN or type designation, see table IV.
4/ The latest version of each cable shall, be applicable.
5/ Cable to be used when performing tests requiring cable except as in 6/ and 7/.
6/ Cable to be used for the +200°C temperature cycling tests.
7/ These are not 50 ohm cables; therefore, when attached to the specified connectors, VSWR, RF leakage, and insertion loss are not applicable.
8/ Dimensions are in inches. Metric equivalents are given for information only.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T16:41Z
Check the source to verify that this is the current version before use.

Supersession data: See table II.

TABLE IV. Supersession data. 1/ 2/

Preferred PIN M39012/8	Superseded PINs or superseded type designation
B0003	UG-1761/U
B0004	UG-1762/U
B0005	UG-1763/U
B0007	UG-1765/U
-0010	M23329/1-11, M23329/1-13
-0011	M23329/1-12
-0012	M23329/1-14
-0013	
-0014	
-0015	M39012/8-0001, UG-571/U
-0016	M39012/8-0002, UG-629/U
-0017	M39012/8-0009
-0018	
B0019	UG-1761/U, M39012/8-0003, M39012/8-0019
B0020	UG-1762/U, M39012/8-0004, M39012/8-0020
B0021	UG-1763/U, M39012/8-0005, M39012/8-0021
B0022	UG-1765/U, M39012/8-0007, M39012/8-0022
B0023	
-0024	M23329/1-15

1/ The superseded PIN or the type designation is for reference only. Where a superseded PIN or type designation is not given, none was assigned or will be assigned. The PIN M39012/7-XXXX shall be used in all cases for marking and identifying the connector.

2/ The basic type designation includes all letter versions of the specified number, e.g. UG-18/U includes UG-18 A/U, UG-18B/U, etc.

Changes from previous issue. Marginal notations are not used in this revision to identify changes with respect to the previous issue due to the extensiveness of the changes.

Referenced documents. In addition to MIL-PRF-39012, this document references the following:

FED-STD-H28
MIL-STD-202
MIL-STD-348
MIL-DTL-22250

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T16:41Z
Check the source to verify that this is the current version before use.

CONCLUDING MATERIAL

Custodians:
Army – CR
Navy – EC
Air Force – 85
DLA - CC

Preparing activity:
DLA - CC

(Project 5935-2015-012)

Review activities:
Army – AT, CR4, MI
Navy – AS, MC, OS, SH
Air Force – 19, 99

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at https://assist.dla.mil .

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T16:41Z
Check the source to verify that this is the current version before use.