MILITARY SPECIFICATION

BLADDER, FLOTATION, MARK 2 MOD 0

1. SCOPE

1.1 Scope. - This specification establishes the requirements for the procurement of Flotation Bladder Mk 2 Mod 0, Bureau of Ordnance LD 288859, which is used to recover submerged Ordnance items.

1.2 Classification. - This flotation bladder is of one type and one class.

2. APPLICABLE DOCUMENTS

2.1 The following specifications, standards, drawings, and publications or such portions thereof as designated herein of the issue in effect on the date of invitation for bids form a part of this specification:

SPECIFICATIONS

FEDERAL

CCC-T-191	Textile Test Methods
PPP-B-621	Boxes, Wood, Nailed and Lock-Corner
PPP-B-636	Boxes, Fiber

MILITARY

MIL-B-131	Barrier Material, Water-Vapor-proof, Flexible

STANDARDS

MILITARY

MIL-STD-105	Sampling Procedures and Tables for Inspection by Attributes

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T09:01Z
Check the source to verify that this is the current version before use.

MIL-STD-129	Marking for Shipment and Storage

DRAWINGS

NAVY DEPARTMENT

BUORD LD No. 288859	Flotation Bladder Mk 2 Mod 0 and all parts and subassemblies listed thereon
DWG. No. 1253025	Segment, Bladder

PUBLICATIONS

BUREAU OF ORDNANCE

OP 400	General Instruction for the Design, Manufacture, and Inspection of Naval Ordnance Equipme

(Copies of specifications, standards, drawings, and publications required by contractors in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

2.2 Other Publications. - The following documents form a part of this specification. Unless otherwise indicated, the issue in effect on date of invitation for bids shall apply.

NATIONAL BUREAU OF STANDARDS PUBLICATIONS

Handbook H28 and 1950 Supplement	Screw thread standards for the Federal Services

(Application for copies should be addressed to the Superintendent of Documents, Government Printing Office, Washington 25, D. C.)

3. REQUIREMENTS

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T09:01Z
Check the source to verify that this is the current version before use.

3.1 Description. - Flotation Bladder Mk 2 Mod 0 is a spherical inflatable float used in the recovery of submerged objects weighing up to 1000 pounds when fully submerged, from depths to 150 feet. It consists of nylon cloth with nylon webbing lifting straps and an inflatable liner of nylon cloth coated on one side with neoprene. This casing and liner are fitted together with a relief and inflation valve which automatically maintains a 3½ psi pressure differential inside the liner by relieving the internal air pressure as the float ascends to the surface. The flotation bladder measures 48 inches in diameter, fully inflated. It is furnished neatly folded in a carrying case which opens automatically upon inflation of the liner.

3.2 General Requirements

3.2.1 Pre-Production Samples. - Unless otherwise specified in the contract or order, pre-production samples of the flotation bladder shall be manufactured using the methods and procedures proposed for the production lot. These samples shall be tested as specified in section 4 herein and are for the purpose of determining that the production item meets the requirements of this specification and the applicable drawings. Provision of samples shall be in accordance with 4.1.2.

3.2.2 Materials. - Unless otherwise specified in the contract, requisition or order, all materials and purchased parts entering into the final assembly of the flotation bladder shall conform strictly to the detailed requirements indicated on the drawings and specifications listed on BUORD LD 288859.

3.2.3 Finishes, Coatings, Construction and Dimensions. - Finishes, coatings, construction and dimensions for the flotation bladder shall be strictly in accordance with the applicable drawings, specifications, and publications listed in BUORD LD 288859.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T09:01Z
Check the source to verify that this is the current version before use.

3.2.4 Moisture, Fungus and Corrosion. - The flotation bladder shall be rendered moisture, fungus and corrosion resistant in accordance with the detail requirements specified in the drawings and specifications listed in BUORD LD 288859.

3.2.5 Marking. - Marking of assemblies, subassemblies and parts shall be in accordance with the applicable drawings listed on BUORD LD 288859.

3.2.6 Interchangeability. - Component parts of assembled units (unless otherwise specified on the applicable drawings) fabricated in strict agreement with their applicable drawings shall assemble with mating components of the unit without selection or fitting. If, during assembly of the fabricated parts of a unit, selection or fitting is required and changes in dimensions are necessary, no changes in the parts as delineated on applicable drawings shall be made without prior revision and correction of the applicable drawings.

3.2.7 Gages. - The contractor shall provide himself with whatever gages are necessary and adequate to insure that the material to which this specification applies will meet the dimensional requirements shown on the applicable drawings. If so stipulated in the contract, order, or requisition, the Government will furnish drawings of pertinent Navy Final Inspection Gages for guidance in the design of the contractor's inspection gages. However, such procedure shall not serve to relieve the contractor of his responsibility in the design and manufacture of such gages as may be required in the satisfactory fulfillment of the contract requirements, but is intended to facilitate acceptance of all components and assemblies by Navy Final Inspection Gages.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T09:01Z
Check the source to verify that this is the current version before use.

3.2.8 Threads. - Unless otherwise specified, all threads shall be in accordance with the National Bureau of Standards Handbook H28 and Supplements thereto. The class or fit for threads shall be as specified on the applicable drawings, the NOT-GO gaging practice shall be as set forth in the supplement to the aforementioned Handbook H28.

3.2.9 Requests for deviation. - Requests for deviation from this specification, applicable drawings, specifications, publications, materials and processes specified herein, shall be as set forth in OP 400.

3.2.10 Conflicting requirements. - Conflicting requirements arising between this specification or any specifications, publications, or drawings listed herein shall be referred in writing to the procuring agency or appointed agent for interpretation and clarification.

3.3 Performance requirements and product characteristics. - The flotation bladder shall meet the following performance requirements and product characteristics.

3.3.1 Design and construction. - The design and construction shall be as shown on the drawings listed on Bureau of Ordnance LD 288859.

3.3.2 Inflation Requirements

3.3.2.1 The inflated flotation bladder shall lift an object that has a submerged weight (negative bouyancy) of 1000 pounds, from a depth of 150 feet of water, when tested in accordance with 4.4.3.1.

3.3.2.2 The carrying case shall open automatically when the bladder is inflated, when tested in accordance with 4.4.3.2.

3.3.2.3 The inflation and relief valve shall automatically maintain an air pressure inside the bladder of 3.5 ± 1.0 psi above the pressure of the surrounding water, when tested in accordance with 4.4.3.3.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T09:01Z
Check the source to verify that this is the current version before use.

3.3.2.4 The loaded bladder shall float at the surface of the water without resubmerging for a period of one hour minimum, when tested in accordance with 4.4.3.4.

3.3.3 Environmental conditions. - The flotation bladder shall operate satisfactorily during and after exposure to the environments described in the following paragraphs.

3.3.3.1 Low temperature. - The flotation bladder shall be subjected to the temperature conditions specified in 4.5.3.1 and shall show no corrosion or damage and shall pass the inflation test of 4.5.3.1. There shall be no leakage causing loss of air pressure. There shall be no tearing or separating of the seams.

3.3.3.2 Humidity. - The flotation bladder shall be subjected to the temperature and humidity conditions specified in 4.5.3.2 and shall show no corrosion or other damage and shall meet the requirements of 3.3.2.

3.3.3.3 Tropical environment. - The flotation bladder shall be exposed to the fungus tests as specified in 4.5.3.3 and shall show no fungus growth, corrosion or other damage and shall meet the requirements of 3.3.2.

3.3.4 The neoprene-coated nylon cloth and seams used for the liner shall be in accordance with BUORD DWG. 1253025 and shall comply with 4.5.2.1 through 4.5.2.11.

4. QUALITY ASSURANCE PROVISIONS AND TEST REQUIREMENTS

4.1 Government inspection. - The Government inspector will make such inspections as are necessary to determine that components and assemblies are in accordance with the requirements of the contract, pertinent drawings and specifications. Unless otherwise specified, these inspections will be conducted in accordance with instructions contained in OP 400.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T09:01Z
Check the source to verify that this is the current version before use.

4.1.1 Sampling. - Unless otherwise specified, and when applicable, the sampling plans and procedures used by the Government inspector in the determination of the acceptability of products submitted by a supplier for Government inspection will be in accordance with the provisions set forth in MIL-STD-105.

4.1.2 Pre-production samples. Unless otherwise specified in the contract or order, pre-production samples of complete flotation bladders, cloth and seams shall be manufactured using the methods and procedures proposed for production. These samples shall be submitted to the Government inspector for inspection, and pre-production tests at an activity designated by the Bureau of Ordnance. The pre-production tests are to determine that the requirements of the contract and this specification are met by the production methods. Further production of the item by the contractor prior to approval by the contracting activity shall be at the contractor's risk. Pre-production samples accepted will be applied as part of the quantity specified by the contract or order.

4.1.2.1 Pre-production sample selection. - Samples for pre-production testing shall be selected as follows:

Five (5) complete flotation bladders, including carrying case, for the tests of 4.4 and 4.5.3.

Five (5) pieces of neoprene-coated inner cloth, each piece containing at least 12 square feet of cloth for the tests of 4.5.2.1 through 4.5.2.10.

Five (5) lengths of cemented and taped seams used in the construction of the bladder, each length being at least two inches wide and at least 48 inches long for the test of 4.5.2.11.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T09:01Z
Check the source to verify that this is the current version before use.

4.1.3 Inspection lot. - An inspection lot is a collection of units of product manufactured or processed under substantially the same conditions and offered for inspection at one time, or during a fixed period of time.

4.1.3.1 Inspection lot size. - The inspection lot size is the number of units of product in an inspection lot. The minimum and maximum inspection lot sizes for inspection purposes are determined by the Government inspector, and may differ from the quantity designated in the contract or order as a lot for shipment, or other purposes.

4.1.4 Periodic production sample. - Unless otherwise specified by the contract or order, a random sample of bladders, cloth and seams will be selected from each grand lot by the Government inspector. These samples will be submitted to an activity designated by the Bureau of Ordnance, for tests to determine compliance of the samples with the requirements of the contract, this specification, and the drawings. A grand lot shall consist of successively produced bladders in the quantity determined by the Government inspector, but not exceeding 300. From each grand lot of 300 to 181, inclusive, samples of five will be selected as specified in 4.1.2.1. When the grand lot size is 180 or less, the size of the sample will be in accordance with the appendix of MIL-STD-105, Table VII, Inspection Level L5, as follows: For grand lots of 66 to 180, the sample size will be three; for 2 to 65, two. For acceptance criteria, see 4.3.2.

4.2 Contractor's inspection. - The contractor shall determine, by whatever means or methods he desires and to the extent necessary, that all supplies and services and parts thereof offered for Government acceptance or delivery conform with the requirements of the contract and all associated applicable documents.

4.3 Classification of tests. - The inspection and testing of the bladder shall be classified as follows:

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T09:01Z
Check the source to verify that this is the current version before use.

4.3.1 Acceptance tests. - These tests are to be accomplished on bladders being submitted for acceptance under contract. Acceptance tests shall be performed by the manufacturer and witnessed by the Government inspector. These tests are defined in 4.4

4.3.2 Pre-production and periodic production tests. - Pre-production and periodic production tests are those which are accomplished on samples selected as specified in 4.1.2 and 4.1.4 which are representative of the production of the bladder after the award of the contract to determine that the lot and production meet the requirements of this specification. These tests are detailed in 4.4 and 4.5. Acceptance shall be based on no defects in a sample. Failure of the material under consideration to comply with these requirements will result in the rejection of the lot or the cessation of production as determined by the procuring activity.

4.4 Acceptance tests

4.4.1 The contractor shall conduct acceptance tests as specified in 4.3.1 to assure that the bladder is in compliance with the requirements of 3.3.2.

4.4.2 Test and inspection equipment and facilities. - Unless otherwise specified in the contract, requisition or order, the manufacturer shall furnish and maintain all necessary test equipment, facilities and personnel for performing all acceptance tests. The test equipment shall be adequate in quantity, and when definite requirements are not specified they shall be of sufficient accuracy and quality to permit performance of the required acceptance tests.

4.4.3 Test procedure

4.4.3.1 Inflation test. - To determine compliance with 3.3.2.1, the sample flotation bladder shall be submerged in a deflated condition and in its carrying case, to a depth of 150 + 5 - 0 feet (or in a test tank capable of producing variable pressure equivalent to 0 to 150 feet of sea water) and attached to a suitable object that has a submerged weight (negative buoyancy) of 1000 pounds. The bladder shall be inflated to operating pressure and shall raise the weight.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T09:01Z
Check the source to verify that this is the current version before use.

4.4.3.2 The carrying case shall open automatically when the bladder is inflated, as specified in 3.3.2.2.

4.4.3.3 The inflation and relief valve shall maintain the air pressure inside the bladder at 3.5 (±1.0) psi above the pressure of the surrounding water as the bladder ascends (or as the pressure in the test tank is reduced) as specified in 3.3.2.3.

4.4.3.4 The bladder shall support its load after breaking the surface (or at zero gage tank pressure), without resubmerging, for a period of one hour minimum, as specified in 3.3.2.4.

4.4.3.5 Acceptance criteria for the inflation test shall be based on Military Standard MIL-STD-105, Inspection Level I, using an AQL Value of 1.0 per cent defective, with acceptance and rejection numbers of 0 and 1, respectively, for sample sizes less than 15.

4.5 Pre-production and periodic production tests.

4.5.1 Cloth and seam tests. - The number of cloth and seam specimens required for the tests of 4.5.2.1 through 4.5.2.11, listed below shall be cut from each sample piece of cloth or seam selected in accordance with 4.1.2.1 and 4.1.4. The average or individual test value, as applicable, obtained for each test is the value to use for a sample; the failure of any specimen to meet any of the requirements of any of the tests shall be cause for rejection of the lot of material represented.

4.5.2 Test procedure.

4.5.2.1 Hydrostatic test. - The hydrostatic test applied to the coated side of the fabric shall be performed according to CCC-T-191, Method 5512, using a Mullen Tester adapted by removing the diaphragm and using water as the liquid. The minimum acceptable pressure for the individual specimen shall be 450 psi with the rubber coating next to the water.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T09:01Z
Check the source to verify that this is the current version before use.

4.5.2.2 Blocking test. - The blocking test shall be performed according to CCC-T-191, Method 5872. The specimen shall show no evidence of blocking as described in CCC-T-191, Method 5872.

4.5.2.3 Flexibility test. - From each sample piece of cloth, two strip specimens shall be cut parallel to the warp threads and two strip specimens shall be cut parallel to the filling threads. The minimum stiffness value for the specimen shall be 3.25 inches in the warp direction and 3.5 inches in the fill direction.

4.5.2.4 Flexibility after heat treatment. - The change in stiffness shall be determined according to CCC-T-191, Method 5870 and 4.5.2.3 above. The maximum acceptable decrease in stiffness for the specimen shall be 8 per cent in the warp direction and 4 per cent in the fill direction.

4.5.2.5 Flexibility after water leaching. - The change in stiffness shall be determined according to CCC-T-191, Method 5830 and 4.5.2.4 above. The maximum acceptable increase in stiffness for the specimen shall be 8 per cent in the warp direction and 8 per cent in the fill direction.

4.5.2.6 Natural weathering test. - A 4-inch by 4-inch fabric specimen, after unprotected exposure to the elements for 30 days, shall show no appreciable change in color, pliability or strength, and shall show no signs of flaking, peeling, checking, cracking or loss of coating.

4.5.2.7 Weatherometer test - The coated side of a 4-inch by 4-inch specimen of fabric shall be subjected to 100 hours in the Twin-Arc-Weatherometer; the temperature of the atmosphere inside the weatherometer shall be $125^{\circ} \pm 5^{\circ}$ F. After this exposure, the specimen shall not have lost more than 25 per cent of its original hydrostatic resistance as determined for the cloth in 4.5.2.1. There shall not be any appreciable increase in the stiffness of the specimen.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T09:01Z
Check the source to verify that this is the current version before use.

4.5.2.8 Breaking strength test. - The breaking strength shall be determined according to CCC-T-191, Method 5100. The minimum acceptable individual value for a specimen shall be 296 pounds.

4.5.2.9 Ageing test. - The ageing test shall be performed according to CCC-T-191, Method 5852. The maximum acceptable increase in breaking strength for the specimen shall be 4 per cent.

4.5.2.10 Strength of coating test. - A test specimen of cloth 6 inches by 6 inches shall be cut from the sample piece of cloth in a direction 45 (±5) degrees to the warp and filling threads and clamped in jaws two inches wide and three inches apart of a standard testing machine (Scott or equal). The specimen shall be pulled apart at a constant rate of two inches per minute until a load of 30 pounds has been applied. The load shall be applied for 30 seconds. The test shall be repeated with a duplicate pull at a 90 degree angle from the first. After both pulls have been completed, the specimen shall be given the hydrostatic test as described in 4.5.2.1 with the coated side next to the water. The minimum acceptable pressure at which water appears shall be 205 psi.

4.5.2.11 Seam adhesion test. - The adhesion test shall be performed on cemented and taped seams according to CCC-T-191, Method 5970 for dry seams and wet seams. The minimum acceptable adhesion strength on any dry seam shall be 15.7 pounds. The minimum acceptable adhesion strength on a wet seam which has been immersed in water for two hours at 75° ± 2° F. and tested wet shall be 12.8 pounds.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T09:01Z
Check the source to verify that this is the current version before use.

4.5.3 Bladder environmental test procedure.

4.5.3.1 Low temperature. - To determine compliance with 3.3.3.1, three (except when the total sample size is three or two instead of five, then two or one respectively) of the flotation bladders used in the tests of 4.4 shall be placed in salt water and the water shall be cooled and maintained at a temperature of 28° F - 0° + 2° F for a period of 48 ± 5 hours. Thereafter, at this temperature the flotation bladder shall be inflated to operating pressure and restrained so that no more than one-third of the bladder breaks the surface of the water. There shall be no tearing or separating of the seams. After one hour minimum of inflation there shall be no loss of air pressure nor leakage.

4.5.3.2 Humidity - To determine compliance with 3.3.3.2, two (except when the total sample size is three or two, then one) flotation bladders (or bladder) used in the tests of 4.4, shall be dried, packed in their carrying cases and then placed in a test chamber. The temperature in the chamber shall be raised from a temperature of between 20° C and 38° C (68° F to 104° F) to 71° C ± 5° C (160° F ± 9°F) during a two hour period. The temperature of 71° C (160° F) and a minimum relative humidity of 95 per cent shall be maintained during the next six-hour period. Distilled or demineralized water having a pH value of between 6.5 and 7.5 at 25° C (77° F) shall be used to obtain the desired humidity. During the following 16-hour period, the temperature in the chamber must drop at a uniform rate to 20° C to 38° C (68° F to 100.4° F) which constitutes one cycle. The cycle shall be repeated a sufficient number of times to extend the total time of the test to 240 hours (10 cycles). At the conclusion of the 240-hour period each flotation bladder shall be subjected to the inflation test and requirements of 4.4.3.1.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T09:01Z
Check the source to verify that this is the current version before use.

4.5.3.3 Tropical environment. - The flotation bladders used in 4.5.3.2 shall be exposed to the fungus tests as required in 3.3.3.3 without drying or wiping prior to performance checking. The bladders shall be placed in a mold chamber maintaining an internal temperature of 86° F ± 5° F and a relative humidity of 90 per cent ± 5 per cent and sprayed with the suspension of mixed spores. These conditions shall be maintained for twenty-eight (28) days. At the conclusion of the test, the bladders shall be allowed to return to room temperature before performance checking. At least five groups of fungi shall be used in coupling inoculation. Five groups of fungi are listed below, and one type of fungus from each group shall be used. In preparing the spore suspension, distilled water (having a pH value between 5.8 and 7.2 at 77° F) shall be prepared by sterilization in convenient containers (approximately 100 milliliters each). Approximately 10 milliliters of the solution shall then be introduced directly into a stock culture of one fungus and shaken vigorously in order that a well sporulated suspension will result without disturbing the agar. This process shall be repeated for each selected type of fungus. The separate spore suspensions from the five types of fungi shall then be mixed together in an atomizer to provide a composite suspension. Actively growing cultures in ripe fruiting condition shall be used for each inoculation and under no condition will the inoculum be kept for more than an 8 hour period. At the conclusion of this test the bladders shall be subjected to the inflation test and requirements of 4.4.3.1.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T09:01Z
Check the source to verify that this is the current version before use.

Group I	Chaetomium globosum USDA 1042.4 ATCC 6205, or
	Myrothecium verrucaria USDA 1334.2, ATCC 9095.
Group II	Rhizorpus nigricans S. N. 32, ATCC 10404, or
	Aspergillus niger USDA TC215-4247, ATCC 6275
Group III	Aspergillus flavus AMC No. 26, ATCC 10836, or
	Aspergillus terreus PQMD 82J, ATCC 10690.
Group IV	Pencillum lute vm USDA 1336.1, ATCC 9776
	Penicillum sp. USDA 1336.2, ATCC 9112, or
	Penicillium citrinum ATCC 9849.
Group V	Memnoniella echinata AMC No. 37, ATCC 9597, or
	Fusarium moniliforme USDA 1004.1, ATCC 10052.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T09:01Z
Check the source to verify that this is the current version before use.

5. PREPARATION FOR DELIVERY

5.1 Preservation and packaging

5.1.1 Level A.

5.1.1.1 Cleaning. - None required

5.1.1.2 Drying. - None required

5.1.1.3 Preservative application. - None required

5.1.1.4 Unit packaging. - The flotation bladder shall be shipped completely assembled, neatly folded, and packaged in its carrying case.

5.1.1.5 Intermediate packaging. - The flotation bladder, packaged as specified in 5.1.1.4, shall be placed in a close fitting intermediate container conforming to the requirements of PPP-B-636, Grade 5, Type SF or CE, and then wrapped with barrier material conforming to MIL-B-131.

5.1.2 Levels B and C do not apply

5.2 Packing

5.2.1 Level A. - The flotation bladder, packaged as described in 5.1.1.4 and 5.1.1.5, shall be packed in a box, wood, nailed conforming to the requirements of PPP-B-621, Class 2, Style 2, Type 2. Corrugated liners shall be used to protect the barrier material.

5.2.2 Levels B and C do not apply

5.3 Marking

5.3.1 Special markings. - Each package shall be clearly labeled or marked "DO NOT STORE NEAR STEAM LINES OR OTHER LOCATIONS WHERE TEMPERATURES IN EXCESS OF 125° F. ARE LIKELY TO OCCUR".

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T09:01Z
Check the source to verify that this is the current version before use.

5.3.2 Normal markings. - In addition to the special markings required by the contract, order, or 5.3.1, all containers shall be marked in accordance with requirements of MIL-STD-129.

6. NOTES

6.1 Intended use. - The Flotation Bladder Mk 2 Mod 0 is intended for spare use in the recovery of submerged items having a negative buoyancy of up to 1000 pounds from a maximum depth of 150 feet of water.

6.2 Ordering data. - Procurement documents should specify the title, number and date of this specification and exceptions to this specification, applicable drawings and other documents.

6.3 Storage. - The ideal storage temperature is between 40° F. and 70° F. High temperatures are more injurious than low temperatures. Temperatures higher than 125° F. are to be avoided, if possible. The ideal humidity conditions for storage are between 40 per cent and 60 per cent.

Notice: When Government drawings, specifications, or other data are used for any purpose other than in connection with a definitely related Government procurement operation, the United States Government thereby incurs no responsibility nor any obligation whatsoever; and the fact that the Government may have formulated, furnished, or in any way supplied the said drawings, specifications, or other data is not to be regarded by implication or otherwise as in any manner licensing the holder or any other person or corporation, or conveying any rights or permission to manufacture, use, or sell any invention that may in any way be related thereto.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T09:01Z
Check the source to verify that this is the current version before use.