MIL-M-21272A(AS)
9 August 1982
SUPERSEDING
MIL-M-21272(AER)
28 January 1958
Naval Aircraft Factory
Specification C-159B
5 August 1952

MILITARY SPECIFICATION

MOTOR UNITS FOR ARRESTING GEAR CONTROL VALVES

This specification is approved for use by Naval Air Systems Command Department of the Navy and is available for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification covers motor units which form a part of the ratio control for arresting gear control valves.

2. APPLICABLE DOCUMENTS

2.1 Government documents.

2.1.1 Specifications, standards and handbooks. Unless otherwise specified, the following specifications, standards and handbooks of the issue listed in that issue of the Department of Defense Index of Specifications and Standards (DoDISS) specified in the solicitation form a part of this specification to the extent specified herein.

SPECIFICATIONS

Federal

FF-B-171	Bearings, Ball, Annular (General Purpose)
FF-B-185	Bearings, Roller, Cylindrical; and Bearings, Roller, Self-Aligning
NN-P-530	Plywood; Flat Panel
TT-P-1757	Primer Coating, Zinc Chromate, Low Moisture Sensitivity
PPP-B-585	Boxes; Wood, Wirebound
PPP-B-591	Boxes, Fiberboard, Wood-Cleated

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: NAEC-ESSD/Code 9311, Lakehurst, NJ 08733, by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

Source: https://assist.dla.mil -- Downloaded: 2026-01-19T09:12Z
Check the source to verify that this is the current version before use.

SPECIFICATIONS (continued)

Federal (continued)

PPP-B-601	Boxes, Wood, Cleated-Plywood
PPP-B-621	Boxes, Wood, Nailed and Lock-Corner
PPP-C-843	Cushioning Material, Cellulosic

Military

MIL-P-116	Preservation-Packaging, Methods of
MIL-B-121	Barrier Material, Greaseproofed, Waterproofed, Flexible
MIL-B-233	Boxes, Repair Parts, Storage
MIL-S-901	Shock Tests, H.I. (High Impact); Shipboard Machinery Equipment and Systems, Requirements for
MIL-C-915	Cable and Cord, Electrical for Shipboard Use, General Specification for
DOD-D-1000	Drawing, Engineering and Associated Lists
MIL-C-2212	Controller, Electric Motor, AC or DC and Associated Switching Devices, Naval Shipboard
MIL-Q-9858	Quality Program Requirements
MIL-P-15024	Plates, Identification - Information and Marking for Identification of Electrical, Electronic and Mechanical Equipment
MIL-E-15090	Enamel, Equipment, Light Gray (Formula No. 11)
MIL-L-15719	Lubricating - Grease (High Temperature) Motor, Ball and Roller Bearings
MIL-C-16173	Corrosion Preventive, Solvent Cutback, Cold Application
MIL-M-17059	Motors, 60 Cycle, Alternating-Current, Fractional HP (Shipboard Use)
MIL-L-17331	Lubricating Oil, Steam Turbine and Gear, Moderate Service
MIL-S-19622	Stuffing Tubes, Nylon
MIL-G-81322	Grease, Aircraft, General Purpose, Wide Temperature Range

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T09:12Z
Check the source to verify that this is the current version before use.

STANDARDS

Military

DOD-STD-100	Engineering Drawing Practices
MIL-STD-105	Sampling Procedures and Tables for Inspection by Attributes
MIL-STD-109	Quality Assurance Terms and Definitions
MIL-STD-129	Marking for Shipment and Storage
MIL-STD-143	Standards and Specifications, Order of Precedence for the Selection of
MIL-STD-710	Synchros, 60 and 400 Cycle
MIL-STD-1186	Cushioning, Anchoring, Bracing, Blocking and Waterproofing; with Appropriate Test Methods

2.1.2 Other Government documents, drawings and publications. The following other Government documents, drawings and publications form a part of this specification to the extent specified herein.

DRAWINGS

Naval Air Engineering Center, Ship and Shore Installations Engineering Department 55-4782 - Valve Control Units, Ratio Controller Assys

(Copies of specifications, standards, handbooks, drawings and publications required by manufacturers in connection with specific acquisition functions should be obtained from the contracting activity or as directed by the contracting officer.)

2.1.3 Order of precedence. In the event of a conflict between the text of this specification and the references cited herein, the text of this specification shall take precedence.

3. REQUIREMENTS

3.1 General. The motor unit is an electrically-driven control mechanism complete with over-travel limit switches, mechanical position indicator, and means of manual operation.

3.2 Materials. Materials shall conform to applicable specifications as specified herein and on the applicable drawings. All materials selected shall be of the best quality, of the lightest practicable weight, and suitable for the purpose intended. The material shall be free from all defects and imperfections that may affect the quality and reliability of the finished products.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T09:12Z
Check the source to verify that this is the current version before use.

3.2.1 Castings. Castings shall be of high quality, smooth, sound, and free from blow holes, porosity, cracks, or other defects.

3.2.1.1 Selection of specifications and standards. Specifications and standards for necessary commodities and services not specified herein shall be selected in accordance with MIL-STD-143.

3.3 Design and construction. The motor unit shall consist of an electrical reversible power drive operated in either direction from commands initiated at a pushbutton station, reduction gearing and housing with a terminal board for internal wiring of a synchro generator, drive screw, over-travel limit switches enclosed in a housing, position indicator. It shall have means for manual operation through an auxiliary handwheel control independent of electrical power drive. However, both systems shall not operate at the same time.

3.3.1 Wiring. Each unit shall have provision for the use of standard Navy waterproof terminal tubes of the size required to permit wiring to related equipment using armored, heat and flame resistant cable in accordance with Specification MIL-C-915.

3.3.2 Driving motor. The driving motor shall be of sufficient capacity to operate the unit satisfactorily. The motor shall conform to all the requirements of MIL-M-17059 and to the following: 40°C ambient temperature, class A insulation, Navy service "A," drip-proof, reversible, constant speed, short time (5 minutes) duty, 3 phase, 440 volts, 60 cycles, normal starting current, high torque, squirrel cage induction type, ball bearings.

3.3.3 Brake requirement. A brake mechanism shall be incorporated to provide instantaneous stopping when motor circuit is broken. This brake shall be in effect until the electric motor is energized.

3.3.4 Reduction gearing and housing. The reduction gearing shall consist of worms and gears as necessary to provide the performance specified. Backlash shall be held to a minimum in accordance with American Gear Manufacturers Association standards. Brinell or Rockwell hardness shall be specified on the applicable drawing for heat treated parts. The entire gear train shall be housed in a watertight housing. Provision shall be made within the housing for adequate lubrication of the gear system with lubricating oil conforming to MIL-L-17331 or grease conforming to MIL-G-81322.

3.3.4.1 Housing design. The housing shall further provide for the mounting of the driving motor and limit switches, position indication, manual control, and for flange mounting of the unit. It shall have dimensions as specified on NAEC Drawing 55-4782 or equivalent.

Source: https://assist.dla.mil -- Downloaded: 2026l0-19T09:12Z
Check the source to verify that this is the currenversion before use.

3.3.5 Stem shaft. The stem shaft shall conform to performance requirements of this specification and to dimensions on the applicable drawing.

3.3.6 Switches. Adjustable limit switches shall be provided for limiting the stroke in either direction. Switches shall be contained within a waterproof housing mounted on the gear case, having a removable cover for access to switch adjustments, and making provisions for the use of standard Navy waterproof terminal tubes, conforming to MIL-S-19622.

3.3.6.1 Limit switch requirements. The limit switch shall further consist of two adjustable sections. Each section shall consist of a minimum of three sets of contacts (one normally open and two normally closed) which, when actuated at the other extreme end position, produces two open and one closed set of contacts for that section. One section of limit switch shall operate in one extreme clockwise shaft position and the other section of limit switch shall operate in the other extreme counter-clockwise shaft position. The limit switch contacts shall be capable of safely interrupting the control circuit and stopping the motor when the drive is in the extreme clockwise position of the output drive shaft.

3.3.7 Mechanical position indicator. A position indicator shall be furnished and provision shall be made for the installation of a numerically graduated dial conforming to the applicable drawing.

3.3.7.1 Parallax-pointer. The indicator pointer shall be of such design that parallax will be at a minimum.

3.3.7.2 Pointer movement. The indicator pointer shall move in a counterclockwise direction as the stem shaft is withdrawn into the motor unit and shall have a sweep conforming with the applicable drawing for the specified stroke. Backlash between the stem shaft and indicator shall be such that performance will conform to the requirements of 4.5.3.3.

3.3.7.3 Additional provisions - installation. Provision only shall be made for installation of a synchro-transmitter conforming with the type specified on NAEC Drawing 55-4782 and in accordance with MIL-STD-710, along with a terminal board for external wiring of the unit.

3.3.8 Manual operation. A handwheel shall be provided to change the ratio setting in either direction in case of power failure. Construction shall be such that the power circuit shall automatically open when the handwheel is engaged and the power circuit shall remain open until the handwheel is disengaged. The handwheel shall not rotate during normal motor operation. Tools shall not be required in changing to or from manual operation. The

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T09:12Z
Check the source to verify that this is the current version before use.

handwheel shall be readily removable and shall be capable of being rapidly reinstalled and engaged as an integral unit. No loose method of attachment such as keys or cotter pins shall be utilized.

3.3.9 Output. The motor unit shall be able to move the stem shaft through 7 inch stroke at an average velocity of 20 inches per minute when opposed by a load of 2500 pounds.

3.3.10 Shock test. The motorized unit shall pass the shock test requirements of MIL-S-901 as outlined in 4.5.4. This requirement may be waived for units that have previously passed this shock test, providing that subsequent to the shock test its design has not been significantly altered.

3.4 Controller (NAEC Part No. 55-4782-3). The controller shall conform to all the requirements of MIL-C-2212 and to the following: size number 1, 40°C ambient temperature, Navy service "A," drip-proof, intermittent duty, magnetic, 440 volts, 3 phase, 60 cycles, across-line, motor starting and reversing, semi-automatic, provision for wiring to three remote pushbutton type master control switches, low-voltage protection, overload protection with emergency-run feature at the controller, short-circuit protection and adequate pilot-circuit protection. The controller shall serve to operate motor only during the time pushbutton is depressed.

3.5 Plans. The manufacturer shall furnish with his quotation sufficient information in duplicate to enable the Government to obtain a clear understanding of the equipment he proposed to furnish. This information may be in the form of blueprint plans or typewritten or printed specifications, in such arrangement as the manufacturer may prefer. Quotations not completely indicating the character of the proposed equipment may be rejected as incomplete. This information shall consist of the following and shall include any other data deemed necessary for a complete determination of the construction and operating characteristics.

a. Outline, overall and principal dimensions.

b. Weights.

c. Complete rating characteristics.

d. Complete description of operation including wiring diagram.

e. An itemized list of spare parts recommended by the bidder for shipboard maintenance and replacement which he will furnish if requested.

Source: https://assist.dla.mil -- Downloaded: 202610-19T09:12Z
Check the source to verify that this is the current version before use.

f. A definite statement as to whether or not any exceptions are being taken to applicable specifications or drawings with full description of such exceptions and consequent departure from the specifications or drawings, if any.

3.5.1 Approval plans. When required, the contractor shall submit for the approval of the Naval Air Engineering Center, Ship Installations Engineering Department (SSIED), Lakehurst, NJ 08733, via the Navy Inspector, plans of the equipment involved as soon as possible after the contract award. The manufacturer shall not proceed with the manufacture or shipment of such equipment prior to approval of these plans by the Government, unless otherwise authorized. Approval of these plans shall in no way relieve the contractor of responsibility of conformance to this specification. Plans for the motor and controller shall be as specified in the specifications previously referenced in items 3.3.2 and 3.4. The plan for the motor unit shall provide an outline of the assembly including space envelope for removal of motor. In addition, an assembly of the reduction gear and housing with cross-sectional views shall be shown. All component parts shall be called out and referenced to a bill of material. The bill of material shall also reference manufacturer's part number designation and military equipment, where known.

3.5.2 Record plans.

a. Certification Data Sheet - Certification data sheets shall be furnished for the motor unit, driving motor and controller. Where the detail specification does not outline format and contents of certification data sheets, the requirements of DOD-D-1000 shall apply.

b. Master Plans - When required, reproducible copies of drawings approved in paragraph 3.5.1 above shall be furnished for record. Engineering drawing practices used shall be in accordance with DOD-STD-100.

3.6 Spare parts. Spare parts for the motor unit specified herein shall be furnished only as required by the procuring activity.

3.6.1 Spare parts - motor units. Spare parts for the motor unit, less motor, specified herein shall be furnished as required by the contract or order. A set of spare parts shall consist of mechanical and electrical parts as may be considered essential by the manufacturer and specifically approved by the procuring activity, such spare parts shall include any special tools necessary for disassembly or maintenance, together with a complete set of gaskets, dust seals or closures. No commercially available standard tools shall be furnished.

Source: https://assist.dla.mil -- Downloaded: 202610-19T09:12Z
Check the source to verify that this is the current version before use.

3.6.2 Spare parts - electrical. Electrical spare parts, when required, shall be furnished in accordance with MIL-M-17059 and MIL-C-2212 (see 6.2).

3.6.3 Spare parts - packaging. All spare parts shall be in a single box in accordance with MIL-B-233 and plainly stenciled "Arresting Gear Spare Parts - Motor Unit (for MK 7 Constant Runout Valve)." All tools shall be contained in a suitable tool kit. All spare parts and tools shall be properly identified.

3.7 Wiring. All wiring integral with the unit or the unit components shall be furnished and installed by the contractor.

3.8 Nameplates. Nameplates shall conform to the requirements of MIL-P-15024. A suitable nameplate shall be attached to the unit in a readily accessible location, marked with this specification number, the manufacturer's name, identification symbols, serial number, Navy contract number, date of manufacture, procuring activity part number, Federal stock number, salient design characteristics (rated torque, rated speed, output, etc.) and provide a blank space for the inspector's official stamping.

3.9 Bearings. Ball and roller bearings shall conform to FF-B-171 and FF-B-185, respectively, and shall be used whenever practicable. Lubrication of bearings shall be in accordance with the requirements of MIL-L-15719.

3.10 Finish. After fabrication, the metallic surface of the motor unit shall be in a clean and smooth condition and shall be painted with one coat of zinc chromate primer conforming to Specification TT-P-1757. After the primer coat has thoroughly dried, one finish coat of light grey enamel, in accordance with Specification MIL-E-15090, shall be applied.

3.11 Interchangeability. All parts having the same manufacturer's part number shall be directly and completely interchangeable with each other with respect to installation and performance. Changes in manufacturer's part numbers shall be governed by the identification requirements of DOD-D-1000.

3.12 Performance characteristics. The entire motor unit shall perform satisfactorily when subjected to the tests specified in section 4.

3.13 Manuals. One instruction and maintenance manual shall be packaged with each motor unit. The instruction and maintenance manual shall be submitted for approval to the Naval Air Engineering Center, Ship and Shore Installation Engineering Department (SSIED), Lakehurst, NJ 08733, prior to acceptance of completed motor units.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T09:12Z
Check the source to verify that this is the current version before use.

3.14 Workmanship. The motor unit, including all parts and accessories, shall be fabricated, constructed and assembled to produce an item free from all defects which would affect proper functioning in service. Particular attention shall be given to neatness and thoroughness of welding, wiring, marking of parts and assemblies, finish, alignment of parts, tightness of screw assemblies and freedom of parts from burrs and sharp edges.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or purchase order, the supplier may utilize his own facilities or any other facility suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.2 Classification of inspections. The inspection of motor units shall be classified as follows:

a. First article inspection - First article inspection consists of examinations and tests performed on samples which are representative of the initial production lot after award of contract to determine that the production item meets the requirements of this specification.

b. Quality conformance inspection - Quality conformance inspection consists of examinations and tests performed on individual products or lots to determine conformance of the products or lots with the requirements set forth in this specification.

4.3 First article inspection. First article inspection shall consist of the examinations and tests as specified in Table I. The inspections shall be made in the sequence shown in Table I.

Source: https://assist.dla.mil -- Downloaded: 20260-19T09:12Z
Check the source to verify that this is the current version before use.

TABLE I. First article inspection.

Inspections	Reference paragraph
Examination	4.5.1
Dimensional	4.5.2
Shock	4.5.4
Full Load	4.5.3.1
Handwheel Force	4.5.3.2
Smoothness of Operation	4.5.3.4

4.3.1 First article sample. Unless otherwise specified, as soon as practicable after award of a contract or order, the contractor shall furnish a first article sample for inspection to determine conformance with this specification. The sample shall be representative of the construction, workmanship, components and materials to be used during production. The sample shall consist of one complete motor unit on contract or order. When a contractor is in continuous production of these motor units from contract to contract, submission of further first article samples on the new contract may be waived at the discretion of the procuring activity (see 6.2). Approval of the first article samples or the waiving of the first article inspection does not preclude the requirements of submitting to the quality conformance inspection. The sample shall be identified with the manufacturer's part number and contract number and shall be inspected as specified herein and in accordance with the contract or order (see 6.2).

4.3.1.1 First article data and disposition. Upon completion of the first article inspection, all the applicable inspection reports and, recommendations and comments pertinent for use in monitoring production will be forwarded to the Government quality control representative (see 6.3). The sample used for first article inspection shall not be considered as part of the quantity to be delivered under contract.

4.3.2 Inspection and quality control program. The inspection and quality control program conducted by the supplier shall be in accordance with MIL-Q-9858.

4.4 Quality conformance inspection. The examinations and tests comprising quality conformance inspection are classified as specified in Table II. The sampling and inspection levels shall conform to MIL-STD-105. Quality assurance terms and definitions shall be in accordance with MIL-STD-109.

Source: https://assist.dla.mil -- Downloaded: 202610-19T09:12Z
Check the source to verify that this is the current version before use.

TABLE II. Quality conformance inspections.

Inspections	Method	Sample Size	Acceptance Criteria 1/
Examination	4.5.1	Every Motor Unit	Reject All Defective Units
Dimensional	4.5.2	Inspection Level S-3	Acceptable Quality Level 1.0
Full Load	4.5.3.1	Inspection Level S-3	Acceptable Quality Level 1.0
Handwheel Force	4.5.3.2	Inspection Level S-3	Acceptable Quality Level 1.0
Mechanical Position Indicator	4.5.3.3	Inspection Level S-3	Acceptable Quality Level 1.0
Smoothness of Operation	4.5.3.4	Inspection Level S-3	Acceptable Quality Level 1.0

1/ The sampling plan acceptance numbers shall apply collectively to all the characteristics within a stated acceptable quality level.

4.5 Inspection methods.

4.5.1 Examination. Each assembled motor unit shall be carefully examined to determine conformance to all the requirements of this specification for which no specific tests are described and to determine conformance to manufacturer's approved material fabrication, specifications and drawings. Also, the inspector shall ascertain that the preparation for delivery conforms to the requirements of section 5.

4.5.2 Dimensional. The following components of each motor unit shall be measured to ascertain that they conform to the dimensions and tolerances specified for NAEC Drawing No. 55-4782.

a. Mating flange.
b. Shaft.
c. Dial.
d. Controller.

4.5.3 Operation.

4.5.3.1 Full load. The full load current draw shall not exceed and the motor speed shall not be less than the motor nameplate ratings. The stem shaft velocity shall also be measured and shall conform to the requirements of paragraph 3.3.9. The drive sleeve RPM may be used to compute motor speed in lieu of direct measurement.

Source: https://assist.dla.mil -- Downloaded: 202610-19T09:12Z
Check the source to verify that this is the current version before use.

4.5.3.1.1 The motor unit shall hold the screw firmly at any position throughout its travel against an applied axial force of 10,000 pounds.

4.5.3.2 Handwheel force. A force of 40 pounds maximum applied at the handwheel shall exert the same force on the stem shaft as the motor.

4.5.3.3 Mechanical position indicator. The mechanical position indicator shall reflect the axial motion of the stem shaft prior to the stem shaft traveling 1/16 inch along its axis when rotated by the handwheel.

4.5.3.4 Smoothness of operation. The motor unit shall operate smoothly at full rated load and shall be free of extra-ordinary noises which are not consistent with or inherent in the design and normal operation of a gear train of this size and speed.

4.5.4 Shock test. Shock tests shall be conducted in accordance with MIL-S-901, Grade A, hull mounted, subsidiary component, Class 1, lightweight, Type B.

4.5.4.1 Method of mounting. Fixture 4-C as shown in MIL-S-901 shall be used to mount the test unit. The motor unit shall be mounted on the shock machine in a manner simulating a normal shipboard installation with the motor and the drive sleeve horizontal.

4.5.4.2 Mode of equipment operation during tests. The motor unit shall be tested in the de-energized condition.

4.5.4.3 Definition of shock failure. The definition of failure from a shock test shall be as follows:

a. There shall be no breakage or appreciable distortion of any parts, including the mounting bolts.

b. If the motor unit will not deliver the required output as specified in 3.3.9, it shall be considered a failure and cause for rejection.

c. Any deformation which will adversely affect operation of the unit or results in the unit functioning in any manner different than it did before the shock test shall be considered a failure and cause for rejection.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T09:12Z
Check the source to verify that this is the current version before use.

d. The motor unit shall be disassembled following checks and inspected thoroughly for damage. Disassembly need be only to the point where the condition of the equipment can be easily observed. All observed effects of the shock test shall be carefully recorded.

4.5.4.4 Shock test sample. Any motor unit which has been subjected to the shock test shall not be acceptable as a deliverable item.

5. PACKAGING

5.1 Preservation and packaging. Preservation and packaging shall be level A or C as specified (see 6.2).

5.1.1 Level A.

5.1.1.1 Cleaning. The entire motor unit shall be thoroughly cleaned in accordance with process C-1 of MIL-P-116.

5.1.1.2 Preservation. Each motor unit shall be slushed with a P-3 type preservative conforming to Specification MIL-C-16173, Grade 3. Excess oil shall be drained from the unit. After slushing and draining all openings in the gear casing, it shall be sealed and the case partially filled with a P-2 type preservative conforming to Specification MIL-C-16173, Grade 2.

5.1.1.3 Unit packaging. Each motor shall be cushioned over all sharp projections with material conforming to Specification PPP-C-843 overwrapped with Grade A, Class 2 barrier material conforming to Specification MIL-B-121 prior to being placed on the appropriate Method II container as prescribed in Specification MIL-P-116.

5.1.2 Level C. When this level is required, each motor unit shall be cleaned, preserved and packaged in accordance with manufacturer's commercial practice.

5.2 Packing. Packing shall be level A or C as specified (see 6.2).

5.2.1 Level A. The motor units preserved and packaged as specified in 5.1.1.2 and 5.1.1.3 should be packed in overseas-type exterior shipping containers conforming to Specifications PPP-B-585, PPP-B-591, PPP-B-601 or PPP-B-621. Plywood, when used, shall conform to Types I or II, Class 2 of Specification NN-P-530.

5.2.2 Level C. Packages which require overpacking for acceptance by the carrier shall be packed in exterior-type shipping containers in a manner that will insure safe transportation at the lowest rate to the point of delivery. Containers shall conform to

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T09:12Z
Check the source to verify that this is the current version before use.

the Consolidated Freight Classification Rules or regulations of other common carriers, as applicable to the mode of transportation. Containers shall be able to withstand storage, rehandling and reshipment without the necessity of repacking.

5.3 Physical protection. Cushioning, blocking, bracing and bolting as required shall be in accordance with MIL-STD-1186 except that for domestic shipments, waterproofing requirements for cushioning materials and containers shall be waived.

5.4 Marking. Interior and exterior containers shall be marked in accordance with MIL-STD-129 and to include the following:

Motor Unit, Ratio Control, for Arresting Gear Control Valves
Specification: MIL-M-21272

Manufacturer's Serial No.
Manufacturer's Part No.
Name of Manufacturer
Name of Contractor (if different from manufacturer)
Contractor or Order No.
NAEC Part No.

6. NOTES

6.1 Intended use. The motor unit in conjunction with a controller and pushbutton is used to actuate the adjustable lever on arresting engine control valves.

6.2 Ordering data. Acquisition documents should specify the following:

a. Title, number and date of this specification.

b. Quantity of motor units or component parts desired.

c. Type of plans, if required by the design activity (3.5).

d. Quantity of spares required (3.6).

e. Applicable levels of packaging and packing (5.1 and 5.2).

f. Items of data required (6.3).

g. First article information and where the samples shall be delivered (4.3).

Source: https://assist.dla.mil -- Downloaded: 202610-19T09:12Z
Check the source to verify that this is the current version before use.

h. Applicable methods of cleaning and preservation (5.1).

i. First article sample subjected to the shock test shall not be considered or shipped as part of the contract or order (4.5).

6.2.1 Acquisition requirements.

6.2.2 Contract data requirements. Items of deliverable data are cited in the following paragraphs:

Paragraph	Data Requirement	Applicable DID
3.5	Plans (of equipment)	---
3.5.2a	Certification data sheets	---
3.5.2b	Master plan (drawings)	---
3.13	Operation and maintenance manual	DI-M-2404
4.3.1.1	First article test report	UDI-T-23790

6.3 Data. For the information of contractors and contracting officers, any of the data specified in applicable documents listed in section 2 of this specification or referenced lower-tier documents need not be prepared for the Government and shall not be furnished to the Government unless specified in the contract or order. The data to be furnished shall be listed on DD Form 1423 (Contractor Data Requirements List), which shall be attached to and made a part of the contract or order.

6.3.1 Manuals. One instruction and maintenance manual shall be packaged with each motor unit. The instruction and maintenance manual shall be submitted for approval to the Naval Air Engineering Center, Ship and Shore Installation Engineering Department (SSIED), Lakehurst, NJ 08733, prior to acceptance of completed motor units.

6.3.2 Provisioning documentation. Provisioning documentation shall be provided for inspection at the time of the first article inspection. If satisfactory, the reproducible list and three copies shall be forwarded.

6.3.3 Plans. Plans as specified in 3.5 shall be submitted only when required by the contracting officer.

6.3.4 First article inspection report. Three copies of the first article inspection report shall be submitted to the acquiring activity for approval.

6.3.5 Drawings and data list. Drawings, engineering and associated lists shall be in accordance with DOD-D-1000.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T09:12Z
Check the source to verify that this is the current version before use.

6.4 Reclaimed materials. The use of reclaimed materials shall be encouraged to the maximum extent possible.

Preparing activity:
Navy - AS
(Project 1710-N038)

Source: https://assist.dla.mil -- Downloaded: 2026-10-19109:12Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

INSTRUCTIONS: This form is provided to solicit beneficial comments which may improve this document and enhance its use. DoD contractors, government activities, manufacturers, vendors, or other prospective users of the document are invited to submit comments to the government. Fold on lines on reverse side, staple in corner, and send to preparing activity. Attach any pertinent data which may be of use in improving this document. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity. A response will be provided to the submitter, when name and address is provided, within 30 days indicating that the 1426 was received and when any appropriate action on it will be completed.

NOTE: This form shall not be used to submit requests for waivers, deviations or clarification of specification requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements.

DOCUMENT IDENTIFIER *(Number)* AND TITLE

MIL-M-21272A(AS) MOTOR UNITS FOR ARRESTING GEAR CONTROL VALVES

NAME OF ORGANIZATION AND ADDRESS OF SUBMITTER

☐ VENDOR ☐ USER ☐ MANUFACTURER

1. ☐ HAS ANY PART OF THE DOCUMENT CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE? ☐ IS ANY PART OF IT TOO RIGID, RESTRICTIVE, LOOSE OR AMBIGUOUS? PLEASE EXPLAIN BELOW.

A. GIVE PARAGRAPH NUMBER AND WORDING

B. RECOMMENDED WORDING CHANGE

C. REASON FOR RECOMMENDED CHANGE(S)

2. REMARKS

SUBMITTED BY *(Printed or typed name and address — Optional)*

TELEPHONE NO.

DATE

DD FORM 1 OCT 76 1426

Replaces edition of 1 Jan 72 which may be used.

S/N 0102-LF-001-4260

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T09:12Z
Check the source to verify that this is the current version before use.