INCH-POUND

MIL-T-21205B(AS)
AMENDMENT 2
31 October 2000
SUPERSEDING
AMENDMENT 1
01 December 1962

MILITARY SPECIFICATION

TRANSMITTER, RATE OF FLOW, FUEL; TRU-12/A (300-500 – 15000 PPH)

INACTIVE FOR NEW DESIGN AFTER 03 DECEMBER 1990

This amendment forms a part of MIL-T-21205B(AS), dated 15 November 1960, and is approved for use by the Naval Air Systems Command, Department of the Navy and is available for use by all Departments and Agencies of the Department of Defense.

PAGE 2

* 3.1: Delete and substitute:

"3.1 First article. When specified (see 6.2), a sample shall be subjected to first article inspection in accordance with 4.1."

PAGE 8

4.2.1.2: Add the following after the table:

"For flows in the 500 to 5000 pph range, three resonance peaks shall be allowable when tested in all three mutually perpendicular axes. The maximum variation or oscillation tolerance of these peaks shall be ±150 pph, only if the oscillation and variation peaks do not occur simultaneously."

PAGE 11

* 6.3: Delete.

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T09:05Z
Check the source to verify that this is the current version before use.

MIL-T-21205B(AS)
AMENDMENT 2

Note: The margins of this amendment are marked with asterisks to indicate where changes from the previous amendment were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous amendment.

Preparing activity:
Navy – AS

(Project 6620-0723)

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T09:05Z
Check the source to verify that this is the current version before use.