MILITARY SPECIFICATION

BINDING, TEXTILE, BORE CLEANING; AND SWABS, SMALL ARMS, CLEANING

This specification is mandatory for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope.- This specification covers bindings and swabs cut from cloth, and used for bore cleaning of artillery and small arms.

1.2 Classification.- The bindings and swabs shall be of the following types and classes as specified (see 6.2):

Type I - Rolls (Bindings)

Class 1 - 2-1/2 inches, wide
Class 2 - 4 inches, wide

Type II - Cut pieces (Swabs)

Class 1 - 2 inches, square
Class 2 - 2-9/16 inches, square
Class 3 - 2-3/16 inches diameter, circular

* 2. APPLICABLE DOCUMENTS

2.1 The following documents of the issue in effect on date of invitation for bids or request for bids or request for proposal, form a part of this specification to the extent specified herein:

SPECIFICATIONS

FEDERAL

CCC-T-191 - Textile Test Methods.
PPP-B-566 - Boxes, Folding, Paperboard.
PPP-B-636 - Box, Fiberboard.

FSC 8315

Source: https://assist.dla.mil -- Downloaded: 202640-21T21:09Z
Check the source to verify that this is the currentversion before use.

PPP-F-320 - Fiberboard; Corrugated and Solid, Sheet Stock (Container Grade) and Cut Shapes.
PPP-T-76 - Tape, Pressure-Sensitive Adhesive Paper, (For Carton Sealing).

STANDARDS

MILITARY

MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes.
MIL-STD-129 - Marking for Shipment and Storage.

(Copies of specifications, standards, drawings and publications required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

2.2 Other publications.- The following document forms a part of this specification to the extent specified herein. Unless otherwise indicated, the issue in effect on date of invitation for bids or request for proposal shall apply.

Rules and Regulations Under the Textile Fiber Products Identification Act

(Copies may be obtained without charge from the Federal Trade Commission, Washington, D.C. 20580.)

3. REQUIREMENTS

3.1 Material.-

3.1.1 Yarn.- The yarn shall be made from clean cotton, carded, drawn and spun into singles yarn for both the warp and filling.

3.2 Color.- The color of the cloth to be cut into bindings and swabs shall be natural, unbleached.

3.3 Physical requirements.- The finished cloth to be cut into bindings and swabs shall conform to the requirements shown in table I.

Source: https://assist.dla.mil -- Downloaded: 202610-21T21:09Z
Check the source to verify that this is the current version before use.

TABLE I.- Physical requirements

Weight (oz/sq. yd.)	Yarns per inch minimum		Breaking strength (lbs.) minimum		Weave
	Warp	Filling	Warp	Filling	
4.7 min. - 5.1 max.	43	39	40	30	Plain

3.4 Finish.- The cloth to be cut into bindings and swabs shall be scoured and have an evenly developed napped surface on one side.

3.5 Cutting.-

3.5.1 Type I.- The finished cloth shall be cut 2-1/2 ± 1/8 inches wide for class 1 bindings and 4 ± 1/8 inches wide for class 2 bindings. The cloth shall be cut parallel to the warp yarns.

3.5.2 Type II.- The finished cloth shall be cut 2 inches square for class 1 swabs, 2-9/16 inches square for class 2 swabs, and 2-3/16 inches diameter for class 3 circular swabs. A minus 1/8 inch tolerance shall be allowed on all specified dimensions. The classes 1 and 2 swabs shall not be cut on the bias.

3.6 Put-up and length.- The type I bindings shall be furnished in tightly rolled lengths of 100 to 104 yards per roll with not more than 4 pieces per roll for class 1 binding, and 50 to 54 yards per roll with not more than 2 pieces per roll for class 2 binding. The type I bindings may be rolled on tubes not more than 1-1/2 inches in diameter. The type II cut pieces (swabs) shall be furnished in units of 200 ± 5 pieces.

3.7 Fiber identification.- Each roll (type I) or intermediate package shall be labeled, ticketed or invoiced for fiber content in accordance with the Textile Fiber Products Identification Act.

3.8 Workmanship.- The finished bindings and swabs shall conform to the quality and grade of product established by this specification. The occurrence of defects shall not exceed the applicable acceptable quality levels.

4. QUALITY ASSURANCE PROVISIONS

* 4.1 Responsibility for inspection.- Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise

Source: https://assist.dla.mil -- Downloaded: 202610-21T21:09Z
Check the source to verify that this is the current version before use.

specified in the contract or order, the supplier may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

* 4.1.1 Certificate of compliance.- Where certificates of compliance are submitted, the Government reserves the right to check test such items to determine the validity of the certification.

* 4.2 Inspection.- Sampling for inspection shall be performed in accordance with MIL-STD-105, except where otherwise indicated hereinafter.

* 4.2.1 Component and material inspection.- In accordance with 4.1 above, components and materials shall be tested in accordance with all the requirements of referenced specifications, drawings and standards unless otherwise excluded, amended, modified or qualified in this specification or applicable purchase document. The methods of testing specified in CCC-T-191, wherever applicable, and as listed in table II shall be followed. The physical values specified in section 3 apply to the results of the determinations made on a sample unit for test purposes as specified in the applicable test method. The lot size shall be expressed in units of one linear yard. The sample unit shall be one yard full width of the finished cloth to be cut into bindings and swabs. The lot shall be unacceptable if one or more sample units fail to meet any test requirement specified. All test reports shall contain the individual values utilized in expressing the final result. The sample size (number of sample units) shall be in accordance with the following:

Lot size (yards)	Sample size
800 or less	2
801 up to and including 22,000	3
22,001 and over	5

TABLE II.- Test methods

Characteristic	Requirement paragraph	Test method
Material:		
Singles, cotton yarn	3.1.1	1/
Weave	3.3	Visual 2/

Source: https://assist.dla.mil -- Downloaded: 202640-21T21:09Z
Check the source to verify that this is the currentversion before use.

TABLE II.- Test methods (cont'd)

Characteristic	Requirement paragraph	Test method
Weight, oz/sq. yd.	3.3	5041
Yarns per inch:		
Warp	3.3	5050
Filling	3.3	5050
Breaking strength (lbs.):		
Warp	3.3	5100
Filling	3.3	5100
Scoured	3.4	1/
Napped	3.4	1/

1/ Unless otherwise specified, a certificate of compliance shall be submitted and will be acceptable for the stated requirement.

2/ One determination and the result reported as "pass" or "fail".

4.2.2 End item examination - type I.- The end item examination of the type I binding shall be in accordance with 4.2.2.1 and 4.2.2.2. The sample unit for these examinations shall be one roll and the lot size shall be expressed in units of rolls.

4.2.2.1 Visual examination.- The AQL (acceptable quality level) for this examination shall be 6.5 defects per 100 units and the inspection level shall be S-4. Defects found in this examination shall be scored in accordance with the following, when examined on the face side (napped) of the binding:

Broken or missing yarns, 2 or more contiguous, 1 inch or more in length.
Hole, cut or tear; 3 or more ruptured yarns at adjoining points.
Face side of binding not napped.
Spot, stain or streak, 2 inches or more in combined warp and filling directions.
Edge not evenly cut on more than half the roll.

Source: https://assist.dla.mil -- Downloaded: 202610-21T21:09Z
Check the source to verify that this is the current version before use.

Not cut parallel to the warp yarn.
Overall uncleanness.
Width not within specified tolerance.
Roll not labeled in accordance with the Textile Fiber Products Identification Act.

4.2.2.2 Examination for length and winding.- The AQL for this examination shall be 4.0 percent defective and the inspection level shall be S-3. A defect shall be considered to exist if any of the following are determined during this examination:

Binding not tightly rolled.
More than the applicable maximum allowable number of pieces per roll (see 3.6).
Less than minimum or more than the maximum total yardage per roll (see 3.6).
Diameter of empty tube more than 1-1/2 inches.

4.2.3 End item examination - type II.- The sample unit for this examination shall be one cut piece and the lot size shall be expressed in units of cut pieces. The AQL shall be 4.0 percent defective and the inspection level shall be level I. The number of bags or wraps from which the sample is to be selected shall be in accordance with table III. An approximate equal number of pieces shall be examined from each bag or wrap in the sample. The required number of pieces shall be inspected on the face side (napped) and visual defects classified as follows:

Hole, cut or tear; 3 or more ruptured yarns at adjoining points.
Edge not evenly cut.
Cut on the bias (class 3, not applicable).
Overall uncleanness.
Face side not napped.
Dimensions not within specified tolerances.

TABLE III.- Sample size, type II

Lot size in cut pieces	Sample size (bags or wraps
1200 or less	3
1201 up to and including 3200	5
3201 up to and including 10,000	8
10,001 up to and including 35,000	13
35,001 up to and including 150,000	20
150,001 and over	32

Source: https://assist.dla.mil -- Downloaded: 202640-21T21:09Z
Check the source to verify that this is the currentversion before use.

4.2.4 Examination of preparation for delivery requirements.- An examination shall be made to determine that packaging, packing and marking requirements of section 5 of this specification are complied with. Defects shall be scored in accordance with the list below. The sample unit shall be one shipping container fully prepared for delivery with the exception that it need not be sealed. Defects of closure listed below shall be examined on shipping containers fully prepared for delivery. The lot size shall be the number of shipping containers in the end item inspection lot. The inspection level shall be S-2 and the AQL shall be 2.5 defects per hundred units.

Examine	Defect
Marking (exterior and interior)	Omitted; incorrect; illegible; of improper size, location, sequence or method of application.
Material	Any component missing. Any component damaged, affecting serviceability.
Workmanship	Inadequate application of components, such as: incomplete closure of container flaps, improper taping, loose strapping, inadequate stapling. Bulging or distortion of container. Improper closure of polyethylene bag or wrap.
Weight (type I)	Net weight exceeds requirements.
Contents (type II)	Number of intermediate packages per container is more or less than specified. Number of bags or wraps per intermediate package is more or less than specified. 1/ Number of cut pieces per bag or wrap is more or less than specified. 1/

1/ For these defects, four intermediate packages shall be examined from each shipping container in the sample and one bag or wrap shall be examined from each of the four intermediate packages.

5. PREPARATION FOR DELIVERY

5.1 Packaging.- Packaging shall be level A or C as specified (see 6.2).

5.1.1 Level A.-

Source: https://assist.dla.mil -- Downloaded: 202610-21T21:09Z
Check the source to verify that this is the current version before use.

5.1.1.1 Type I.- Three rolls of bindings of one class only, put up as specified, shall be wrapped or bagged together in minimum 0.0015-inch thick transparent plastic film. The wrap or bag shall be secured with gummed or pressure-sensitive tape or a mechanical wire tie (plastic or paper covered soft wire).

5.1.1.2 Type II.-

5.1.1.2.1 Unit package.- Two hundred cut pieces, of one class only, shall be completely wrapped or bagged in minimum 0.0015-inch thick transparent plastic film. The wrap or bag shall be secured by heat sealing or a mechanical wire tie (plastic or paper covered soft wire).

5.1.1.2.2 Intermediate package.- One thousand cut pieces, of one class only, unit packaged as specified in 5.1.1.2.1 shall be placed in a snug-fitting paperboard box conforming to variety 2, style II, type A, class "a" of PPP-B-566, with closure secured with pressure-sensitive tape conforming to PPP-T-76.

5.1.2 Level C.- Bindings and swabs shall be preserved and packaged to afford adequate protection against deterioration and physical damage during shipment from the supply source to the first receiving activity. The supplier may use his standard practice when it meets these requirements.

5.2 Packing.- Packing shall be level A, B or C as specified (see 6.2).

5.2.1 Level A.-

5.2.1.1 Type I.- Rolls, of one class only, packaged as specified in 5.1, shall be packed in a snug-fitting fiberboard shipping container conforming to style RSC-L, grade V2s of PPP-B-636. The inside of each container shall be fitted with a taped liner conforming to type CF, class weather-resistant, variety DW, grade V15c of PPP-F-320. Each shipping container shall be closed, waterproofed, and reinforced with strapping or tape banding in accordance with the appendix of PPP-B-636. The weight of the contents of each shipping container shall not exceed 65 pounds.

5.2.1.2 Type II.- Forty thousand cut pieces, of one class only, packaged as specified in 5.1, shall be packed in a snug-fitting fiberboard shipping container conforming to style RSC, grade V2s of PPP-B-636. Each shipping container shall be closed, waterproofed, and reinforced with strapping or tape banding in accordance with the appendix of the container specification.

Source: https://assist.dla.mil -- Downloaded: 202640-21T21:09Z
Check the source to verify that this is the current version before use.

5.2.2 Level B.-

5.2.2.1 Type I.- Rolls, of one class only, packaged as specified in 5.1, shall be packed in a fiberboard shipping container conforming to style RSC-L, type CF (variety SW) or SF, class domestic, grade 275 of PPP-B-636. The inside of each container shall be fitted with a taped liner conforming to type CF, class domestic, variety DW, grade 275 of PPP-F-320. Each shipping container shall be closed in accordance with method II as specified in the appendix of PPP-B-636. The weight of the contents of each shipping container shall not exceed 65 pounds.

5.2.2.2 Type II.- Forty thousand cut pieces, of one class only, packaged as specified in 5.1, shall be packed in a snug-fitting fiberboard shipping container conforming to style RSC, type CF (variety SW) or SF, class domestic, grade 275 of PPP-B-636. Each shipping container shall be closed in accordance with method II as specified in the appendix of PPP-B-636.

5.2.2.3 When specified (see 6.2), the shipping container for rolls and cut pieces shall be a grade V3c or V3s fiberboard box fabricated in accordance with PPP-B-636 and closed in accordance with the appendix of the container specification. The shipping container material may also be grade V4s of PPP-F-320.

5.2.3 Level C.- Bindings and swabs, packaged as specified in 5.1, shall be packed in a manner to insure carrier acceptance and safe delivery at destination at the lowest transportation rate for such supplies. Containers shall be in accordance with rules or regulations of carriers applicable to the mode of transportation.

5.3 Marking.- In addition to any special marking required by the contract or order, wrapped or bagged rolls, intermediate packages, and shipping containers shall be marked in accordance with MIL-STD-129.

6. NOTES

6.1 Intended use.- Bindings and swabs covered by this specification are intended for use in cleaning bores of artillery and small arms.

6.2 *Ordering data.- Procurement documents should specify the following:*

(a) Title, number and date of this specification.
(b) Type and class required (see 1.2).
(c) Selection of applicable levels of packaging and packing (see 5.1 and 5.2).
(d) When weather-resistant grade fiberboard shipping containers are required for level B packing (see 5.2.2.3).

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T21:09Z
Check the source to verify that this is the current version before use.

6.3 The cloth described in this specification was developed from a commercial designation 40-1/2 inches, 42 by 44, 3.00 yards per pound, soft filled sheeting.

6.4 The margins of this specification are marked with an asterisk to indicate where changes (additions, modifications, corrections, deletions) from the previous issue were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and suppliers are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship of the last previous issue.

Custodians:

Army - GL
Navy - SA

Review activities:

Army - MC
Navy - SA

User activity:

Navy - MC

Preparing activity:

Army - GL

Project No. 8315-0134

*U.S. GOVERNMENT PRINTING OFFICE: 1971-714-161/3857

Source: https://assist.dla.mil -- Downloaded: 202640-21T21:09Z
Check the source to verify that this is the current version before use.