MIL-R-43323E
26 SEP 1986
SUPERSEDING
MIL-R-43323D
23 May 1978

MILITARY SPECIFICATION

# RIFLE BUTT POCKET AND STRAP ASSEMBLY

This specification is approved for use by all Departments and Agencies of the Department of Defense.

## 1. SCOPE

* 1.1 Scope. This document covers one type of rifle butt pocket with strap.

## 2. APPLICABLE DOCUMENTS

* 2.1 Government documents.

* 2.1.1 Documents. Following documents form a part of this document to the extent specified herein. Unless otherwise specified, the issues of these documents shall be those listed in the issue of the Department of Defense Index of Specifications and Standards (DODISS) and supplement thereto, cited in the solicitation.

SPECIFICATIONS

FEDERAL

| | | |
|---|---|---|
| A-A-203 | - | Paper, Kraft, Untreated |
| V-T-285 | - | Thread, Polyester |
| DDD-L-20 | - | Label: For Clothing, Equipage, and Tentage (General Use) |
| PPP-B-636 | - | Boxes, Shipping, Fiberboard |

---

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: U.S. Army Natick Research, Development and Engineering Center, Natick, MA 01760-5014 by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

---

AMSC N/A FSC 8465

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T21:10Z
Check the source to verify that this is the current version before use.

MILITARY

MIL-H-639 - Hooks (For Belts, Straps, and Equipage Items)
MIL-W-4088 - Webbing, Textile, Woven Nylon
MIL-H-9890 - Hardware, Individual Load Carrying Equipment: and Hardware, Miscellaneous
MIL-W-17337 - Webbing, Textile, Woven Nylon
MIL-W-27265 - Webbing, Textile, Woven Nylon Impregnated
MIL-L-35078 - Loads, Unit: Preparation of Semiperishable Subsistence Items; Clothing, Personal Equipment and Equipage; General Specification for

STANDARDS

FEDERAL

FED-STD-751 - Stitches, Seams, and Stitchings

MILITARY

MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes
MIL-STD-129 - Marking for Shipment and Storage
MIL-STD-147 - Palletized Unit Loads
MIL-STD-731 - Quality Of Wood Members For Containers and Pallets

DRAWINGS

U.S. ARMY NATICK RESEARCH, DEVELOPMENT AND ENGINEERING CENTER

2-3-169 - Rifle Butt Pocket and Strap Assembly

(Copies of documents required by contractors in connection with specific acquisition functions should be obtained from the contracting activity or as directed by the contracting activity.)

* 2.2 Other publications. The following documents form a part of this document to the extent specified herein. Unless otherwise specified, the issues of the documents which are DOD adopted shall be those listed in the issues of the DODISS specified in the solicitation. Unless otherwise specified, the issues of documents not listed in the DODISS shall be the issues of the nongovernment documents which are current on the date of the solicitation.

AMERICAN SOCIETY FOR TESTING AND MATERIALS (ASTM)

D-3951 - Standard Practice for Commercial Packaging



Source: https://assist.dla.mil -- Downloaded: 2026-10-21T21:10Z
Check the source to verify that this is the current version before use.

(Application for copies should be addressed to the American Society for Testing and Materials, 1916 Race Street, Philadelphia, PA 19103.)

(Technical society and technical association documents are generally available for reference from libraries. They are also distributed among technical groups and using Federal agencies.)

* 2.3 Order of precedence. In the event of a conflict between the text of this document and the references cited herein, the text of this document shall take precedence. Nothing in this document, however, shall supersede applicable laws and regulations unless a specific exemption has been obtained.

3. REQUIREMENTS

3.1 Samples.

* 3.1.1 Guide samples. Samples of the end item, when furnished, are solely for guidance and information to the contractor (see 6.3). Variations from this document may appear in the sample, in which case this document shall govern.

* First article. When specified in the contract or purchase order, a sample shall be subjected to first article inspection (see 4.3, 6.2, and 6.4).

3.2 Materials (see 6.5).

3.2.1 Webbing, nylon, 1 inch wide. The 1 inch nylon webbing shall be dyed Olive Drab 7 and shall conform to class 2 of MIL-W-17337.

3.2.2 Webbing, nylon, 1-23/32 inch wide. The 1-23/32 inch webbing shall be dyed Olive Drab 7 and shall conform to type VIII, class 1 or 2 of MIL-W-4088. The 1-23/32 inch webbing shall be resin impregnated to conform to class R of MIL-W-27265.

3.2.3 Thread, polyester. The thread for all stitching shall be size FF conforming to type I, class 1, subclass A of V-T-285. The thread shall be dyed Olive Drab S-1 (C.A. 66022) and shall show fastness to weathering equal to or better than the standard sample. When no standard sample is available, the thread shall show good fastness to weathering.

3.2.4 Keeper, clamp, 1 inch with loop. The keeper shall conform to type IX, class A, of MIL-H-9890.

3.2.5 Hook, double. The double hook shall conform to type I, class 1, of MIL-H-639.

3.3 Construction. The construction shall conform in all respects to Drawing 2-3-169 and shall be as specified herein.

* 3.3.1 Stitches, seams, and stitching. All stitches, seams, and stitching shall be performed using stitch type 301 of FED-STD-751 with 6 to 8 stitches per inch.



Source: https://assist.dla.mil -- Downloaded: 2026-10-21T21:10Z
Check the source to verify that this is the current version before use.

* 3.3.1.1 Automatic stitching. Automatic stitching machines may be used to perform any of the stitch patterns provided the requirements for the stitch patterns, stitches per inch, and size and type of thread are met; and at least three tying, overlapping, or backstitches are used to secure the ends of stitching.

* 3.3.1.2 Type 301 stitching. Ends of all stitching shall be backstitched or overstitched not less than 1/2 inch except where ends are turned under or caught in other seams and stitching. Thread tensions shall be maintained so that there will be no loose stitching resulting in loose bobbin or top thread or excessively tight stitching resulting in puckering of the materials sewn. The lock shall be imbedded in the materials sewn.

3.3.1.2.1 Repairs of type 301 stitching. Repairs of type 301 stitching shall be as follows:

a. When thread breaks, skipped stitches, run-offs, or bobbin runouts occur during sewing, the stitching shall be repaired by restarting the stitching a minimum of 1/2 inch back of the end of the stitching. 1/

b. Thread breaks or two or more consecutive skipped or run-off stitches noted during inspection of the item shall be repaired by overstitching. The stitching shall start a minimum of 1/2 inch in back of the defective area, continue over the defective area, and continue a minimum of 1/2 inch beyond the defective area onto the existing stitching. Loose or excessively tight stitching shall be repaired by removing the defective stitching, without damaging the materials, and restitching in the required manner. 1/

1/ When making the above repairs, the ends of stitching are not required to be backstitched.

3.3.1.3 Thread ends. All thread ends shall be trimmed to 1/4 inch maximum length.

3.3.2 Fusing of nylon webbing. Cut ends of webbing shall be fused smooth and even as indicated on Drawing 2-3-169. Fusing of the webbing ends shall be accomplished prior to assembling for stitching.

3.3.3 Repairs. Repairs such as mends, darns, or splices are not permitted on the rifle butt pocket and strap assembly.

3.4 Marking. The identification marking shall be applied in the location shown on Drawing 2-3-169 and shall conform to type IV, class 5 of DDD-L-20. The letters US shall be applied in the size characters and in the location indicated on the drawing and shall conform to type IV, class 9 of DDD-L-20. Fastness of the class 9 marking shall be as specified for class 5 marking.



Source: https://assist.dla.mil -- Downloaded: 2026-10-21T21:10Z
Check the source to verify that this is the current version before use.

3.5 Workmanship. The rifle butt pocket and strap assembly shall conform to the quality of product established by this document and occurrence of defects shall not exceed the applicable acceptable quality levels.

4. QUALITY ASSURANCE PROVISIONS

* 4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the contractor is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or purchase order, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in this document where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

* 4.1.1 Responsibility for compliance. All items must meet all requirements of sections 3 and 5. The inspection set forth in this document shall become a part of the contractor's overall inspection system or quality program. The absence of any inspection requirements in the document shall not relieve the contractor of the responsibility of assuring that all products or supplies submitted to the Government for acceptance comply with all requirements of the contract. Sampling in quality conformance does not authorize submission of known defective material, either indicated or actual, nor does it commit the Government to acceptance of defective material.

4.2 Classification of inspection. The inspection requirements specified herein are classified as follows:

a. First article inspection (see 4.3).
b. Quality conformance inspection (see 4.4).

* 4.3 First article inspection. When a first article is required (see 3.1), it shall be examined for the defects specified in 4.4.3 and 4.4.4. The presence of any defect shall be cause for rejection of the first article.

* 4.4 Quality conformance inspection. Unless otherwise specified, sampling for inspection shall be preformed in accordance with MIL-STD-105.

4.4.1 Component and material inspection. In accordance with 4.1, components and materials shall be inspected in accordance with all the requirements of referenced documents unless otherwise excluded, amended, modified, or qualified in this document or applicable purchase document.



Source: https://assist.dla.mil -- Downloaded: 2026-10-21T21:10Z
Check the source to verify that this is the current version before use.

4.4.2 In-process inspection. Inspection shall be made at any point or during any phase of the manufacturing process to determine whether cut lengths, listed below, prior to assembly are in accordance with specified requirements of Drawing 2-3-169. The Government reserves the right to exclude from acceptance any material or service for which in-process inspection has indicated non-conformance.

| Check for | Component |
|---|---|
| Cut length | Piece "A" |
| Cut length | Piece "B" |
| Cut length | Keeper chape |
| Cut length | Rifle strap |

* 4.4.3 End item visual examination. The end item shall be examined for the defects listed below. The lot size shall be expressed in units of rifle butt pocket and strap assemblies. The sample unit shall be one rifle butt pocket and strap assembly. The inspection level shall be II and the acceptable quality level (AQL), expressed in terms of defects per hundred units, shall be 2.5 for major defects and 6.5 for total (major and minor combined) defects.

| Examine | Defect | Classification Major | Minor |
|---|---|---|---|
| Webbing | Any hole, cut, tear, or smash. | X | |
| | Not firmly or tightly woven, edge frayed or scalloped. | X | |
| | Abrasion mark, slub, or broken end or pick. | | X |
| | Multiple floats. | | X |
| Hardware | Broken, malformed, corroded area, burr, or sharp edge. | X | |
| | Finish not as specified. | | X |
| | Any required component improperly set or reversed. | X | |
| | Any required component not specified type. | X | |
| Open seam | 3/4 inch or less. | | X |
| | More than 3/4 inch. | X | |

NOTE: A seam shall be classified as open when one or more stitches joining a seam are broken or when two or more continuous skipped or run-off stitches occur.



Source: https://assist.dla.mil -- Downloaded: 2026-10-21T21:10Z
Check the source to verify that this is the current version before use.

| Examine | Defect | Classification Major | Minor |
|---|---|---|---|
| Run-off | (To be scored as "open seam.") | | |
| Seam or stitch type | Wrong seam or stitch type. | X | |
| Ends of stitching | Not backstitched or secured as specified. | X | |
| Stitch tension | Loose, resulting in loosely exposed top or bobbin thread; tight, resulting in excessive tightness of fabric on seams. | X | |
| Stitches per inch | One stitch less than minimum specified. | | X |
| | Two or more stitches less than minimum specified. | X | |
| | One stitch in excess of maximum specified. | | X |
| | Two or more stitches in excess of maximum specified. | X | |
| Stitching margin | Not as specified. | | X |
| Thread break | Backstitched less than 1/2 inch. | | X |
| NOTE: | Thread breaks not backstitched or overstitched, shall be scored as "open seam". | | |
| Boxstitching or "W" stitching | Not positioned as specified. | | X |
| | Dimensions of stitching not within specified range. | | X |
| Stitching | Any required row of stitching omitted. | X | |
| | Not through required layers of webbing. | X | |



Source: https://assist.dla.mil -- Downloaded: 2026-10-21T21:10Z
Check the source to verify that this is the current version before use.

| Examine | Defect | Classification Major | Minor |
|---|---|---|---|
| Component and assembly | Any component part omitted or not as specified or any required operation omitted (unless otherwise classified herein). | X | |
| | Needle chews. | X | |
| | Any mend, darn, or splice. | X | |
| Keeper chape | Turned under ends not abutted. | | X |
| Rifle strap | Any end not fused. | | X |
| | Free end not cut as specified. | | X |
| Piece "B" | Any end not fused. | | X |
| Cleanness | Noticeable grease or oil stain, 1 square inch or larger. | | X |
| Thread ends | Not trimmed to 1/4 inch maximum length. | | X |
| Marking, identification and "US" | Omitted, incorrect, illegible, misplaced, or size of characters not as specified. | | X |

* 4.4.4 End item dimensional examination. The end item shall be examined for compliance with the dimensions and tolerances specified on Drawing 2-3-169. Any dimension that exceeds the specified tolerance shall be classified as a defect. The lot size shall be expressed in units of rifle butt pocket and strap assemblies. The sample unit shall be one end item. The inspection level shall be S-3 and the AQL, expressed in terms of defects per hundred units, shall be 4.0.

* 4.4.5 Packaging inspection. The fully packaged end items shall be examined for the defects listed below. The lot size shall be expressed in units of shipping containers.. The sample unit shall be one shipping container fully packaged. The inspection level shall be S-2 and the AQL, expressed in terms of defects per 100 units, shall be 2.5.



Source: https://assist.dla.mil -- Downloaded: 2026-10-21T21:10Z
Check the source to verify that this is the current version before use.

| Examine | Defect |
|---|---|
| Marking (exterior and interior) | Omitted; incorrect; illegible; of improper size, location, sequence, or method of application. |
| Materials | Any component missing, damaged, or not as specified. |
| Workmanship | Inadequate application of components, such as: incomplete sealing or closure of flap, improper taping, loose strapping, or inadequate stapling.<br>Bulged or distorted container. |
| Content | Number per container is more or less than required. 1/ |

1/ One shipping container in the sample shall be examined for content.

4.4.6 Palletization examination. The fully packaged and palletized end items shall be examined for the defects listed below. The lot size shall be expressed in units of palletized unit loads. The sample unit shall be one palletized unit load, fully packaged. The inspection level shall be S-1 and the AQL, expressed in terms of defects per hundred units, shall be 2.5.

| Examine | Defect |
|---|---|
| Finished dimensions | Length, width, or height exceeds specified maximum requirement. |
| Palletization | Pallet pattern not as specified.<br>Interlocking of loads not as specified.<br>Load not bonded with required straps as specified. |
| Weight | Exceeds maximum load limits. |
| Marking | Omitted; incorrect; illegible; of improper size, location, sequence, or method of application. |

## 5. PACKAGING

* 5.1 Preservation. Preservation shall be level A or Commercial, as specified (see 6.2).

5.1.1 Level A. Each rifle butt pocket and strap assembly shall be compactly folded and securely tied with cotton tape or twine.



Source: https://assist.dla.mil -- Downloaded: 2026-10-21T21:10Z
Check the source to verify that this is the current version before use.

* 5.1.2 Commercial. Rifle butt pocket and strap assemblies shall be preserved in accordance with ASTM D 3951.

* 5.2 Packing. Packing shall be level A, B, or Commercial, as specified (see 6.2).

* 5.2.1 Level A packing. Two hundred rifle butt pocket and strap assemblies, preserved as specified in 5.1, shall be packed in a snug-fitting fiberboard shipping container conforming to style RSC-L, grade V2s of PPP-B-636. The inside of each shipping container shall be fitted with a box liner conforming to type CF, class weather-resistant, variety DW, grade V15c of PPP-B-636. Each container shall have the contents completely covered on the top and bottom with a sheet of 30-pound minimum basis weight kraft paper conforming to A-A-203. Each shipping container shall be closed in accordance with method III, waterproofed in accordance with method V, and reinforced as specified in the appendix of PPP-B-636 except that the inspection shall be in accordance with 4.4.5. Shipping containers shall be arranged in unit loads in accordance with MIL-L-35078 for the type and class of load specified (see 6.2). Strapping shall be limited to nonmetalic strapping, except for type II, class F loads.

* 5.2.2 Level B packing. Two hundred rifle butt pocket and strap assemblies, preserved as specified in 5.1, shall be packed in a snug-fitting fiberboard shipping container conforming to style RSC-L, type CF (variety SW) or SF, class domestic, grade 275 of PPP-B-636. The inside of each shipping container shall be fitted with a box liner conforming to type CF, class domestic, variety DW, grade 275 of PPP-B-636. Each container shall have the contents completely covered on the top and bottom with a sheet of 30-pound minimum basis weight kraft paper conforming to A-A-203. Each shipping container shall be closed in accordance with method II as specified in the appendix of PPP-B-636 except the inspection shall be in accordance with 4.4.5.

5.2.2.1 Weather-resistant fiberboard containers. When specified (see 6.2), the shipping container shall be a grade V3c, V3s, or V4s fiberboard box fabricated in accordance with PPP-B-636 and closed in accordance with method III as specified in the appendix of PPP-B-636 except that the inspection shall be in accordance with 4.4.5.

* 5.2.3 Commercial packing. Rifle butt pocket and strap assemblies preserved as specified in 5.1, shall be packed in accordance with ASTM D 3951.

* 5.3 Palletization. When specified (see 6.2), rifle butt pocket and strap assemblies, packed as specified in 5.2.2 or 5.2.3, shall be palletized on a 4-way entry pallet in accordance with load type Ia of MIL-STD-147. Pallet types shall be type I (4-way entry), type IV, or type V in accordance with MIL-STD-147. Pallets shall be fabricated from wood groups I, II, III, or IV of MIL-STD-731. Each prepared load shall be bonded with primary and secondary straps in accordance with bonding means K and L or film bonding means O or P. Pallet pattern shall be in accordance with the appendix of MIL-STD-147. Interlocking



Source: https://assist.dla.mil -- Downloaded: 2026-10-21T21:10Z
Check the source to verify that this is the current version before use.

of loads shall be effected by reversing the pattern of each course. If the container is of a size which does not conform to any of the pallet patterns specified in MIL-STD-147, the pallet pattern used shall first be approved by the contracting officer.

* 5.3 Marking. In addition to any special marking required by the contract or purchase order, shipping containers and palletized unit loads shall be marked in accordance with MIL-STD-129 or ASTM D 3951, as applicable.

6. NOTES

6.1 Intended use. One rifle butt holder and strap is to be issued with each field pack to individual military personnel involved in skiing, snowshoeing, or mountain operations. It serves to facilitate carrying of the individual weapon.

* 6.2 Ordering data. Acquisition documents should specify the following:

a. Title, number and date of this document.
b. When a first article is required (see 3.1.2, 4.3, and 6.4)
c. Selection of the applicable levels of preservation and packing (see 5.1 and 5.2).
d. Type and class of unit load required (see 5.2.1).
e. When weather-resistant grade fiberboard shipping containers are required for level B packing (see 5.2.2.1).
f. When palletization is required (see 5.3).

6.3 Samples. For access to samples, address the contracting activity issuing the invitation for bids.

6.4 First article. When a first article sample is required, it shall be inspected and approved under the appropriate provisions of FAR 52.209. The first article should be a preproduction sample. The contracting officer should specify the appropriate type of first article and the number of units to be furnished. The contracting officer should include specific instructions in all acquisition instruments regarding arrangements for selection, inspection and approval of the first article.

* 6.5 Recycled material. It is encouraged that recycled material be used when practical as long as it meets the requirements of this document (see 3.2).

6.6 Changes from previous issue. The margins of this document have been marked with an asterisk (*) to indicated where changes (additions, modifications, corrections, deletions) from the previous issue were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content as written, irrespective of the marginal notations and relationship to the last previous issue.



Source: https://assist.dla.mil -- Downloaded: 2026-10-21T21:10Z
Check the source to verify that this is the current version before use.

6.7 Subject term (key word) listing.

Field pack
Individual equipment
Rifle
Weapons carrier

Custodians:

Army - GL
Navy - MC
Air Force - 99

Review activities:

Air Force - 82
DLA - CT

User activity:

Air Force - 45

Preparing activity:

Army - GL

Project No. 8465-0921



Source: https://assist.dla.mil -- Downloaded: 2026-10-21T21:10Z
Check the source to verify that this is the current version before use.