W-L-00116/33A
May 27, 1976

SUPERSEDING
W-L-116/33-T
January 15, 1969

INTERIM FEDERAL SPECIFICATION SHEET
LAMP FLUORESCENT
TRADE NO. F96T12/CW/HO, RAPID START, 105 WATT, T-12 BULB (96")
COOL WHITE, RECESSED DOUBLE CONTACT BASE, HIGH OUTPUT
(DETAIL SPECIFICATION)

The complete requirements for Lamp, Fluorescent described herein shall consist of this document and W-L-00116D.

This Interim Federal Specification Sheet was developed by General Services Administration, Federal Supply Service, Mechanical and Electrical Division, Washington, DC 20406, based upon currently available technical information. It is recommended that Federal agencies use it in procurement and forward recommendations for changes to the preparing activity at the address shown above.

The General Services Administration has authorized the use of this Interim Federal Specification Sheet as a valid exception to W-L-116a dated June 23, 1964.

Requirements:

TABLE I.

Lamp Size		Base	Color	Required Life (hours)	Minimum Lumens	
Nominal Watts	Bulb				at 100 hours	at 40% of Life
105	T-12	Recessed Double Contact	Cool White	12,000	8400	7200

Dimensions: A deviation in dimension from ANSI C78. 702 shall be considered a defect.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:24Z
Check the source to verify that this is the current version before use.