AA-D-195b
Interim Amendment-3
January 29, 1963
SUPERSEDING
Interim Amendment-2
February 23, 1962

INTERIM AMENDMENT TO

FEDERAL SPECIFICATION

DESK, FLAT TOP, STEEL, CONFERENCE-TYPE

This Interim Amendment was developed by GSA, FSS, Standardization Division, Washington 25, D. C., based upon currently available technical information. It is recommended that Federal agencies use it in procurement and forward recommendations for changes to the preparing activity at the address shown above.

The General Services Administration has authorized Federal agencies to use this Interim Amendment as a valid exception to Federal Specification AA-D-195b.

Page 1, paragraph 2.1, Federal Specifications: Add the following:

"PPP-C-843 - Cushioning Material, Cellulosic.
PPP-T-97 - Tape; Pressure-sensitive, Filament Reinforced".

Page 2, paragraph 2.1, Military Specifications: Add the following:

"MIL-W-12332(ORD) - Welding, Resistance, Spot and Projection; for Fabricating Assemblies of Low-carbon Steel".

Page 3. Add a new paragraph as follows:

"3.2.4.1 Spot welding.- Spot welds shall not be closer to the edge of either adjoining member than 1/2 the greatest dimension of the spot weld, nor shall they be centered closer together than twice the greatest dimension. Squeeze time, weld time and hold time shall be controlled to produce uniform welds that will meet the test specified in 4.5.4. All exposed spot or projection welds shall be filled and ground smooth. The term "electric welding" is deleted herein and "spot welded on maximum of 4 inch centers" is substituted therefor."

Page 5, continuation of paragraph 3.2.10.2, 10th line from top. Delete "16 pounds" and substitute "50 pounds".

FSC 7110

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:39Z
Check the source to verify that this is the current version before use.

Page 5, paragraph 3.2.11. Delete the entire paragraph and substitute the following: -

"3.2.11 Drawers.- The number, kind and minimum inside clear dimensions of the drawers shall be as shown in figure 1. Each storage drawer shall be equipped with a minimum of one partition. Each letter drawer shall be equipped with a compressor for front to back filing. The compressor shall be controlled by spring tension and shall operate easily within the drawer when released and be held firmly when engaged. The compressor face shall be not less than 18 gage (0.0478 inch) steel and the tension release lever shall be smoothly formed and reinforced for strength and convenience of releasing. The letter drawer shall also be equipped with hanging file supports as specified in 3.2.11.3.1. The front of the drawers shall be flush with the front section of the desk. Drawers shall fit into pedestal opening without binding and without a gap."

Page 5, paragraph 3.2.11.3, 17th line. After "drawer sides" delete period and add the following:

"which shall be a minimum of 9-3/8 inches inside height".

Page 5, paragraph 3.2.11.3.1. Delete entire paragraph and substitute the following:

"3.2.11.3.1 Hanging file supports.- The letter drawer shall be equipped with hanging file supports consisting of two removable supports and one removable partition. The hanging file supports shall accommodate side-to-side filing of letter size hanging folders and shall be located in the front part of the drawer, and shall hold hanging folders which are 11-3/4 inches wide by 9-7/8 inches high (9-7/8inches includes 5/84inch high tab). The folders are hung by means of arms which end in hooks and which extend 5/8 inch beyond each side of the folder. The supports shall be located across the drawer. One support shall be located sufficiently back from the inside of the drawer front to provide clearance for the folder arm and hook to rest and slide easily on the support. The other support shall be located approximately 12 inches back of the first support. The removable partition shall be located a sufficient distance from the second support to provide clearance for the folder arm and hook to rest and slide easily on the second support. The upper edges of the file supports and the upper edge of the partition shall be the same height as the drawer side which has an inside height of 9-3/8 inches. The edges of the supports and the partition shall be formed in a bead or fold to prevent rough or sharp edges. Any bends in the design for the purpose of attachment to the drawer sides shall not interfere with insertion or withdrawal of hanging files. The letter drawer sides shall be punched to hold supports and partition firmly in place. The partition shall be held in a vertical position at all times. The supports shall have sufficient strength and rigidity to hold the full capacity of hanging folders and filing material without sagging."

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:39Z
Check the source to verify that this is the current version before use.

Page 6, paragraph 3.2.11.4. Delete second sentence and substitute the following:

"The tray shall have not less than three compartments; two of which shall be 3 inches wide, plus or minus 3/8 inch; and one pencil compartment."

Page 6, paragraph 3.2.11.4, 7th line. Delete "2 inches wide" and substitute "3 inches wide".

Page 6, paragraph 3.2.11.5, 21st line. After "storage drawer operation", add the following:

"The nylon bearing surface (button) shall have a formed or split shank which will lock the button securely in place."

Page 6, paragraph 3.2.12, 13th line. Delete "20 gage (0.0359 inch) steel." and substitute the following:

"22 gage (0.0299 inch) steel formed in a box channel shape and joining the front and back uprights."

Page 7, paragraph 3.2.13. Delete last sentence and substitute the following:

"The back panel shall be located in from the back of the pedestal over a range of from 1-1/4 inches to 1-3/4 inches."

Page 7, paragraph 3.2.14. Delete the entire paragraph and substitute the following:

"3.2.14 Sliding shelf.- The drawer pedestal sliding shelf shall be not less than 18 gage (0.0478 inch) steel formed channel shape on the front and side edges and with the front edge folded over. Alternatively, the sliding shelf may be formed of not less than 20 gage (0.0359 inch) steel formed channel shape along the sides, with the front edge folded over forming a double thickness across the front; the sides shall be reinforced with not less than 16 gage (0.0598 inch) steel channels inset and spot welded to the side channels of the top plate of the sliding shelf. The sliding shelf shall operate on 16 gage (0.0598 inch) steel runners formed channel and Z shape which will permit the shelf to extend horizontally not less than 14-3/4 inches from the front of the top of the desk. Alternatively, the shelf may operate on 18 gage (0.0478 inch) steel runners when the steel runners, formed channel and Z shape, shall be incorporated as part of a one-piece formed assembly consisting of the desk front and rear horizontal tie members, the two steel runners, and the necessary reinforcing gussets and stops. Rubber or felt bumpers or coil or leaf springs shall be provided as a noise reductin stop when the shelf is fully extended or pushed into the pedestal. The shelf may incorporate a convenience tray with a sliding palstic or metal cover."

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:39Z
Check the source to verify that this is the current version before use.

Page 9. Add a new paragraph as follows:

"4.5.4 Spotwelds.- Spotwelds shall meet the peel test specified in 4.1.4 of MIL-W-12332(ORD) and button diameter shall conform to Table II as specified therein."

Page 9, paragraph 5.1.1.1. Delete entire paragraph and substitute the following:

"5.1.1.1 Drawers and sliding shelves.- All drawers shall be prevented from vibrating while in transit by wedging cushioning material conforming to type III of PPP-C-843 between the drawer and the drawer frame. The sliding shelf shall be secured closed by means of pressure-sensitive adhesive tape conforming to PPP-T-97 applied over edges of shelf and adjacent desk body, or by wedging cushioning material as specified for drawers between the sliding shelf and the shelf frame, or by the use of commercial type clips designed for this purpose. All drawers shall be secured closed by locking the center drawer. The keys shall be placed in a cotton cloth drawstring bag, the bag securely knotted closed, and then securely tied to a drawer handle. If design of drawer handle precludes attachment of the bag, the key inside the bag shall be taped to the inside of the center drawer. Loose drawer partitions shall be wrapped in cushioning material specified or similar cushioning material and secured within the drawer with tape specified."

GSA-WASH DC 63-10251 Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:39Z
Check the source to verify that this is the current version before use.