AA-T-112
Interim Amendment-3(GSA-FSS)
June 10, 1966
SUPERSEDING
Interim Amendment-2(GSA-FSS)
July 7, 1961

INTERIM AMENDMENT

TO

FEDERAL SPECIFICATION

TABLES, WOOD, GENERAL OFFICE

This interim amendment was developed by the Standardization Division, Federal Supply Service, General Services Administration, Washington, D. C. 20406, based upon currently available technical information. It is recommended that Federal agencies use it in procurement and forward recommendations for changes to the preparing activity at the address shown above.

The General Services Administration has authorized the use of this interim amendment as a valid exception to Federal Specification AA-T-112, dated July 25, 1955.

Page 1, lower right hand corner Add "FSC 7110

Page 1, Section 2 Delete entire section and substitute the following

[illegible] POST [illegible]

2.1 Specifications and standards. The following specifications and standards, of the issues in effect on date of invitation for bids or request for proposal, form a part of this specification to the extent specified herein.

Federal Specifications

L-P-00508	-	Plastic Sheet, Laminated, Decorative, and Nondecorative.
L-T-0041	-	Table Top and Furniture Assemblies (Plastic Thermosetting Resin Laminate).
TT-L-57	-	Lacquer, Rubbing, Clear (for Wood Furniture)
TT-L-58	-	Lacquer; Spraying, Clear and Pigmented Cellulose Nitrate (General Interior Use).
UU-P-271	-	Paper, Wrapping, Waterproofed Kraft.
MMM-A-100	-	Adhesive, Animal-glue.
MMM-A-125	-	Adhesive, Casein-type, Water-and Mold-resistant.
MMM-A-188	-	Adhesive, Urea-resin-type (Liquid and Powder).
MMM-A-260	-	Adhesive, Water-resistant, (for Sealing Waterproofed Paper).
PPP-B-585	-	Boxes, Wood, Wirebound.
PPP-B-591	-	Boxes, Fiberboard, Wood-cleated.
PPP-B-601	-	Boxes, Wood, Cleated-plywood.
PPP-B-621	-	Boxes, Wood, Nailed and Lock-corner.
PPP-B-636	-	Boxes, Fiberboard.
PPP-B-640	-	Boxes, Fiberboard, Corrugated, Triple-wall.
PPP-P-291	-	Paperboard, Wrapping, Cushioning.

Federal Standards:

Fed. Std. No. 123 - Marking for Domestic Shipment (Civilian Agencies).

FSC 7110

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:39Z
Check the source to verify that this is the current version before use.

(Activities outside the Federal Government may obtain copies of Federal Specifications, Standards, and Handbooks as outlined under General Information in the Index of Federal Specifications and Standards and at the prices indicated in the Index. The Index, which includes cumulative monthly supplements as issued, is for sale on a subscription basis by the Superintendent of Documents, U.S. Government Printing Office, Washington, D.C., 20402.

(Single copies of this specification and other product specifications required by activities outside the Federal Government for bidding purposes are available without charge at the General Services Administration Regional Offices in Boston, New York, Washington, D.C., Atlanta, Chicago, Kansas City, Mo., Dallas, Denver, San Francisco, Los Angeles, and Seattle, Wash.

(Federal Government activities may obtain copies of Federal Specifications, Standards, and Handbooks and the Index of Federal Specifications and Standards from established distribution points in their agencies.)

Military Standards:

MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes.
MIL-STD-129 - Marking for Shipment and Storage.

(Copies of Military Specifications and Standards required by contractors in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

2.2 Other publications. The following documents form a part of this specification to the extent specified herein. Unless otherwise indicated, the issue in effect on date of invitation for bids or request for proposal shall apply.

Commercial Standard:

CS35-61 - Hardwood Plywood

(Copies of the Commercial Standard referenced above, which is a Department of Commerce publication, may be obtained upon application, accompanied by money order, coupon, or cash, to the Superintendent of Documents, Government Printing Office, Washington, D. C. 20402. Prices may be obtained from the Superintendent of Documents).

Page 3, Table I.- Adhesives, next to last line: Delete "CS-35-49" and substitute "CS35-61.

Page 4, paragraph 3.1.4.3, line 3: Delete "CS-35-49" and substitute "CS35-61."

Page 4, paragraph 3.1.4.3, lines 7 and 8: After "1/28 inch thick" add", except for walnut which shall be not less than 1/32 inch thick,".

Page 4, paragraphs 3.1.5 and 3.1.5.1: Delete entire paragraphs and substitute the following:

"3.1.5 Laminated plastic sheets.

3.1.5.1 Decorative face sheets. The decorative face sheets shall conform to style D, type I, grade HP, class 1, finish A (satin) of L-P-00508 and the nominal thickness shall be 0.062 (1/16) inch. The decorative laminate shall simulate the general appearance of other exposed wood parts for color, grain, and finish.

3.1.5.2 Nondecorative backing sheets. The nondecorative backing sheets shall conform to style ND, type V, grade HP of L-P-00508 and the nominal thickness shall be 0.030 inch.

Source: https://assist.dla.mil -- Downloaded: 202610-26T11:39Z
Check the source to verify that this is the current version before use.

Page 5, Table II Delete first, second and third columns and substitute the following:

Color of finish	Exposed parts 6	
	Veneers (except legs)	Solid parts and veneered legs (one only for any one item)
Light oak	Oak	Oak
Walnut	Beech Birch Cherry Mahogany 2 Maple Pecan Walnut	Beech Birch Cherry Mahogany 2 Maple Pecan Walnut

Page 5, Table II, footnote 6: Delete entire footnote.

Page 5, after footnote 5: Add the following new footnote 6:

6 Must of like species in any one table, i.e., if pecan veneer is used, solid pecan shall also be used."

Page 5, paragraph 3.2.3.1: Delete entire paragraph and substitute the following:

"3.2.3.1 Tops, decorative laminate. When decorative laminate is specified as a top surfacing (see 6.2), the tops shall be surfaced with plastic face sheets, specified in 3.1.5.1, and with plastic backing sheets specified in 3.1.5.2. The table top assembly shall conform to the requirements of type II of L-T-0041. The edge banding (solid wood molding) shall be applied as specified in 3.2.3 before the decorative laminate is applied to the plywood top, and the nondecorative backing sheet is applied to the underside of the top. The top edge and corners of the solid wood molding and decorative laminate top surfacing shall be rounded on a uniform radius of not less than 1/8 inch. The lower edge of the molding and nondecorative backing sheet shall be eased to approximately a 1/16 inch radius or chamfer."

Page 7, paragraph 3.3.2, line 1: After "underside of" add "the wood veneer."

Page 7, paragraph 3.3.2.2, line 1: After "underside of" add "the wood veneer."

Page 7, paragraph 3.3.2.2, lines 1 and 2: After "underside of the" add "wood veneer."

Page 7, paragraph 3.4: Delete entire paragraph and substitute the following:

"3.4 Identification Marking. Each item shall be permanently and legibly marked in an inconspicuous place with the specification number, Federal Stock Number, contract number, date of manufacture and the manufacturer's name or trade-mark, so that the source of supply may be readily determined.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:39Z
Check the source to verify that this is the current version before use.

Page 8, Section 5 Delete entire section and substitute the following:

"5. PREPARATION FOR DELIVERY

5.1 Packaging. Packaging shall be level A, B, or C, as specified (see 6.1).

5.1.1 Level A or B. The legs shall be removed from the table and the nuts shall be replaced and tightened on bolts. The legs shall be individually wrapped in a sheet of machine-glazed kraft paper. Two legs shall be nested head-to-foot and overwrapped in at least two thicknesses of single-face corrugated fiberboard (flexible) conforming to type I of PPP-P-291, and taped. The wrapped legs shall be placed in a fiberboard box conforming to PPP-B-636, class domestic, style optional, minimum 175 p.s.i. bursting strength. The box containing wrapped legs shall be secured to prevent opening during shipment. The drawer shall be immobilized by means of strips of commercial pressure-sensitive tape, minimum 2-inch width, applied over all applicable edges of the drawer front and adjacent surfaces of the table. Alternatively, metal drawer clips may be used. All finished surfaces of the table shall be completely covered with a sheet of machine-glazed kraft paper having a minimum basis weight of 30 pounds per ream (24 by 36 - 500). The paper shall be taped to the underside of the apron and drawers. The top of the table shall be cushioned with a pad fabricated from one of the following materials or a combination of these materials to provide built-up cushioning of not less than 3/4 inch in thickness:

1. Macerated paper.
2. Shredded paper.
3. Wood wool.
4. Laminated creped cellulose wadding backed with corrugated fiberboard
5. Wood fiber felt.
6. Creped cellulose wadding
7. Excelsior (sealed ends).
8. Cotton wadding.
9. Molded pulpboard.

Table sizes 1, 2, and 3 shall have the wrapped legs positioned lengthwise against the front and rear of the drawer, and table size 4 shall have the legs positioned inside of apron. All legs shall be secured to prevent movement in transit.

5.1.2 Level C. Table shall be packaged in accordance with the supplier's commercial practice.

5.2 Packing. Packing shall be level A, B, or C, as specified (see 6.1).

5.2.1 Level A. Each table, packaged as specified in 5.1.1, shall be covered with a shroud constructed of material conforming to UU-P-271, class H or M. All seams of the shroud shall be sealed with adhesive conforming to MMM-A-260. The shrouded table shall be packed in any of the containers conforming to the following specifications at the option of the contractor:

Specification	Type or Class
PPP-B-585	Class 3 use
PPP-B-591	Class II
PPP-B-601	Overseas type
PPP-B-621	Class 2
PPP-B-640	Class 2, grade A

Closure and strapping shall be in accordance with the appendix to the applicable box specification.

5.2.2 Level B. Each table, packaged in accordance with 5.1.1, shall be packed in a new fiberboard shipping container constructed to conform to class domestic, style FTC (full-telescope), of PPP-B-636. Burst test of fiberboard used in construction of the container shall be not less than 350 p.s.i., and the container shall be closed and strapped in accordance with the appendix of the box specification. Prior to closure, folded or built-up pads of corrugated fiberboard of not less than 2-1/4 inches thickness by 4-inches in width by not less than 18 inches in length shall be placed and secured by tape, between the outside surfaces of table aprons and inside surface of container, on both sides and both ends of the table. Pads shall be centered to aprons, approximately equidistant from ends of aprons. Box containing legs shall be placed and secured as specified in 5.1.1 prior to closure and strapping. Alternatively, in lieu of metal strapping, plastic-laminating fiber strapping may be used, substituted for metal strapping size for size in accordance with the fiber strip manufacturer's table of recommended replacement for metal strap.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:39Z
Check the source to verify that this is the current version before use.

5.2.3 Level C Tables shall be packed to insure carrier acceptance and safe delivery to destination in containers complying with the rules and regulations applicable to the mode of transportation.

5.3 Marking.

5.3.1 Civil agencies. In addition to markings required by the contract or order, the packages and shipping containers shall be marked in accordance with Fed. Std. No. 123.

5.3.2 Military activities. In addition to markings required by the contract or order, the packages and shipping containers shall be marked in accordance with MIL-STD-129.

Page 9, paragraph 6.1. Delete entire paragraph and substitute the following.

6.1 Ordering data. Purchasers should select the preferred options permitted herein and include the following information in procurement documents:

(a) Title, number, and date of this specification.

(b) Size (see 1.2.1)

(c) Color (see 1.2.2)

(d) When plastic laminate tops are required (see 3.2.3.1).

(e) Selection of applicable level of packaging and packing required (see 5.1 and 5.2).

Page 10, paragraph 6.5 Delete entire paragraph.

Page 10: Delete Patent Notice paragraph.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:39Z
Check the source to verify that this is the current version before use.