NOTICE OF
CHANGE

DOD-STD-35-125(MI)
NOTICE 2
18 SEPTEMBER 1992

MILITARY STANDARD

AUTOMATED ENGINEERING
DOCUMENT PREPARATION SYSTEM

DISPLAYS, ELECTRO-OPTICAL

TO ALL HOLDERS OF DOD-STD-35-125(MI):

1. THE FOLLOWING PAGES OF DOD-STD-35-125(MI) HAVE BEEN REVISED AND SUPERSEDE THE PAGES LISTED.

| NEW PAGE | DATE | SUPERSEDED PAGE | DATE |
|---|---|---|---|
| v | 18 SEPTEMBER 1992 | v | 30 AUGUST 1978 |
| vi | 18 SEPTEMBER 1992 | vi | 30 AUGUST 1978 |
| 1 | 30 AUGUST 1978 (Reprinted without change) | | |
| 2 | 18 SEPTEMBER 1992 | 2 | 30 AUGUST 1978 |
| 3 | 18 SEPTEMBER 1992 | 3 | 30 AUGUST 1978 |
| 4 | 18 SEPTEMBER 1992 | 4 | 30 AUGUST 1978 |
| 9 | 18 SEPTEMBER 1992 | 9 | 30 AUGUST 1978 |
| 10 | 18 SEPTEMBER 1992 | 10 | 30 AUGUST 1978 |
| 59 | 30 AUGUST 1978 (Reprinted without change) | | |
| 60 | 18 SEPTEMBER 1992 | 60 | 30 AUGUST 1978 |
| 61 | 18 SEPTEMBER 1992 | 61 | 30 AUGUST 1978 |
| 62 | 30 AUGUST 1978 (Reprinted without change) | | |
| 87 | 30 AUGUST 1978 (Reprinted without change) | | |
| 88 | 18 SEPTEMBER 1992 | 88 | 30 AUGUST 1978 |
| 89 | 18 SEPTEMBER 1992 | 89 | 30 AUGUST 1978 |
| 90 | 30 AUGUST 1978 (Reprinted without change) | | |

2. RETAIN THIS NOTICE PAGE AND INSERT BEFORE THE TABLE OF CONTENTS.

3. Holders of DOD-STD-35-125(MI) will verify that page changes and additions indicated above have been entered. The notice page will be retained as a check sheet. This issuance, together with appended pages is a separate publication. Each notice is to be retained by stocking points until the Military Standard is completely revised or canceled.

Custodians:
Army-MI

Review activities:
Army-AT, AV, CR, ER
ME, MR, SC

User activity
Army - AR

Preparing activity:
Army - MI

(Project EGDS-A459)

AMSC N/A

AREA EGDS

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 202640-23T21:04Z
Check the source to verify that this is the current version before use.

CONTENTS

| | | | Page |
|---|---|---|---|
| Paragraph | 1. | SCOPE | 1 |
| | 1.1 | General | 1 |
| | 1.2 | Purpose | 1 |
| | 1.3 | Utilization | 1 |
| | 1.4 | Military Specification Exception Title Index | 1 |
| | 2. | APPLICABLE DOCUMENTS | 3 |
| | 2.1 | Government documents | 3 |
| | 2.2 | Non-Government publications | 3 |
| | 3. | DEFINITIONS | 5 |
| | 4. | GENERAL REQUIREMENTS | 7 |
| | 4.1 | Introduction | 7 |
| | 4.2 | Specification Requirement Sheet (SRS) | 7 |
| | 4.3 | Configuration | 7 |
| | 4.3.1 | Dimensions | 7 |
| | 4.3.2 | Illustrations | 7 |
| | 4.4 | Units of measure | 7 |
| | 5 | DETAILED REQUIREMENTS | 9 |
| | 5.1 | Introduction | 9 |
| | 5.2 | MSE Formats | 9 |
| | 5.3 | Referenced documents | 9 |
| | 5.4 | Deleted | 9 |
| | 5.5 | Tabulation | 10 |
| | 5.6 | Segment table | 13 |
| | 5.7 | Function table | 13 |
| | 5.8 | Keyword Code Index (KCI) and Standard Paragraphs | 17 |
| | 5.8.1 | Interrelationship of Codes | 17 |
| | 5.8.2 | Automatic MSE Data | 17 |
| | 5.8.3 | DOD-STD-35 Tables | 17 |

FIGURES

| | | | |
|---|---|---|---|
| Figure | 1. | Example of SRS entries for a function table | 14 |
| | 2. | Example of a function table printed in an MSE | 15 |





Source: https://assist.dla.mil - Downloaded: 202610-23T21:04Z
Check the source to verify that this is the current version before use.

CONTENTS (CONT)

Page

TABLES

| | | | |
|---|---|---|---|
| Table | I. | Title Index | 2 |
| | II. | Deleted | 10 |
| | III. | Tabulation Candidates | 11 |
| | IV. | Numeric segment | 129 |
| | V. | Alphanumeric segment | 130 |
| | VI. | Special character segment | 132 |
| | VII. | Function | 133 |
| | VIII. | Terminal assignment | 134 |

APPENDICES

| | | | |
|---|---|---|---|
| Appendix | A. | Tables | 127 |
| | B. | Illustrations | 135 |
| | C. | Characteristic Code Index | 149 |
| | | Index | 161 |



Source: https://assist.dla.mil -- Downloaded: 202610-23T21:04Z
Check the source to verify that this is the currentversion before use.

# 1. SCOPE

1.1 General. This dash-numbered part of the Automated Engineering Document Preparation System (AEDPS), provides detailed requirements for the preparation of Military Specification Exception (MSE) documentation for electro-optical displays.

1.2 Purpose. This military standard provides the necessary information to prepare a Specification Requirement Sheet (SRS) which will be used to generate an MSE by automated data processing.

1.3 Utilization. General instructions, quality assurance provisions, packaging, and notes, applicable to all AEDPS dash-numbered parts have been included in the basic document (DOD-STD-35) to avoid redundancy. Unless otherwise specified in this dash-numbered part, the following list contains additional subjects that are applicable to all AEDPS dash-numbered parts and are included in DOD-STD-35:

a. Writing Methodology
b. Document and Part Numbering
c. Applicable Documents
d. Single and Multi-item Specifications (Tabulation)
e. Keyword Code Index (KCI)
f. General Requirements of AEDPS

1.4 Military Specification Exception Title Index. The title code for an MSE shall be selected from one of the MSE titles listed in the Title Index (see table I). Data bases have been established for the generation of MSE's for the MSE titles indicated. If a suitable title code is not contained in the Title Index, leave the title code spaces on the SRS blank, and attach a request for the assignment of a title code. Include in the request the desired title and the base document identifier. A code will be assigned and the code, title, and base document will be made a part of the Title Index.

One of the six-digit codes listed in the Title Index entered on an SRS, specifies that the title of the MSE will be the title shown in the Title Index.

Each MSE title listed in the Title Index, is compatible with the document(s) listed with that title under base document. The list of base documents may or may not be a complete listing. The information is intended for the user's reference; when more than one document is listed for an MSE title, this information will be found useful in determining which of the documents is most suitable for use as the base document.



Source: https://assist.dla.mil -- Downloaded: 2026-10-23T21:04Z
Check the source to verify that this is the current version before use.

The MSE title may or may not be the same as the title used in DODISS, FIIG, or the base document. In general, the MSE title uses the basic federal item name listed in Cataloging Handbook H6. However, titles with additional modifying and identifying words are provided to assist in defining the scope of the MSE. Also, less restrictive titles are provided to prevent exclusion of items.

TABLE I. TITLE INDEX

| MSE TITLE | TITLE CODE | BASE DOCUMENT NUMBER | BASE DOCUMENT COVERAGE |
|---|---|---|---|
| DISPLAY, ELECTRO-OPTICAL | 906001 | MIL-D-28803 | READOUTS, SEGMENTED |
| INDICATOR, DIGITAL DISPLAY | 906002 | MIL-D-28803 | READOUTS, SEGMENTED |
| READOUT, INCANDESCENT TYPE | 906003 | MIL-R-39027 | READOUTS, INCANDESCENT |
| READOUT, SEGMENTED | 906004 | MIL-D-28803 | READOUTS, SEGMENTED |



Source: https://assist.dla.mil -- Downloaded: 2026-10-23T21:04Z
Check the source to verify that this is the current version before use.

## 2. APPLICABLE DOCUMENTS

2.1 Government documents.

2.1.1 Specifications, standards, and handbooks. The following specifications, standards, and handbooks form a part of this document to the extent specified herein. Unless otherwise specified, the issues of these documents are those listed in the issue of the Department of Defense Index of Specifications and Standards (DODISS) and supplement thereto, cited in the solicitation.

SPECIFICATIONS

MILITARY

| | |
|---|---|
| MIL-D-28803 | Readouts, Segmented, General Specification For |

STANDARDS

MILITARY

| | |
|---|---|
| DOD-STD-35 | Automated Engineering Document Preparation System |
| MIL-STD-108 | Definition of and Basic Requirements for Enclosures for Electric and Electronic Equipment |
| MIL-STD-130 | Identification Marking of U.S. Military Property |
| MIL-STD-202 | Test Methods for Electronic and Electrical Component Parts |
| MIL-STD-810 | Environmental Test Methods |
| MIL-STD-1285 | Electronic Parts Marking |

(Unless otherwise indicated, copies of federal and military specifications, standards, and handbooks are available from the Standardization Documents Order Desk, Bldg 4D, 700 Robbins Avenue, Philadelphia, PA 19111-5094.)



Source: https://assist.dla.mil -- Downloaded: 202640-23T21:04Z
Check the source to verify that this is the currentversion before use.

2.2 Non-Government publications. The following document(s) form a part of this document to the extent specified herein. Unless otherwise specified, the issues of the documents which are DoD adopted are those listed in the issue of the DODISS cited in the solicitation. Unless otherwise specified, the issues of documents not listed in the DODISS are the issues of the documents cited in the solicitation.

| | |
|---|---|
| ASTM E 308 | Spectrophotometry and Description of Color in CIE 1931 System, Rec. Practice For |
| ASTM E 380 | Standard for Metric Practice |

(Application for copies should be addressed to the American Society for Testing and Materials,, 1916 Race St., Philadelphia, Pa. 19103.)



Source: https://assist.dla.mil -- Downloaded: 202610-23T21:04Z
Check the source to verify that this is the current version before use.

# 5. DETAILED REQUIREMENTS

5.1 Introduction. This section provides instructions for completion of the SRS and references for instructions on specific requirements contained in DOD-STD-35.

5.2 MSE formats. AEDPS has the capability to prepare a six-section or a single-section document. The six-section document appears similar to a six-section military specification. The single-section document appears similar to a military specification sheet. Specification requirements described in DOD-STD-35 are applicable to either of the formats selected. It is mandatory that one of the two following codes and an "X" be entered on the SRS to create the desired MSE format:

a. 0700 for a six-section format

b. 0800 for a single-section format

5.3 Referenced documents. Section 2 of the MSE may contain a list of all referenced documents within Sections 3, 4, and 5 of the MSE. Instructions for referencing documents to appear in Section 2 of the forthcoming MSE are contained in DOD-STD-35.

5.4 Deleted


Source: https://assist.dla.mil -- Downloaded: 2026-10-23T21:04Z
Check the source to verify that this is the current version before use.

5.5 Tabulation. Instructions for tabulation are provided in DOD-STD-35. Table III provides codes for column headings which may be used for electro-optical display characteristics. When different units of measure within one system (U.S. or SI) are available for specifying a characteristic, only one of the units may be tabulated; e.g. either ounces or pounds.



Source: https://assist.dla.mil -- Downloaded: 202610-23T21:04Z
Check the source to verify that this is the current version before use.

| CHAR CODE | STANDARD PARAGRAPH |
|---|---|

1872 CHROMATICITY. THE REQUIREMENT(S) SHALL BE IN ACCORDANCE WITH THE BASE DOCUMENT, EXCEPT 1872.

1873 CHROMATICITY. THE CHROMATICITY EXPRESSED AS X AND Y COORDINATES ON THE CIE CHROMATICITY DIAGRAM SHALL BE IN ACCORDANCE WITH THE CHROMATICITY TABLE.

CHROMATICITY TABLE

| COORDINATES | |
|---|---|
| X | Y |
| 3900 | 3901 |
| 3902 | 3903 |
| 3904 | 3905 |
| 3906 | 3907 |

1874 CHROMATICITY. TESTING SHALL BE PERFORMED IN ACCORDANCE WITH THE BASE DOCUMENT, EXCEPT 1874.

1876 CHROMATICITY. TESTING SHALL BE PERFORMED IN ACCORDANCE WITH 1876.

1878 THE SPECTROGRAPHIC MEANS SHALL BE BY SPECTROPHOTOMETER.

1880 THE SPECTROGRAPHIC MEANS SHALL BE BY SPECTRORADIOMETRIC.

1882 THE SPECTROGRAPHIC MEANS SHALL BE BY VISUAL COMPARATOR.

1838 THE SOURCE ILLUMINATE SHALL BE 1838 DEGREES KELVIN.



Source: https://assist.dla.mil -- Downloaded: 2026-10-23T21:04Z
Check the source to verify that this is the current version before use.

KEYWORD CODE INDEX (KCI)

| CHARACTERISTIC NAME | CHAR CODE |
|---|---|
| CONTRAST RATIO | |
| REQUIREMENTS (SELECT ONE) | |
| PER BASE DOCUMENT EXCEPT ____ | 1884 |
| RATIO (NUMBER) | 1886 |
| TEST METHODS (SELECT ONE) | |
| PER BASE DOCUMENT EXCEPT ____ | 1888 |
| PER MIL-D-28803. | 1890 |
| ILLUMINATED (SELECT ONE) | |
| ALL SEGMENTS ILLUMINATED. | 1892 |
| ALTERNATE SEGMENTS ILLUMINATED. | 1894 |
| ILLUMINATION (SELECT ONE) | |
| INCIDENTAL ILLUMINATION | |
| (LUX) | 1896 |
| (FOOTCANDLES) | 1898 |
| MEASURING DEVICE (TYPE) | 1900 |
| DIELECTRIC WITHSTANDING VOLTAGE AT REDUCED BAROMETRIC PRESSURE | |
| REQUIREMENTS (SELECT ONE) | |
| PER BASE DOCUMENT EXCEPT ____ | 4908 |



Source: https://assist.dla.mil -- Downloaded: 2026-10-23T21:04Z
Check the source to verify that this is the current version before use.

| CHAR CODE | STANDARD PARAGRAPH |
|---|---|
| 1884 | CONTRAST RATIO. THE REQUIREMENT(S) SHALL BE IN ACCORDANCE WITH THE BASE DOCUMENT, EXCEPT 1884. |
| 1886 | CONTRAST RATIO. THE CONTRAST RATIO SHALL BE 1886. |
| 1888 | CONTRAST RATIO. TESTING SHALL BE PERFORMED IN ACCORDANCE WITH THE BASE DOCUMENT, EXCEPT 1888. |
| 1890 | CONTRAST RATIO. TESTING SHALL BE PERFORMED IN ACCORDANCE WITH MIL-D-28803. |
| 1892 | ALL SEGMENTS SHALL BE ILLUMINATED. |
| 1894 | ALTERNATE SEGMENTS SHALL BE ILLUMINATED. |
| 1896 | THE INCIDENTAL ILLUMINATION SHALL BE 1896 LUX. |
| 1898 | THE INCIDENTAL ILLUMINATION SHALL BE 1898 FOOTCANDLE(S). |
| 1900 | THE MEASURING DEVICE TYPE SHALL BE 1900. |
| 4908 | DIELECTRIC WITHSTANDING VOLTAGE AT REDUCED BAROMETRIC PRESSURE. THE REQUIREMENT(S) SHALL BE IN ACCORDANCE WITH THE BASE DOCUMENT, EXCEPT 4908. |



Source: https://assist.dla.mil -- Downloaded: 202610-23T21:04Z
Check the source to verify that this is the currentversion before use.

KEYWORD CODE INDEX (KCI)

| CHARACTERISTIC NAME | CHAR CODE |
|---|---|
| DIELECTRIC WITHSTANDING VOLTAGE AT REDUCED BAROMETRIC PRESSURE (CONT) | |
| REQUIREMENTS (CONT) | |
| NO EVIDENCE OF FLASHOVER, MECHANICAL DAMAGE, ARCING, OR INSULATION BREAKDOWN. | 4906 |
| MAXIMUM LEAKAGE (MILLIAMPERES) | 4894 |
| REMAIN WITHIN SPECIFIED TOLERANCE. | 4901 |
| TEST METHODS (SELECT ONE) | |
| PER BASE DOCUMENT EXCEPT ____ | 4884 |
| PER MIL-STD-202, METHOD 301. | 6300 |
| *ALTITUDE PER METHOD 105 OF MIL-STD-202 | |
| *TEST CONDITION (LETTER) | 4886 |
| *TEST VOLTAGE (SELECT ONE) | |
| (VOLTS, DC) | 4885 |
| (VOLTS, AC) | 4849 |



Source: https://assist.dla.mil -- Downloaded: 2026-10-23T21:04Z
Check the source to verify that this is the current version before use.

| CHAR CODE | STANDARD PARAGRAPH |
|---|---|
| 1397 | MOISTURE RESISTANCE. TESTING SHALL BE PERFORMED IN ACCORDANCE WITH METHOD 106 OF MIL-STD-202. |
| 1395 | POLARIZING VOLTAGE SHALL BE 1395 VOLTS, DC. |
| 4981 | LOADING VOLTAGE SHALL BE 4981 VOLTS, DC. |
| 4980 | LOADING VOLTAGE SHALL BE 4980 VOLTS, AC. |
| 4991 | 4991 PERCENT OF THE SAMPLE SHALL BE SUBJECTED TO THE POLARIZING VOLTAGE. |
| 4985 | STEP 7A OF METHOD 106 OF MIL-STD-202 IS NOT APPLICABLE. |
| 4986 | STEP 7B OF METHOD 106 OF MIL-STD-202 IS NOT APPLICABLE. |
| 1449 | MOUNTING SHALL BE IN ACCORDANCE WITH 1449. |
| 4983 | PERFORM DIELECTRIC WITHSTANDING VOLTAGE TEST AT HIGH HUMIDITY. |
| 4984 | PERFORM DIELECTRIC WITHSTANDING VOLTAGE TEST AFTER DRYING. |
| 1954 | OVERLOAD. THE REQUIREMENT(S) SHALL BE IN ACCORDANCE WITH THE BASE DOCUMENT, EXCEPT 1954. |



Source: https://assist.dla.mil -- Downloaded: 202640-23T21:04Z
Check the source to verify that this is the currenversion before use.

KEYWORD CODE INDEX (KCI)

| CHARACTERISTIC NAME | CHAR CODE |
|---|---|
| OVERLOAD (CONT) | |
| REQUIREMENTS (SELECT ONE) | |
| NO EVIDENCE OF ELECTRICAL OR MECHANICAL DAMAGE. | 1956 |
| TEST METHODS (SELECT ONE) | |
| PER BASE DOCUMENT EXCEPT ____ | 1958 |
| PER MIL-D-28803. | 1860 |
| OVERVOLTAGE (PERCENT OF RATED VOLTAGE) | 1962 |
| MINIMUM TIME (SELECT ONE) | |
| (MILLISECONDS) | 1964 |
| (SECONDS) | 1966 |
| RESISTANCE TO SOLDERING HEAT | |
| REQUIREMENTS (SELECT ONE) | |
| PER BASE DOCUMENT EXCEPT ____ | 4700 |
| NO EVIDENCE OF PHYSICAL DAMAGE. | 4701 |
| REMAIN WITHIN SPECIFIED TOLERANCE. | 4718 |
| TEST METHODS (SELECT ONE) | |
| PER BASE DOCUMENT EXCEPT ____ | 4689 |



Source: https://assist.dla.mil -- Downloaded: 202640-23T21:04Z
Check the source to verify that this is the current version before use.

| CHAR CODE | STANDARD PARAGRAPH |
|---|---|
| 1956 | OVERLOAD. THERE SHALL BE NO EVIDENCE OF ELECTRICAL OR MECHANICAL DAMAGE. |
| 1958 | OVERLOAD. TESTING SHALL BE PERFORMED IN ACCORDANCE WITH THE BASE DOCUMENT, EXCEPT 1958. |
| 1960 | OVERLOAD. TESTING SHALL BE PERFORMED IN ACCORDANCE WITH MIL-D-28803. |
| 1962 | THE OVERVOLTAGE SHALL BE 1962 PERCENT OF THE RATED VOLTAGE. |
| 1964 | THE DURATION SHALL BE NOT LESS THAN 1964 MILLISECOND(S). |
| 1966 | THE DURATION SHALL BE NOT LESS THAN 1966 SECOND(S). |
| 4700 | RESISTANCE TO SOLDERING HEAT. THE REQUIREMENT(S) SHALL BE IN ACCORDANCE WITH THE BASE DOCUMENT, EXCEPT 4700. |
| 4701 | RESISTANCE TO SOLDERING HEAT. THERE SHALL BE NO EVIDENCE OF PHYSICAL DAMAGE. |
| 4718 | ITEM(S) SHALL REMAIN WITHIN SPECIFIED TOLERANCE. |
| 4689 | RESISTANCE TO SOLDERING HEAT. TESTING SHALL BE PERFORMED IN ACCORDANCE WITH THE BASE DOCUMENT, EXCEPT 4689. |




Source: https://assist.dla.mil -- Downloaded: 2026-10-23T21:04Z
Check the source to verify that this is the current version before use.

KEYWORD CODE INDEX (KCI)

| CHARACTERISTIC NAME | CHAR CODE |
|---|---|
| RESISTANCE TO SOLDERING HEAT (CONT) | |
| TEST METHODS (CONT) | |
| PER MIL-STD-202, METHOD 210. | 4698 |
| *TEST CONDITION (LETTER) | 4691 |
| NUMBER OF TERMINATIONS TESTED (QUANTITY) | 4694 |
| DEPTH OF IMMERSION IN SOLDER (SELECT ONE) | |
| (INCHES) | 4692 |
| (MILLIMETERS) | 4669 |
| IMMERSION IN FLUX PERMITTED. | 4671 |
| SPECIAL PREPARATIONS PERMITTED. | 4989 |
| COOLING TIME (MINUTES) | 4695 |
| SALT SPRAY | |
| REQUIREMENTS (SELECT ONE) | |
| PER BASE DOCUMENT EXCEPT ____ | 4878 |
| NO EVIDENCE OF CORROSION, PHYSICAL DAMAGE, OR DEGRADATION OF PERFORMANCE. | 4782 |
| TEST METHODS (SELECT ONE) | |
| PER BASE DOCUMENT EXCEPT ____ | 4770 |



Source: https://assist.dla.mil -- Downloaded: 2026-10-23T21:04Z
Check the source to verify that this is the current version before use.