NOTICE OF
CHANGE

MIL-STD-35-106(MI)
NOTICE 2
18 SEPTEMBER 1992

MILITARY STANDARD

AUTOMATED ENGINEERING
DOCUMENT PREPARATION SYSTEM

COUNTERS, RECIPROCATING AND ROTATING

TO ALL HOLDERS OF MIL-STD-35-106(MI):

1. THE FOLLOWING PAGES OF MIL-STD-35-106(MI) HAVE BEEN REVISED AND SUPERSEDE THE PAGES LISTED.

NEW PAGE	DATE	SUPERSEDED PAGE	DATE
1-3	18 SEPTEMBER 1992	1-3	24 NOVEMBER 1975
1-4	24 NOVEMBER 1975	(Reprinted without change)	
2-1	18 SEPTEMBER 1992	2-1	24 NOVEMBER 1975
2-2	18 SEPTEMBER 1992	2-2	24 NOVEMBER 1975
5-3	18 SEPTEMBER 1992	5-3	24 NOVEMBER 1975
5-4	24 NOVEMBER 1975	(Reprinted without change)	
5-33	24 NOVEMBER 1975	(Reprinted without change)	
5-34	18 SEPTEMBER 1992	5-34	24 NOVEMBER 1975
5-35	18 SEPTEMBER 1992	5-35	24 NOVEMBER 1975
5-36	24 NOVEMBER 1975	(Reprinted without change)	
5-63	18 SEPTEMBER 1992	5-63	24 NOVEMBER 1975
5-64	18 SEPTEMBER 1992	5-64	24 NOVEMBER 1975
5-81	18 SEPTEMBER 1992	5-81	24 NOVEMBER 1975
5-82	18 SEPTEMBER 1992	5-82	24 NOVEMBER 1975
5-83	18 SEPTEMBER 1992	5-83	24 NOVEMBER 1975
5-84	18 SEPTEMBER 1992	5-84	24 NOVEMBER 1975

AMSC N/A AREA EGDS
DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T21:02Z
Check the source to verify that this is the current version before use.

2. RETAIN THIS NOTICE PAGE AND INSERT BEFORE THE TABLE OF CONTENTS.

3. Holders of MIL-STD-35-106(MI) will verify that page changes and additions indicated above have been entered. The notice page will be retained as a check sheet. This issuance, together with appended pages is a separate publication. Each notice is to be retained by stocking points until the Military Standard is completely revised or canceled.

Custodians:
Army-MI

Review activities:
Army-AT, AV, CR, ER
ME, MR, SC

User activity
Army - AR

Preparing activity:
Army - MI

(Project EGDS-A447)

Source: https://assist.dla.mil -- Downloaded: 202610-23T21:02Z
Check the source to verify that this is the current version before use.

provided to assist a designer in defining the scope of the MSE. To allow the designer flexibility, the title is generally not as restrictive as the basic specification to which the exception is taken. The reverse AEDPS Title comprises the words that will appear in the Scope paragraph (1.1) of the MSE.

If the item selected from the AEDPS document becomes an item of supply, then the Cataloging Handbook H6 nomenclature must be used.

The MSE title may or may not be the same as the title used in DODISS, FIIG or the document to which the MSE document was written. Documents referenced in the MSE that will be listed in the Applicable Documents paragraph (2.1) of the MSE will be identified by the exact title that appears on the referenced document. The title written on the MSE or in DODISS or FIIG will not be entered in paragraph 2.1.

1.4.2 Index

The Military Specification Exception Title index is as follows:

RELATED DOCUMENT	RELATED DOCUMENT COVERAGE	MSE TITLE	MSE TITLE CODE
	Electrically Actuated (AC or DC), Miniature, Hermetically Sealed	Counter, Electrical	172001
	Fixed Mounting, Ratcheting, Manually Operated	Counter, Reciprocating	172002
GG-C-00620	Hand Held, Manually Operated		
MIL-C-60618	Mechanical, Direct Drive	Counter, Rotating	172003

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T21:02Z
Check the source to verify that this is the current version before use.

SECTION 2

APPLICABLE DOCUMENTS

2.1 Government documents.

2.1.1 Specifications, standards, and handbooks. The following specifications, standards, and handbooks form a part of this document to the extent specified herein. Unless otherwise specified, the issues of these documents are those listed in the issue of the Department of Defense Index of Specifications and Standards (DODISS) and supplement thereto, cited in the solicitation.

SPECIFICATIONS

FEDERAL

GG-C-00620	Counter, Reciprocating, Hand Held

MILITARY

MIL-C-60618	Counter, Rotating, Mechanical, Direct Drive

STANDARDS

FEDERAL

FED-STD-595	Colors

MILITARY

MIL-STD-202	Test Methods For Electronic and Electrical Component Parts
MIL-STD-461	Electromagnetic Interference Characteristics Requirements for Equipment
MIL-STD-462	Electromagnetic Interference Characteristics, Measurement Of
MIL-STD-810	Environmental Test Methods

(Unless otherwise indicated, copies of federal and military specifications, standards, and handbooks are available from the Standardization Documents Order Desk, Bldg 4D, 700 Robbins Avenue, Philadelphia, PA 19111-5094.)

Source: https://assist.dla.mil -- Downloaded: 202640-23T21:02Z
Check the source to verify that this is the currenversion before use.

2.2 Non-Government publications. The following document(s) form a part of this document to the extent specified herein. Unless otherwise specified, the issues of the documents which are DoD adopted are those listed in the issue of the DODISS cited in the solicitation. Unless otherwise specified, the issues of documents not listed in the DODISS are the issues of the documents cited in the solicitation.

ASTM E 380	Metric Practice Guide
H6	Federal Item Name Directory For Supply Cataloging

(Copies of Standards and Handbooks required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

Source: https://assist.dla.mil -- Downloaded: 202610-23T21:02Z
Check the source to verify that this is the current version before use.

5.6 Dimensions and Figures

All specification requirements for dimensions and figures described in MIL-STD-35 are applicable.

The figures applicable to counters are contained in Section 7. It is mandatory to enter on the SRS Code 1009 and a figure number.

5.7 Applicable Documents

The documents listed in the Applicable Document List of Section 5 of MIL-STD-35 and appropriate codes form Table B of MIL-STD-35 shall be entered on the SRS. In addition, the appropriate documents shown in the DOCUMENTS column below and the applicable codes from Table B of MIL-STD-35 shall be entered on the SRS when the codes listed in the CODES column are used to specify tests or requirements. Shown parenthetically in the CODES column is a reference to the applicable test or requirement. A document designation, with a code from TABLE B, is entered on the SRS only once.

DOCUMENTS	CODES
FED-STD-595	1578, 1579, 1581, and 1583 (Color of Figures)
GG-C-00620	1922 (Determination of Actuation Force) 1954 (Count Life) 2452 (Drop Test)
MIL-C-60618	2224 (Operability) 2172 (Speed)
MIL-STD-202	6300 (DWV at Reduced Barometric Pressure) 4862 (DWV at Sea Level) 4853 (Humidity)

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T21:02Z
Check the source to verify that this is the current version before use.

DOCUMENTS (CONT)	CODES (CONT)
	1511 (Insulation resistance) 4732 (Seal) 1482 (Shock, high impact) 1500 (Shock, specified pulse) 4683 (Solderability) 4714 (Thermal shock) 1447 (Vibration, high frequency)
MIL-STD-461	2522 - 2526 (Electromagnetic interference)
MIL-STD-462	2514 - 2516 (Electromagnetic interference)
MIL-STD-810	2412 (Altitude) 4755 (Fungus) 2582 (High temperature) 4781 (Humidity) 2682 (Low temperature) 4780 (Power supply varation) 2883 (Shock) 1514 (Vibration)
Document to which exception is being taken.	1006

In addition, when the codes listed below are used to specify mounting or special preparations in accordance with a document, the document number with an appropriate code from Table B of MIL-STD-35 must be entered on the SRS.

6280	DWV at reduced barometric pressure
5000	DWV at sea level
4773	Salt fog
1468	Shock, high impact
4684	Shock, specified pulse
4719	Thermal shock
4707	Vibration, high frequency

For these codes any document from the Index, 1.4.2, may be used to specify which test in the document contains applicable mounting or preparation requirements. Enter on the SRS the test name and the document number (Example 2).

Source: https://assist.dla.mil -- Downloaded: 2026-04-23T21:02Z
Check the source to verify that this is the current version before use.

To detail a low temperature test, it is mandatory to use Code 2682. Other codes are optional. These codes and information concerning them are as follows:

Code 2682 and an "X", entered on the SRS, will specify to test in accordance with Procedure I of Method 502 of MIL-STD-810.

Code 2684 and a value, entered on the SRS, will specify the non-operating temperature in degrees Celsius.

Code 2685 and a value, entered on the SRS, will specify the conditioning time in hours. Code 2684 is mandatory if Code 2685 is used.

Code 2686 and a value, entered on the SRS, will specify the lowest operating temperature in degrees Celsius.

Code 2690 is the 1006 requirement code (5.4).

Code 2691 is the 1006 except requirement code (5.4).

To detail requirements, it is mandatory to use Code 2692. Other codes are optional. These codes and information concerning them are as follows:

Code 2692 and an "X", entered on the SRS, will specify there shall be no evidence of physical damage.

Code 2694 and an "X", entered on the SRS, will specify that there shall be no degradation of performance after the low temperature test.

Code 2697 and a value, entered on the SRS, will specify the minimum insulation resistance in megohms.

Code 2698 and an "X", entered on the SRS, will specify there shall be no evidence of flashover, arcing, or insulation breakdown when the dielectric withstanding voltage test is performed.

Code 2700 or Code 2701, or both and a value(s), entered on the SRS, will specify the maximum drive shaft torque at low temperature in ounce-inches or newton-metres, respectively.

Code 2703 or Code 2704, or both and a value(s), entered on the SRS, will specify the maximum reset shaft torque at low temperature in ounce-inches or newton-metres, respectively.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T21:02Z
Check the source to verify that this is the current version before use.

Code 2706 and an "X", entered on the SRS, will specify that during and after the test there shall be no miscounting when the counter accuracy is tested. Do not use 2706 with Code 2707.

Code 2707 and a value, entered on the SRS, will specify the maximum difference in percent which shall be allowed between the reading of the counter under test and the control counter during and after the low temperature test.

5.26 Magnetic Position

Code 2200 is the 1006 test code (5.4).

Code 2202 is the 1006 except test code (5.4).

Code 2204 and a document number, entered on the SRS, will specify to test in accordance with the document number entered.

Code 2210 is the 1006 requirement code (5.4).

Code 2212 is the 1006 except requirement code 5(.4).

Code 2214 and a value, entered on the SRS, will specify the maximum compass needle deflection deflection in degrees.

5.27 Operability

Code 2220 is the 1006 test code (5.4).

Code 2222 is the 1006 except test code (5.4).

Code 2224 and an "X", entered on the SRS, will specify to test in accordance with MIL-C-60618.

Code 2230 is the 1006 requirement code (5.4).

Code 2231 is the 1006 except requirement code (5.4).

To detail requirements there are six codes available. None of these codes are mandatory. These codes and information concering them are as follows:

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T21:02Z
Check the source to verify that this is the current version before use.

Code 2233 or 2234, or both and a value(s), entered on the SRS, will specify the maximum drive shaft torque in ounce-inches or newton-metres, respectively.

Code 2236 or 2237, or both and a value(s), entered on the SRS, will specify the maximum reset shaft torque in ounce-inches or newton-metres, respectively.

Code 2239 or 2240, or both and a value(s), entered on the SRS, will specify the maximum reset shaft force in pounds or newtons, respectively.

5.28 Power Supply Variation

Code 2250 is the 1006 test code (5.4).

Code 2251 is the 1006 except test code (5.4).

Code 2252 and a document number, entered on the SRS, will specify to test in accordance with the document number entered.

To detail voltage and frequency exceptions to MIL-C-83040, twelve codes are available. Codes for three different ac test voltages and either one or two frequencies for each voltage are available. Two codes are also available to specify dc voltage exceptions. Information converning these codes is as follows:

Code 2254 and a value, entered on the SRS, will specify a test voltage in volts ac. Code 2255 is mandatory if Code 2254 is used. Code 2256 is optional.

Code 2255 or Code 2256, or both and a value(s), entered on the SRS, will specify the test frequency(s) in hertz.

Code 2258 and a value, entered on the SRS, will specify a test voltage in volts ac. Code 2259 is mandatory if Code 2258 is used. Code 2260 is optional.

Code 2259 or Code 2260, or both and a value(s), entered on the SRS, will specify the test frequency(s) in hertz.

Code 2262 or a value, entered on the SRS, will specify a test voltage in volts ac. Code 2263 is mandatory if Code 2262 is used. Code 2264 is optional.

Code 2263 or Code 2264, or both and a value(s), entered on the SRS, will specify the test frequency(s) in hertz.

Code 2266 and a value, entered on the SRS, will specify a test voltage in volts dc.

Source: https://assist.dla.mil -- Downloaded: 202610-23T21:02Z
Check the source to verify that this is the currenversion before use.

Code 2267 and a value, entered on the SRS, will specify a test voltage in volts dc.

Code 2270 is the 1006 requirement code (5.4).

Code 2272 is the 1006 except requirement code (5.4).

Code 2274 and a value, entered on the SRS, will specify the maximum difference in percent between the readings of the counter under test and the control number.

5.29 Salt Fog

Code 4776 is the 1006 test code (5.4).

Code 4779 is the 1006 except test code (5.4).

To detail a salt fog test, Code 4780 is mandatory. Other codes are optional. These codes and information concerning them are as follows:

Code 4780 and an "X", entered on the SRS, will specify to test in accordance with Method 509 of MIL-STD-810.

Code 4786 and a value, entered on the SRS, will specify percent of salt in the solution that will be used for the test, if other than 5 percent.

Code 4783 and a value, entered on the SRS, will specify the exposure time in hours, if other than 48 hours.

Code 4775 and a value, entered on the SRS, will specify the drying period in hours.

There are three codes to specify mounting. Only one of these codes may be used. These codes and information concerning them are as follows:

Code 4765 and an "X", entered on the SRS, will specify that mounting shall be by normal mounting means.

Code 4766 and an "X", entered on the SRS, will specify that mounting shall be by any suitable method.

Code 4773 and a document designation, entered on the SRS, will specify that mounting shall be in accordance with the document. The applicable test name from the reference document should be entered on the SRS in addition to the document designation (5.7).

Source: https://assist.dla.mil -- Downloaded: 20260-23T21:02Z
Check the source to verify that this is the current version before use.

SPECIFICATION REQUIREMENTS LIST (SRL)

REF. PARA.	CHARACTERISTIC NAME	CODE
5.10.7	PULSING CHARACTERISTICS (CONT)	
	RESET OPRATION	
	MINIMUM PULSE TIMING	
	ON-TIME (MS)	1875
	OFF-TIME (MS)	1876
	MAXIMUM ON TIME (S)	1878
5.10.8	RATED LIFE (SELECT ONE)	
	MILLIONS OF COUNTS (NO.)	1880
	MILLIONS OF REVOLUTIONS (NO.)	1882
5.11	DESIGN RELIABILITY RATING	
	*FAILURE RATE (PCT/1000 HR)	7025
	*CONFIDENCE LEVEL (PCT)	7026
	AVERAGE IMPULSE RATE (PULSES PER MINUTE)	2490
	TEST TEMPERATURE (DEG C)	7029

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T21:02Z
Check the source to verify that this is the current version before use.

SPECIFICATION REQUIREMENTS LIST (SRL)

CHARACTERISTIC

REF. PARA.	NAME	CODE
5.12	ACCURACY	
	(SELECT ONE TEST METHOD)	
	TEST PER 1006 DOCUMENT.	1900
	TEST PER 1006 DOCUMENT EXCEPT ____	1901
	TEST PER (DOC DES)	1902
	(SELECT ONE REQUIREMENT)	
	REQUIREMENT(S) PER 1006 DOCUMENT.	1910
	REQUIREMENT(S) PER 1006 DOCUMENT EXCEPT ____	1911
	REQUIREMENT(S) AS FOLLOWS:	
	NO SKIPPING OR OVER-ADVANCING OF ANY NUMBER OF NUMBERS.	1912
	MAXIMUM DIFFERENCE BETWEEN COUNTER UNDER TEST AND CONTROL COUNTER READINGS (PLUS OR MINUS PCT)	1914
5.13	ALTITUDE	
	(SELECT ONE TEST METHOD)	
	TEST PER 1006 DOCUMENT.	2410
	TEST PER 1006 DOCUMENT EXCEPT ____	2411

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T21:02Z
Check the source to verify that this is the current version before use.

SPECIFICATION REQUIRMENTS LIST (SRL)

CHARACTERISTIC

REF. PARA.	NAME	CODE
5.25 (CONT)	LOW TEMPERATURE (CONT)	
	TEST PER MIL-STD-810 METHOD 502, PROCEDURE I.	2682
	NONOPERATING TEMPERATURE (DEG C)	2684
	CONDITIONING TIME (HR)	2685
	LOWEST OPERATING TEMPERATURE (DEG C)	2686
	(SELECT ONE REQUIREMENT)	
	REQUIREMENT(S) PER 1006 DOCUMENT.	2690
	REQUIREMENT(S) PER 1006 DOCUMENT EXCEPT ____	2691
	REQUIREMENT(S) AS FOLLOWS:	
	*NO EVIDENCE OF PHYSICAL DAMAGE.	2692
	NO DEGRADATION OF PERFORMANCE AFTER LOW TEMPERATURE TEST.	2694
	MINIMUM INSULATION RESISTANCE (MEGOHMS)	2697
	NO EVIDENCE OF FLASHOVER, ARCING, OR BREAKDOWN RESULTING FROM DWV TEST.	2698
	MAXIMUM DRIVE TORQUE AT LOW TEMPERATURE	
	(OZ. - IN.)	2700
	(N - M)	2701

Source: https://assist.dla.mil -- Downloaded: 202610-23T21:02Z
Check the source to verify that this is the current version before use.

SPECIFICATION REQUIRMENTS LIST (SRL)

CHARACTERISTIC

REF. PARA.	NAME	CODE
5.25 (CONT)	LOW TEMPERATURE (CONT)	
	MAXIMUM RESET TORQUE AT LOW TEMPERATURE	
	(OZ. - IN.)	2703
	(N - M)	2704
	ACCURACY DURING AND AFTER TEST (SELECT ONE)	
	NO MISCOUNTING ALLOWED.	2706
	MAXIMUM DIFFERENCE BETWEEN COUNTER UNDER TEST AND CONTROL COUNTER READINGS (PLUS OR MINUS PCT)	2707
5.26	MAGNETIC POSITION	
	(SELECT ONE TEST METHOD)	
	TEST PER 1006 DOCUMENT.	2200
	TEST PER 1006 DOCUMENT EXCEPT ____	2202
	TEST PER (DOC DES)	2204
	(SELECT ONE REQUIREMENT)	
	REQUIREMENT(S) PER 1006 DOCUMENT.	2210
	REQUIREMENT(S) PER 1006 DOCUMENT EXCEPT _____	2212

Source: https://assist.dla.mil -- Downloaded: 202610-23T21:02Z
Check the source to verify that this is the current version before use.

SPECIFICATION REQUIREMENTS LIST (SRL)

CHARACTERISTIC

REF. PARA.	NAME	CODE
5.26 (CONT).	MAGNETIC POSITION (CONT)	
	REQUIREMENT(S) AS FOLLOWS:	
	MAXIMUM COMPASS NEEDLE DEFLECTION (DEG)	2214
5.27	OPERABILITY	
	(SELECT ONE TEST METHOD)	
	TEST PER 1006 DOCUMENT.	2220
	TEST PER 1006 DOCUMENT EXCEPT ____	2222
	TEST PER MIL-C-60618.	2224
	(SELECT ONE REQUIREMENT)	
	REQUIREMENT(S) PER 1006 DOCUMENT.	2230
	REQUIREMENT(S) PER 1006 DOCUMENT EXCEPT _____	2231
	REQUIREMENT(S) AS FOLLOWS:	
	MAXIMUM DRIVE SHAFT TORQUE	
	(OZ - IN.)	2233
	(N - M)	2234

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T21:02Z
Check the source to verify that this is the current version before use.

SPECIFICATION REQUIREMENTS LIST (SRL)

CHARACTERISTIC

REF. PARA.	NAME	CODE
5.27 CONT.	OPERABILITY (CONT)	
	MAXIMUM RESET SHAFT TORQUE	
	(OZ - IN.)	2236
	(N - M)	2237
	MAXIMUM RESET SHAFT FORCE	
	(LBS)	2239
	(N)	2240
5.28	POWER SUPPLY VARIATION	
	(SELECT ONE TEST METHOD)	
	TEST PER 1006 DOCUMENT.	2250
	TEST PER 1006 DOCUMENT EXCEPT ____	2251
	TEST PER (DOC DES)	2252
	VOLTAGE (VAC)	2254
	*FREQUENCY (HZ)	2255
	FREQUENCY (HZ)	2256

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T21:02Z
Check the source to verify that this is the current version before use.