MIL-D-23828C
6 March 1986
SUPERSEDING
MIL-D-23828B
7 December 1970

MILITARY SPECIFICATION

DISPENSERS, SILVERWARE

This specification is approved for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This document covers silverware dispensers.

1.2 Classification. The silverware dispensers shall be of the following types and sizes as specified (see 6.2).

Type I - Countertop, movable.

Size 4 - 4 silverware cylinders.
Size 6 - 6 silverware cylinders.
Size 16 - 16 silverware cylinders.

Type II - Console, caster-mounted, 16 silverware cylinders.

2. APPLICABLE DOCUMENTS

2.1 Government documents. Unless otherwise specified, the following documents of the issue in effect on date of invitation for bids or request for proposal, form a part of this document to the extent specified herein.

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: U.S. Army Natick Research, Development and Engineering Center, Natick, MA 01760-5014, by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

AMSC N/A FSC 7320

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T18:01Z
Check the source to verify that this is the current version before use.

FEDERAL

PPP-B-601 - Boxes, Wood, Cleated-Plywood.
PPP-B-636 - Boxes, Shipping, Fiberboard

STANDARDS

MILITARY

MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes.
MIL-STD-129 - Marking for Shipment and Storage.

(Copies of documents required by contractors in connection with specific acquisition functions should be obtained from the contracting activity or as directed by the contracting activity.)

* 2.2 Other publications. Unless otherwise specified, the following documents of the issue in effect on date of invitation for bids or request for proposal, form a part of this document to the extent specified herein.

NATIONAL SANITATION FOUNDATION (NSF)

Listing of Food Service Equipment.
Standard No. 2 - Food Service Equipment.
C-2 - Basic Criteria for the Evaluation of Special Equipment and/or Devices.

(Application for copies should be addressed to the National Sanitation Foundation, 3475 Plymouth Rd., P.O. Box 1468, Ann Arbor, Michigan 48106.)

AMERICAN SOCIETY FOR TESTING AND MATERIALS (ASTM)

A 167 - Stainless and Heat-Resisting Chromium-Nickel Steel Plate, Sheet and Strip
D 3951 - Standard Practice for Commercial Packaging.
F 861 - Commercial Dishwashing Racks.

(Application for copies should be addressed to the American Society for Testing and Materials, 1916 Race Street, Philadelphia, PA 19103.)

(Technical society and technical association documents are generally available for reference from libraries. They are also distributed among technical groups and using Federal agencies.)

2.3 Order of precedence. In the event of a conflict between the text of this document and the references cited herein (except for associated detail specifications, specification sheets or MS standards), the text of this document shall take precedence. Nothing in this document, however, shall supersede

Source: https://assist.dla.mil -- Downloaded: 20260-19T18:01Z
Check the source to verify that this is the current version before use.

applicable laws and regulations unless a specific exemption has been obtained.

3. REQUIREMENTS

3.1 Standard product. The dispenser shall be the manufacturer's current standard commercial product which meets or exceeds the requirements of this document and is identifiable by the manufacturer's established model number or equivalent designation. The dispenser shall be new and unused except to the extent required to perform the tests specified herein.

3.2 Codes and standards. The silverware dispensers shall conform to the applicable requirements of NSF Standard No. 2 and Criteria C-2. Satisfactory evidence that these requirements have been met shall be submitted to the contracting officer or his authorized representative prior to the start of production (see 4.5).

3.3 Materials (see 6.3) and components. Materials and components shall be as specified herein. Parts for which materials are not definitely specified shall be fabricated of materials acceptable under NSF Standard No. 2, or, if not covered therein, of materials used in the manufacturer's standard product. Materials shall be free of defects or imperfections that may contribute to premature failure of the equipment or reduced or impair the usability of the unit.

3.3.1 Stainless steel. Sheet metal used in the construction of the dispensers shall be stainless steel, conforming to the requirements of ASTM A 167 for class 302 or 304. For type I, sizes 4 and 6 dispensers, stainless steel sheet shall have a thickness of not less than 0.0312-inch (22 gage); for type I, size 16, and type II dispensers, stainless steel sheet shall have a thickness of not less than 0.050-inch (18 gage).

3.4 Interchangeability. All dispensers of the same type and size furnished under a specific contract shall be identical to the extent required to permit interchangeability of replaceable parts, components and assemblies.

3.5 Design. The silverware dispenser shall be of the slanted top design with openings for the number of silverware cylinders specified in 1.2. The silverware dispenser shall be so designed as to facilitate maintenance and cleaning. The design shall be such as to prevent conditions hazardous to personnel or deleterious to equipment. The silverware dispenser shall consist of a cabinet with removable silverware cylinders capable of being easily cleaned and sanitized. Type I dispensers shall be movable and for use on countertops. Type II dispensers shall be console-mounted on casters. The dispensers shall have cylinders conforming to 3.7 and shall be in the quantities indicated (see 1.2).

3.6 Construction. The silverware dispenser and component parts thereof shall be constructed in accordance with the requirements of NSF Standard No. 2 and

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T18:01Z
Check the source to verify that this is the current version before use.

Criteria C-2 except as otherwise specified herein. The silverware dispenser shall be constructed of stainless steel specified in 3.3.1, and shall be fabricated of angles and channels welded to form a rigid construction. Reinforcing and framing shall meet the requirements of NSF Standard No. 2. Holes in the cabinet top shall have a diameter of 4 inches ± 1/16 inch with a 3/16-inch minimum turn-down lip, or shall otherwise have the edges formed or reinforced to increase rigidity necessary to support the loaded cylinders.

3.6.1 Type I, size 16 and type II, guides and rests. Type I, size 16 and type II dispensers shall be provided with guides and rests. The guides and rests shall be stainless steel angles welded to the underside of the slanted top to provide support for the cylinders. The guides and rests shall be so placed as to be easily cleaned and eliminate harborage for vermin.

3.6.2 Supports. The dispenser shall be supported as specified in 3.6.2.1 and 3.6.2.2.

3.6.2.1 Type I, sizes 4, 6, and 16. Type I, sizes 4, 6, and 16 dispensers shall be supported in accordance with the manufacturer's standard practice. The supports shall not mar or have other deleterious effects on countertops.

3.6.2.2 Type II. Type II dispensers shall be furnished with casters in accordance with the requirements of NSF Basic Criteria C-2 and as specified herein. The casters shall be the heavy-duty swivel, single wheel, double-ball bearing type having adequate strength to support the fully loaded dispenser. The wheels, including treads, shall have a minimum diameter of 5 inches. The treads shall be not less than 1-3/8 inches in width and shall be composed of phenolic resin, polyurethane elastomeric rubber, or polychoroprene compound. Unless otherwise specified (see 6.2), the casters shall be securely fastened to the dispenser by bolts, nuts, and lockwashers. One caster at each end of the dispenser shall be provided with a foot-operated brake to prevent travel when the dispenser is in a stationary position. The overall height of the caster assembly shall be sufficient to provide not less than 6-inch unobstructed clearance between the floor and the lowest horizontal dispenser member. The type II silverware dispenser with cylinders shall be fully loaded and rolled over an obstacle without any visible damage or deformation to the unit or to the caster(s), or caster mounting(s) when tested as specified in 4.4.2.

3.6.3 Push-bar for type II dispenser. Type II dispensers shall be furnished with a push-bar in accordance with the manufacturer's standard practice. The push-bar shall be stainless steel and shall be suitably located to prevent injury to personnel. When specified (see 6.2), bumpers shall be provided on the ends of the push-bar.

3.6.4 Shelves for type II dispenser. Type II dispensers shall be provided with two stainless steel shelves having a thickness of not less than 18 gage. Each shelf shall have a minimum area of 640 square inches and a clear height not less than 11 inches. The shelves, including reinforcing and framing, shall be

Source: https://assist.dla.mil -- Downloaded: 20261O-19T18:01Z
Check the source to verify that this is the current version before use.

in accordance with NSF Standard No. 2 and Criteria C-2. The bottom of the cabinet, if closed, may be used as a shelf.

3.6.5 Bumpers for type II dispensers. Unless otherwise specified (see 6.2), rubber-wrap-around or corner bumpers shall be provided for type II dispensers.

3.6.6 Tray rail. When specified (see 6.2), the type II dispenser shall be equipped with a tray rail or shelf with supporting hardware fabricated of stainless steel specified in 3.3.1. The tray-rail or shelf and supporting hardware shall be removable. The tray rail or shelf shall be not less than 10 inches and not more than 15 inches wide and shall extend the full length of the dispenser. The tray rail or shelf shall not have any distortion and the dispenser shall not tip when tested as specified in 4.4.1.

3.7 Silverware cylinders. The silverware cylinders shall be type IV or type V of ASTM F 861, as specified (see 6.2).

3.8 Identification marking. The dispensers, shall be furnished with a data-name plate in accordance with the applicable requirements of MIL-STD-130 except the requirements for; (a) Methods of applying, (b) Identification tags, (c) Information not required and (d) Optional marking information shall not apply. The data plates shall be made of minimum 20 gauge corrosion-resisting metal and attached to the dispensers by rivets, screws or welding in such a manner as to meet the applicable National Sanitation Foundation sanitary requirements for this equipment. The plate shall contain the following information which shall be stamped, engraved or applied by photosensitive means.:

National Stock Number
Procurement Instrument Identification Number
Specification Data
Manufacturer's Name, Address and Telephone Number
Supplier's Name, Address and Telephone Number (list only if different from Manufacturer)
Manufacturer's Model Number
Government Approved Manual Number (see 6.2).

Each plate shall be placed so that it is readily visible to the operator during normal operating use and so as to not adversely affect the life and utility of the dispenser.

3.8.1 Markers. When specified (see 6.2), removable, stainless steel identifying markers shall be furnished in the quantity and with the wording specified (see 6.2). Markers shall be located in accordance with the manufacturer's standard practice.

3.9 Workmanship.

3.9.1 Welding. Surfaces of parts to be welded shall be free from oxide, scale, paint, grease, or other foreign matter. Welds shall be continuous and

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T18:01Z
Check the source to verify that this is the current version before use.

sound, smooth, and free from porosity, cracks, incomplete fusion, or deformation of materials. All scale or flux deposits (when flux is used) shall be removed from the finished welds. Weld penetration shall provide transference of maximum design stress through the base metal juncture. Fillets shall be provided where necessary to reduce stress concentration.

3.9.2 Finish. All parts of the dispenser shall be smooth on surfaces and edges and shall be free from rough grinding marks, trimming marks, pits, scale, die-marks, and kinks. Weld beads shall be ground, polished, and blended with adjacent surfaces. Stainless steel shall have No. 3 finish for exposed surfaces, and a No. 2D or a No. 2B finish for unexposed surfaces.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the contractor is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or purchase order, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the document where such inspections are deemed necessary to assure that supplies and services conform to prescribed requirements.

4.1.1 Responsibility for compliance. All items must meet all requirements of sections 3 and 5. The inspection set forth in this document shall become a part of the contractor's overall inspection system or quality program. The absence of any inspection requirements in the document shall not relieve the contractor of the responsibility of assuring that all products or supplies submitted to the Government for acceptance comply with all requirements of the contract. Sampling in quality conformance does not authorized submission of known defective material, either indicated or actual, nor does it commit the Government to acceptance of defective material.

4.1.2 Dimensional requirements. Unless otherwise specified in the contract or purchase order, the contractor is responsible for assuring that all specified dimensions have been met. When dimensions cannot be examined on the end item, inspection shall be made at any point, or at all points in the manufacturing process necessary to assure compliance with all dimensional requirements.

4.1.3 Certificate of compliance. When certificates of compliance are submitted, the Government reserves the right to check test such items to determine the validity of the certification.

4.2 Quality conformance inspection. Unless otherwise specified, sampling for inspection shall be performed in accordance with MIL-STD-105.

4.2.1 Component and material inspection. In accordance with 4.1, components and materials shall be inspected in accordance with all the requirements of

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T18:01Z
Check the source to verify that this is the current version before use.

referenced documents unless otherwise excluded, amended, modified, or qualified in this document or applicable purchase document.

4.2.2 End item visual examination. The end item shall be examined for the defects listed in table I. The lot size shall be expressed in units of dispensers of one type and size offered for acceptance at one time. The sample unit shall be one completely fabricated and assembled dispenser. The inspection level shall be II and the acceptable quality level (AQL), expressed in terms of defects per hundred units, shall be 2.5 for major defects and 6.5 for total (major and minor combined) defects.

TABLE I. End item visual defects

Defects	Classification Major	Minor
Type and size not as specified	X	
Material not as specified.	X	
Design not as specified.	X	
Construction not as specified.	X	
Guides and rests missing or broken; do not provide support for cylinders.	X	
Supports for type I, sizes 4, 6, and 16 dispensers not as specified.	X	
Casters for type II dispensers not as specified; brakes missing.	X	
Push-bar for type II dispensers missing; not as specified.	X	
Shelves for type II dispensers missing or not as specified.	X	
Silverware cylinders missing or not as specified.	X	
Workmanship not as specified.	X	
Finish not as specified.	X	
Tray rail or shelf for type II dispenser, when specified, missing.	X	
Tray rail or shelf and supporting hardware not removable.	X	
Tray rail or shelf does not extend the full length of the dispenser.	X	
Data-name plates - Omitted or not as specified; information incomplete or not legible; not located so as to be readily visible to operator.		X
When required, markers missing or not as specified.		X

4.2.3 End item dimensional examination. The end item shall be examined for conformance to the dimensions specified in 3.6, 3.6.2.2, 3.6.4 (height and area of shelves) and 3.6.6. Any dimension not as specified shall be classified as a defect. The lot size shall be expressed in units of dispensers of one type and

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T18:01Z
Check the source to verify that this is the current version before use.

size offered for acceptance at one time. The sample unit shall be one dispenser. The inspection level shall be S-2 and the AQL, expressed in terms of defects per hundred units, shall be 4.0.

4.2.4 End item testing (type II only). One representative type II dispenser shall be selected from the lot and tested as specified in 4.4.1 and 4.4.2. Any test failure shall be cause for rejection of the lot.

4.2.5 Packaging examination. An examination shall be made to determine that preservation, packing, and marking comply with the section 5 requirements. Defects shall be scored in accordance with the list below. The sample unit shall be one shipping container fully packaged. The lot size shall be the number of containers in the inspection lot. The inspection level shall be S-2 and the AQL, expressed in terms of defects per hundred units, shall be 4.0.

Examine	Defect
Markings (exterior)	Missing; incorrect; illegible; of improper size, location, sequence, or method of application.
Workmanship	Contents of shipping containers not immobilized, cushioned, blocked, braced, or waterproofed as specified. Bulged or distorted container.
Materials	Component missing, damaged, or otherwise defective.

4.3 Code and standard compliance. Certifications, certified test reports or listing marks for standards submitted in accordance with 3.2 shall be examined and validated as proof of compliance. Prior to Government approval of first shipment, the contractor shall submit to the contracting officer or his authorized representative for approval, certification that the silverware dispensers he proposes to furnish under this document meet the applicable requirements of NSF Standard No. 2 and Criteria C-2 as follows:

a. A listing in the current edition of the NSF "Listing of Food Service Equipment" and display of the NSF seal on the finished dispenser, or

b. A certification for the dispensers issued by NSF under their special one-time contract evaluation/certification service, or

c. A certified test report, acceptable to the contracting officer with the advice of the Army Surgeon General from an independent testing laboratory, indicating that the dispenser has been tested and conforms to the specified NSF Standard No. 2 and Criteria C-2.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T18:01Z
Check the source to verify that this is the current version before use.

4.4 Methods of inspection.

4.4.1 Tray rail and stability test. The type II dispenser with tray rail or shelf shall be tested without silverware. The tray rail or shelf shall be loaded with an equally distributed load of 40 pounds for 10 minutes. The dispenser shall not tip over during this period. At the end of this period the load shall be removed and the tray rail or shelf shall be examined for any deformation to determine conformance with 3.6.6. Any nonconformance shall constitute failure of this test.

4.4.2 Obstacle test. The type II silverware dispenser with cylinders shall be loaded and tested with silverware or weights totalling 110 pounds. The fully loaded silverware dispenser shall pass over a 2-1/8 inch obstacle 10 times at a minimum speed of 2 miles per hour. At the end of this period, the silverware or weights shall be removed and the silverware dispenser shall be examined for any damage or deformation or failure of caster(s) or caster mounting(s) to determine conformance with 3.6.2.2. Any nonconformance shall constitute failure of this test.

5. PACKAGING.

5.1 Preservation. Preservation shall be level A or Commercial as specified (see 6.2).

5.1.1 Level A. Each dispenser shall be unit pack in a box conforming to PPP-B-636 (weather resistant), and shall be cushioned to prevent movement.

5.1.2 Commercial. The dispensers shall be preserved in accordance with ASTM D 3951.

5.2 Packing. Packing shall be level A, B, or Commercial as specified (see 6.2).

5.2.1 Level A packing. The dispensers, preserved as specified in 5.1 shall be packed in a cleated-plywood box conforming to PPP-B-601 (overseas type).

5.2.2 Level B packing. Dispensers, preserved as specified in 5.1, shall be packed as specified for level A, except that boxes shall be domestic type or class as applicable.

5.2.3 Commercial packing. Dispensers, preserved as specified in 5.1, shall be packed in accordance with ASTM D 3951.

5.3 Marking. In addition to any special marking required by the contract or purchase order, unit packs and shipping containers shall be marked in accordance with MIL-STD-129 or ASTM D 3951, as applicable.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T18:01Z
Check the source to verify that this is the current version before use.

6. NOTES

6.1 Intended use. The silverware dispensers are intended to be used as a means for storing and dispensing silverware in dining facilities at the end of the food serving counter. Type I, sizes 4, 6, and 16 dispensers shall be mounted on the counter. Type II dispensers shall be caster-mounted.

6.2 Ordering data. Acquisition documents should specify the following:

a. Title, number, and date of this document.
b. Type and size required (see 1.2).
c. When casters are to be welded to the dispensers (see 3.6.2.2).
d. When bumpers on the ends of the push-bar are required (see 3.6.3).
e. When rubber-wrap-around or corner bumpers are not required (see 3.6.5).
f. When tray rail or shelf is required for type II dispensers (see 3.6.6).
g. Whether type IV or type V cylinders of ASTM F 861 are required (see 3.7).
h. Government approved manual number to be included on data-name plate (see 3.8).
i. When removable, stainless steel, identifying markers are to be furnished and the quantity and the wording required (see 3.8.1).
j. Level of preservation and level of packing required (see 5.1 and 5.2).

6.3 Recycled material. It is encouraged that recycled material be used when practical as long as it meets the requirements of the document (see 3.3).

6.4 Changes from previous issue. Asterisks are not used in this revision to identify changes with respect to the previous issue due to the extensiveness of the changes.

Custodians:

Army - GL
Navy - YD
Air Force - 99

Review activities:

Army - MD, TS
Air Force - 84
Navy - MS, MC
DLA - GS

Preparing activity:

Army - GL

Project No. 7320-0762

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T18:01Z
Check the source to verify that this is the current version before use.

INSTRUCTIONS: In a continuing effort to make our standardization documents better, the DoD provides this form for use in submitting comments and suggestions for improvements. All users of military standardization documents are invited to provide suggestions. This form may be detached, folded along the lines indicated, taped along the loose edge *(DO NOT STAPLE)*, and mailed. In block 5, be as specific as possible about particular problem areas such as wording which required interpretation, was too rigid, restrictive, loose, ambiguous, or was incompatible, and give proposed wording changes which would alleviate the problems. Enter in block 6 any remarks not related to a specific paragraph of the document. If block 7 is filled out, an acknowledgement will be mailed to you within 30 days to let you know that your comments were received and are being considered.

NOTE: This form may not be used to request copies of documents, nor to request waivers, deviations, or clarification of specification requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements.

(Fold along this line)

(Fold along this line)

DEPARTMENT OF THE ARMY

U.S. ARMY NATICK RESEARCH, DEVELOPMENT
and ENGINEERING CENTER
ATTN: STRNC-ES
Natick, MA 01760-5014

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

NO POSTAGE
NECESSARY
IF MAILED
IN THE
UNITED STATES

BUSINESS REPLY MAIL
FIRST CLASS PERMIT NO. 12062 WASHINGTON D. C.
POSTAGE WILL BE PAID BY THE DEPARTMENT OF THE ARMY

Commander
U.S. Army Natick Research, Development
and Engineering Center
ATTN: STRNC-ES
Natick, MA 01760-5014

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T18:01Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

(See Instructions – Reverse Side)

1. DOCUMENT NUMBER	2. DOCUMENT TITLE
MIL-D-23828C	DISPENSERS, SILVERWARE

3a. NAME OF SUBMITTING ORGANIZATION	4. TYPE OF ORGANIZATION *(Mark one)*
	☐ VENDOR ☐ USER ☐ MANUFACTURER ☐ OTHER *(Specify)*: _____
b. ADDRESS *(Street, City, State, ZIP Code)*	

5. PROBLEM AREAS

a. Paragraph Number and Wording:

b. Recommended Wording:

c. Reason/Rationale for Recommendation:

6. REMARKS

7a. NAME OF SUBMITTER *(Last, First, MI)* – Optional	b. WORK TELEPHONE NUMBER *(Include Area Code)* – Optional
c. MAILING ADDRESS *(Street, City, State, ZIP Code)* – Optional	8. DATE OF SUBMISSION *(YYMMDD)*

DD FORM 82 MAR 1426 PREVIOUS EDITION IS OBSOLETE.

NATICK OP-1, Feb 86

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T18:01Z
Check the source to verify that this is the current version before use.