MILITARY SPECIFICATION

INDICATOR, MULTI-VOLTAGE, MULTI-FREQUENCY,
AND POLARITY, HAND, PORTABLE

This amendment forms a part of MIL-I-23830C(SHIPS), dated 4 August 1975, and is approved for use within the Naval Sea Systems Command, Department of the Navy, and is available for use by all Departments and Agencies of the Department of Defense.

PAGE 1

At bottom of page: Add the following statement:

"Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: Commander, Naval Sea Systems Command, SEA 55Z3, Department of the Navy, Washington, DC 20362-5101 by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter."

2.1 STANDARDS, MILITARY, add:

"DOD-STD-1399, - Interface Standard for Shipboard Systems -
Section 300 Electric Power Alternating Current."

PAGE 2

* 3.3.1.2, line 3: Delete "plus and minus 10" and substitute "plus and minus 10 to 20".

* 3.3.2.1, line 4: Delete "the 10" and substitute "the 10 to 20".

3.3: Add the following sentence: "Indicator above 100 V shall be capable of withstanding voltage surges to 2500 volts."

PAGE 3

3.3.3, line 9: Delete "about 1/2 inch long which is connected to the lead wire", and substitute "a minimum of 1/2 inch long and 0.0625 ± 0.005 inch diameter which is connected to the lead wire. The prods shall require a minimum of 30 pounds of pull to remove them from their insulated handle."

AMSC N/A FSC 6625
DISTRIBUTION STATEMENT A Approved for public release; distribution unlimited

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T18:02Z
Check the source to verify that this is the current version before use.

* 3.12, last line: Delete "(see 4.3.1)" and substitute "The description of capabilities shall include a statement that the indicator measures average rms voltage (see 4.3.1)."

PAGE 4

4.3, line 2: Delete "Naval Ship Engineering Center" and substitute "Naval Sea Systems Command".

Add to table I:

"Examination and tests	Requirement paragraph	Test paragraph
Voltage surge	3.3	4.8.4.1"

PAGE 6

4.8.4, lines 1 through 3: Delete and substitute:

"4.8.4 Voltage and frequency variations. The indicator shall be tested at plus or minus 10 and 20 percent of nominal voltages (28, 115, 220, 440 Vac; 28, 115, 250 and 500 Vdc) with applicable concurrent variations of plus or minus 10 and 20 percent of nominal."

Add new paragraph 4.8.4.1:

"4.8.4.1 Voltage surge. The indicator when energized at 120 V and 450 V shall be subjected to an impulse test with spikes to 2500 V in accordance with DOD-STD-1399, section 300. The indicator shall be fully operational after test."

PAGE 7

4.8.12, delete in its entirety, and substitute:

"4.8.12 Mechanical conformance tests.

"4.8.12.1 Drop. A drop test shall be made to determine conformance to the rugged construction requirements of 3.3. The drop test shall consist of dropping the indicator with leads and prods free and at the same level from a height of 3 feet to a flat concrete floor. There shall be no mechanical damage to the indicator, leads, or prods which expose internal conductors or affects the use of the unit for the designed purpose. The indicating device shall not be dislocated during the drop test (see 3.3.4).

"4.8.12.2 Test lead. With the test leads suspended from the indicator, hang a 30 pound weight from each test prod. The wires shall not pull out of the case or exert any pressure on the soldered connection. The weight shall then be lifted by the prod handle. The handle shall not separate from the prod."

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T18:02Z
Check the source to verify that this is the current version before use.

6.3 Delete and substitute:

"6.3 Qualification. With respect to products requiring qualification, awards will be made only for products which are, at the time set for opening of bids, qualified for inclusion in Qualified Products List QPL-23830 whether or not such products have actually been so listed by that date. The attention of the contractors is called to these requirements, and manufacturers are urged to arrange to have the products that they propose to offer to the Federal Government tested for qualification in order that they may be eligible to be awarded contracts or purchase orders for the products covered by this specification. The activity responsible for the Qualified Products List is the Naval Sea Systems Command, SEA 55Z3, Department of the Navy, Washington, DC 20362-5101 and information pertaining to qualification of products may be obtained from that activity. Application for qualification tests shall be made in accordance with "Provisions Governing Qualification SD-6" (see 6.3.1)."

LAST PAGE

DD Form 1426, Standardization Document Improvement Proposal: Delete address and substitute:

"COMMANDER
NAVAL SEA SYSTEMS COMMAND (SEA 55Z3)
DEPARTMENT OF THE NAVY
WASHINGTON, DC 20362-5101"

NOTE: The margins of this amendment are marked with asterisks to indicate where changes (additions, modifications, corrections, deletions) from the previous amendment were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous amendment.

Preparing activity:
Navy - SH
(Project 6625-N836)

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T18:02Z
Check the source to verify that this is the current version before use.