MILITARY SPECIFICATION

ACCESSORY SET MARK 1 MOD 1

This specification is approved for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification establishes the requirements for the procurement of Accessory Set Mark 1 Mod 1, LD 479701, referenced herein as the the accessory set.

2.1 The Accessory Set Mark 1 Mod 1 includes the following:

(a) Cable Assemblies, CA-55, CA-57, CA-58, CA-90, CA-91, CA-796 CA-797, CA-799 and CA-1321.
(b) Adapters, Test, Mark 21 Mod O, Mark 26 Mod O, Mark 28 Mod O and Mark 38 Mod O.

2. APPLICABLE DOCUMENTS

2.1 The following documents, of the issue in effect on date of invitation for bids or request for proposal, form a part of this specification to the extent specified herein.

SPECIFICATIONS

FEDERAL

PPP-F-320	Fiberboard: Corrugated and Solid, Sheet Stock (Container Grade), and Cut Shapes
PPP-B-601	Boxes, Wood, Cleated-Plywood
PPP-B-621	Boxes, Wood, Nailed and Lock Corner
PPP-B-636	Boxes, Shipping, Fiberboard
PPP-C-843	Cushioning Material, Cellulosic
PPP-B-1055	Barrier Material, Waterproofed, Flexible

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T09:35Z
Check the source to verify that this is the current version before use.

STANDARDS

MILITARY

MIL-STD-129	Marking for Shipment and Storage
MIL-STD-481	Cinfiguration control Engineering Changes, Deviations and waivers (Short Form)

DRAWINGS

NAVAL ORDNANCE SYSTEMS COMMAND

LD 479701	Accessory Set Mark 1 Mod 1
LD 284866	Preparation for Delivery for Test Set Cables
Dwg 883198	Cable Assembly CA-799
Dwg 883202	Cable Assembly CA-796
Dwg 893796	Cable Assembly CA-797
DWg 1260785	Cable Assembly CA-55
Dwg 1260787	Cable Assembly CA-57
Dwg 1260789	Cable Assembly CA-58
Dwg 1274694	Cable Assembly CA-90
Dwg 1274696	Cable Assembly CA-91
Dwg 3175691	Cable Assenbly CA-1321

PUBLICATIONS

NAVAL ORDNANCE SYSTEMS COMMAND

OS 7192	Descriptions and Requirements Adapter, Test, Mark 21 Mod 0
OS 7285	Descriptions and Requirements Adapter, Test, Mark 26 Mod 0
OS 7287	Descriptions and Requirements Adapter, Test, Mark 28 Mod 0
OS 7667	Descriptions and Requirements Adapter, Test, Mark 38 Mod 0

(Copies of specifications, standards, drawings and publications required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T09:35Z
Check the source to verify that this is the current version before use.

2.2 Other publications. The following document forms a part of this specification to the extent specified herein, Unless otherwise indicated, the issue in effect on date of invitation for bids or request for proposal shall apply.

NATIONAL BUREAU OF STANDARDS

Handbook H28 Screw Thread Standards for the Federal Services

(Application for copies should be addressed to the Superintendent of Documents, Government Printing Office, Washington 25, DC 20402.)

3. REQUIREMENTS

3.1 Description. The components of Accessory Set Mark 1 Mod 1 are used, individually, with Test Set Mark 127 in performing load, no-load, continuity and leakage resistance tests on batteries used in underwater mines. The adapters (see 1.2 (b)) incorporate load resistors and meter multiplier resistors to adapt Test Set Mark 127 to the particular battery under test.

* 3.1.1 The following tabulation is a cross reference of each component (see 1.2) and the battery with which it is associated.

COMPONENT	BATTERY
Cable Assembly CA-55	Mark 111 Mod 1
Cable Assembly CA-57	Mark 112 Mod 1
Cable Assembly CA-58	Mark 113 Mod 0
Cable Assembly CA-90	Mark 109 Mod 1
* Cable Assembly CA-91	Mark 110 Mod 1
Cable Assembly CA-796	Mark 106 Mod 0
Cable Assembly CA-797	Mark 105 Mod 0
Cable Assembly CA-799	Mark 108 Mod 0
* Cable Assembly CA-1321	Mark 116 Mod 1
Adapter, Test, Mark 21 Mod 0	Mark 121 Mod 0
Adapter, Test, Mark 26 Mod 0	Mark 114 Mod 0
Adapter, Test, Mark 28 Mod 0	Mark 115 Mod 1
Adapter, Test, Mark 38 Mod 0	Mark 117 Mod 0

3.2 General requirements.

3.2.1 First article sample. Unless otherwise specified in the contract or order (see 6.2), a first article sample of the accessory set is required and shall be manufactured using the methods and procedures proposed for production. The sample shall be tested as specified in Section 4 for the purpose of determining that, prior to starting production, the contractor's production methods are capable of producing items that comply with the technical requirements of the contract (see 4.3.1).

Source: https://assist.dla.mil -- Downloaded: 202610-19T09:35Z
Check the source to verify that this is the current version before use.

3.2.2 Materials. Unless otherwise specified in the contract, requisition or order (see 6.2) all materials and purchased parts entering into the final assembly of the accessory set shall be in strict accordance with the detailed requirements of the documents listed on LD 479701.

3.2.3 Finishes, coatings, construction and dimensions. Finishes, coatings, construction and dimensions for the Accessory Set shall be in accordance with the applicable documents listed on LD 479701.

3.2.4 Soldering. All connections shall be soldered using solder and flux as specified on the drawings, The connection shall be mechanically secure before soldering. All loose and excess solder shall be removed immediately after each soldering operation. All flux shall be removed.

3.2.5 Interchangeability. Component parts of assembled units (unless otherwise specified on the applicable drawings) fabricated in accordance with their applicable drawings shall be interchangeable and shall assemble with mating components of the unit without selection or fitting.

3.2.6 Gages. The contractor shall provide himself with whatever gages are necessary and adequate to insure that the material to which this specification applies will meet the dimensional requirements shown on the applicable drawings,

3.2.7 Threads. Unless otherwise specified, all threads shall be in accordance with the National Bureau of Standards Handbook H28.

3.2.8 Requests for deviation. Requests for deviation from this specification, applicable drawings, specifications, publications, materials or processes specified herein shall be as set forth in MIL-STD-481.

3.2.9 Conflicting requirements. Conflicting requirements arising between this specification or any specifications, publications or drawings listed herein shall be referred in writing to the procuring agency or appointed agent for interpretation and clarification.

3.3 Performance requirements and product characteristics. The Accessory Set shall meet the following performance requirements and product characteristics :

3.3.1 Electrical continuity. The cable assemblies and test adapters (see 1.2) shall have electrical continuity between the directly wired terminals of their respective connectors such that the d-c resistance measured in accordance-with 4.6.1 is equal to or less than 0.15 ohm.

Source: https://assist.dla.mil -- Downloaded: 2026l0-19T09:35Z
Check the source to verify that this is the currentversion before use.

3.3.2 D-C resistance. The d-c resistances of load resistors and meter multiplier resistors in each of the cable assemblies and test adapters shall be within the specified tolerance when tested in accordance with 4.6.2,

3.3.3 Insulation resistance. The cable assemblies and test adapters shall exhibit insulation resistance between each circuit and all other circuits and to ground (defined as unused contacts and shells of connectors, center post of battery plugs and metal-junction box shells all jumpered together as a common ground). The insulation resistance shall be equal to or greater than 500 megohms when measured as specified in 4.6.3 at a test potential of 500 ± 50 volts d. c. The insulation resistance test shall be conducted after the 'item to be tested has been conditioned for a period of at least twenty-four hours at a temperature of 25 ± 1°C (77 ± 2°F), at a relative humidity of 75 ± 5 percent. The test shall be performed either with the unit still in the conditioning chamber or within one-half hour after removal therefrom.

3.3.4 Adapter test requirements. Each Test Adapter, Mark 21 Mod 0, Mark 26 Mod 0, Mark 28 Mod 0, or Mark 38 Mod 0, shall meet the requirements of OS 7192, OS 7285, OS 7287 or OS 7667, respectively (see 4.6.4).

3.4 Clean-up. Prior to and after final assembly and packaging all components of the accessory set shall be thoroughly cleaned of loose, spattered, or excess solder, metal chips and filings, or other such foreign matter. Burns and sharp edges as well as rosin flash shall be removed, All components shall be free of moisture, corrosion, dirt and dust at time of packaging.

3.5 Workmanship. The equipment, including all parts and accessories, shall be constructed and finished in a manner to assure compliance with all requirements of this specification. Particular attention shall be paid to neatness and thoroughness of soldering, plating, crimping, marking of parts and assemblies, and freedom of parts from burrs and sharp edges. The standard of workmanship exhibited in any approved first article sample, subject to any qualification stated in the Government's notice of approval, shall determine the requirements of the contract relative to workmanship insofar as not specifically covered by applicable specifications,

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or order, the supplier may use his own any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

Source: https://assist.dla.mil -- Downloaded: 2026l0-19T09:35Z
Check the source to verify that this is the currentversion before use.

4.2 Classification of inspections. Inspection of the material covered by this specification shall be classified as follows:

a, First article inspection (see 4.3.1)
b. Quality conformance inspection (see 4.3.2)

4.3 Inspections.

4.3.1 First article inspection. A first article sample of one Accessory Set manufactured in accordance with 3.2.1 shall be subjected to the examinations and tests specified in 4.5 and 4.6 at an activity designated by the procuring agency (see 6.2). Acceptance of the sample shall be based on no defects. Further production of the accessory sets by the supplier, prior to approval of the sample, shall be at the supplier's risk.

4.3.2 Quality conformance inspection. Each accessory set shall be subjected to the examinations of 4.5 and the tests of 4.6. Only accessory sets successfully passing this inspection shall be accepted.

4.3.3 Test conditions, Unless otherwise specified, the accessory sets shall be subjected to quality conformance and first article inspections under the following conditions:

a. Temperature: Room ambient 14 to 29°C (55 to 85°F)
b. Humidity: 35 to 70 percent, relative.

4,4 Special test equipment. The following items of test equipment are required to perform the tests of 4.6:

4,4.1 Ohmmeter or bridge, direct current, 0.05 to 1.00 ohm range, ± 5 percent accuracy.

4.4.2 Wheatstone Bridge, direct current, 1.0 ohm to 2 megohm range, ± 0.1 percent accuracy,

4.4.3 Megohmmeter, 500 ± 50 volts d-c test potential, capable of measuring 500 megohms or more, ± 5.0 percent accuracy.

4.4.4 Necessary wires, plugs, etc. for testing purposes.

4.5 Examinations. Each accessory set shall be examined in accordance with 4.5.1 and 4.5.2.

4.5.1 Solder examination. Electrical connections shall be examined prior to soldering to determine that all connections are mechanically secure. After soldering, the units shall be examined to determine that there are no cold solder joints and that all excess flux and all solder spatter has been removed.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T09:35Z
Check the source to verify that this is the current version before use.

4.5.2 Cleanliness examination. Each accessory set shall be examined for cleanliness. The presence of any visible moisture, corrosion or other contamination, metal chips, loose solder, burrs or sharp edges shall cause the test set to be regarded as defective.

4.6 Tests. Each accessory set shall be tested as follows:

NOTE : Test probes shall not be used to make electrical connections to connectors. Jigs made up of mating connectors shall be used. Mating connectors can be wired or their solder pots can be used as the test points.

4.6.1 Electrical Continuity (M101). Measure the d-c resistance between each directly connected pair of terminals as indicated in the following tabulations. The tests shall be performed using an ohmmeter or bridge having the minimum accuracy and range specified in 4.4.1. A measured resistance exceeding 0.15 ohms shall constitute a defect.

Cable Assembly CA-55, Drawing 1260785:

Measure From Plug P1, Contact	To Plug S1, Contact
1	V
1	T
2	P
7	S
8	R

Cable Assembly CA-57, Drawing 1260787:

Measure From Plug P1, Contact	To Plug S1, Contact
1	V
1	T
5	P
6	S
8	R

Cable Assembly CA-58, Drawing 1260789:

Measure From Plug P1, Contact	To Plug S1, Contact
1	V
1	T
2	P
7	S
8	R

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T09:35Z
Check the source to verify that this is the current version before use.

Cable Assembly CA-90, Drawing 1274694:

Measure From Plug Pl, Contact	To Plug S1, Contact
1	R
2	P
7	S
8	T
8	V
Plug Sl, A	B

Cable Assembly CA-91, Drawing 1274696:

Measure From Plug Pl, Contact	To Plug S1, Contact
1	R
5	S
6	P
8	T
8	V
Plug S1,A	B

* Cable Assembly CA-797, Drawing 893796:

Measure From Plug Pl, Contact	To Terminal Lug, P2
B	(-) (Black)

Cable Assembly CA-796, Drawing 883202:

Measure From Plug Pl, Contact	To Terminal Lug, P5
V	(-)

Cable Assembly CA-799, Drawing 883198:

Measure From Plug Pl, Contact	To Terminal Clip, P2
V	(-)

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T09:35Z
Check the source to verify that this is the current version before use.

Cable Assembly CA-1321, Drawing 3175691

Measure From Plug Pl, Contact	To Plug P2, Contact
1	R
3	P
4	S
8	T, V

4.6.2 D-C resistance (M102). Measure the d-c resistance through each resistance path as indicated in the following tabulations, using an instrument or instruments with the minimum requirements of 4.4.2 over the range specified. Any measured d-c resistance outside the specified range shall constitute a defect.

Cable Assembly CA-55, Drawing 1260785:

Measure From Plug Pl, Contact	To Plug S1, Contact	Resistance (ohms	Remarks
2	A	18,200 ± 1.0%	R2
2	J	1.5 ± 3.0%	Rl
7	B	17,800 ± 1.0%	R3

Cable Assembly CA-57, Drawing 1260787:

Measure From Plug Pl, Contact	To Plug S1, Contact	D-C Resistance (ohms)	Remarks
5	J	10 ± 3.0%	R1
5	A	76,000 ± 1.0%	R2
6	B	74,000 ± 1.0%	R3

Cable Assembly CA-58, Drawing 1260789

Measure From Plug Pl, Contact	To Plug S1, Contact	D-C Resistance (ohms)	Remarks
2	J	450 ± 3.0%	Rl
2	A	279,000 ± 1.0%	R2
7	B	279,000 ± 1.0%	R3

Cable Assembly CA-90, Drawing 1274694:

Measure From Plug S1, Contact	To Plug Pl, Contact	D-C Resistance (ohms)	Remarks
A	2	17,750 ± 1.0%	R2
J	2	1.0 ± 5.0%	Rl

Source: https://assist.dla.mil -- Downloaded: 2026l0-19T09:35Z
Check the source to verify that this is the current version before use.

Cable Assembly CA-91, Drawing 1274696:

Measure From Plug Pl, Contact	To Plug S1, Contact	D-C Resistance (ohms)	Remarks
6	A	74,000 ± 1.0%	R2
6	J	20 ± 5.0%	R1

Cable Assembly CA-796, Drawing 883202:

Measure From Plug Pl, Contact	To Terminal Lug	D-C Resistance (ohms)	Remarks
A	P2 (+135)	1,690,000 ± 1.0%	Rl
B	P3 (+73 1/2)	917,000 ± 1.0%	R2
c	P4 (+67 1/2)	842,000 ± 1.0%	R3
H	P2 (+135)	29800 ± 5.0%	R4

Cable Assembly CA-797, Drawing 893796:

Measure From Plug Pl, Contact	To Terminal Lug	D-C Resistance (ohms)	Remarks
A	P3	9.0 ± 5.0%	R1
c	P3	36,500 ± 1.0%	R2

Cable Assembly CA-799, Drawing 883198:

Measure From Plug Pl, Contact	To Terminal Clip	D-C Resistance (ohms)	Remarks
A	P2 (+3)	36,500 ± 1.0%	N
B	P2 (+1 1/2)	17,750 ± 1.0%	R2
H	P2 (+3)	62 ± 5.0%	R3

Cable Assembly CA-1321, Drawing 3175691:

Measure From Plug PI, Contact	To Plug P2, Contact	D-C Resistance (ohms)	Remarks
3	A	112,000 ± 1%	w
3	H	36 ± 1%	R1

Source: https://assist.dla.mil -- Downloaded: 2026t0-19T09:35Z
Check the source to verify that this is the currentversion before use.

4.6.3 Insulation resistance (M103). After the completion of the specified conditioning period (see 3.3.3), measure the insulation resistance between each circuit and every other circuit, not connected by design, and to ground (defined in 3.3.3). The insulation resistance measurements shall be made, using an instrument having the minimum requirements specified in 4.4.3, in accordance with the following tabulations. Any measured resistance less than 500 megohms shall constitute a defect.

Cable Assemblies CA-55, Drawing 1260785, CA-57, Drawing 1260787 and CA-58, Drawing 1260789:

Measure From Plug S1, Contact	To Plug S1, Contact
T	P, R, S and ground
P	R, S and ground
S	R and ground
R	ground

Cable Assemblies CA-90, Drawing 1274694 and CA-91, Drawing 1274696:

Measure From Plug S1, Contact	To Plug S1, Contact
T	P, R, S and ground
P	R, S and ground
R	S and ground
S	ground

Cable Assembly CA-797, Drawing 893796:

Measure From Terminal	To Terminals
P2	P3 and ground
P3	ground

Cable Assembly CA-796, Drawing 883202:

Measure From Terminal	To Terminals
P2	P3, P4, P5 and ground
P3	P4, P5 and ground
P4	P5 and ground
P5	ground

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T09:35Z
Check the source to verify that this is the current version before use.

Cable Assembly CA-799, Drawing 883198:

Measure From Terminal	To Terminals
P2 (+1 1/2)	P2 (+3), P2(-) and ground
P2 (+3)	P2 (-) and ground
P2 (-)	ground

Cable Assembly CA-1321, Drawing 3175691:

Measure From Plug Pl, Contact	To Plug P2, Contact
1	P, S, T and ground
3	S, T and ground
4	T and ground
8	ground

4.6.4 Adapter, Test (M104). Each Test Adapter; Mark 21 Mod 0, Mark 26 Mod 0, Mark 28 Mod 0 or Mark 38 Mod 0, shall be tested in accordance with OS 7192, OS 7285, OS 7287 or OS 7667, respectively, and in every case shall be acceptable.

5. PREPARATION FOR DELIVERY

5.1 Preservation and packaging.

5.1.1 Level A.

5.1.1.1 Cleaning, drying and preservative application. (Not applicable)

5.1.1.2 Component packaging. All cable assemblies and test adapters listed in LD 479701 shall be individually packaged in accordance with the requirements specified in LD 284866,

5.1.1.2.1 Each cable assembly, test adapter and connection box individually packaged as specified under 5,1.1.2, shall be positioned and stowed within the appropriate instrument case and compartment as designated on the stowage charts for the Accessory Set. All voids and spaces shall be filled, employing corrugated fiberboard material and cellulosic cushioning.

5.1.1.2.2 When individually packaged cables, test adapters or connection boxes cannot be-consolidated and stowed in their respective compartments due to their packaged size, unit containers shall be omitted or reduced in cubage. If unit containers are omitted, corrugated fiberboard material and cushioning shall be employed to provide mechanical protection to the components.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T09:35Z
Check the source to verify that this is the current version before use.

5.1.1.3 Unit packaging. Each accessory set shall be individually packaged in a conforming fiberboard box, PPP-B-636, W5c or W5s compliance symbol . Sufficient fillers and folded corner pads, fabricated from the same box material, shall be utilized within the carton to provide a tight pack and to prevent direct contact between protrusions of the accessory case and the walls of the fiberboard box.

5.1.1.4 Intermediate package. (Not applicable)

5.1.1.5 Cushioning. The cable assemblies, test adapters and connection box, packaged as specified under 5.1.1.2, shall incorporate sufficient cushioning material, bracing or other adequate shock absorbing devices, when positioned in their respective compartment within the accessory set case, to insure a tight pack. At the time of packaging or packing, the moisture content of the cushioning material shall be no more than 5 percent. The pH range of the material shall be between 6.0 and 8.0.

5.1.1.5.1 Cushioning materials shall meet the requirements of PPP-C-843, Type II, Class A and PPP-F-320, Type, Class, Variety, Grade and Flute design optional.

5.1.2 Level B and C. (Not applicable)

5.2 Packing.

5.2.1 Level A.

5.2.1.1 Exterior containers. Each accessory set, packaged as described in 5.1.1.3 shall be packed in an overseas-type, wood-cleated plywood box or in a Class 2, Style 2, 2 1/2, 3 or 4 nailed wood box conforming to the requirements of PPP-B-601 or PPP-B-621, respectively.

5.2.1.1.1 When a nailed wood box is selected to be used for shipment, box lumber shall conform to Group I, II or III woods of PPP-B-621. The lumber shall be of one inch nominal thickness and surfaced on both sides.

5.2.1,1.2 A Class H, L-2 or M case liner, fabricated from flexible water-proofed barrier material conforming to the requirements of PPP-B-1055, shall be incorporated within the shipping container.

5.2.2 Level B and C. (Not applicable)

5.3 Marking.

5.3.1 Special marking. Unless otherwise specified (see 6.2), no special markings are required.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T09:35Z
Check the source to verify that this is the current version before use.

5.3.2 Normal marking. In addition to any special marking required by the contract or order, all marking shall be in accordance with MIL-STD-129, including serial numbers.

6. NOTES

* 6.1 Intended use. The Accessory Set Mark 1 Mod 1 is used with Test Set Mark 127 in the testing of batteries for use in mines and mine components.

6.2 Ordering data. Procurement documents should specify the following:

* 6.2.1 Procurement requirements:

a. Title, number and date of this specification.
* b. Whether a first article sample is required (see 3.2.1 and 6.3)
c. Assigned activity for first article inspection (see 4.3,1)
* d. Any exceptions to the materials and parts requirements of the documents listed on LD 479701 (see 3.2.2).
e. That level A packaging and packing is required (see 5.1 and 5.2)
f. Any special markings required (see 5.3.1).

* 6.2.2 Contract data requirements. Any data required for delivery in connection with this document shall be specified on a DD Form 1423 incorporated into the contract. Such data will be delivered as identified on completed (numbered) DIDs (Data Item Descriptions/DD Form 1664) which will be documented in the Applicable ADL (Authorized Data List).

* 6.3 First article sample waiver. First article samples submitted and approved on a recent contract may be accepted by the procuring activity in lieu of an additional first article inspection. When the first article sample is waived (see 6.2.l(b)) the procurement document should contain a statement specifying that the standards of workmanship exhibited by the previously approved first article sample shall determine the minimum requirements of the current contract or order.

6.4 The margins of this specification are marked with an asterisk (*) to indicate where changes (additions, modifications, corrections, deletions) from the previous issue were made. This was done as a convenience only and the Government assumes no responsibility whatsoever for any inaccuracies in these notations. Bidders and suppliers are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous issue.

Custodian:
NAVY-OS

Preparing Activity
NAVY-OS
Project No. 4923-N001

Source: https://assist.dla.mil -- Downloaded: 2026l0-19T09:35Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

OMB Approval
No. 22-R255

INSTRUCTIONS: The purpose of this form is to solicit beneficial comments which will help achieve procurement of suitable products at reasonable cost and minimum delay, or will otherwise enhance use of the document. DoD contractors, government activities, or manufacturers/vendors who are prospective suppliers of the product are invited to submit comments to the government. Fold on lines on reverse side, staple in corner, and send to preparing activity. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements. Attach any pertinent data which may be of use in improving this document. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity.

DOCUMENT IDENTIFIER AND TITLE

MIL-A-21430B(OS), Accessory Set Mark 1 Mod 1

NAME OF ORGANIZATION AND ADDRESS

CONTRACT NUMBER

MATERIAL PROCURED UNDER A

☐ DIRECT GOVERNMENT CONTRACT ☐ SUBCONTRACT

1. HAS ANY PART OF THE DOCUMENT CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE?

A. GIVE PARAGRAPH NUMBER AND WORDING.

B. RECOMMENDATIONS FOR CORRECTING THE DEFICIENCIES

2. COMMENTS ON ANY DOCUMENT REQUIREMENT CONSIDERED TOO RIGID

3. IS THE DOCUMENT RESTRICTIVE?

☐ YES ☐ NO *(If "Yes", in what way?)*

4. REMARKS

SUBMITTED BY *(Printed or typed name and address - Optional)*

TELEPHONE NO.

DATE

DD FORM 1 JAN 72 1426 REPLACES EDITION OF 1 JAN 66 WHICH MAY BE USED

S/N 0102-014-1802

Source: https://assist.dla.mil -- Downloaded: 202610-19T09:35Z
Check the source to verify that this is the current version before use.

FOLD

POSTAGE AND FEES PAID

U.S.MAIL

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

Commanding Officer
Naval Ordnance Station (502)
Indian Head, MD 20640

FOLD

Source: https://assist.dla.mil -- Downloaded: 202610-19T09:35Z
Check the source to verify that this is the current version before use.