[INCH-POUND]
A-A-52545A
February 4, 1997
SUPERSEDING
A-A-52545
December 12, 1995

COMMERCIAL ITEM DESCRIPTION

HEATERS, VEHICULAR COMPARTMENT 28 VOLT, DC

The General Services Administration has authorized the use of this commercial item description (CID) for all federal agencies.

1. SCOPE. This CID covers two types of heaters of 28 volt (V) direct current (dc) nominal rating, used for heating crew and engine compartments of military vehicles or equipment. Type I heaters are intended for use on military vehicles or equipment which may be required to operate in an ambient temperature to minus 65 degrees Fahrenheit (-65°F); from which a supply of gasoline is available; when heated air is required without the vehicle engine being operated. Type II heaters are intended for use on military vehicles or equipment from which a supply of heated circulating liquid (engine coolant) is available, which may be required to operate in an ambient temperature to -25°F.

1.1 Classification. Heaters shall be of the following types and capacities, as specified (see 6.2):

Type I - Gasoline Fired:
Capacity A - 20 000 British thermal units per hour (Btu/hr).
Capacity B - 30 000 Btu/hr.
Capacity C - 60 000 Btu/hr.

Type II - Liquid Coolant Operated:
Capacity B - 30 000 Btu/hr.

Beneficial comments, recommendations, additions, deletions clarifications, etc. and any other data which may improve this document should be sent by letter to: U.S. Army Tank-automotive and Armaments Command, ATTN: AMSTA-TR-E/BLUE, Warren, MI 48397-5000.

ASMC N/A FSC 2540

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T09:12Z
Check the source to verify that this is the current version before use.

2. SALIENT CHARACTERISTICS

2.1 Materials. Materials for type I heaters shall be as specified in the applicable engineering drawing (AED). Materials for type II heaters shall be in accordance with the manufacturer's material specifications for heaters. The use of recovered material made in compliance with regulatory requirements is acceptable providing all requirements of this CID are met (see 4.1).

2.2 Design and construction. Unless otherwise specified, type I heaters shall fall within the envelope outline of the AED and shall conform to the detail requirements for mounting dimensions, external electrical connections and fuel inlet. Type II heaters shall be constructed in accordance with figures 1, 2, and 3. Type I and type II heaters shall meet the applicable requirements of Federal Motor Carrier Safety Regulations (FMCSR) in effect on date of manufacture.

2.2.1 Interchangeability. All parts having the same manufacturer's or Army part numbers shall be completely interchangeable with each other with respect to installation and performance.

2.3 Controls. When specified (see 6.2), heaters shall be furnished complete with controls to start, stop, and operate heaters.


2.4 Coolants. Type II heaters shall perform as specified herein using the following type coolants/rust inhibitors:

a. Water and antifreeze compound conforming to A-A-870.
b. Arctic type antifreeze compound of a single phase homogeneous mixture. This compound shall provide protection against freezing in regions where the ambient temperature remains close to -40°F for extended periods of time, but may drop to as low as -90°F.
c. Water and corrosion inhibiting compound consisting of the chemical composition shown in table I.

TABLE I. Chemical composition.

Components	Weight percent
Distilled or deionized water (total added)	63.4 ±0.6
Sodium metaborate ($Na_2B_2O_4$ $8H_2O$)	29.0 ±0.3
Potassium Silicate solution	4.6 ±0.2
Sodium mercaptobenzothiazole, 50% aqueous solution, by weight	3.0 ±0.1

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T09:12Z
Check the source to verify that this is the current version before use.




NOTES:

1. Dimensions are in inches, maximum, except detail C, unless otherwise specified. Detail C tolerances are ±0.06.
2. Basic assembly is shown. Heater may be adapted to various configurations by rearranging or interchanging end panels or blower housing attachment.

FIGURE 1. Type II heater.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T09:12Z
Check the source to verify that this is the current version before use.




NOTES:

1. Dimensions are in inches. Unless otherwise specified tolerances are ±0.010 for shell, ±0.003 for washer and ± 0.007 for terminal.
2. The cable shall be unshielded single conductor type, 14 AWG size, with outside diameter of 0.160 ±0.010. The cable shall be designed and constructed as shown in A-A-52499.
3. Shell material shall be rubber grade M5BC610A14C12E034F19 or equivalent as specified in ASTM D2000.
4. Shell shall be marked “OZ” (ozone resistant).
5. Washer material shall be brass, temper 2 hard minimum.
6. Finished washer shall have burrs and sharp edges removed.
7. Terminal material shall be brass, temper 2 hard minimum.
8. Terminal finish shall be silver plate, 0.0002 minimum thickness.

FIGURE 2. Type II heater connector assembly.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T09:12Z
Check the source to verify that this is the current version before use.



NOTES:

1. Material shall be brass. Handle may be zinc plated steel.
2. Dimensions are in inches.

FIGURE 3. Type II - Heater vent.

2.5 Fuel. Type I heaters shall perform as specified in 2.6.1 using military combat grade automotive gasoline or commercial grade automotive gasoline.

2.6 Performance.

2.6.1 Type I heater.

2.6.1.1 Heat output. With inlet air temperature at -65 ±5°F, the type I heaters shall have a heat output as specified in table II.

2.6.1.2 Air discharge rate. The type I heaters when performing at high setting, shall discharge air at not less than the rates specified in table II.

2.6.1.3 Fuel flow. Consumption of gasoline conforming to 2.5 in type I heaters shall not exceed the flow rate values specified in table II.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T09:12Z
Check the source to verify that this is the current version before use.

TABLE II. Type I Heaters.

		Capacity		
		A	B	C
Heat output: Btu/hr.	High setting	18 000	27 000	54 000
	Low setting	7 200	16 200	27 000
Air discharge: ft^3/min 1/	Unrestricted	80	105	200
	Air back pressure	50 at 0.5 inch H_20	85 at 1 inch H_20	150 at 1 inch H_20
Fuel flow: Gal/hr.	High heat	0.29	0.48	0.83
	Low heat	0.13	0.30	0.44
Current: Amperes	Start	12	18	21
	Run	4	7	11

1/ ft^3/min = cubic feet per minute.

2.6.1.4 Current. Using a starting voltage of 24 ±0.5 Vdc and a test ambient temperature of -65°F, the current shall be not more than the values specified in table II.

2.6.1.5 Overheat switch. The overheat switch shall break the circuit and cut off the flow of fuel when the ventilating air mixed with ambient air is heated to a temperature of 375 ±25°F.

2.6.1.6 Cycling. Type I heaters shall start in less than four minutes and purge in less than three minutes when cycled at high setting for 50 cycles at an ambient temperature of -65 ±5°F. Each cycle shall consist of starting at high heat, running for 15 minutes, purging, and cooling the heater for 35 minutes with auxilary blower.

2.6.1.7 Endurance. The heater shall operate without a breakdown of the heat exchanger, electrical motor, combustion air blower wheel, ventilating air blower wheel, or fuel control valve during not less than 500 hours of continuous use, operating at ambient temperatures as low as -65°F, alternately at high and low heat settings, for 24 hour periods and cycling 20 minutes "ON" and 10 minutes "OFF".

2.6.1.8 Safety. All heaters shall comply to DoT standards cited in 49 CFR, section 177.834 in effect on date of manufacture.

2.6.2 Type II heaters.

2.6.2.1 Heat output and air discharge. The heat output and air discharge rate shall be not less than values in table III, as determined per SAE J638 procedure.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T09:12Z
Check the source to verify that this is the current version before use.

TABLE III. Type II heat output and air discharge.

Inches H_2O back pressure	Heat output Btu/hr	Air discharge: ft^3/min
0	28 000	150
1.6	15 000	75

2.6.2.2 Cycling. The heater shall have no coolant leakage from the coolant circulation system when cycled at 20 cycles per minute, pressure rise and fall from 0 to 32 pounds per square inch (psi), for 2500 total cycles. Cycling shall be accomplished at ambient temperature of -25 ±5°F.

2.6.2.3 Endurance. The heater shall operate without a breakdown of the heat exchanger, electric motor or fan during not less than 250 hours of continuous operation with a coolant temperature of 180 ±5°F with zero back pressure, and not less than 250 hours with 1.6 inches of H_2O back pressure. Starting time to full load shall be 10 seconds maximum.

2.6.3 Type I and II heaters.

2.6.3.1 Voltage. The heater shall start and operate satisfactorily at an applied voltage of 20 to 28.5 Vdc.

2.7 Environmental.

2.7.1 Low temperature operation. Type I heaters shall have operational stability at temperatures to -65 ±5°F and type II heaters shall have operational stability at temperatures to -25°F.

2.7.2 Vibration. The heaters shall start and operate while vibrating at an amplitude of 0.25 inch for one hour in the direction of each of the three major axes of the heater. While accelerating and decelerating at a uniform rate for an interval of one minute, the frequency shall vary through a range of 10 to 55 cycles per second. There shall be no evidence of leakage of fuel from the type I heaters, or of coolant from the type II heaters during or after the vibration.

2.7.3 Corrosion resistance. With all duct openings sealed, the heaters shall show no evidence of corrosion that would affect their functioning after being subjected to a 96-hour salt solution spray.

2.7.4 Electromagnetic interference. Unless otherwise specified (see 6.2) or in applicable drawings, the heaters shall meet the electromagnetic interference requirements of products offered commercially.

2.8 Identification and markings. Identification and markings shall be permanent and legible and shall include as a minimum, the manufacturer's identification code (CAGE), the engineering drawing part number (type I heaters) and PIN AA52545-1 (type II heater).

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T09:12Z
Check the source to verify that this is the current version before use.

2.9 Nameplate. A nameplate shall be attached to the heater in a location, such that the plate may be easily read when the heater is installed in the vehicle. The location of the nameplate shall be as specified in the contract or ordering data (see 6.2). The nameplate shall contain the following minimum information:

HEATER 28 VOLTS DC
ENGINEERING DRAWING PART NUMBER (TYPE I HEATERS)
PIN AA52545-1 (TYPE II HEATERS)
MANUFACTURER'S IDENTIFICATION
MANUFACTURER'S SERIAL NUMBER

2.10 Painting. The exterior surfaces of the type I heater case and outlet adapter shall be cleaned, degreased, and then painted with paint heat tested to 400°F. Other surfaces of the type I heater, and the exterior surfaces of the type II heater shall be finished as specified in the contract (see 6.2).

3. QUALITY ASSURANCE PROVISIONS

3.1 Product conformance. The products provided shall meet the salient characteristics of this commercial item description, conform to the producer's own drawings, specifications, standards, and quality assurance practices, and be the same product offered for sale in the commercial market. The Government reserves the right to require proof of such conformance.

4. REGULATORY REQUIREMENTS

4.1 Recovered materials. The offeror/contractor is encouraged to use recovered materials to the maximum extent practicable, in accordance with paragraph 23.403 of the Federal Acquisition Regulation (FAR).

5. PACKAGING. Preservation, packing, and marking shall be as specified in the contract or order (see 6.2).

6. NOTES

(This section contains information of a general or explanatory nature that may be helpful, but is not mandatory.)

6.1 Addresses for obtaining copies of referenced documents.

6.1.1 Government documents. Copies of FMCSR 49 CFR Parts 100 to 177 can be obtained from Superintendent of Documents, Government Printing Office, Washington, DC 20402-9371. Copies of A-A-870 "Antifreeze/Coolant, Engine: Ethylene Glycol, Inhibited Concentrated" and

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T09:12Z
Check the source to verify that this is the current version before use.

A-A-52499 “Lead, Electrical (Storage Battery)” are available from the Defense Printing Services Detachment Office, Bldg. 4D (Customer Service), 700 Robbins Avenue, Philadelphia, PA 19111-5094.

6.1.2 Non-Government documents. Copies of SAE J638 “Motor Vehicle Heater Test Procedure, Recommended Practice,” can be obtained from the Society of Automotive Engineers (SAE), 400 Commonwealth Drive, Warrendale, PA 15096. Copies of ASTM D2000 “Standard Classification System for Rubber Products in Automotive Applications (SAE Recommended Practice J200) (DoD Adopted)” can be obtained from American Society for Testing and Materials, 100 Barr Harbor Drive, West Conshohocken, PA 19428-2959.

6.2 Ordering data. Acquisition documents must specify the following:

a. Title, number, and date of this CID.
b. Issue of Department of Defense Index of Specifications and Standards (DoDISS) and the specific issue of individual documents referenced.
c. Type and capacity of heater.
d. Title, number, and revision letter of the AED for type I heaters.
e. PIN for type II heaters.
f. Quantity of heaters required.
g. Electromagnetic interference requirements if other than commercially available.
h. Location of nameplate.
i. If controls are to be furnished.
j. Surface finish of heaters.
k. Selection of applicable level of packaging requirements.

6.3 Cross-reference. Heaters conforming to this CID are interchangeable/substitutable with heaters conforming to MIL-H-3199E and MS51326A(AT).

MILITARY INTERESTS:

Custodians:
Army - AT
Navy - MC
Air Force - 99

Review Activities:
DLA - CS

CIVIL AGENCY COORDINATING ACTIVITY:
GSA - FSS

Preparing Activity:
Army - AT

(Project 2540-0441)

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T09:12Z
Check the source to verify that this is the current version before use.