METRIC

MIL-P-63245B(AR)
AMENDMENT 2
06 November 1996
SUPERSEDING
AMENDMENT 1
23 April 1996

MILITARY SPECIFICATION

PROJECTILE, 155MM, HE, M795
METAL PARTS ASSEMBLY

This amendment forms a part of MIL-P-63245B (AR), dated 16 October 1995, and is approved for use by the US Army Armament, Research, Development and Engineering Center and is available for use by all Departments and Agencies of the Department of Defense.

PAGE 2

*2.1.1 STANDARDS:

Delete: MILITARY (Advisory)

MIL-STD-410 - Nondestructive Testing Personnel Qualification and Certification

MIL-STD-1949 - Inspection, Magnetic Particle

PAGE 3

*2.2 Non-Government publications:

Add: E1444 - Magnetic Particle Testing

Add:

AMERICAN NATIONAL STANDARDS INSTITUTE

CP 189 - Standard for Qualification and Certification of Nondestructive Testing Personnel

DISTRIBUTION STATEMENT A. **Approved for public release; distribution is unlimited.**

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:28Z
Check the source to verify that this is the current version before use.

PAGE 7

4.3.1.1: Delete “Base Cover .....9326051.....5”

PAGE 10

Table I. First Article Inspection:
Delete “Base Cover (Dwg. 9326051) Examination of characteristics
5 3.2 4.4.2.1”

PAGE 11

*4.4.1.1: Change first sentence from:

“Heat treatment inspection lots shall not exceed one mill heat of steel or 2000 components, whichever is smallest.”

To:

“Heat treatment inspection lots shall not exceed one mill heat of steel or 2500 components, whichever is smallest.”

PAGE 14

4.4.2.1: Delete in its entirety.

PAGE 20

4.4.2.5: Special Defect 11: Delete in its entirety.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:28Z
Check the source to verify that this is the current version before use.

PAGE 30

*4.5.4: Change first sentence from:

"The inspection shall be in accordance with MIL-STD-1949, or equivalent commercial standard as approved by the contracting officer, using the continuous, wet fluorescent method.

To:

"The inspection shall be in accordance with ASTM E1444, using the continuous, wet fluorescent method."

*4.5.4: Change next to last sentence from:

"The requirement of MIL-STD-1949 to check system effectiveness by means of steel ring specimen shall be waived."

To:

"The requirement of ASTM E 1444 to check system effectiveness by means of steel ring specimen shall be waived."

*4.5.4.1:

Change From:

"Operator qualification. For operation of magnetic particle equipment, personnel shall be qualified and certified in accordance with MIL-STD-410, Level I, or equivalent commercial standard as approved by the contracting officer. For set-up and calibration of magnetic particle equipment, personnel shall be qualified and certified in accordance with MIL-STD-410, Level II."

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:28Z
Check the source to verify that this is the current version before use.

To:

"Operator qualification. For operation of magnetic particle equipment, personnel shall be qualified and certified in accordance with ANSI CP 189, Level I. For set-up and calibration of magnetic particle equipment, personnel shall be qualified and certified in accordance with ANSI CP 189, Level II."

*4.5.5:

Change from:

"Ultrasonic inspection. The projectiles shall be ultrasonically inspected using equipment and procedures in accordance with 4.5.5.1. ultrasonic energy shall be used at right angles to assure that orientation does not prevent detection of a defect. Standards, in accordance with 4.5.5.3, shall be used to check the effectiveness of the inspection process. Any projectile failing to meet the requirements of 3.8 shall be classed defective and removed from the lot. All projectiles rejected by ultrasonics shall be visually inspected for the location of the discontinuity. If the discontinuity can be observed visually, it shall be characterized as a critical defect, and appropriate action shall be taken.

To:

"Ultrasonic inspection. The projectiles shall be ultrasonically inspected using equipment and procedures in accordance with 4.5.5.1. Ultrasonic energy shall be used at right angles to assure that orientation does not prevent detection of a defect. Standards, in accordance with 4.5.5.3, shall be used to check the effectiveness of the inspection process. Any projectile failing to meet the requirements of 3.8 shall be classed defective and removed from the lot. All projectiles rejected by ultrasonics shall be visually inspected at the location of the ultrasonic indication. An ultrasonic critical defect shall be defined as any ultrasonic reject that has a visual crack or pipe or a visual defect other than a crack or pipe (Lap, Fold, Seam, etc.) that has an ultrasonic signal that is twice the level of the ultrasonic standard notch for that area. Visual defects other than cracks or piping

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:28Z
Check the source to verify that this is the current version before use.

shall be statically evaluated by a level II inspector to determine if a critical defect exists. Critical defect determination shall be accomplished before the start of the next production shift."

PAGE 32

*4.5.5.4: Change from:

"Operator qualification. Personnel performing the ultrasonic inspection shall be certified in accordance with MIL-STD-410 or equivalent commercial standard as approved by the contracting officer, with the following exception:"

To:

"Operator qualification. Personnel performing the ultrasonic inspection shall be certified in accordance with ANSI CP-189, with the following exception:"

The margins of this amendment are marked with an asterisk or vertical lines to indicate where changes (additions, modifications, corrections, deletions) from the previous amendment were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous amendment.

Custodian:
Army-AR

Preparing activity:
Army-AR

(Project 1320-0021)

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:28Z
Check the source to verify that this is the current version before use.