METRIC

MIL-P-63252A(AR)
AMENDMENT 1
10 October 1996

MILITARY SPECIFICATION

PROJECTILE, 155MM, HE, M795
LOADING, ASSEMBLING AND PACKING

This amendment forms a part of MIL-P-63252 (AR), dated 28 September 1995 and is approved for use by the US Army Armament, Research, Development and Engineering Center and is available for use by all Departments and Agencies of the Department of Defense.

PAGE 6

3.4.1 Mating surfaces, Change:

From:

"The mating surfaces of threads shall be free of caked explosive and all threads shall be free of foreign material. If a chemical cleaner is required, acetone or methylene chloride shall be used. Care shall be taken to prevent the chemical cleaner from coming into contact with the charge and becoming entrapped in the projectile."

To:

"The mating surfaces of threads shall be free of caked explosive or exudate and all threads shall be free of foreign material. If a chemical cleaner is required it shall be approved by the procuring agency. Care shall be taken to prevent the chemical cleaner from coming into contact with the charge and becoming entrapped in the projectile."

PAGE 7

3.7 Exudation: Delete in its entirety.

AMSC N/A FCS 1320
DISTRIBUTION STATEMENT A. **Approved for public release; distribution is unlimited**

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:28Z
Check the source to verify that this is the current version before use.

PAGE 7

3.8.2 Protection of the rotating band, Change:

From:

"Protection of the rotating band, Care shall be exercised at all times so that the rotating band of each projectile will not be nicked or burred."

To:

"Rotating band. The surface of the rotating band lands shall be examined for surface damage.

a. On the forward land, there shall be no evidence of raised copper due to nicks, digs or damage of any kind.

b. On the aft three lands, any nicks or digs extending 1/2 the land width or less are acceptable, provided the maximum band diameter is not exceeded."

PAGE 15

4.4.2.2 Special Defect a, Change:

From:

"Presence of explosive on exterior of shell body, threads and forward face."

To:

"Presence of explosive or exudate on exterior of shell body, threads and forward face."

PAGE 16

4.4.2.3: Major 104 Change:

From:

"Gage"

To:

"Visual"

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:28Z
Check the source to verify that this is the current version before use.

PAGE 16

4.4.2.3: Major 105 Change:

From:

“Visual”

To:

“Gage”

4.4.2.3: Minor 202 delete in its entirety.

PAGE 18

4.4.2.5: Minor 201 Change:

From:

“Grommet missing, damaged or improperly assembled”

To:

“Rotating band cover, damaged or improperly placed”

PAGE 23

4.4.3.3: Delete in its entirety.

PAGE 27

4.5.3: Delete in its entirety.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:28Z
Check the source to verify that this is the current version before use.

PAGE 29

6.8.1 Delete in its entirety and substitute the following:

"6.8.1 Radiographic film sources. Approved list of film types and vendors for use in radiographing this projectile:

Eastman Kodak Company
1187 Ridge Road, West
Rochestor, NY 14650

Film Type: AA, T, AX-1, M, MX

Agfa Corporation
NDT Systems
100 Challenger Road
Ridgefield Park, NJ 07660

Film Type: Agfa D7

Fugi Industrial Radiographic Products
Corporate Headquarters
20 North Ave.
Larchaont, NY 10538

Film Type: Fuji 100"

Custodian:
Army-AR

Preparing activity:
Army-AR

(Project-1320-0022)

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:28Z
Check the source to verify that this is the current version before use.