MIL-I-14651
31 July 1986
SUPERSEDING
MIL-I-3037G(IN PART)
30 September 1981

MILITARY SPECIFICATION

INSIGNIA, EMBROIDERED, RANK, GRADE AND SERVICE STRIPES, GENERAL SPECIFICATION FOR

This specification is approved for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification establishes the requirements for Schiffli Embroidered Insignia of Rank, Grade and Service Stripes.

1.2 Classification. The insignia covered by this specification shall be of the following types, styles, sizes, classes and subclass as specified (see 6.2).

Type I - Army Enlisted Grade
- Style 1 - Army Green
  - Size 1 - Men
  - Size 2 - Women
- Style 2 - Army Blue
  - Size 1 - Men
  - Size 2 - Women
- Style 3 - Army White
  - Size 1 - Men
  - Size 2 - Women
- Style 4 - Subdued
  - Class 1 - Sergeant Major of the Army
  - Class 2 - Command Sergeant Major
  - Class 3 - Sergeant Major
  - Class 4 - First Sergeant
  - Class 5 - Master Sergeant

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be used in improving this document should be addressed to: Director, The Institute of Heraldry, US Army, Cameron Station, Alexandria, VA 22304-5050, by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

AMSC N/A FSC 8455

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T04:25Z
Check the source to verify that this is the current version before use.

Class 6 - Sergeant First Class and Platoon Sergeant
Class 7 - Staff Sergeant
Class 8 - Sergeant
Class 9 - Corporal
Class 10 - Private First Class
Class 11 - Private
Class 12 - Specialist Four

Type II - Air Force Enlisted Grade
Style 1 - Full color
Style 2 - Subdued
Style 3 - Dress
Style 4 - Desert
Size 1 - Large
Size 2 - Small
Class 1 - Chief Master Sergeant of the Air Force
Class 2 - Chief Master Sergeant
Class 3 - Senior Master Sergeant
Class 4 - Master Sergeant
Class 5 - First Sergeant Device
Class 6 - Technical Sergeant
Class 7 - Staff Sergeant
Class 8 - Sergeant
Class 9 - Senior Airman
Class 10 - Airman First Class
Class 11 - Airman

Type III - Marine Corps Enlisted Grade
Style 1 - Service
Style 2 - Band Service
Style 3 - Dress
Style 4 - Band Dress
Size 1 - Men
Size 2 - Women
Class 1 - Sergeant Major of the Marine Corps (size 1 only)
Class 2 - Sergeant Major
Class 3 - Master Gunnery Sergeant
Class 4 - First Sergeant
Class 5 - Master Sergeant
Class 6 - Gunnery Sergeant
Class 7 - Staff Sergeant
Class 8 - Sergeant
Class 9 - Corporal
Class 10 - Lance Corporal
Class 11 - Private First Class

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T04:25Z
Check the source to verify that this is the current version before use.

Type IV - General Officers, Army and Air Force, Embroidered Rank
- Style 1 - Army
- Style 2 - Air Force on olive green base cloth
- Style 3 - Air Force on ultramarine base cloth
- Style 4 - Air Force on khaki base cloth
- Class 1 - General
- Class 2 - Lieutenant General
- Class 3 - Major General
- Class 4 - Brigadier General
- Size 1 - 1 inch star
- Size 2 - 5/8 inch star
- Size 3 - 3/8 inch star (Style 2, 3 and 4, Class 1 only)
- Size 4 - 3/4 inch star (Style 2, 3 and 4 only)

Type V - Officers, Army and Air Force, Embroidered Rank
- Style 1 - Army
- Style 2 - Air Force with olive green base cloth
- Style 3 - Air Force with ultramarine blue base cloth
- Style 4 - Air Force with khaki base cloth
- Class 1 - Colonel
- Class 2 - Lieutenant Colonel
- Class 3 - Major
- Class 4 - Captain
- Class 5 - First Lieutenant
- Class 6 - Second Lieutenant
- Class 7 - Chief Warrant Officer W-4
- Class 8 - Chief Warrant Officer W-3
- Class 9 - Chief Warrant Officer W-2
- Class 10 - Warrant Officer W-1

Type VI - Insignia, Stripes, Service
- Style 1 - Army
- Size 1 - Men
- Size 2 - Women
- Style 2 - Marine Corps
  - Class 1 - Service
  - Class 2 - Dress (Size 1 only)
  - Size 1 - Men
  - Size 2 - Women
  - Subclass 1 - First Enlistment
  - Subclass 2 - Second Enlistment
  - Subclass 3 - Third Enlistment
  - Subclass 4 - Fourth Enlistment
  - Subclass 5 - Fifth Enlistment
  - Subclass 6 - Sixth Enlistment
  - Subclass 7 - Seventh Enlistment

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T04:25Z
Check the source to verify that this is the current version before use.

Type VII - Insignia, Bar, Overseas Service
Class 1 - Army
Size 1 - Men
Size 2 - Women

2. APPLICABLE DOCUMENTS

2.1 Government documents.

2.1.1 Specifications and standards. The following specifications and standards form a part of this specification to the extent specified herein. Unless otherwise specified, the issues of these documents shall be those listed in the issue of the Department of Defense Index of Specifications and Standards (DODISS) and supplement thereto, cited in the solicitation.

SPECIFICATIONS

FEDERAL

V-T-276 - Thread, Cotton.
UU-P-268 - Paper, Kraft, Untreated, Wrapping.
CCC-C-461 - Cloth, Twill, Uniform cotton.
PPP-B-636 - Boxes, Shipping, Fiberboard.
PPP-B-676 - Boxes, Setup.
PPP-T- 45 - Tape, Gummed, Paper, reinforced and plain, for sealing and securing.

MILITARY

MIL-C-82252 - Cloth, Broadcloth, Wool, and Wool-Synthetic (Moth-proofed).

STANDARDS

FEDERAL

FED-STD-191 - Textile, Test methods.
FED-STD-751 - Stitches, Seams and Stitchings.

MILITARY

MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes
MIL-STD-129 - Marking for Shipment and Storage
MIL-STD-794 - Parts and Equipment, Procedures for packaging of.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T04:25Z
Check the source to verify that this is the current version before use.

2.1.2 Other Government documents, drawings, and publications. The following other Government documents, drawings, and publications form a part of this specification to the extent specified herein. Unless otherwise specified, the issues shall be those in effect on the date of the solicitation.

DRAWINGS

THE INSTITUTE OF HERALDRY

B-3-(Series) Insignia of Grade/Rank, Various
B-11-(Series) Service Stripes, Various

(Copies of specifications, standards, and other Governments documents required by contractors in connection with specific acquisition functions should be obtained from the contracting activity or as directed by the contracting officer.)

2.2 Other publications. The following documents forms a part of this specification to the extent specified herein. Unless otherwise specified, the issues of the documents which are DOD adopted shall be those listed in the issue of the DODISS specified in the solicitation. Unless otherwise specified, the issues of documents not listed in the DODISS shall be the issue of the nongovernment documents which is current on the date of the solicitation.

THE COLOR ASSOCIATION OF THE UNITED STATES

The Standard Color Reference of America, Tenth Edition.
United States Army Color Card, The Official Colors for Branches, Agencies, etc.
DOD Standard Shades for Heraldic Yarns for Embroidery and Ribbons, 1974.

AMERICAN SOCIETY FOR TESTING AND MATERIALS

ASTM-D-3951 - Standard practice for commercial packaging

(Application for copies should be addressed to the American Society for Testing and Materials, 1916 Race Street, Philadelphia PA 19103.)
(Nongovernment standards and other publications are normally available from the organizations which prepare or which distribute the documents. These documents also may be available in or through libraries or other informational services.)

2.3 Order of precedence. In the event of a conflict between the text of this specification and the references cited herein, (except for associated detail specifications, specification sheets or MS standards) the text of this specification shall take precedence. Nothing in this specification, however, shall supersede applicable laws and regulations unless a specific exemption has been obtained.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T04:25Z
Check the source to verify that this is the current version before use.

3. REQUIREMENTS

3.1 Guide samples. Unless otherwise specified (see 6.2), samples shall be furnished by the contracting officer to be used for guidance, information and as a standard for colorfastness. Variation from this specification may appear in the guide samples in which event the specification shall govern.

3.2 First article. Unless otherwise specified (see 6.2), before production is commenced, a sample of the finished item shall be submitted or made available to the contracting officer or his representative for inspection and/or testing as specified in 4.4. Approval of the first article sample authorizes the commencement of production but does not relieve the contractor of responsibility for compliance with all provisions of the specification. The samples shall be manufactured in the same facilities to be used for the manufacture of the production items.

3.3 Materials. Materials shall conform to the referenced specifications and the requirements specified herein.

3.3.1 Embroidery yarn. The embroidery yarn shall be a semidull continuous filament, regenerated cellulose type rayon, two-ply schiffli type yarn. The yarn shall be 150, 100 or 75 denier as specified on the applicable cartoon or drawing.

3.3.1.1 Color. Unless otherwise specified, the color of the embroidery yarns for the background (when applicable) and device shall be as shown on table I or the applicable cartoon or drawing. The border stitching when required shall match the color of the base cloth. The use of sulphur dyes is prohibited.

TABLE I. Color of embroidered yarns.

	Background	Device 1/
Type I (all styles)	NA	Goldenlight HG 67107
Type II		
Style 1	Flag Blue HY 67124	Silver Gray HAM 67137
Style 2	NA	Flag Blue HY 67124
Style 3	Graphite Blue HCF 67181	Metallic Silver
Style 4	NA	Spice Brown 67196
Type III		
Style 1, size 1	NA	Olive HAJ 67134
Style 1, size 2	NA	2/
Style 2	NA	Olive HAJ 67134
Style 3	NA	3/
Style 4	NA	3/

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T04:25Z
Check the source to verify that this is the current version before use.

TABLE I. Color of embroidered yarns- continued.

	Background	Device 1/
Type IV		
Style 1	NA	As specified on cartoon
Style 2	NA	As specified on cartoon
Type V (all styles)	NA	As specified on cartoon
Type VI		
Style 1	NA	Goldenlight HG 67107 and Army Green HAF 67131
Style 2, class 1	NA	Olive HAJ 67134
Style 2, class 2	NA	3/
Type VII	NA	Goldenlight HG 67107 and Army Green HAF 67131

1/ Border stitching for type I and type II insignia shall be the same color as the background. Star for Senior Airman, Airman First Class, and Airman shall be same color as background.

2/ Device stitching for type III, style 1, size 2 shall be Olive HAJ 67134, Spruce Green HAE 67130 or Gold HF 67106 as specified (see 6.2).

3/ Device stitching for type III, style 3, 4 and type VI, style 2 shall be Olive HAJ 67134 or Gold HF 67106 as specified (see 6.2).

3.3.1.2 Matching. The color shall match the standard sample when viewed under filtered tungsten lamps which approximate artificial daylight having a correlated color temperature of 7000 plus or minus 500 K, with illumination of 100 plus or minus 20 foot candles, and shall be a good match to the sample under incandescent lamplight at 2300 plus or minus 100 K.

3.3.1.3 Colorfastness. When tested as specified in 4.6.5, the dyed embroidered yarn shall show good fastness to wet-dry cleaning, bleaching, light, and fair fastness to laundering except that for black, blue, and red shade the fastness to bleaching shall be not less than fair as defined in FED-STD-191.

3.3.2 Base cloth.

3.3.2.1 Except type III and type VI, style 2. The base cloth for all insignia, except type III and type VI, style 2, shall be cotton or 50/50 or 65/35 cotton/polyester blend three up, one down, left hand twill, 7.0 to 8.3 ounces per square yard, single ply warp and filling, with a breaking strength of not less than 150 lbs in the warp and 80 lbs in the filling. The residual shrinkage shall be not more than 2 percent in either the warp or filling direction and the cloth shall have not less than fair colorfastness to laundering when tested as specified in 4.6.1.1.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T04:25Z
Check the source to verify that this is the current version before use.

3.3.2.2 Type III, style 1, 2 and type VI, style 2, class 1. The base cloth for type III, style 1, 2 and type VI, style 2, class 1 shall be cotton uniform twill conforming to type III or type IV of CCC-C-461, with the exception that the requirements for seams efficiency and fastness to perspiration shall not apply. The base cloth specified in 3.3.2.1 may be used as an alternate.

3.3.2.3 Type III, style 3, 4 and type VI, style 2, class 2. Wool base cloth for type III, style 3, 4 and type VI, style 2, class 2 insignia shall conform to type 1, class 4 of MIL-C-82252, except the finished cloth shall show fair fastness to crocking perspiration, wet-dry cleaning and light when no standard is available.

3.3.2.4 Color. The color of the base cloth shall be as follows:

Type, style, class	Base cloth
Type I	
Style 1	Army Green 159
Style 2	Dark Blue 152
Style 3	White
Style 4	Olive Green 107
Type II	
Style 1 and 3	Dark Blue 152
Style 2	Olive Green 107
Style 4	Khaki 80162
Type III	
Style 1	Khaki 2101 or 2120
Style 2	1/
Style 3	1/
Style 4	1/
Type IV	
Style 1	Olive Green 107
Style 2	Olive Green 107
Style 3	Ultramarine Blue 1588
Style 4	Khaki 80162
Type V	
Style 1	Olive Green 107
Style 2	Olive Green 107
Style 3	Ultramarine Blue 1588
Style 4	Khaki 80162
Type VI	
Style 1	Army Green 159
Style 2 class 1	Khaki 80162
Style 2 class 2	Scarlet 2501
Type VII	
Class 1	Army Green 159

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T04:25Z
Check the source to verify that this is the current version before use.

1/ Base cloth shall be Khaki 2101, Khaki 2120, Light Green 2223, White 3006, or Scarlet 2501 as specified (see 6.2). Scarlet 2501 shall be washed after the dyeing process in order to remove the excess dye and avoid bleeding of the color during future laundering actions.

3.3.3 Buckram. The buckram or backing material, where specified, shall be a light, open-weave, single ply fabric weighing 2.5 ounces (minimum) per square yard having a minimum thread count of 40 ends in the warp and 20 ends in the filling. The buckram shall have a minimum breaking strength of 30 pounds in the warp direction and 20 pounds in the filling direction. Testing shall be in accordance with 4.6.1.1.

3.3.4 Bobbin yarn. The bobbin yarn used in the Schiffli embroidery shall be a continuous multi-filament nylon or two-ply cotton yarn. The yarn shall be undyed except that the yarn for type I, insignia may be dyed black. When the bobbin yarn is dyed black, the yarn shall show fair fastness to wet-dry cleaning, bleaching and laundering as defined by FED-STD-191. The use of sulphur dyes is prohibited. Testing shall be in accordance with 4.6.1.1.

3.3.5 Thread. The thread for stitching the turned under edges of type III, style 1, size 1; type III, style 2; and type VI, style 2, class 1 insignia shall be cotton thread conforming to type IA3, 3 ply, ticket No. 50 of V-T-276. The thread shall be dyed Khaki shade P-1, Cable No. 66019 (see 2.2) and shall show good fastness to laundering, bleaching, perspiration and light as defined by FED-STD-191.

3.3.6 Overedge stitching yarn and thread. The yarn and thread used for overedge stitching shall be 600 or 1200 denier multi-filament bright rayon for cover thread (see 3.5.1.6) and type I, ticket No. 00, 3 ply of V-T-276 for needle and looper threads.

3.3.6.1 Color. The color of the yarn and the thread used for overedge stitching shall be as specified for the embroidered edge on the applicable drawing or cartoon. The use of sulphur dyes is prohibited.

3.3.6.2 Colorfastness. When tested as specified in 4.6.1, the dyed overedge stitching yarn and thread shall show good fastness to wet-dry cleaning, light, and fair fastness to laundering except that for black, blue, and red shades, the fastness to bleaching shall be not less than fair as defined in FED-STD-191.

3.4 Design. The design and color for the background and device of the insignia shall be as shown on the original design drawing or applicable Government cartoon. Each pair of grade insignia for Sergeant Major of the Marine Corps shall consist of a left and right insignia conforming to drawing B-3-82 and produced in a manner that when the insignia are worn, the head of the eagle and the flukes of the anchor are towards the front.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T04:25Z
Check the source to verify that this is the current version before use.

3.5 Construction. The insignia shall be embroidered on a Schiffli embroidery machine in accordance with this specification. When furnished by the Government the applicable cartoon shall form a part of this specification. Designation of a specific embroidery span on a Government cartoon does not constitute a mandatory requirement, if all other requirements are met. Cartoons are furnished for the placement of different types of stitches. The cartoon will normally indicate the number of under, cover and miscellaneous stitches to produce an insignia as well as a mandatory requirement for total minimum stitches. The manufacturer, at his discretion, may vary the under and cover stitches provided he meets the total minimum stitches required and produces a product equal to, or better than, the standard or guide sample. The density of cover stitches may be increased in critical areas where defects may occur. All thread ends shall be trimmed.

3.5.1 Embroidery stitches. The embroidery stitches shall be of the type, length, number and density specified on the applicable Government cartoon. The total stitches specified on the cartoon are full stitches and constitute two revolutions or movements of the machine. Underlay stitches shown on the cartoon by numbers are 1/2 stitches (one movement of the machine) but are converted to full stitches on the tabular listing. Except where otherwise indicated in the cartoon, all letters shall be underlaid and formed with Blatt stitches. When required by contract provisions, the contractor shall submit a sample for approval. When a contractor's sample has been specifically approved for appearance of the embroidery stitching prior to production, deliveries shall be in this respect equal to the approved sample. The embroidery stitches for Marine Corps insignia shall not be more than 1/8 inch in length. Care shall be taken in embroidering the crossed rifles device on the material of type III, style 1 and style 3 insignia so that:

a. The point at which the rifles cross is at the vertical center of the insignia.

b. The crossed rifles device shall be horizontally balanced and equally divided left and right of the vertical centerline.

c. The ends of each rifle shall be equidistant from the edges of the arcs.

3.5.1.1 Background stitches. Insignia requiring background stitching shall have either horizontal or vertical background stitching (as indicated on applicable Government cartoon) and the stitch shall be 6/32 inch in length with a plus or minus tolerance of 1/32 inch interlocking in evenly spaced rows (satin fill). Horizontal background stitching shall run in a vertical row and vertical background stitching to run in a horizontal row. The visible width of the embroidered row shall not be more than 5/64 inch. The number of visual rows and the density (number of stitches per inch in a stitch line) shall be as indicated on the applicable Government cartoon.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T04:25Z
Check the source to verify that this is the current version before use.

3.5.1.2 Device stitches. Unless otherwise specified, device stitches shall be in accordance with the applicable Government cartoon with respect to spacing the rows, number of visible rows and length and density of stitches. Translation of curvatures and other device features shall be executed with embroidery stitching finished evenly to effect a clean outline.

3.5.1.3 Underlay stitches. When underlay stitches are required, the number of stitches shall be as indicated on the cartoon. Where underlay is required in areas of design showing rows of stitches, the underlay stitches shall be inserted in a criss-cross pattern. In other areas requiring underlay, the underlay stitches shall be inserted in the direction most suitable for proper design execution.

3.5.1.4 Stiele stitches. The length and density of required stiele stitches shall be in accordance with the applicable Government cartoon. The stiele stitches shall be tightly drawn and well executed to produce a clear, sharp edging. For Marine Corps insignia, background stitching between rows of stiele stitches in the arcs and bars, shall be 1/16 inch and these areas, as well as all center devices (star, bursting bomb, diamond, or crossed rifles) shall be well-rounded and raised with sufficient and properly inserted underlay stitches to produce the fullness and depth shown in the approved sample. The stiele stitches for Marine Corps insignia shall not be more than 1/32 inch in length.

3.5.1.5 Border stitches. All type I and type II except type I style 4 insignia shall be bordered by a schrage stitch or a combination of a blatt stitch with a stiele stitch provided it is equal in density to the specified schrage stitch.

3.5.1.6 Overedge stitching. Overedge stitching shall be superimposed over the border of all type I, style 1, 2 and 3 and type II, insignia using yarn and thread specified in 3.3.6. The overedge stitching shall conform to stitch type 504 or 505 of FED-STD-751 except two ends of 600 denier or one end of 1200 denier shall be use for the cover threads. These shall be 24 stitches, plus or minus 4 stitches per inch and the stitch length shall be 1/8 inch, plus or minus 1/32 inch. Tolerance on width shall be acceptable only if the overedge stitching completely covers the border stitching. On type I, insignia except class 12, and type II, class 1, 2 and 3, the overedge shall start and finish at the top point. The overedge for type II, class 4 thru 11 will start and finish at the upper left point. The overedge for type I, class 12 will start and finish at the bottom point. Where practical overedge stitching shall be continuous from start to finish. The rounding of corners or angles shall not be permitted. If the stitching runs off a corner and begins in a new direction, the stitching ends shall be trimmed before being locked in by overedge stitching in the new direction. The final free end of the overedge stitching shall be brought to the back of the insignia and secured with adhesive or fused with a hot iron. The free end shall not be less than 1/2

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T04:25Z
Check the source to verify that this is the current version before use.

inch in length and no adhesive shall be permitted within 1/8 inch of the finished insignia edge. The color of the overedge stitching shall be the same shade as the embroidered border.

3.5.1.6.1 Optional methods of securing final free end. At the option of the contractor, the final free end of the overedge stitching may be secured by blind-stitching 1/4 inch or less of the terminal end to the back of the insignia by hand or machine; or where size and configuration permit the final end may be secured by application of a 3/8 inch by 1 inch (approximate) rectangle of masking tape. No part of the tape shall be within 1/8 inch of the finished edge of the insignia.

3.5.2 Stiffener.

3.5.2.1 Type I, style 1, 2, 3 type II; type VI, style 1; and type VII. Type I, style 1, 2, 3 type II; type VI, style 1; and type VII insignia may be treated on the reverse side with a fabric finish which will stiffen the insignia to facilitate subsequent processing. The fabric finish shall not affect the colors on the face of the insignia, cause puckering, seriously affecting appearance of insignia, and shall not react adversely to storage, laundering, wet-dry cleaning or ironing. The use of buckram specified in 3.3.3 shall be permitted provided that it does not protrude at any point beyond the outline of the finished insignia. A clear plastic type backing fused into the material shall be permitted for use provided it is not heat transferable when pressed at temperatures up to 302 degrees fahrenheit.

3.5.2.2 Type III, style 1 and 2 and type VI, style 2, class 1. Type III, style 1 and 2 and type VI, style 2, class 1 insignia shall be coated on the back with a natural rubber base adhesive dispersed in aliphatic hydrocarbon solvents, which shall give the insignia and stripes a firm finish equal to the approved sample. The coating shall not affect the color of the finished insignia or stripe in any way. The use of other coatings shall not be permitted.

3.5.2.3 Type III, style 3, 4 and type VI, style 2, class 2. Type III, style 3, 4 and type VI, style 2, class 2 insignia shall be backed with buckram specified in 3.3.3. The buckram shall not protrude beyond the outline of the finished insignia by more than 1/32 inch.

3.5.3 Cutting.

3.5.3.1 Type I, style 1, 2, 3 and type II. Type I, style 1, 2, 3 and type II insignia shall be cut in single units and the base cloth shall be evenly trimmed as close to the outside of the embroidered border edge as is possible without cutting the stitching. The base cloth shall be trimmed close enough to insure the overedge stitching covers the embroidered border.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T04:25Z
Check the source to verify that this is the current version before use.

3.5.3.2 Type III, style 1 and 2, size 1 and type VI, style 2, class 1. Type III, style 1 and 2, size 1 and type VI, style 2, class 1 insignia shall be finished by uniformly turning under the raw edges of the background material 3/16 to 1/4 inch and uniformly stitching the turned under edges to the body of the insignia using 1/16 to 1/8 inch stitching margin with 12 to 16 stitches per inch, 301 stitch type and EFa-1 stitching type in accordance with FED-STD-751. The corners and points of the cloth shall be neatly turned and caught in the stitching so that no raw edge is exposed on the front of the finished insignia. The turning when completed, shall produce a border on the face side 1/8 plus 1/16, minus 0, inch wide from edge of finished embroidery around the entire insignia and a point located at the apex of the insignia, no wider than 1/8, plus 1/16, minus 0 inch. The two lower insignia, no wider than 1/8, plus 1/16 minus 0 inch. The two lower points of the PFC insignia (class 11 insignia) shall have a finish no wider than 1/8, plus 1/16 minus 0 inch.

3.5.3.3 Type III, style 3, 4 and type VI, style 2, class 2. Type III, style 3, 4 and type VI, style 2, class 2 insignia shall be cleanly cut to form uniform edges and well defined corners and points. Sergeant Major of the Marine Corps grade insignia and service stripes shall be cut in pairs, one left and one right. In addition the service stripe shall be cut with the top and bottom edges parallel with the warp and the bottom leading point of the sides cut on a 30 degrees angle to the warp.

3.5.3.4 Type VI, style 1 and type VII. Type VI, style 1 and type VII insignia shall be cut in strips, one unit wide and approximately one yard in length. The side of the strips shall be cut so as to have a 1/8 inch border outside the embroidered edge.

3.5.3.5 Type I, style 4; type IV and type V. Type I, style 4 type IV and type V insignia shall be cut so that a minimum of 5/8 inch base material is available between the design and raw edge.

3.6 Tolerances. Unless otherwise specified, the overall measurements of the finished insignia shall be within a tolerance of plus or minus 1/8 inch of the required measurements. Where no tolerances are cited, design dimensions shall have a tolerance of plus or minus 1/32 inch.

3.7 Workmanship. The finished insignia shall be clean and well made and shall conform to the quality and grade of product established by this specification.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the contractor is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or purchase order, the contractor may use his own or any other facilities suitable for the performance of the inspection require-

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T04:25Z
Check the source to verify that this is the current version before use.

ments specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.1.1 Responsibility for compliance. All items must meet all requirements of sections 3 and 5. The inspection set forth in this specification shall become a part of the contractor's overall inspection system or quality program. The absence of any inspection requirements in the specification shall not relieve the contractor of the responsibility of assuring that all products or supplies submitted to the Government for acceptance comply with all requirements of the contract. Sampling in quality conformance does not authorize submission of known defective material, either indicated or actual, nor does it commit the Government to acceptance of defective material.

4.2 Classification of inspections. The inspection requirements specified herein are classified as follows:

a. First article inspection (see 4.4).

b. Quality conformance inspection (see 4.5).

4.2.1 Certificate of compliance. When certificates of compliance are submitted, the Government reserves the right to check test such items to determine the validity of the certification.

4.3 Inspection conditions. Unless otherwise specified, all inspections shall be performed in accordance with the test conditions specified in (applicable test method document or applicable paragraph(s) in the specification).

4.4 First article inspection. Inspection and testing of the first article sample shall be made on a completely finished insignia for all provisions of this specification applicable to the end product examination and tests.

4.5 Quality conformance inspection. Inspection shall be in accordance with provisions set forth in MIL-STD-105, except where otherwise indicated.

4.6 Quality assurance inspection. Inspection shall be in accordance with the provisions set forth in MIL-STD-105 except when otherwise specified hereafter.

4.6.1 Component and material inspection. In addition to the quality assurance provisions of the subsidiary specifications and drawings, inspection shall be performed on components and materials as specified herein.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T04:25Z
Check the source to verify that this is the current version before use.

4.6.1.1 Testing of components. Components and materials shall be tested as specified in table II. The methods of testing specified in FED-STD-191, wherever applicable, and as specified herein shall be followed. The sample size for each characteristic of each component shall be as follows:

Lot size (unit)	Sample size
800 or less	2
801 to 22,000	3
22,001 to over	5

The lot shall be unacceptable if one or more units of any component fail to meet the requirements in table II. The unit of expressing lot size and sample unit shall be as follows:

Component	Lot size expressed as	Sample size for testing
Buckram	Yard	1 linear yard full width
Embroidery yarn	pound	1 holder for every color
Bobbin yarn	pound	5 bobbins for dyed yarn 1 bobbin for natural yarn
Cotton or polyester/cotton base cloth (as applicable)	yard	3-1/2 yards full width

When the data in the "#determ per s/u" and "Results reported as" columns are not specified in table II, they shall be as required in the referenced test method.

TABLE II. Component tests.

Component	Characteristic	Rqm't para	Test method	#determ per s/u	Results reported as
Embroidery yarn	Material ident	3.3.1 1/	1500 or 1520	-	To nearest denier
	Ply	3.3.1	Visual	1	Pass or fail
	Denier	3.3.1	4021	1	To nearest denier
	Presence of sulphur	3.3.1.1 1/	2020	1	Pass or fail
	Color 2/	3.3.1.1.	Visual	1	Pass or fail
Base cloth	Material ident	3.3.2	1/	-	-
	Weave	3.3.2	Visual	1	Pass or fail
	Weight	3.3.2	5041	5	Nearest 0.1 oz/sq
	Ply	3.3.2	Visual	1	Pass or fail
	Breaking strength:				
	Warp (lbs)	3.3.2	5100	5	Nearest 1 lb.
	Filling (lbs)	3.3.2	5100	5	Nearest 1 lb.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T04:25Z
Check the source to verify that this is the current version before use.

TABLE II. Component tests - continued.

Component	Characteristic	Rqm't para	Test method	#determ per s/u	Results reported as
	Shrinkage:				
	Warp	3.3.2	5550	3	Nearest 0.1%
	Filling	3.3.2	5550	3	Nearest 0.1%
	Colorfastness to laundering	3.3.2	5610	1	Pass or fail
Bobbin yarn	Material ident	3.3.4 1/	1200 & 1530	1 -	Pass or fail -
	Ply (when cotton yarn is used)	3.3.4	Visual	1	Pass or fail
	Color (when applicable) 2/	3.3.4	Visual	1	Pass or fail
	Presence of sulphur	3.3.4 1/	2020	1	Pass or fail
	Colorfastness to (when applicable):				
	wet-dry cleaning	3.3.4	5622	-	-
	Bleaching	3.3.4	5600	-	-
	Laundering	3.3.4	5614	-	-
Buckram	Weave	3.3.3	Visual	1	Pass or fail
	Weight	3.3.3	5041	5	Nearest 0.1 oz/sq yd
	Yarn count:				
	Filling	3.3.3	5050	5	-
	Warp	3.3.3	5050	5	Nearest whole number
	Breaking strength:				
	Warp (lbs)	3.3.3	5100	5	Nearest 1 lb.
	Filling (lbs)	3.3.3	5100	5	Nearest 1 lb.
Natural rubber base adhesive		3.5.2.2 3/	-	-	-
Overedge stitching yarn	Material ident	3.3.6	1500 or 1520	-	-
	Ply	3.3.6	Visual	1	Pass or fail
	Denier	3.3.6	4021	1	To nearest denier
	Presence of sulphur	3.3.6.1 1/	2020	1	Pass or fail
	Color	3.3.6.1	Visual	1	Pass or fail

1/ Unless otherwise specified a contractor's certification of compliance may be accepted as evidence of conformance.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T04:25Z
Check the source to verify that this is the current version before use.

2/ When Government certified yarn is used, this test may be omitted by contractor (see 6.4). The Government reserves the right to draw samples for verification.

3/ Accepted on contractor's certification of compliance.

4.6.2 Visual examination of the end item. Defects found during this examination shall be assigned from 1 to 3 demerit points, as prescribed in table IV, and all demerit points found shall be added accordingly. All defects shall be so scored, except where two or more classifications of table IV are applicable for a single location condition, in which case the highest point count applicable shall be scored. The lot size, sample size and sample unit shall be expressed in units of one finished insignia each item not paired, one pair for paired insignia and one strip for insignia furnished in strips. The sample size and maximum sum of points permitted shall be as shown in table III, expressed as maximum sum of points for 3 and 2 point defects combined, and for all defects combined. The lot shall be unacceptable if the sum of the point value of the examined sample exceeds the limits established in table III. Normal inspection distance for workmanship shall be at arm's length (16 to 22 inches). Examination for other defects may be determined at an inspection distance suitable for such examinations.

TABEL III. Maximum sums of points

Lot size	Sample	3 & 2 points combined	3, 2 and 1 points combined
(Regular inspection)			
Under 3200	125	25	35
3201 - 10,000	200	35	53
10,001 - 35,000	315	53	75
35,001 - 150,000	500	75	110
150,001 and up	800	110	150
(Tightened inspection)			
3201 - 10,000	200	30	45
10,001 - 35,000	315	45	68
35,001 - 150,000	500	68	103
150,001 and up	800	103	138

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T04:25Z
Check the source to verify that this is the current version before use.

TABLE IV. Defects

Examine	Defect	Point count		
Base cloth	Other than specified	3	-	-
	Any splice, cut, hole or tear visible on face.	3	-	-
	Color shade not as specified	3	-	-
Stiffener/backing	Buckram omitted or incomplete when required.	3	-	-
	Back not coated with rubber base adhesive when required.	3	-	-
	Coating not uniform or incomplete	-	-	1
	Buckram protrudes more than 1/32 inch beyond finished insignia.	-	-	1
	Stiffener visible on front.	3	-	-
	Stiffener/backing not as specified.	3	-	-
Construction (embroidery)	Embroidery yarn not an acceptable match	3	-	-
	Background not as specified	3	-	-
General	Device not as specified	3	-	-
	Background not interlocked in evenly spaced rows	-	-	1
	Spacing of rows not in accordance with cartoon	-	2	-
	Non-uniform embroidery stitch density	-	-	1
	Bobbin thread showing on face	-	2	-
	Tight tension-distorted surface of face side.	3	-	-
	Loose tension-loopy surface	-	*	-
	Traveling (walking) stitches on face of insignia	-	*	-
	Broken stitches or stitching incomplete (missing)	-	*	-
Design	Any departure from cartoon or drawing	3	-	-
	Design or device poorly defined, sharp outline lacking.	3	-	-
	Shift, device or outline misshaped.	-	*	-
	Device flat-underlay missing or not well rounded or prominent, underlay insufficient.	-	-	1
	Design in adequately covered with base cloth, background, or underlay showing through (thin or uneven stitch density)	3	-	-
	Border not constructed of schrage stitches or a combination of blatt and stiele stitches when required.	3	-	-
	Curvature or design features fuzzy, not clearly outlined	-	2	-
	Stiele stitches not firmly drawn to produce clearly defined rows or edges.	-	2	-
	Stiele stitch in arcs, bars or device not as required by cartoon.	-	2	-

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T04:25Z
Check the source to verify that this is the current version before use.

TABLE IV. Defects - Continued.

Examine	Defect	Point count		
Workmanship	Kinked, bunched, tangled yarn on face	-	*	-
General	Broken, Scuffed, or cut yarns on face	-	*	-
	Spot, stain, stiffener, or foreign matter on face	-	*	-
	Two or more thread ends untrimmed	-	-	1
	More than two stumps longer than 1/16 inch. .	-	-	1
	Creased or folded, will not flatten by manual pressure	-	*	-
	Not paired, left and right, when required . .	3	-	-
	Embroidery yarn not an acceptable match when paired.	3	-	-
Finish	Omitted completely or not as specified. . . .	3	-	-
(border and edges)	Final free end not secured on back of insignia			
(Type I and II)	as specified	-	2	-
Style 1, 2, 3	Final free end not specified length	-	-	1
and 4	Overedge does not adequately cover border . .	-	2	-
	Bunched or tangled yarns.	-	2	-
	Broken or skipped stitches.	-	2	-
	Ravelled, ends not secured.	-	2	-
	Run-off, not caught in base cloth	-	2	-
	Not 20-28 stitches per inch on hem.	-	2	-
	Start and finish not at specified point . . .	-	-	1
	Angles or pointed corners rounded off	-	-	1
	Tight or loose tension.	-	-	1
	Overedge less than 3/32 or more than 5/32 inch length	-	-	1
	Continuity lacking when design required continuity	-	-	1
	Adhesive from final end exposed on finished edge	-	-	1
	Cut schrage or border stitches not adequately covered by overedge stitching.	3	-	-
	Wrong stitch type	3	-	-
	Not finished as specified	3	-	-
Borders	Not uniform in width or unevenly trimmed. . .	-	2	-
(base cloth)	Not cut in strips one unit wide when required	3	-	-
Types I,II,IV,V,	Corners or points not well defined.	-	2	-
VI,VII as appli-	Top and bottom edges not parallel to warp			
cable	when required.	-	-	1
	Free material between edge design and raw edge of material not as specified.	3	-	-
	Not cut in single units when required	3	-	-

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T04:25Z
Check the source to verify that this is the current version before use.

TABLE IV. Defects - Continued.

Examine	Defect	Point count		
Hems and edges (Type III and VI) (as applicable)	Any raw edge not turned under	-	2	-
	Any raw edge not firmly secured to back of insignia by stitching	-	2	-
	Stitching irregular or unevenly gauged	-	2	-
	Less than 12 or more than 16 stitches per inch	-	-	1
	Loose tension, loopy thread on hem	-	-	1
	Wrong seam type or stitching type	3	-	-
	Borders around face of insignia not uniform in width	-	2	-
	Corners and points not mitered, creased and folded down neatly (e.g. open or poorly formed)	-	2	-
	Corners and points not caught on back by stitching	-	2	-
	Stitching margin not as specified	-	-	1
	Opposing corners not uniform in appearance	-	2	-
	Upper or lower apex point more than 3/16 inch	3	-	-
	Bottom leading point of sides not cut 30 degree angle to warp	-	-	1

*Defects designated by an (*) asterisk shall be classed as follows:
3 point defect when seriously affecting appearance or serviceability.
2 point defect when affecting appearance but not seriously.
1 point defect when affecting serviceability but not seriously.

4.6.3 Examination for dimensions. Measurements shall be taken of all points, lines, areas, curves, radii and spaces for which dimensions are specified in the drawing, including:

Overall length
Overall width
Border width
Turn-under
Device location
Device dimension
Spaces and distances between intermediate points
Width of stiele stitch in Marine Corps insignia
Width of background for Marine Corps insignia

The lot size shall be expressed in units of one insignia each for individual insignia, one pair for paired insignia, and one strip for insignia furnished in strips. The sample unit shall be one completely fabricated insignia. For paired insignia, when applicable, the selection shall be by pairs. For insignia furnished in strips, when applicable, the selection shall be by strips. Each measurement found to be outside of the specified tolerances

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T04:25Z
Check the source to verify that this is the current version before use.

shall be scored as a defect. The total defects found shall not exceed the maximum of the table in this paragraph. The sample shall be selected at random from among the units selected for visual examination. For type VI, style 1 and type VII, consecutive insignia shall be examined in each strip. No more than one strip shall be examined from each bundle. The tolerances for paragraph 3.6 or any other specific tolerances provided shall be applied.

Lot size	Sample size	No. of defects (Max)
Under 3200	5	0
3201 to 22,000	15	1
over 22,000	25	2

4.6.4 Examination of preparation for delivery requirements. An examination shall be made to determine that the packaging, packing and marking requirements of section 5 of this specification are complied with. Defects shall be scored in accordance with table V. The sample unit shall be one shipping container fully prepared for delivery with the exception it need not be sealed. The lot size shall be the number of shipping containers in the end item inspection lot. The inspection level shall be S-2 and the AQL shall be 4.0 defects for hundred units.

TABLE V. Classification of preparation for delivery defects.

Examination	Defects
Markings (exterior and interior)	Omitted, incorrect, illegible, of improper size, location, sequence or method of application.
Materials	Any component missing.
	Any component damaged, affecting serviceability.
Workmanship	Inadequate application of components, such as, incomplete closure of container flaps, improper taping, loose strapping, inadequate stapling.
	Bulging or distortion of containers.
Weight	Net weight exceeds requirements.
Preservation (when applicable)	Omitted or not uniformly distributed in container.

4.6.4.1 Examination of count.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T04:25Z
Check the source to verify that this is the current version before use.

4.6.4.1.1 All insignia except type VI, style 1 and type VII. An examination shall be made to determine that the number of insignia per bundle, package, set-up box and shipping container is as required by section 5 of this specification. Table VI shall govern this examination.

4.6.4.1.2 Type VI, style 1 and type VII. An examination shall be performed to determine that the marking of strips, number of strips per package, marking of packages and marking of shipping containers is as required by this specification. Table VI shall govern this examination.

TABLE VI. Examination of count.

Examine	Unit of product or lot expressed in units of	Sample size #Units in lot	#Units selected
Unit Packaging:			
a. Number of insignia per bundle	One bundle	Up to 300	5
		301 - 500	10
		501 - 800	15
		801 - 1300	25
		1301 & over	30
b. Number of acceptable stripes or bars per strip	One strip	Up to 500	5
		501 - 1200	8
		1201 & over	13
c. Number of strips per bundle	One package	Up to 5	All
		6 to 9	5
		10 and over	7
Intermediate packaging.			
d. Number of bundles	One set up box	Up to 300	5
		301 - 500	10
		501 - 800	15
		801 - 1300	25
		1301 & over	30
Packing:			
e. Number of set-up boxes per shipping container	One shipping container	Up to 3	All
		4 to 6	3
		7 & over	4
f. Number of bundles per shipping container	One shipping container	up to 5	All
		6 to 9	5
		10 & over	7

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T04:25Z
Check the source to verify that this is the current version before use.

The lot shall be unacceptable if any of the defects listed below are found:

a. Number of insignia per bundle. The average number of insignia per bundle is less than specified

b. Number of bundles per set-up box. The number of bundles in any set-up box is less than specified.

c. Number of set-up boxes per shipping container. The total number of insignia in a shipping container is less than the total indicated on outside container marking.

d. Number of bundles per shipping containers. The number of bundles of insignia in a shipping container is less than specified.

The lot shall be unacceptable if any of the following defects are found:

a. Marking of strips. One or more strips not tagged, ticketed or marked as required, or marked incorrectly.

b. Number of strips per package. The average number of strips per package is less than 20.

c. Number of insignia per package. The number of insignia marked on the outside of the package is more than the total of acceptable insignia indicated by the individual strip tags, tickets or markings in the package.

d. Number of insignia per shipping container. The number of insignia marked on the shipping container is more than the total of insignia marked on the packages in the container.

4.6.5 Testing of the end item. The end item shall be tested as specified in table VII. The lot size shall be expressed in units of one insignia. The unit of product shall be eight (8) insignia. The lot shall be unacceptable if one or more units fail to meet the requirements referenced in table VII. The sample size shall be as follows:

Lot size (each)	Sample size
22,000 or less	2
22,001 and over	3

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T04:25Z
Check the source to verify that this is the current version before use.

TABLE VII. End item testing.

Characteristic	Rqm't para	Test method
Embroidery and overedge stitching yarn:		
Colorfastness tp:		
Wet-dry cleaning	3.3.1.3 and 3.3.6.2	5622
Bleaching 1/	3.3.1.3 and 3.3.6.2	5600
Light	3.3.1.3 and 3.3.6.2	5660 2/
Laundering 3/	3.3.1.3 and 3.3.6.2	5610
Overedge stitching thread:		
Stitches per inch	3.5.1.6	5052 4/
Fabric finish:		
Plastic backing	3.5.2.1	5/
Natural rubber base adhesive	3.5.2.2	4/

1/ Not to be performed on material specified in 3.3.2.3.

2/ In the event of dispute resulting from the test with method 5660 or a result of anomalous behavior of certain dye types or formulations, the contracting officers may authorize the exposure to natural light in accordance with test method 5662.

3/ Only the stain on the fiber of the color transfer cloth represented in the basic materials being tested shall be evaluated.

4/ The contractor shall furnish a certificate of compliance.

5/ Test will be accomplished by ironing the insignia against cloth material at required temperature. If plastic transfers to the cloth, the entire lot shall be unacceptable.

4.6.6 Palletization examination. An examination shall be made to determine that the palletization is in compliance with the section 5 requirements. Defects shall be scored in accordance with the list below. The sample unit shall be one palletized unit load fully packaged. The lot size shall be the number of palletized unit loads in the inspection lot. The inspection level shall be S-1 and the acceptable quality level (AQL), expressed in terms of defects per hundred units, shall be 6.5.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T04:25Z
Check the source to verify that this is the current version before use.

Examine	Defect
Finished dimensions	Length, width, or height exceeds specified maximum requirements.
Palletization	Pallet pattern not as specified. Interlocking of loads not as specified. Load not bonded with required straps as specified.
Weight	Exceeds maximum load limits.
Marking	Omitted; incorrect; illegible; of improper size, location, sequence, or method of application

5. PACKAGING

5.1 Preservation. Preservation shall be levels A, C or commercial as specified (see 6.2). Except where the insignia are made from moth-repellent cloth, not less than 2 ounce of naphthlalene flakes, or other equivalent, moth-repellent shall be uniformly distributed throughout the contents of each shipping container packed with insignia which has base cloth specified in 3.3.2.3.

5.1.1 Level A.

5.1.1.1 Unit packaging.

5.1.1.1.1 Type 1, style 1, 2, and 3. Insignia of one type, class size, and style shall be put up in bundles of twenty each and securely tied, or cross tied, with cotton twine or thread. Unless otherwise specified, insignia of one type, style, class and size may be placed in a clear polyethylene bag or blister pack. Closure of each bag shall be by heat-sealing or tape closure.

5.1.1.1.2 Type II. Except for sizes 1 and 2, class 5, insignia shall be put in bundles of 6 pairs (12 each) and securely tied or cross-tied with cotton twine or thread. All bundles shall be placed into a polyethylene bag except size 1 and size 2 class 5 insignia which shall be placed loose into a polyethylene bag. Closure shall be accomplished by heat sealing or taping.

5.1.1.1.3 Type VI, style 1 and type VII. Type VI, style 1 and type VII insignia will be in strips of approximately one yard each and shall be folded neatly in half. Each strip shall contain the minimum number of insignia as shown herein. A strip may be pieced together to obtain the minimum number per strip. A strip shall contain no more than two pieces and shall be attached with tape at the cut on the reverse side. Twenty folded strips, placed ten

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T04:25Z
Check the source to verify that this is the current version before use.

high and two wide, shall be completely wrapped in 30-pound minimum basis weight kraft paper conforming to grade B of UU-P-268. The wrap shall be secured with 2 inch minimum width gummed tape conforming to PPP-T-45.

Type, style and size	Minimum acceptable insignia
Type VI, style 1, size 1	60
Type VI, Style 1 , Size 2	85
Type VII, size 1	85
Type VII, Size 2	100

5.1.1.1.3.1 Marking of strips. Each strip shall bear a tag or ticket* carrying the following information in ink or indelible pencil:

Total number of service stripes or overseas bars in the strip.
Number of defective insignia in the strip with each defection insignia defaced with marking pen.
Number of acceptable insignia in the strip.

*In lieu of using tag or ticket, the required information may be marked on the back of each strip in a non-wax marking pencil.

5.1.1.1.3.2 Marking of bundles. The total number of acceptable insignia shall be marked in each package of 20 strips.

5.1.1.1.4 Type III, and type VI style 2. Except as specified herein, insignia of one type, class, style, size, and subclass only, shall be put-up in bundles of ten pair, securely tied or cross tied with cotton twine or thread. Type III, styles 1 and 2 class 1 and type VI style 2 insignia shall be put-up in matched pairs consisting of left and right-hand insignia. Each matched pair shall be placed into a snug-fitting commercial grade, clear, polyethylene bag. Closure of each bag shall be by heat sealing or tape closure. Ten (10) pair of bagged insignia of one type, class, size, and style shall be put-up in bundles and securely tied or cross tied with cotton twine or thread.

5.1.1.1.5 Type I, style 4, type IV and type V. Insignia of one subclass only shall be packaged in pairs and ten pairs shall be placed in polyethylene bags and taped closed. A pair of type V, class 1 insignia shall consist of one left and one right-hand insignia.

5.1.1.2 Intermediate packaging.

5.1.1.2.1 Type I, style 1, 2 and 3. Ten bundles (200 insignia) of one type, class, style, and size of insignia packaged as specified in 5.1.1.1, shall be placed in a set-up paperboard box conforming to type I, variety 1, class A, style 3 or 4 of PPP-B-676. Closure shall be in accordance with the appendix of the container specification.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T04:25Z
Check the source to verify that this is the current version before use.

5.1.1.2.2 Type II insignia. Thirty bundles of one style only packaged as specified in 5.1.1.1.2, shall be placed in a set-up paperboard box conforming to type I, variety 1, class A, style 3 or 4 of PPP-B-676. Closure shall be in accordance with the appendix of the specification.

5.1.1.2.3 Type I, style 4, type IV and type V. Two hundred pair, 20 unit packages of one class only packaged as specified in 5.1.1.1, shall be placed in a set-up paperboard box conforming to type I, variety 1, class A, style 3 or 4 of PPP-B-676. Closure shall be in accordance with the appendix of the container specification.

TABLE VIII. Bundles per container.

Class (Type III) Subclass (Type VI)	Type III		Type VI, Class 1	Style 2 Class 2
	Style 1 and 2	Style 3 and 4		
1	40	30	200	160
2	40	30	110	85
3	40	30	75	60
4	40	30	55	45
5	40	30	45	35
6	40	30	50	30
7	50	40	30	25
8	50	40	-	-
9	50	40	-	-
10	80	60	-	-
11	120	90	-	-

5.1.2 Level C. Insignia shall be packaged to the MIL-STD-794 requirements for this level.

5.1.3 Commercial. Insignia shall be preserved in accordance with the applicable requirements of ASTM-D-3951.

5.2 Packing. Packing shall be level A, B, C or commercial as specified (see 6.2).

5.2.1 Level A. Insignia preserved, as specified, shall be packed in a snug-fitting fiberboard shipping container conforming to class weather-resistant, V3a or V3c of PPP-B-636. Closure shall be in conformance with the appendix of the appropriate container specification. The weight of the contents of each shipping container shall not exceed the size and weight limitation of the container specification.

5.2.2 Level B.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T04:25Z
Check the source to verify that this is the current version before use.

5.2.2.1 All insignia, except type III and type VI, style 2. All insignia, preserved as specified in 5.1, except for type III and type VI style 2 insignia shall be packed in a snug-fitting fiberboard box conforming to class domestic, grade 200 of PPP-B-636. Closure shall be in accordance with the container specification. The weight in each shipping container shall not exceed the weight and size limitation of the container specification.

5.2.2.2 Type III and type VI, style 2. Type III and type VI, style 2 insignia preserved as specified in 5.1, shall be packed in a snug-fitting fiberboard box conforming to class domestic, grade 200 of PPP-B-636. The number of bundles per shipping container shall be as specified in table VIII. Each container shall have the contents covered on top and bottom with a sheet of 30 pound minimum basis weight kraft paper. Toward the end of the contract or when there is less than the required amounts per shipping container of the same material, types, classes, sizes or subclasses, combinations may be packed within the same shipping container.

5.2.3 Level C. Insignia of one type, style, size, class and subclass only, preserved as specified in 5.1, shall be packed to the MIL-STD-794 requirements for this level.

5.2.4 Commercial. Insignia preserved as specified in 5.1, shall be packed in accordance with the applicable requirements of ASTM-D-3951.

5.3 Palletization. Unitized loads, commensurate with the level of packing specified in the contract or order, shall be palletized in accordance with MIL-STD-147. Palletized loads shall be uniform in size and quantities to the greatest extent possible. If the container is of a size which does not conform to any of the pallet patterns specified in MIL-STD-147, the pallet pattern used shall first be approved by the contracting officer.

5.4 Marking. In addition to any special marking required by the contract or purchase order, intermediate boxes and shipping containers shall be marked in accordance with MIL-STD-129 or ASTM-D-3951.

5.4.1 Unit packaging. Unit packaging shall have the required information legibly printed or stamped in black on the bag across the center face, or on a white paper label inserted with in the bag so as to permit ready identification. When unit packaging is secured by cotton twine or thread, the label shall be non-adhesive and secured under the tie. The bag or label shall indicated the following:

Stock Number
Nomenclature
Quantity

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T04:25Z
Check the source to verify that this is the current version before use.

5.4.2 Marking of shipping containers packed with mixed insignia. In addition to the marking required in 5.4, shipping containers packed with mixed types, classes, subclasses or any combination shall have securely attached to the end and side, directly under the printing or stenciling, a white paper label 5 by 4 inches with the words designating the combination plainly stamped or printed thereon, and under these words shall be legibly printed the correct quantity of each container therein.

6. NOTES.

6.1 Intended use. The insignia covered by this specification are intended to be worn by Department of Defense personnel to designate wearers grade/rank, length of service, or overseas service.

6.2 Ordering data.

6.2.1 Ordering data. Procurement documents should specify the following:

a. Title, number and date of this specification.
b. Type, style, class, size class and subclass required (see 1.2).
c. Drawing number (see 2.1.2).
d. When a guide sample will not be furnished (see 3.1).
e. When a first article is not required (see 3.2).
f. Color of embroidery yarn when not specified by classification (see 3.3.1.1).
g. Color of base cloth when not specified by classification (see 3.3.2.4).
h. Cartoon (see 3.5).
i. Selection of applicable levels of packaging and packing (see 5.1 and 5.2).
j. When palletization is required (see 5.3).

6.3 Samples. For access to samples, address the contracting activity issuing the invitation for bids.

6.4 First article. When a first article inspection is required, the item should be a first article sample, or it may be a standard production item from the contractor's current inventory as specified in (4.4). The first article should consist of one completed insignia. The contracting officer should include specific instructions in acquisition documents regarding arrangements for examinations, approval of first article test results and disposition of first articles. Invitations for bids should provide that the Government reserves the right to waive the requirement for samples for first article inspection to those bidders offering a product which has been previously acquired or tested by the Government, and that bidders offering such products, who wish to rely on such production or test, must furnish evidence with the bid that prior Government approval is presently appropriate for the pending contract.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T04:25Z
Check the source to verify that this is the current version before use.

6.5 Supersession data. This specification includes, in part, the requirements of MIL-I-3037G dated 30 September 1981 and Amendment 3 thereto dated 31 December 1982.

6.6 Certification of embroidery yarn. Converters and suppliers of embroidery yarns may avail themselves of Government certification of their product with respect to shade matching, luster and colorfastness properties, once it is delivered into Government contractor's plant. Embroidery yarn which has not been so certified may cause delays in the manufacturing of insignia pending completion of Government certification tests. Inquiries about the certification procedures may be addressed to Defense Personnel Support Center, 2800 South 20th Street, Philadelphia, PA 19101-8419.

6.7 Cross-reference. Previous classifications listed in MIL-I-3037 have been changed to the new classifications indicated in 1.2 this specification. New items may be binned with or substituted for previous items.

Previous classification under MIL-I-3037	New classification under this specification
Material A	
Type II, class 1	Type I
Type II, class 2	Type II
Type II, class 3	Type III
Type III, class 4, subclass 1 to 4	Type IV
Type III, class 4, subclass 5 to 10	Type V
Type IV	Type VI
Material B	
Type I	Type III
Type II	Type VI
Type V	Type VII

6.8 Subject term (key word) listing.

Schiffli
Embroidered
Insignia
Flags
Rank
Grade
Service stripes
Cartoon

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T04:25Z
Check the source to verify that this is the current version before use.

Custodians:
Army - IH
Air Force - 11
Navy - NU

Review activities:
Air Force - 82,99
Navy - MC

User activities:
Air Force - 45

Preparing activity:
Army - IH

(Project No. 8455 - Ø199)

FSC 8455

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T04:25Z
Check the source to verify that this is the current version before use.

INSTRUCTIONS: In a continuing effort to make our standardization documents better, the DoD provides this form for use in submitting comments and suggestions for improvements All users of military standardization documents are invited to provide suggestions. This form may be detached, folded along the lines indicated, taped along the loose edge *(DO NOT STAPLE)*, and mailed. In block 5, be as specific as possible about particular problem areas such as wording which required interpretation, was too rigid, restrictive, loose, ambiguous, or was incompatible, and give proposed wording changes which would alleviate the problems Enter in block 6 any remarks not related to a specific paragraph of the document. If block 7 is filled out, an acknowledgement will be mailed to you within 30 days to let you know that your comments were received and are being considered.

NOTE This form may not be used to request copies of documents, nor to request waivers, deviations, or clarification of specification requirements on current contracts Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document*(s)* or to amend contractual requirements.

(Fold along this line)

(Fold along this line)

DEPARTMENT OF THE ARMY

The Institute of Heraldry, US Army
Cameron Station, 5010 Duke Street
Alexandria, Virginia 22304-5050

NO POSTAGE NECESSARY IF MAILED IN THE UNITED STATES

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

BUSINESS REPLY MAIL
FIRST CLASS PERMIT NO 12062 WASHINGTON D C

POSTAGE WILL BE PAID BY THE DEPARTMENT OF THE ARMY

Director
The Institute of Heraldry, US Army
ATTN: DAPC-PDH-T
Cameron Station, 5010 Duke Street
Alexandria, Virginia 22304-5050

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T04:25Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

(See Instructions – Reverse Side)

1 DOCUMENT NUMBER	2 DOCUMENT TITLE
MIL-I-14651	Insignia, Embroidered, Rank, Grade and Svc. Stripes, Gen Spec fo

3a. NAME OF SUBMITTING ORGANIZATION	4 TYPE OF ORGANIZATION *(Mark one)*
b ADDRESS *(Street, City, State, ZIP Code)*	☐ VENDOR ☐ USER ☐ MANUFACTURER ☐ OTHER *(Specify)* _____

5 PROBLEM AREAS

a. Paragraph Number and Wording

b Recommended Wording

c. Reason/Rationale for Recommendation

6. REMARKS

7a. NAME OF SUBMITTER *(Last, First, MI)* – Optional	b. WORK TELEPHONE NUMBER *(Include Area Code)* – Optional
c. MAILING ADDRESS *(Street, City, State, ZIP Code)* – Optional	8 DATE OF SUBMISSION *(YYMMDD)*

(TO DETACH THIS FORM, CUT ALONG THIS LINE.)

DD FORM 82 MAR 1426 PREVIOUS EDITION IS OBSOLETE.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T04:25Z
Check the source to verify that this is the current version before use.