NOT MEASUREMENT SENSITIVE

MIL-I-14651
INTERIM AMENDMENT 2
3 December 1993
MIL-I-14651
INTERIM AMENDMENT 1
25 November 1991

MILITARY SPECIFICATION

INSIGNIA, EMBROIDERED, RANK, GRADE AND SERVICE STRIPES,
GENERAL SPECIFICATION FOR

This amendment forms a part of MIL-I-14651, dated 31 July 1986, and is approved for use by all Departments and Agencies of the Department of Defense.

PAGE 3

Paragraph 1.2 - Delete the following:

Under Type VI, Style 2, Class 2, Delete "(Size 1 only)"

PAGE 4

Paragraph 1.2 - Add the following:

"Type VIII - Air Force Enlisted Grade (New)
Style 1 - Full Color
Style 2 - Subdued
Style 3 - Desert
Size 1 - Large
Size 2 - Small
Class 1 - Chief Master Sergeant of the Air Force
Class 2 - Chief Master Sergeant
Class 3 - Chief Master Sergeant with First Sergeant Device
Class 4 - Senior Master Sergeant
Class 5 - Senior Master Sergeant with First Sergeant Device
Class 6 - Master Sergeant
Class 7 - Master Sergeant with First Sergeant Device
Class 8 - Technical Sergeant
Class 9 - Staff Sergeant
Class 10 - Senior Airman
Class 11 - Airman First Class
Class 12 - Airman

AMSC N/A FSC 8455
DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T04:25Z
Check the source to verify that this is the current version before use.

Paragraph 2.1.1 -

Under "SPECIFICATIONS, FEDERAL"

Delete: "V-T-276 - Thread, Cotton"

Add: "NN-P-71 - Pallets, Material Handling Wood Stringer Construction 2-Way and 4-Way (Partial)"

Under "SPECIFICATIONS, MILITARY" - add:

"MIL-C-29405 - Cloth Broadcloth, Wool and Wool/Nylon
MIL-P-15011 - Pallets, Material Handling, Wood Post Construction, 4-Way Entry"

Under "STANDARDS, MILITARY" - add:

" MIL-STD-147 - Palletized Unit Loads"

PAGE 5

Paragraph 2.1.2 - Insert below line 4:

"COMMERCIAL ITEM DESCRIPTION

A-A-52094 Thread, Cotton"

PAGE 6 AND 7

Paragraph 3.3.1.1 -

Revise Table I - Type III and VI as follows:

	BACKGROUND	DEVICE 1/
"Type III		
Style 1, size 1	NA	Olive HAJ 67134
Style 1, size 2	NA	Olive HAJ 67134
Style 2	NA	Olive HAJ 67134
Style 3	NA	Gold HF 67106
Style 4	NA	Gold HF 67106
Type VI		
Style 2, class 1	NA	Olive HAJ 67134
Style 2, class 2	NA	Gold HF 67106"

PAGE 7

Add to Table I - Type VIII as follows:

Source: https://assist.dla.mil -- Downloaded: 202640-18T04:25Z
Check the source to verify that this is the current version before use.

	BACKGROUND	DEVICE 1/
"Type VIII		
Style 1	Graphite Blue HCF 67181	White HA 67101
Style 2	NA	Flag Blue HY 67124
Style 3	NA	Spice Brown HCV 67196"

Delete note 1/, 2/ and 3/ in their entirety and add the following:

"1/ Border stitching for Type I, II and VIII insignia shall be the same color as the background. The star for Type II, Class 9 (Senior Airman), Class 10 (Airman First Class) and Class 11 (Airman) shall be the same color as the background."

Paragraph 3.3.1.3 - Delete paragraph in its entirety and add the following:

"3.3.1.3 Colorfastness. When tested as specified in 4.6.1, the dyed embroidered yarn shall show good fastness to wet-dry cleaning, laundering and light except the colorfastness for black, blue and red shades shall be not less than fair for laundering as defined in FED-STD-191."

Paragraph 3.3.2.2 - Delete paragraph in its entirety and add the following:

"3.3.2.2 Type III, Style 1 and 2. The base cloth for Type III, Style 1 and 2 shall be cotton uniform twill conforming to Type III or IV of CCC-C-461, with the exception that the requirements for seam efficiency and fastness to perspiration shall not apply. The base cloth specified in 3.3.2.1 may be used as an alternate (see 6.2)."

Paragraph 3.3.2.3 - Delete paragraph in its entirety and add the following:

"3.3.2.3 Type III and Type VI, Style 2. Wool base cloth for Type III and Type VI, Style 2 insignia shall conform to Type 1, Class 4 of MIL-C-82252 or Types I or II of MIL-C-29405, except the finished cloth shall show fair fastness to crocking perspiration, wet-dry cleaning and light when no standard is available (see 6.2)."

Paragraph 3.3.2.4 -

Revise Type III and Type IV as follows:

TYPE, STYLE, CLASS	BASE CLOTH
Type III	
Style 1	1/ and 2/
Style 2	1/ and 2/
Style 3	2/
Style 4	2/
Type VI	
Style 1	Army Green 159
Style 2, Class 1	Scarlet 2501
Style 2, Class 2	Scarlet 2501

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T04:25Z
Check the source to verify that this is the current version before use.

Add Type VIII as follows:

TYPE, STYLE, CLASS	BASE CLOTH	
Type VIII		
Style 1	Dark Blue	152
Style 2	Olive Green	107
Style 3	Khaki	80162

PAGE 9

Paragraph 3.3.2.4 -

Delete Note 1/ in its entirety and add the following:

"1/ Base cloth shall be Khaki 2101, Khaki 2120 or Scarlet 2501 as specified (see 6.2). Scarlet 2501 shall be washed after the dyeing process in order to remove the excess dye and avoid bleeding of the color during future laundering actions."

Add Note 2/ as follows:

"2/ Base cloth shall be wool scarlet 2501 as specified."

Paragraph 3.3.5 - Delete paragraph in its entirety and add the following:

"3.3.5 Thread. The thread for stitching the turned under edges of Type III, Styles 1 and 2 insignia shall be cotton thread conforming to Type I, 3 ply, ticket No. 50 of A-A-52094. The thread shall be dyed Khaki shade P-1, Cable No. 66019 (see 2.2) and shall show good fastness to laundering, bleaching, perspiration and light as defined by FED-STD-191."

PAGE 11

Paragraph 3.5.1.5 - Delete paragraph in its entirety and add the following:

"3.5.1.5 Border stitches. All Type I (except Style 4), Type II, Type III on wool base cloth and Type VI on wool base cloth shall be bordered by a schrage stitch or a combination of a blatt stitch with a stiele stitch provided it is equal in density to the specified schrage stitch."

PAGE 11 & 12

Paragraph 3.5.1.6 - Delete paragraph in its entirety and add the following:

"3.5.1.6 Overedge stitching. Overedge stitching shall be superimposed over the border of all Type I, Style 1, 2 and 3; Type II; Type III on wool base cloth, Type VI, Style 2 on wool base cloth insignia and Type VIII insignia using yarn and thread specified in 3.3.6. The overedge stitching shall conform to stitch type 504 or 505 of FED-STD-751 except two ends of 600 denier

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T04:25Z
Check the source to verify that this is the current version before use.

or one end of 1200 denier shall be used for the cover threads. These shall be 24 stitches, plus or minus 4 stitches per inch and the stitch length shall be 1/8 inch, plus or minus 1/32 inch. Tolerance on width shall be acceptable only if the overedge stitching completely covers the border stitching and does not cover the stripe. On Type I insignia except Class 12; Type II, Class 1, 2 and 3; and Type VIII, Class 1 through 6; the overedge shall start and finish at the top point. The overedge for Type II, Class 4 thru 11; Type III on wool base cloth and Type VI, Style 2 on wool base cloth and Type VIII, Class 7 through 12 shall start and finish at the upper left point. The overedge for Type I, Class 12 shall start and finish at the bottom point. Where practical, overedge stitching shall be continuous from start to finish. The rounding of corners or angles shall not be permitted. If the stitching runs off a corner and begins in a new direction, the stitching ends shall be trimmed before being locked in by overedge stitching in the new direction. The final free end of the overedge stitching shall be brought to the back of the insignia and secured with adhesive or fused with a hot iron. The free end shall not be less than 1/2 inch in length and no adhesive shall be permitted within 1/8 inch of the finished insignia edge. The color of the overedge stitching shall be the same shade as the embroidered border."

PAGE 12

Paragraph 3.5.2.1 - Change paragraph title and first sentence to the following:

"3.5.2.1 Type 1, Style 1, 2, 3; Type II; Type VI, Style 1; Type VII and Type VIII. Type I, Style 1, 2 and 3; Type II; type VI, Style 1; Type VII and Type VIII insignia may be treated on the reverse side with a fabric finish which will stiffen the insignia to facilitate subsequent processing."

Paragraph 3.5.2.2 - Delete paragraph in its entirety and add the following:

"3.5.2.2 Type III, Style 1 and 2. Type III, Style 1 and 2 insignia shall be coated on the back with a natural rubber base adhesive dispersed in aliphatic hydrocarbon solvents, which shall give the insignia and stripes a firm finish equal to the approved sample. A clear plastic type backing fused into the material may be permitted for use provided it is not heat transferable when pressed at temperatures up to 302 degrees Fahrenheit."

Paragraph 3.5.2.3 - Delete paragraph in its entirety and add the following:

"3.5.2.3 Type III and Type VI, Style 2. Type III and Type VI, Style 2 insignia on wool base cloth shall be backed with buckram specified in 3.3.3."

Paragraph 3.5.3.1 - Change paragraph title and first sentence to the following:

"3.5.3.1 Type I, Style 1, 2, 3; Type II and Type VIII. Type 1, Style 1, 2, 3; Type II and Type VIII insignia shall be cut in single units and the base cloth shall be evenly trimmed as close to the outside of the embroidered border edge as is possible without cutting the stitching."

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T04:25Z
Check the source to verify that this is the current version before use.

PAGE 13

Paragraph 3.5.3.2 - Delete paragraph in its entirety and add the following:

"3.5.3.2 Type III, Styles 1 and 2, Sizes 1 and 2. Type III, Styles 1 and 2, Sizes 1 and 2 insignia shall be finished by uniformly turning under the edges of the background material 3/16 to 1/4 inch and uniformly stitching the turned under edges to the body of the insignia using 1/16 to 1/8 inch stitching margin with 12 to 16 stitches per inch, 301 stitch type and EFa-1 stitching type in accordance with FED-STD-751. The corners and points of the cloth shall be neatly turned and caught in the stitching so that no raw edge is exposed on the front of the finished insignia. The turning, when completed, shall produce a border on the face side of size 1 insignia of 3/16 plus 0, minus 1/16 inch and on size 2 insignia of 1/8 plus 1/16, minus 0 inch from finished edge of embroidery and a point located at the apex of the insignia no wider than 1/8 plus 1/16 inch minus 0 inch. The two lower points of the PFC (class 11) insignia shall finish no wider than 1/8 plus 1/16 inch minus 0 inch."

Paragraph 3.5.3.3 - Delete paragraph in its entirety and add the following:

"3.5.3.3 Type III on wool base cloth and Type VI, Style 2 on wool base cloth. Type III on wool base cloth and Type VI, Style 2 on wool base cloth insignia shall be cleanly cut to form uniform edges and well defined corners and points. Sergeant Major of the Marine Corps grade insignia and service stripes shall be cut in pairs, one left and on right. In addition, the service stripe shall be cut with the top and bottom edges parallel with the warp and the bottom leading point of the sides cut on a 30 degree angle to the warp. Type III on wool base cloth and Type VI, Style 2 on wool base cloth shall be cut to provide a 3/16 inch border."

PAGE 17

Paragraph 4.6.2 - Under TABLE III. Maximum sums of points. - add the following below "(Tightened inspection)":

Lot size	Sample	3 & 2 points combined	3, 2 and 1 points combined
Under 3200	125	21	30

PAGE 18

TABLE IV. Defects - Under "Stiffener/backing", delete the following defect

"Buckram protrudes more than 1/32 inch beyond finished insignia..... - - 1'

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T04:25Z
Check the source to verify that this is the current version before use.

PAGE 24

Paragraph 4.6.5 -

Table VII. End Item Testing. - Delete the following requirement:

"Bleaching 1/ 3.3.1.3 and 3.3.6.2 5600."

Delete Note 1/ in its entirety.

PAGE 25

Paragraph 5.1.1.1.1 - Delete paragraph in its entirety and add the following:

"5.1.1.1.1 Type I, Style 1, 2 and 3. Insignia of one type, class size, and style shall be put up in bundles of ten pair and securely tied, or cross tied, with cotton twine or thread. Unless otherwise specified, insignia of one type, style, class and size may be placed in a clear polyethylene bag or blister pack. Closure shall be accomplished by heat sealing or taping."

PAGE 26

Paragraph 5.1.1.1.4 - Delete paragraph in its entirety and add the following:

"5.1.1.1.4 Type III and Type VI, Style 2. Except as specified herein, insignia of one type, class, style, size, and subclass only, shall be put-up in bundles of ten pair, securely tied or cross tied with cotton twine or thread. Type III, styles 1 and 3, class 1 and type VI style 2 insignia shall be put-up in matched pairs consisting of left and right-hand insignia. All other Type III insignia shall be packaged in matched pairs. Each matched pair shall be placed into a snug-fitting commercial grade, clear, polyethylene bag. Closure of each bag shall be by heat sealing or tape closure. Ten (10) pair of bagged insignia of one type, class, size, and style shall be put-up in bundles and securely tied or cross tied with cotton twine or thread."

PAGE 27

Paragraph 5.1.1.2.2 - Change paragraph title to read as follows:

"5.1.1.2.2 Type II and Type VIII insignia."

PAGE 28

Paragraph 5.4.1 - Delete paragraph in its entirety and add the following:

"5.4.1 Unit packaging. Unit packaging shall have the required information legibly printed or stamped in black on the bag across the center face, or on a

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T04:25Z
Check the source to verify that this is the current version before use.

white paper label inserted within the bag so as to permit ready identification. When unit packaging is secured by cotton twine or thread, the label shall be non-adhesive and secured under the tie. The bag or label shall indicate the following:

Stock Number
Nomenclature
Quantity (pairs)
Contractor
Contract Number"

Paragraph 5.3 - Delete paragraph in its entirety and add the following:

"5.3 Palletization. Unitized loads, commensurate with the level of packing specified in the contract or order, shall be palletized on a 4-way entry pallet in accordance with load Type 1A of MIL-STD-147. Each prepared load shall be bonded with primary and secondary straps in accordance with bonding means C, K and L or O or P. Pallet pattern shall be in accordance with the appendix of MIL-STD-147. The pallet shall be 4-way, Type I, Class 1, Style 1, Size A, Wood Group I, II, III or IV of MIL-P-15011, or, 4-way, Type IV, V or VIII, Class 1, Style A, Size 2, Wood Group I, II, III or IV, Grade A of NN-P-71. Interlocking of loads shall be effected by reversing the pattern of each course. If the container is of a size which does not conform to any of the patterns specified in MIL-STD-147, the pallet pattern used shall be approved by the contracting officer."

Paragraph 6.2.1, Sub-paragraph "g" - Delete sub-paragraph "g" in its entirety and add the following:

"g. Color of base cloth when not specified by classification (see 3.3.2.2, 3.3.2.3 and 3.3.2.4)."

Preparing activity:
Army - IH

(Project No. 8455-0748)

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T04:25Z
Check the source to verify that this is the current version before use.

NOTICE OF INACTIVATION FOR NEW DESIGN

NOT-MEASUREMENT SENSITIVE

MIL-I-14651
NOTICE 1
25 January 1999

MILITARY SPECIFICATION

INSIGNIA, EMBROIDERED, RANK, GRADE AND SERVICE STRIPES, GENERAL SPECIFICATION FOR

MIL-I-14651, including Interim Amendment 2, dated 3 December 1993, is inactive for new design and is no longer used, except for replacement purposes.

Custodians:
Army - IH

Preparing activity:
Army - IH

AMSC N/A **FSC 8455**

DISTRIBUTION STATEMENT A: Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T04:25Z
Check the source to verify that this is the current version before use.

NOTICE OF CANCELATION

NOT-MEASUREMENT SENSITIVE

MIL-I-14651
INTERIM AMENDMENT 2
NOTICE 2
6 May 1999

MILITARY SPECIFICATION

INSIGNIA, EMBROIDERED, RANK, GRADE AND SERVICE STRIPES, GENERAL SPECIFICATION FOR

MIL-I-14651 Interim Amendment 2, dated 25 January 1999, is hereby canceled without replacement.

Custodians:
Army - IH

Preparing activity:
Army - IH

AMSC N/A **FSC 8455**

DISTRIBUTION STATEMENT A: Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T04:25Z
Check the source to verify that this is the current version before use.