GGG-C-00116D(GSA-FSS)
March 16, 1971
SUPERSEDING
Int. Fed. Spec. GGG-C-00116C(NAVY-Ships)
October 15, 1964 and
INTERIM REVISION OF
Fed. Spec. GGG-C-116B
September 4, 1957

# INTERIM FEDERAL SPECIFICATION

# CASE, TWIST DRILL; AND

# STAND, TWIST DRILL

This Interim Federal Specification was developed by the Standardization Division, Federal Supply Service, General Services Administration, Washington, DC 20406, based upon currently available technical information. It is recommended that Federal agencies use it in procurement and forward recommendations for changes to the preparing activity at the address shown above.

## 1. SCOPE AND CLASSIFICATION

1.1 Scope. This specification covers cases and stands used for containing sets of twist drills in an orderly manner to facilitate use, and to prevent loss or damage.

1.1.1 Federal specification coverage. This specification covers only the types, classes, styles, and sizes of cases and stands generally purchased by the Federal Government, and does not include all types, classes, styles, and sizes which are commercially available.

1.2 Classification.

1.2.1 Types and sizes. Cases and stands for twist drill sets shall be of the following types and sizes as specified (see 6.2):

Type I. Cases.

Size A - For straight shank wire-gage drills 1 through 60 in accordance with GGG-D-751, type C.
Size B - For straight shank wire-gage drills 61 through 80 in accordance with GGG-D-751, type C.
Size D - For straight shank letter drills A through Z in accordance with GGG-D-751, type D.
Size E - For straight shank fractional drills 1/16 through 1/2 inch by 64ths in accordance with GGG-D-751, type B, class 1.
Size F - For tapered shank fractional drills 33/64 through 3/4 inch by 64ths in accordance with GGG-D-751, type E.
Size G - For tapered shank fractional drills 49/64 through 1 inch by 64ths in accordance with GGG-D-751, type E.

Type II. Stands.

Size A - For straight shank wire-gage drills 1 through 60 in accordance with GGG-D-751, type C.
Size B - For straight shank wire-gage drills 1 through 80 in accordance with GGG-D-751, type C.
Size C - For straight shank letter drills A through Z in accordance with GGG-D-751, type D.
Size D - For straight shank fractional drills 1/16 through 1/2 inch by 64ths in accordance with GGG-D-751, type B, class 1.

FSC 5140

Dates.

The body of the base and the striking end

Source: https://assist.dla.mil -- Downloaded: 202640-26T12:372
Check the source to verify that this is the currentversion before use.

## 2. APPLICABLE DOCUMENTS

2.1 The following documents of the issues in effect on the date of invitation for bids or request for proposal, form a part of this specification to the extent specified herein:

Federal Specifications:

GGG-D-751 - Drills, Twist (Taper-square, Straight and Taper-round Shanks).
PPP-P-40 - Packaging and Packing of Hand Tools.

(Activities outside the Federal Government may obtain copies of Federal Specifications, Standards, and Handbooks as outlined under General Information in the Index of Federal Specifications and Standards, and at the prices indicated in the Index. The Index, which includes cumulative monthly supplements as issued, is for sale on a subscription basis by the Superintendent of Documents, U.S. Government Printing Office, Washington, D. C., 20402.

(Single copies of this specification and other Federal specifications required by activities outside the Federal Government for bidding purposes are available without charge from Business Service Centers at the General Services Administration Regional Offices in Boston, New York, Washington, D.C., Atlanta, Chicago, Kansas City, Mo., Fort Worth, Denver, San Francisco, Los Angeles, and Seattle, Washington.

(Federal Government activities may obtain copies of Federal Specifications, Standards, and Handbooks and the Index of Federal Specifications and Standards from established distribution points in their agencies.)

Military Standard :

MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes.

(Copies of Military Specifications and Standards required by contractors in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

## 3. REQUIREMENTS

3.1 Design. Drill cases and stands furnished under this specification shall be designed to hold and store the quantity, size, and type of drills in the set to be contained, as specified (see 1.2.1 and 6.2). They shall be capable of withstanding frequent and rough usage without showing signs of damage affecting serviceability, or disassembly of the components.

The holes for containing each individual drill shall be in drill size sequence, clearly and permanently marked with the number, letter, or fractional size designation of the drill. The diameter of the holes shall be such as to permit easy removal of the drills, and the depth shall be adequate to hold the drills in an upright position.

3.2 Dimensions. Overall dimensions of drill cases and stands shall be at the manufacturer's option except that the size shall be the minimum necessary to serve the purpose intended.

3.3 Material. Unless otherwise specified (see 6.2), drill cases shall be made of sheet steel, and drill stands shall be made of die cast metal of any suitable alloy. Plastic, when used, shall be a polypropylene base composition. Wood shall be good-quality, knot-free, straight-grained hardwood.

3.4 Finish. Drill cases and stands shall be coated or treated to resist normal environmental corrosion in accordance with standard commercial practice.

3.5 Type I cases. Type I cases shall be furnished in size A, B, D, E, F, or G as identified in 1.2.1. They shall consist of an outer case, a hinged cover, and one or more hinged drill holders. Each drill holder shall have a minimum pivot action of 90 degrees to permit its use as a stand.



Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:37Z
Check the source to verify that this is the current version before use.

3.6 Type II stands. Type II stands shall be furnished in size A, B, C, or D as identified in 1.2.1. Unless otherwise specified (see 6.2), type II drill stands shall be furnished without covers. When covers are furnished, their periphery shall match the periphery of the stand and shall overlap the stand to form a friction fit. The base of the stand shall be of a size, shape, and weight which would prevent easy tip-over of the stand.

3.7 Tap-drill index. Type I, sizes A and E cases shall be furnished with the manufacturer's standard tap-drill index indicating the tap drill to be used for NC and NF threads through 1/2-inch thread sizes.

3.8 Identification marking. Each drill case shall be permanently marked on the outside cover with the manufacturer's identification and the range and graduations of the drills that are to be contained in the case.

3.9 Workmanship. The drill cases and stands shall be free from burrs and sharp edges or imperfections that may affect the appearance or serviceability of the finished product.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements, as specified herein. Except as otherwise specified, the supplier may utilize his own facilities or any commercial laboratory acceptable to the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure that supplies and services conform to prescribed requirements.

4.2 Sampling.

4.2.1 Lot. All drill cases and all drill stands of the same type, class, and size presented for acceptance at one time shall be considered a lot for the purpose of sampling.

4.2.2 Sampling for examination. A random sample of drill cases or drill stands shall be selected from each lot in accordance with MIL-STD-105, at inspection level II. The acceptable quality level (AQL) shall be 2.5 percent defective.

4.3 Quality conformance inspection. Each of the sample drill cases or drill stands selected in accordance with 4.2.2 shall be inspected to verify compliance with this specification. Quality conformance inspection shall consist of the following:

(a) Examination (see 4.3.1).

(b) Tests (see 4.3.2).

(c) Inspection of preservation, packaging, packing, and marking (see 4.3.3).

4.3.1 Examination. Each of the sample drill cases or drill stands selected in accordance with 4.2.2 shall be examined for materials, design, construction, size, and depth of drill-receiver holes, tap drill index, and workmanship to determine compliance with the requirements of this specification. Any drill case or drill stand in the sample containing one or more visual defects shall not be offered for delivery. If the number of defective drill stands or drill cases in any sample exceeds the acceptance number for the sample, this shall be cause for rejection of the lot represented.

4.3.2 Drop test. Two drill cases or stands shall be selected at random, and dropped three times from a height of three feet onto a concrete or tiled floor. An effort shall be made to cause the drill case or drill stand to hit the floor on different surfaces or corners on each drop. Any sign of fracture affecting serviceability, or disassembly of the components shall be cause for rejection of the lot represented.

4.3.3 Inspection of preparation for delivery requirements. An inspection shall be made to determine compliance with the packaging, packing, and marking requirements of section 5.



Source: https://assist.dla.mil -- Downloaded: 202610-26T12:37Z
Check the source to verify that this is the currentversion before use.

5. PREPARATION FOR DELIVERY

5.1 Preservation, packaging, packing, and marking. Preservation, packaging, packing, and marking shall be in accordance with PPP-P-40. The levels of preservation, packaging, and packing shall be as specified (see 6.2).

6. NOTES

6.1 Intended use. The drill cases and drill stands covered by this specification are intended for retaining and storing sets of twist drills in size number sequence and to preclude the drills from coming in contact with each other and causing damage to cutter edges.

6.2 Ordering data. Purchasers should select the preferred options permitted herein, and include the following information in procurement documents:

(a) Title, number, and date of this specification.

(b) Type, class, and size required (see 1.2.1 and 3.1).

(c) Material, when different (see 3.3).

(d) When drill stand covers are required (see 3.6).

(e) Level of preservation, packaging, and packing required (see 5.1).



GSA DC 71-1226

Source: https://assist.dla.mil -- Downloaded: 202610-26T12:37Z
Check the source to verify that this is the currentversion before use.

GENERAL SERVICES ADMINISTRATION - FEDERAL SUPPLY SERVICE

# SPECIFICATION COMMENT SHEET

BUDGET BUREAU NO. 29-R0175

## INSTRUCTIONS

This form provides a way for users of this specification to inform the originator of problems encountered in its use. It is not to be used to request changes to accommodate proprietary features. All comments will be considered and appreciated, but please do not expect a reply. To comment: detach, complete, and mail to: General Services Administration, FSS (FSEK), Wash., DC 20406.

NOTE: Comments on this form do not constitute or imply authorization to waive any part of the document or serve to amend contractual requirements.

1. SPECIFICATION GGG-C-00116D(GSA-FSS)
CASE, TWIST DRILL; AND STAND, TWIST DRILL

| 2. CONTRACT NO. *(If any)* | 3. QUANTITY ON CONTRACT *(Optional)* | 4. DOLLAR VALUE *(Optional)* |
|---|---|---|
| | | |

5. GENERAL NATURE OF PROBLEM *(e.g., inspection difficulties, manufacturers unable to meet tolerances, containers collapse under normal warehousing conditions, etc.)*

6. SPECIFIC REQUIREMENTS AFFECTED *(Include paragraph number and lines of wording)*

7. SPECIFIC PROBLEMS *(e.g. tests in 4.2.2 will not assure that the battery will last required time; temperature ranges in table 2 do not conform to commercially available items.)*

8. RECOMMENDATIONS

| 9. NAME OF MANUFACTURER, ASSOCIATION, GOVT., AGENCY, ETC. | 10. ADDRESS *(Number, Street, City, State and Zip Code)* |
|---|---|
| | |

| 11. NAME AND TITLE OF SUBMITTER | 12. DATE |
|---|---|
| | |

FORM GSA FEB 89 2200

Source: https://assist.dla.mil -- Downloaded: 202640-26T12:37Z
Check the source to verify that this is the current version before use.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:37Z
Check the source to verify that this is the current version before use.