GGG-C-120a
AMENDMENT—2
December 26, 1963

SUPERSEDING
Interim Amendment—1,
May 9, 1962

FEDERAL SPECIFICATION

CALKING GUN, BULK AND CARTRIDGE COMPOUNDS

This amendment, which forms a part of Federal Specification GGG-C-120a dated April 29, 1959, was approved by the Commissioner, Federal Supply Service, General Services Administration, for the use of all Federal agencies.

Page 1, paragraph 1.2.1, line 6: Delete "see 6.3" and substitute "see 3.7.3 and table Ia."

Pages 1 and 2, paragraph 2.1. Under *Military Specifications*: add "MIL-H-15424 —Hand Tools; Packaging of." Under *Military Standards*: add "MIL-STD-105—Sampling Procedures and Tables for Inspection by Attributes."

Page 3, table I, footnote: Delete "see 6.3" and substitute "see 3.7.3 and table Ia."

Page 4, paragraph 3.6.6, line 10: Delete "see 6.3" and substitute "(see 3.7.3 and table Ia)."

Page 4, paragraph 3.7, line 9: Delete "(see 6.3)" and substitute "(see 3.7.3 and table Ia)."

Page 4, following paragraph 3.7.2 insert new paragraph 3.7.3 as follows:

3.7.3 *Cartridges for type I, styles* 1 *and* 2 *guns.* Cartridges shall be filled with grade I plastic compound, as specified in, and procured under the requirements of Federal Specification TT-C-598. (Note: Basically the remainder of this paragraph is to establish dimensional requirements for the cartridges, or packages, which contain the calking compound so as to provide interchangeability in the type I guns in this specification.) Also note that in tables I and Ia the cubic contents of the cartridges and the cubic contents of bulk compound for the same size gun are not equivalent, the reason being that some of the bulk compound is displaced in the gun barrel by the cartridge shell and its end components. The shell of the cartridge shall be a cylinder approximately 0.050 inch thick. The cartridge shall be provided with either a plastic or metal inverted cup washer that serves as a plunger component in forcing the compound through the cartridge cylinder when the ratcheting mechanism of the gun is actuated. The opposite end of the cartridge shall be provided with a metal end cap having an opening for the discharge of the compound. The opening shall be provided with a spout or without a spout, as specified (see 6.2). When spouts are specified, each spout shall be made of plastic and the effective spout length shall be not less than 2 inches nor more than 3-1/2 inches. The cartridges for guns covered by this specification shall be in accordance with table Ia.

TABLE Ia.—*Cartridge sizes*

Outside diameter + 0 − 1/16	Length + 1/16 − 1/4	Cartridge capacity	
Inches	*Inches*	*Rated*	*Approximate cubic inch equivalent*
2	7	5/8 pint	18
2	8-1/2	1/10 gallon	23
2	10	1 pint	29

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:37Z
Check the source to verify that this is the current version before use.

Page 5, paragraphs 4.1 through 4.3 and tables II and III: Delete in their entirety and substitute the following:

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified, the supplier may utilize his own facilities or any commercial laboratory acceptable to the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure that supplies and services conform to prescribed requirements.

4.2 Sampling for inspection and acceptance. Sampling for inspection and acceptance shall be performed in accordance with the provisions set forth in MIL-STD-105, except where otherwise indicated herein.

4.2.1 *Inspection of materials and components.* In accordance with 4.1, the supplier is responsible for insuring that materials and components used were manufactured, tested, and inspected in accordance with the requirements of referenced subsidiary specifications and standards to the extent specified herein, or, if none, in accordance with this specification.

4.2.2 *Inspection of the end item.* Inspection of the calking guns shall be performed as specified in the following paragraphs. A lot shall consist of calking guns of the same type and style. The sample unit shall be one completely fabricated and assembled calking gun.

4.2.2.1 *Visual examination.* Each sample unit shall be visually examined for the defects set forth in table II. The inspection level shall be level S-4, with an acceptable quality level of 2.5 defects expressed in terms of defects per hundred units.

TABLE II.—*Classification of defects*

Examine	Defect	Major	Minor
Finish	Not plated or coated as specified	X	
	Chipping or peeling	X	
Design	Not similar to reference figure; not suitable for purpose intended	X	
	Plunger rods not as specified for style and type gun ...	X	
Construction and workmanship	Not free of burrs or sharp edges that can cause injury to operating personnel	X	
	Component missing, or improperly assembled	X	
	Rear cap not readily assembled or disassembled from barrel	X	
	Teeth of ratchet missing, broken, or damaged (when applicable)	X	
	Replaceable parts not interchangeable	X	
	Movable parts not freely adjustable or too tight	X	
	Trigger binds, does not operate freely	X	
Marking	Missing, incorrect, not legible		X

4.2.2.2 *Dimensional examination.* Each sample unit shall be examined for dimensions specified in applicable paragraphs and tables. Any nonconformance with requirements shall constitute a defect. The inspection level shall be level S-2, with an acceptable quality level of 4.0 expressed in terms of defects per hundred units.

4.2.2.3 *Testing.* Each sample unit shall be tested as specified in paragraphs 4.3.1 and 4.3.2. Any determination not within specified requirements shall constitute a defect. The inspection level shall be S-2, with an ac-

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:37Z
Check the source to verify that this is the current version before use.

ceptable quality level of 4.0 defects expressed in terms of defects per hundred units.

4.2.3 *Examination of preparation for delivery.* Examination to determine compliance with preparation for delivery shall be made in accordance with MIL-H-15424.

Page 5, paragraphs 4.4 and 4.4.1. Change paragraph numbers to "4.3" and "4.3.1", respectively.

Page 6, paragraph 4.4.2. Change paragraph number to "4.3.2".

Page 6, paragraph 4.5. Delete.

Page 7, paragraph 6.2, option "(g)". Delete and substitute the following:

(*g*) When cartridges are to be procured, state with or without spout (see 3.7.3). It should be noted that the calking compound is to be procured under TT-C-598.

Page 7, paragraph 6.3. Delete.

Page 7, table IV. Delete.

Page 8, paragraph 6.6. Delete and substitute the following:

6.6 Transportation description. Transportation descriptions and minimum weights applicable to this commodity are:

Rail:

Calking guns, hand, without kits or tanks.
Carload minimum weight 30,000 pounds, subject to Rule 34, Uniform Freight Classification.

Motor:

Calking guns, hand, without kits or tanks.
Truckload minimum weight 30,000 pounds, subject to Rule 115, National Motor Freight Classification.

MILITARY CUSTODIANS:

Army—GL

Navy—Sh

Air Force—MOAMA

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:37Z
Check the source to verify that this is the current version before use.