INTERIM AMENDMENT TO

FEDERAL SPECIFICATION

CALKING GUN, BULK AND CARTRIDGE COMPOUNDS

This Interim Amendment was developed by the Standardization Division, Federal Supply Service, General Services Administration, Washington, D. C. 20407, based upon currently technical available information. It is recommended that Federal agencies use it in procurement and forward recommendations for changes to the preparing activity at the address shown above.

NOTE: The details of Amendment-2 form a part of this amendment although not reproduced herein. The Specification and Amendment 2 are modified by this Interim Amendment as provided below. Otherwise Federal Specification GGG-C-120a and Amendment-2 remain in effect until publication of the fully coordinated Amendment-4.

Page 1, paragraph 1.2.1: Add the following in proper sequence:

"Type III - For cartridge compounds and with ratchet plunger rod".

Page 2, paragraph 3.2: Add to the last sentence, "except as noted (see 3.6, 3.6.1 and 3.6.2)".

Page 3: Add the following to table I:

TABLE I

Type	Style	Bulk capacity (minimum)	Cartridge sizes [1]		Capacity of gun (minimum)	Weight of gun (minimum)	
			Diameter	Length			
		Pints	Inches	Inches	Cu. In.	Pounds	Ounces
III		8/10	2	8-1/2	21	1	4

[1] For cartridge capacities see 6.3.

Page 3, paragraph 3.6: Delete "The gun shall consist" and substitute "The type I and II guns shall consist".

Add to paragraph 3.6 the following:

"The type III gun shall consist essentially of an open half barrel, fixed end caps, handle, plunger rod, and small components".

Page 3, paragraph 3.6.1: Delete "The barrel shall" and substitute "The barrel of the type I and II guns shall".

Add to paragraph 3.6.1 the following:

"The barrel of the type III gun shall be semi-circular in shape and of steel at least 0.026 inch thick".

Page 3, paragraph 3.6.2: Delete "The front cap shall be" and substitute "The front cap of the type I and II guns shall be".

Add to paragraph 3.6.2 the following:

"The front cap of the type III gun shall be of steel at least 0.045 inch thick, cup-shaped, and slotted to allow the insertion of the cartridge in the barrel".

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:37Z
Check the source to verify that this is the current version before use.

Page 3, paragraph 3.6.3: Delete "The rear cap and gun handle shall be" and substitute "The rear cap and gun handle of the type I and II guns shall be".

Add to paragraph 3.6.3 the following:

"The rear cap of the type III gun shall be of steel at least 0.045 inch thick, cup-shaped and and attached to the barrel. The rear cap shall be attached to the handle. The handle shall be of such size as to provide a firm grip for one-hand operation of the gun".

Page 4, paragraph 3.6.8: Delete "The calking guns shall" and substitute "The type I and II calking guns shall".

Page 4, add the following paragraph:

3.10 Type III.- Type III guns shall be of the half-barrel or drop in type for use of cartridge compounds. The barrel, caps and plunger components shall be of such design as to satisfactorily function with a spouted cartridge of 2 inch nominal diameter and 8-1/2 inch length. Discharge nozzles are not required.

GSA DC 64-13645

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:37Z
Check the source to verify that this is the current version before use.