GGG-S-64
Interim Amendment-3 (DOD)

31 December 1963

INTERIM AMENDMENT

TO

FEDERAL SPECIFICATION

SAW, CROSSCUT, HAND, ONE-MAN AND TWO-MAN

This Interim Amendment was developed by the U.S. Army Natick Laboratories (GL) based on currently available technical information. This Interim Amendment has been approved by the Department of Defense and is mandatory for use by the Departments of the Army, the Navy and Air Force. It is recommended that Federal Agencies use it in procurement. The General Services Administration has authorized the use of this Interim Amendment as a valid exception to Federal Specification GGG-S-64, dated March 26, 1954 and Amendment-2, dated August 20, 1959.

Page 1, Title - Delete "Saw, Crosscut, Hand, One-Man and Two-Man" and substitute "Saws, Crosscut, One-Man and Two-Man".

Page 1, paragraphs 2.1 through 2.3 - Delete and substitute the following:

"2.1 The following documents, of the issue in effect on date of invitation for bids or request for proposal, form a part of this specification to the extent specified herein:

FEDERAL STANDARDS

Fed. Std. No. 102 - Preservation, Packaging, and Packing Levels
Fed. Std. No. 123 - Marking for Domestic Shipment (Civilian Agencies)
Fed. Test Method Std. No. 151 - Metals; Test Methods

(Activities outside the Federal Government may obtain copies of Federal Specifications, Standards, and Handbooks as outlined under General Information in the Index of Federal Specifications Standards and Handbooks and at the prices indicated in the Index. The Index, which includes cumulative monthly supplements as issued, is for sale on a subscription basis by the Superintendent of Documents, U.S. Government Printing Office, Washington, D. C., 20402.

(Single copies of this specification and other product specifications required by activities outside the Federal Government for bidding purposes are available without charge at the General Services Administration Regional Offices in Boston, New York, Washington, D.C., Atlanta, Chicago, Kansas City, Mo., Dallas, Denver, San Francisco, and Auburn, Washington.

/FSC 5110/

Source: https://assist.dla.mil -- Downloaded: 202640-26T12:36Z
Check the source to verify that this is the current version before use.

(Federal Government activities may obtain copies of Federal Specifications, Standards, and Handbooks and the Index of Federal Specifications, Standards, and Handbooks from established distribution points in their agencies.)

MILITARY SPECIFICATION

MIL-H-15424 - Hand Tools, Packaging of.

MILITARY STANDARDS

MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes.

MIL-STD-129 - Marking for Shipment and Storage.

MIL-STD-130 - Identification Marking of U.S. Military Property.

(Copies of specifications and standards required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)"

Page 4, Table I, column 1, item 2 - Delete "4-1/2" and substitute "3-1/2".

Page 4, Table I, column 4, item 1 - Delete "6" and substitute "5-3/4".

Page 6, Table II, columns 2 and 7 - Delete and substitute the following:

Thickness of cutting edge Inch	At center Minimum Inches
0.072 to 0.083	5-3/4
.078 to .083	5-3/4
.078 to .083"	6

Page 6, Table III, column 2 - Delete and substitute the following:

Thickness of cutting edge Inch
0.072 to 0.083
.072 to .083
.078 to .083
0.083

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:36Z
Check the source to verify that this is the current version before use.

Pages 7 and 8, paragraphs 4.1 through 4.2.1 and tables VIII and IX.- Delete and substitute the following:

"4.1 Responsibility for inspection.- Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified, the supplier may utilize his own facilities or any commercial laboratory acceptable to the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

"4.2 Sampling for inspection and acceptance.- Sampling for inspection and acceptance shall be made in accordance with the provisions set forth in MIL-STD-105, except as otherwise indicated hereinafter.

"4.2.1 Inspection of materials and components.- In accordance with 4.1 above, the supplier is responsible for insuring that materials and components used were manufactured, tested and inspected in accordance with the requirements of referenced subsidiary specifications and standards to the extent specified herein, or, if none, in accordance with this specification.

"4.2.2 End item inspection.- The lot shall be all saws of each type, style and class submitted for acceptance at one time. The sample unit shall be one completely fabricated saw.

"4.2.2.1 Visual examination.- Examination of the sample unit shall be in accordance with the classification of defects set forth below. The inspection level shall be level II with acceptable quality levels (AQL's) of 2.5 major defects and 6.5 for total defects, expressed in terms of defects per hundred units.

Examine	Defect	Classification Major	Minor
Finish:			
Saw	Not polished.	X	
	Dull spots (not evenly polished).		X
Handles	Not stained and either waxed or lacquered.	X	
	Finish not transparent (conceals grain of wood).		X
	Not smooth.		X
	Stain not dry (transfers to hands).	X	

Source: https://assist.dla.mil -- Downloaded: 202610-26T12:36Z
Check the source to verify that this is the current version before use.

Examine	Defect	Classification Major	Minor
Handles (cont'd)	Area not finished.		X
	Scratch or mar affecting appearance.		X
	Dirt, grit or foreign matter imbedded in finish.		X
Design	Not specified type, class or style (handle or saw as applicable).	X	
	Blade contains cracks, segregations, inclusions or seams.	X	
	Handles not hardwood, not straight grained or contains a knot or knots.	X	
Workmanship and Construction (Handles)	Handle not attached as specified.		X
	Ferrules, clasps, washers, guards nuts or pin missing (as applicable).	X	
	Loop type, style a or b handle will not tighten (nut stripped), cross threaded or nut not properly imbedded in handle.	X	
	Loop of the style b handle does not extend the full length of the handle.	X	
	Loop does not properly engage the metal cap (see 3.9.1.1).		X
	Style c handle metal face plate or washer missing.	X	
	Pin loose or threads stripped or cross threaded (wing nut will not tighten).	X	

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:36Z
Check the source to verify that this is the current version before use.

Examine	Defect	Classification Major	Minor
Workmanship and Construction (Handles) (cont'd)	Style d handle, guard not reversible, not pin type, is not secure in both the vertical or horizontal position.	X	
	Handle cracked, split or chipped.	X	
	Handle not of such size as to be used while wearing heavy gloves when required (see 3.8).	X	
	Handle poorly shaped, rough surface, tool mark, small gouge or machine skip.		X
	Burr or sliver on handle.	X	
	Bird peck, hole, abrupt dip in grain.		X
	Decay.	X	
Workmanship and Construction: Saw	Tooth broken, not sharp, chipped, or cracked; hammer marks or high-spots.	X	
	Back not curved or straight back as specified.	X	
	Style A and B, cutting teeth improperly set or improperly filed or beveled.	X	
	Style A, B or C, raker teeth set or swaged.	X	
	Style A, B or C, raker prongs not filed as specified.	X	
	Style C, cutting teeth set or not filed as specified to a beveled point or angle (see 3.4.3).	X	
	Blade not straight and true (applicable to all blades).	X	

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:36Z
Check the source to verify that this is the current version before use.

Examine	Defect	Classification Major	Minor
Workmanship and Construction: Saw (cont'd)	Not taper ground from the cutting edge to the back of the blade except type II, (see 3.6).	X	
	Type II blades not taper ground on back edge of the saw from handle end to center of saw (see 3.6).	X	
	Type I saw not provided with a supplementary handle as specified.	X	
	Handles for or on the Type II saw or the supplementary handle for the Type I saw cannot be firmly attached or removed without the use of tools.	X	
	Back edge of saw contains burr or sharp edge.		X
Marking	Missing, incomplete, not legible and permanent.		X

"4.2.2.2 Dimensional examination.- Inspection of the sample unit shall be made for dimensional defects. Any dimension not within specified requirements shall be classified a defect. The inspection level shall be S-2 with an AQL of 4.0, expressed in terms of defects per hundred units.

"4.2.2.3 End product tests.- Each sample unit shall be subjected to all the tests specified under paragraph 4.3. Any evidence of noncompliance shall be classified a defect. The inspection level shall be level S-3 with an AQL of 2.5 defects per hundred units. Five hardness determinations shall be taken on each saw.

"4.2.3 Examination of preparation for delivery.- Examination shall be made to determine compliance with preservation packaging, packing and marking requirements in accordance with section 5 and Specification MIL-H-15424."

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:36Z
Check the source to verify that this is the current version before use.

Page 8.- Delete paragraphs 4.3 and 4.3.1 and substitute the following:

"4.3 Tests.-

"4.3.1 Hardness.- Tests shall be performed in accordance with Method 243.1 of Fed. Test Method Std. No. 151 for compliance with 3.3.

Page 9.- Delete paragraph 4.3.3 and 4.4.

Page 9.- Delete section 5 and substitute the following:

"5. PREPARATION FOR DELIVERY

Federal Standard No. 102 shall be referred to for definitions and application of the various levels of preservation, packaging, and packing for civil agency procurements.

"5.1 Levels A, B, and C.- Saws shall be preserved, packaged, and packed for each level of protection in accordance with the applicable requirements of Specification MIL-H-15424, except that only nailed wood boxes shall be used for exterior shipping containers (see 6.2).

"5.2 Marking.-

"5.2.1 Civil agencies.- In addition to any special marking required by the contract or order, interior packages and shipping containers shall be marked in accordance with Federal Standard No. 123.

"5.2.2 Military requirements.- In addition to any special marking required by the contract or order, interior packages and shipping containers shall be marked in accordance with Standard MIL-STD-129."

Page 9.- paragraph 6.2, subparagraph (f).- Delete and substitute:

"f. Selection of the applicable levels of preservation, packaging and packing (see 5.1)."

Page 10.- paragraph 6.5.- Change motor portion to read as follows:

"Truckload weight 30,000 pounds, subject to rule 115, National Motor Freight classification."

Page 10.- Delete section 7.

Page 10.- Delete the Military interest symbols and substitute:

Source: https://assist.dla.mil -- Downloaded: 202610-26T12:36Z
Check the source to verify that this is the currentversion before use.

GGG-S-64
Int Amend-3 (DOD)

MILITARY CUSTODIANS:

Army - GL
Navy - Ships
Air Force - MOA

Project No. 5110-0158

Interested activities:

Review

Navy - Ships
Air Force - MOA

User

Army - MD
Navy - Docks

Reviewer and User information is current as of the date of this document. For future coordination of changes to this document, draft circulation should be based on the information in the current Federal Supply Classification Listing of DOD Documents.

GSA DC-A911700130

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:36Z
Check the source to verify that this is the current version before use.