GGG–S–75
OCTOBER 3, 1955
SUPERSEDING
Int. Fed. Spec. GGG–S–0075 (GSA–FSS)
March 8, 1954, and
Fed. Spec. GGG–H–101
August 22, 1938

FEDERAL SPECIFICATION

SAW SET, HAND

This specification was approved by the Commissioner, Federal Supply Service, General Services Administration, for the use of all Federal agencies.

1. SCOPE AND CLASSIFICATION

1.1 Scope. — This specification covers saw sets used for setting teeth on hand, band, buck, panel, back, and pulpwood saws.

1.1.1 *Federal specification coverage.* — Federal specifications do not include all types, classes, and sizes of the commodities indicated by the titles of the specifications, or which are commercially available, but are intended to cover the types, etc., generally used by the Federal Government.

1.2 Classification.

1.2.1 *Type.*—Saw sets covered by this specification shall be of one type.

2. APPLICABLE SPECIFICATIONS, STANDARDS AND OTHER PUBLICATIONS

2.1 Specifications.—There are no other Federal specifications applicable to this specification except those referenced in section 7 as applicable to individual departments.

(Activities outside the Federal Government may obtain copies of Federal Specifications and Standards as outlined under General Information in the Index of Federal Specifications and Standards and at the prices indicated in the Index. The Index, which includes cumulative monthly supplements as issued, is for sale on a subscription basis by the Superintendent of Documents, U. S. Government Printing Office, Washington 25, D. C.

(Single copies of this specification and other product specifications required by activities outside the Federal Government for bidding purposes are available without charge at the General Services Administration Regional Offices in Boston, New York, Atlanta, Chicago, Kansas City, Mo., Dallas, Denver, San Francisco, Los Angeles, Seattle, and Washington, D. C.

(Federal Government activities may obtain copies of Federal Specifications and Standards and the Index of Federal Specifications and Standards from established distribution points in their agencies.)

2.2 Standards.—The following standard, of the issue in effect on date of invitation for bids, forms a part of this specification:

Military Standard:

MIL–STD–105—Sampling Procedures and Tables for Inspection by Attributes.

(Copies of Military specifications, standards, and drawings required by contractors in connection with specific procurement functions should be obtained from the procuring agency or as directed by the contracting officer.)

2.3 Other publications.—The following publication, of the issue in effect on date of invitation for bids, forms a part of this specification:

Governmental:

National Bureau of Standards Handbook:

H28—Screw-Thread Standards for Federal Services.

(Copies of the National Bureau of Standards Handbook H28 may be obtained upon application, accompanied by money order, coupon, or cash to the Superintendent of Documents, Government Printing Office, Washington 25, D. C. Price may be obtained from the Superintendent of Documents.)

2.4 Specifications, standards, and other publications applicable only to individual departments are listed in section 7.

362243—55—No. 69

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:36Z
Check the source to verify that this is the current version before use.

3. REQUIREMENTS

3.1 Illustrations. — The illustrations shown herein are for the convenience of identification, and are not intended to preclude the purchase of saw sets which are otherwise in accordance with the requirements of this specification.

3.2 Material.—The saw sets shall be of high-grade ferrous materials of such composition and quality as to produce tools conforming to the requirements hereinafter specified.

3.3 Design.—The saw sets shall be of either a straight lever grip or pistol grip so designed and constructed that by the movement of the operating lever(s) the saw teeth are set when the plunger is caused to move forward and impinge on an anvil located in the head of the tool. A spiral spring or other suitable means shall be provided for the return of the lever(s) to the open position.

3.4 Screw threads.—The screw threads used with saw sets shall be in conformance with the current issue of the National Bureau of Standards Handbook H28.

3.5 Marking for identification. — The saw sets shall be marked in a plain and permanent manner with the manufacturer's name or with a trade-mark of such known character that the source of manufacture may be readily determined.

3.6 Finish. — The saw sets shall have a smooth even surface thoroughly cleaned and substantially free from scale, pits, nodules, burrs, cracks, sharp edges or other detrimental defects. Surfaces not usually ground or buffed shall have a surface finish conforming to good manufacturing practice.

3.7 Component parts.—The saw sets shall be composed essentially of a body, lever handle, anvil, plunger, and gage screw, guide plate or guide plunger.

3.7.1 *Body.*—The body shall be of steel, gray or malleable iron. The handle portion of the body shall be smooth, knurled, or impressed and so shaped to afford a comfortable handgrip. The head of the body shall be constructed in such a manner that the saw teeth are in plain view to enable the operator to properly adjust the tool to the tooth being set.

3.7.2 *Lever handle.*—The lever handle shall be of steel or malleable iron smoothly finished to afford a comfortable handgrip in any position. The lever handle shall be hinged to the body in such a manner that positive pressure may be applied to the plunger.

3.7.3 *Anvil.*—The anvil shall be of tool steel properly hardened to a Rockwell hardness value of not less than 50 nor more than 60 on the C scale when tested as specified in 4.5.1. The anvil shall be graduated and numbered for setting saws with a pitch range of from 4 to 14 teeth per inch. The anvil shall be rigidly secured to the head of the body and be adjustable in order that the graduated numbers on the anvil may be indexed to correspond with the number of saw teeth per inch. The tooth contact surface of the angle or bevel shall be smoothly finished and so regulated as to prevent the saw tooth from being torn or distorted when set is made. A knurled thumb nut or other suitable means shall be provided for locking the anvil in any position of adjustment.

3.7.4 *Plunger.*—The plunger shall be of tool steel properly hardened to a Rockwell hardness value of not less than 54 nor more than 60 on the C scale when tested as specified in 4.5.1. The tooth contact surface at the end of the plunger shall be smoothly finished to assure a smooth even bend of the saw tooth after set is made. The end of the plunger, when in normal position, shall be approximately 1/8 inch from the anvil. The plunger shall be capable of setting the cutting edges of saw teeth having a thickness of 0.049 inch or less. The plunger and the mating face of the anvil shall be parallel at the point of contact in any adjustable position of the anvil.

3.7.5 *Gage screw, guide plate or guide plunger.*—The gage screw, guide plate or guide plunger shall be of steel. Means shall be provided for locking the screw or plate in position when adjusted to the thickness of the saw. When the guide plunger is used, it shall provide sufficient pressure to guide the saw with each set of the tooth.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:36Z
Check the source to verify that this is the current version before use.

3.8 Saw sets shall be similar to figure 1.



Straight lever grip. Pistol grip.

FIGURE 1.—Saw sets, hand.

3.9 **Workmanship.**—Workmanship shall be first class in every respect and free from any imperfections which may affect the appearance, durability, and serviceability of the saw sets.

4. SAMPLING, INSPECTION AND TEST PROCEDURES

4.1 **Inspection lot.**—All saw sets of the same design presented at one time shall be considered a lot for purposes of acceptance, inspection and tests.

4.2 **Sampling for inspection.**

4.2.1 *Sampling for visual and dimensional inspection.*—A random sample of saw sets shall be taken, as specified in table I, from each inspection lot of material offered for Government inspection of visual and dimensional characteristics with lot acceptance based on the following sampling inspection requirements in accordance with Military Standard MIL-STD-105.

4.2.2 *Sampling for lot acceptance tests.* — A random sample of saw sets shall be taken by or under the supervision of the Government inspector from each inspection lot in accordance with table II and shall be subjected to the hardness and performance tests specified in 4.5.1 and 4.5.2.

TABLE I.—*Sampling for visual and dimensional inspection A.Q.L. (approx.) = 1.5 percent defective*

Number of saw sets in the lot	Number of saw sets in the sample
40 and under	Inspection level III
41 to 300	Inspection level II
301 and over	Inspection level I

NOTE: The Government inspector may institute tightened or reduced inspection in accordance with section 9 of Military Standard MIL-STD-105.

TABLE II.—*Sampling for lot acceptance tests*

Number of saw sets in inspection lot	Number of saw sets in the sample	Acceptance number (defective)	Rejection number (defective)
15 and under	3	0	1
16 to 40	5	0	1
41 to 110	7	0	1
111 to 300	10	0	1
301 to 800	15	1	2
801 to 1300	20	1	2
1301 and over	30	2	3

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:36Z
Check the source to verify that this is the current version before use.

4.3 Inspection.

4.3.1 *Visual and dimensional inspection.* — Each of the sample saw sets taken in accordance with 4.2.1 shall be visually and dimensionally inspected by or under the supervision of the Government inspector to verify conformance with the requirements of this specification. Any saw set in the sample containing one or more visual or dimensional defects shall be rejected, and if the number of defective saw sets in any sample exceeds the acceptance number for that sample, the lot represented by the sample shall be rejected.

4.4 Lot acceptance tests.

4.4.1 *Testing of sample saw sets for lot acceptance.*—Each of the sample saw sets taken in accordance with table II shall be tested in accordance with 4.5.1 and 4.5.2 to verify compliance with the requirements of this specification. Any sample saw set which does not meet the requirements for any of these characteristics shall be rejected and if the number of nonconforming saw sets in any sample exceeds the acceptance number for that sample, the lot represented by the sample shall be rejected.

4.5 Test procedures.

4.5.1 *Hardness test.* — Each of the sample saw sets taken shall be tested to determine whether the anvil and plunger conform to the Rockwell hardness specified in 3.7.3 and 3.7.4. The hardness readings shall be taken at not less than six different points on both the anvil and plunger, using a normal Rockwell hardness testing machine and the Rockwell C scale. In order that the Rockwell reading may be accurately obtained, care shall be exercised in supporting the anvil and plunger so that no movement will occur and the surface under test will be aligned normal to the indentor.

4.5.2 *Performance test.* — Each of the saw sets taken shall be tested in the following manner: The saw sets shall be subjected to setting teeth on three separate saws having 4 to 6 points, 8 to 10 points, and 14 to 16 points per inch, respectively. The set of each of the points shall be uniform and the deflection or bend shall not extend more than one-half the depth of the tooth. Each individual saw set subjected to the test shall set at least ten teeth on each saw to determine compliance with the requirements of this specification. The saw sets and their component members shall show no mechanical defects or undue wear.

4.6 Rejected lots.—Rejected lots may be offered again for Government inspection provided the contractor has repaired or removed all nonconforming saw sets. The Government inspector shall again take and examine samples from such resubmitted lots to verify compliance with the requirements of this specification.

5. PREPARATION FOR DELIVERY

5.1 Preservation. — Cleaning and preservation shall be in accordance with the manufacturer's standard practice.

5.2 Packaging. — Commercial packages will be acceptable.

5.3 Packing. — The equipment shall be packed in substantial commercial containers of the type, size, and kind commonly used for the purpose in such manner as to insure acceptance and safe delivery to the carrier.

5.4 Marking.

5.4.1 *Interior containers.*—Packages and interior containers shall be marked with the name of the material and the name or trade-mark of the manufacturer, of such known character that the source of supply may be readily determined.

5.4.2 *Exterior containers.*—Shipping containers shall be marked with the name of the item, the type and class, and the quantity therein, as defined by the contract or order under which shipment is made, the name of the contractor, and the number of the contract or order.

6. NOTES

6.1 Ordering data.—Purchasers should exercise any desired options offered herein and

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:36Z
Check the source to verify that this is the current version before use.

procurement documents should specify the following (see 3.3 and section 7):

(a) Title, number, and date of this specification.

(b) Whether preparation for immediate use, domestic storage, or overseas shipment is required (see sections 5 and 7).

(c) Unit packages in intermediate containers, if other than specified (see 7.2.2.1.2.1).

6.2 Illustrations. — The illustrations shown herein are descriptive and not restrictive and are not intended to preclude the purchase of saw sets otherwise conforming to this specification.

6.3 Transportation description. — The applicable transportation description is as follows:

Tools, not otherwise indexed by name.
Carload minimum weight 30,000 pounds.

Mechanics' hand tools, not otherwise indexed.
Truckload minimum weight 30,000 pounds.

Minimum weights shown apply when material is transported at classification ratings. They will vary when material moves on commodity rates. When in doubt consult General Services Administration Regional Traffic Manager.

Patent notice.—When Government drawings, specifications or other data are used for any purpose other than in connection with a definitely related Government procurement operation, the United States Government thereby incurs no responsibility nor any obligation whatsoever; and the fact that the Government may have formulated, furnished, or in any way supplied the said drawings, specifications, or other data, is not to be regarded by implication or otherwise as in any manner *licensing* the holder or any other person or corporation, or conveying any rights or permission to manufacture, use, or sell any patented invention that may in any way be related thereto.

7. DEPARTMENTAL REQUIREMENTS

7.1 The following specifications, standards, and other publications, of the issues in effect on date of invitation for bids, form a part of this specification for purchases made under this specification by the respective departments.

7.2 Army, Navy, and Air Force.

7.2.1 *Applicable specifications, standards, and other publications:*

Federal Specifications:

NN-B-591 — Boxes, Fiberboard, Wood-Cleated.

NN-B-621—Boxes; Wood, Nailed and Lock-Corner.

NN-B-631—Boxes; Wood, Wirebound, (for Domestic Shipment).

UU-T-116—Tape, Paper, Gummed, Water-Resistant.

LLL-B-631—Boxes; Fiber, Corrugated (for Domestic Shipment).

LLL-B-636—Boxes, Fiber, Solid (for Domestic Shipment).

PPP-B-601 — Boxes, Wood, Cleated-Plywood.

Military Specifications:

JAN-B-121—Barrier-Materials, Greaseproof.

JAN-P-103—Packaging and Packing for Overseas Shipment — Boxes, Wood-Cleated; Solid Fiberboard.

JAN-P-106—Packaging and Packing for Overseas Shipment—Boxes, Wood, Nailed.

MIL-B-107—Boxes, Wood, Wirebound (Overseas Type).

JAN-P-108—Packaging and Packing for Overseas Shipment — Boxes; Fiberboard (V-Board and W-Board), Exterior and Interior.

MIL-P-116—Preservation, Methods of.

JAN-P-120—Packaging and Packing for Overseas Shipment — Cartons, Folding, Paperboard.

JAN-P-133—Packaging and Packing for Overseas Shipment—Boxes, Set-Up, Paperboard.

MIL-B-10377—Boxes, Wood, Cleated, Veneer, Paper Overlaid.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:36Z
Check the source to verify that this is the current version before use.

Military Standards:

MIL-STD-129—Marking of Shipments.

MIL-STD-130—Identification Marking of U. S. Military Property.

Other publication:

Nongovernmental:

Consolidated Classification Committee:

Consolidated Freight Classification Rules and Container Specification.

(Copies of specifications and standards required by contractors in connection with specific procurement functions should be obtained from the procuring agency or as directed by the contracting officer.

(Application for copies of the Consolidated Freight Classification Rules and Container Specification should be addressed to the Consolidated Classification Committee, 202 Chicago Union Station, Chicago 6, Illinois.)

7.2.2 *Preparation for delivery.*

7.2.2.1 *Preservation and packaging.*

7.2.2.1.1 *Domestic shipment—immediate use.*—Preservation and packaging of the commodity shall be in accordance with the manufacturer's commercial practice.

7.2.2.1.2 *Domestic shipment and storage or overseas shipment.*—Cleaning, preservation and packaging shall be in accordance with Military Specification MIL-P-116, as applicable. All surfaces to which a preservative is to be applied, shall be cleaned and dried using the most applicable of cleaning processes C-2 through C-13, and drying procedures D-1 through D-4. All bare, unpainted, metal surfaces on each saw set shall be coated with type P-2 or P-6 preservative; unit protected by method I and enclosed in a folding carton or set-up box conforming to Military Specifications JAN-P-120, JAN-P-133, and Federal Specifications LLL-B-631 or LLL-B-636, respectively. After the application of type P-2 or P-6 preservative, the saw set shall be wrapped with greaseproof barrier-material conforming to type II, grade A, class 1 of Military Specification JAN-B-121.

7.2.2.1.2.1 *Intermediate containers.*—Unless otherwise specified in the contract or order, 12 units, packaged in accordance with 7.2.2.1.2 shall be snugly packed into an intermediate container (see 6.1). Intermediate containers shall be fiberboard boxes conforming to Military Specification JAN-P-108, with compliance symbol as applicable. The boxes shall be closed and sealed in accordance with the appendix of the box specification, and in addition all joints and seams, including those occurring in the manufacture of the boxes, shall be covered with minimum 3-inch wide gummed tape, extended over all corners and edges at least 3 inches. Gummed tape shall conform to Federal Specification UU-T-116.

7.2.3 Packing.

7.2.3.1 *Domestic shipment—immediate use.*—The saw sets preserved and packaged as specified in 7.2.2.1.1 shall be packed in a manner to insure carrier acceptance and safe delivery at destination. Containers shall be in accordance with the Consolidated Freight Classification Rules or regulations of other carriers as applicable to the mode of transportation.

7.2.3.2 *For domestic shipment and storage.*—The saw sets preserved and packaged as specified in 7.2.2.1.2 and 7.2.2.1.2.1 shall be packed in wood-cleated fiberboard, wood-cleated plywood, nailed wood, wirebound, corrugated, or solid fiberboard boxes conforming to Federal Specifications NN-B-591, NN-B-621, NN-B-631, LLL-B-631, LLL-B-636, PPP-B-601 or Military Specification MIL-B-10377, respectively. The gross weight of wood boxes and wood-cleated fiberboard boxes shall not exceed approximately 200 pounds; of fiberboard boxes 90 pounds.

7.2.3.3 *For overseas shipment.*—Saw sets preserved and packaged as specified in 7.2.2.1.2 and 7.2.2.1.2.1 shall be packed in wood-cleated solid fiberboard, cleated plywood, nailed wood, or wirebound wood boxes conforming to Federal Specification PPP-B-601, or Military Specifications JAN-P-103, JAN-P-106, MIL-B-10377 and MIL-B-107. The gross weight of wood and wood type shipping containers shall not exceed 200 pounds; of fiberboard boxes 70 pounds.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:36Z
Check the source to verify that this is the current version before use.

7.2.4 *Marking.*

7.2.4.1 *Marking for shipment and storage.*—In addition to any special marking required by the contract or order, interior packages and exterior shipping containers shall be marked in accordance with Military Standard MIL–STD–129.

7.2.4.2 *Marking for identification.*—In addition to the marking specified in 3.5, saw sets shall be marked in accordance with Military Standard MIL–STD–130.

MILITARY INTEREST:
Army—C E O Q Sig T
Navy—Sh A MC Or Y
Air Force.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:36Z
Check the source to verify that this is the current version before use.