INTERIM AMENDMENT

TO

FEDERAL SPECIFICATION

CASSETTES, MAGNETIC TAPE, AUDIO RECORDING
(TWIN-HUB, COPLANAR)

This Interim Amendment was developed by the General Services Administration, Federal Supply Service, Office of Standards and Quality Control, Washington, D. C. 20406, based upon currently available technical information. It is recommended that Federal agencies use it in procurement and forward recommendations for changes to the preparing activity at the address shown above.

The General Services Administration has authorized the use of this Interim Amendment as a valid exception to Federal Specification W-C-1684, dated April 4, 1977.

Page 7

Table III: Delete in its entirety and substitute new table III as follows:

TABLE III. Magnetic tape performance requirements

Characteristic	Measurement			Units
	Oxide Characteristic AP			
	C-30, C-45 C-60	C-90	C-120	
Maximum recording level relative to reference recording level	+ 4 max. - 0 min.	+ 4 max. - 1 min.	+ 3 max. - 2 min.	Decibels
Output at maximum recording level relative to reference output level	+ 6 max. - 0 min.	+ 6 max. - 1 min.	+ 3 max. - 2 min.	Decibels
Harmonic distortion (max.) @ standard recording level	1	1	1	Percent
Sensitivity relative to reference output level	- 17 max. - 20 min.	- 17 max. - 21 min.	- 17 max. - 23 min.	Decibels
Frequency response: @ 6000 Hz @ 8000 Hz @ 10000 Hz	 + 3, - 2 + 3, - 3 + 4, - 3	 + 3, - 2 + 4, - 3 + 5, - 3	 + 5, - 1 + 6, - 1 No +, - 1 limit	 Decibels Decibels Decibels
Uniformity @ 333 Hz @ 8000 Hz	 20 30	 20 30	 20 30	 Percent Percent
Reference level to bias noise ratio (min.)	50	50	50	Decibels

Paragraph 3.13, line 3, following "specified herein": Delete "and shall conform to the mechanical requirement of 3.8.2,".

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:34Z
Check the source to verify that this is the current version before use.

Page 8

Table IV, under Examinations, measurements, and test, Group A: Delete "General dimensional measurements."

Page 9

Table IV, under Examinations, measurements, and test Group D: Delete "Detail dimensional measurements" and substitute "Cassette dimensional measurements".

Table IV, under Test Method Paragraph, Group D for Cassette dimensional measurements:

delete 4.6.5.2 and substitute 4.6.5.

Paragraph 4.4.1.1, line 4: Delete "10 percent" and substitute "6.5 percent".

Page 10

Paragraph 4.6.1, subparagraph (c): Delete last sentence.

Page 12

Paragraph 4.6.7.3, line 5: Delete "for both channel 1 and channel 2."

Page 14

Paragraph 4.6.9.2: Delete in its entirety and substitute new paragraph as follows:

"4.6.9.2 Operational life test. A 333 Hz signal shall be recorded onto the cassette tape to be tested at standard recording level (see 4.6.7.1.6) with operating bias current (see 4.6.7.1.3). The recorded signals shall be played back and the average output voltage measured and noted as the initial output level. The test cassette shall then be life tested by repetitive cycling until it has reached 28 cycles or fails, whichever comes first. One cycle shall consist of playing the cassette from end to end in one direction, and then fast rewinding from end to end in the other direction. The cassettes shall be turned over after every 7 cycles. Upon completion of the 28 cycles the previously recorded signal shall be played back and the average output voltage measured (in dB) and noted as the final output level. The initial output voltage level shall be compared with the final output voltage level for conformance to 3.13."

Page 15

Paragraph 4.6.13.1.2: Delete in its entirety and substitute new paragraph as follows:

"4.6.13.1.2 Preparation of samples. Samples shall be subjected to the preliminary conditioning specified in paragraph 4.6.2 before testing is begun."

Page 16

Paragraph 4.6.13.2.2: Delete first sentence in its entirety.

Page 18

Figure 1, after Operational Life Test: Delete "Frictional torque".

GSA-DC-76-2758

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:34Z
Check the source to verify that this is the current version before use.