FEDERAL SPECIFICATION SHEET

CONNECTOR, RECEPTACLE, ELECTRICAL, SPECIFIC PURPOSE, SINGLE, GENERAL GRADE, LOCKING, 3 POLE, 3 WIRE, 15 AMPERES, 125 VOLTS, 10 AMPERES, 250 VOLTS, 50/60 HERTZ

This cancellation is approved by the Assistant Administrator, Office of Federal Supply and Services, General Services Administration.

Federal Specification Sheet W-C-596/54B, dated September 4, 1981, is hereby canceled. For future requirements, use W-C-596/120, Connectors, Receptacle, Electrical, Special Purpose, Single, Grounding, 3 Pole, 4 Wire, 20 Amperes, 125/250 Volts, 50/60 Hertz, dated August 11, 1978.

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assistdla.mil -- Downloaded: 2026-10-26T11:20Z
Check the source to verify that this is the current version before use.

W-C-596/56B
CANCELLATION
May 14, 1985

FEDERAL SPECIFICATION SHEET

CONNECTOR, RECEPTACLE, ELECTRICAL, SPECIFIC PURPOSE,
SINGLE, GENERAL GRADE, LOCKING, 4 POLE, 4 WIRE, 20 AMPERES,
3 PHASE WYE, 120/208 VOLTS, 50/60 HERTZ

This cancellation is approved by the Assistant Administrator, Office of Federal Supply and Services, General Services Administration.

Federal Specification Sheet W-C-596/56B, dated September 4, 1981, is hereby canceled. For future requirements, use W-C-596/136, Connectors, Receptacle, Electrical, Special Purpose, Single, Grounding, 4 Pole, 5 Wire, 20 Amperes, 120/208 Volts, 50/60 Hertz, 3-Phase, Y, dated August 11, 1978.

FSC 5935

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil - Downloaded: 2025-10-26T11:29Z
Check the source to verify that this is the current version before use.

FEDERAL SPECIFICATION SHEET

CONNECTOR, RECEPTACLE, ELECTRICAL, GENERAL PURPOSE, SINGLE, GENERAL GRADE, GROUNDING, 3 POLE, 4 WIRE, 50 AMPERES, 125/250 VOLTS, 50/60 HERTZ

This cancellation is approved by the Assistant Administrator, Office of Federal Supply and Services, General Services Administration.

Federal Specification Sheet W-C-596/62B, dated September 4, 1981, is hereby canceled. For future requirements, use MIL-C-22992E, Connectors, Plugs and Receptacles, Electrical, Waterproof, Quick Disconnect, Heavy Duty Type General Specification For, dated August 28, 1974.

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.
Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:29Z
Check the source to verify that this is the current version before use.

FEDERAL SPECIFICATION SHEET

CONNECTOR, PLUG, ELECTRICAL, GENERAL PURPOSE, GENERAL GRADE, GROUNDING, 3 POLE, 4 WIRE, 60 AMPERES, 125/250 VOLTS, 50/60 HERTZ

This cancellation is approved by the Assistant Administrator, Office of Federal Supply and Services, General Services Administration.

Federal Specification Sheet W-C-596/63B, dated September 4, 1981, is hereby canceled. For future requirements, use MIL-C-22992E, Connectors, Plugs and Receptacles, Electrical, Waterproof, Quick Disconnect, Heavy Duty Type General Specification For, dated August 28, 1974.

FSC 5935

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.
Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:29Z
Check the source to verify that this is the current version before use.

NOTICE: When Government drawings, specifications, or other data are used for any purpose other than in connection with a definitely related Government procurement operation, the U. S. Government thereby incurs no responsibility, nor any obligation whatsoever; and the fact that the Government may have formulated, furnished, or in any way supplied the said drawings, specifications, or other data is not to be regarded by implication or otherwise as in any manner licensing the holder or any other person or corporation, or conveying any rights or permission to manufacture, use, or sell any patented invention that may be in any way related thereto. Referenced documents shall be the issue in effect on date of invitation for bids.

MIL-STD-717 (NORD)

16 June 1959
Superseding NAVORD OS 8727
dated 15 May 1958

MILITARY STANDARD

FORMULA FOR BINDER SOLUTION II

Ingredient	Binder, Cellulose Nitrate Camphor	Acetone
Specification	MIL-B-10854, Any Form	JAN-A-489
Percent by Weight	8.0 ± 0.1	92.0 ± 0.1

REQUIREMENT:

The binder ingredient shall be completely dissolved prior to use of the binder solution.

CAUTION: Due to its high volatility and ease of ignition, extreme caution should be exercised in handling acetone. See section 6.7 of MIL-P-21355 (NOrd) for general safety precautions.

Copies of *specifications, standards, drawings and publications* required by contractors in connection with specific procurement functions should be obtained from the procuring agency or as directed by the contracting officer.

☆U.S. GOVERNMENT PRINTING OFFICE: 1976-603-766/5723

FSC 1375

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:29Z
Check the source to verify that this is the current version before use.

DD-T-741
CANCELLATION
October 20, 1977

FEDERAL SPECIFICATION

TUBING, GLASS
(LABORATORY USE)

This cancellation was approved by the Commissioner, Federal Supply Service, General Services Administration, Washington D.C. 20406.

Federal Specification DD-T-741, dated April 29, 1954, is hereby canceled due to insufficient procurement requirements.

U.S. GOVERNMENT PRINTING OFFICE: 1978 - 261-427/2217

FSC 6640

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:29Z
Check the source to verify that this is the current version before use.

MIL-STD-734(OS)
NOTICE 1
20 July 1977

MILITARY STANDARD

FORMULA FOR PRIME COMPOSITION III

MIL-STD-734 (WEP), dated 31 May 1960, is hereby cancelled. There is no superseding document.

Preparing Activity
NAVY - OS

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use concerning this document should be addressed to: Commanding Officer, Naval Ordnance Station (611), Indian Head, MD 20640, by letter.

FSC 1370

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:29Z
Check the source to verify that this is the current version before use.