INCH-POUND
MIL-PRF-39035D
AMENDMENT 2
13 June 2002
SUPERSEDING
AMENDMENT 1
1 September 1998

PERFORMANCE SPECIFICATION

RESISTORS, VARIABLE, NONWIRE WOUND (ADJUSTMENT TYPE),
NONESTABLISHED RELIABLILTY, AND ESTABLISHED RELIABILITY,
GENERAL SPECIFICATION FOR

This amendment forms a part of MIL-PRF-39035D, dated 12 February 1998, and is approved for use by all Departments and Agencies of the Department of Defense.

PAGE 1

* Delete and substitute:

" Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be used in improving this document should be addressed to: Defense Supply Center, Columbus, ATTN: DSCC-VAT, Post Office Box 3990, Columbus OH 43216-5000, by using the Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter. "

PAGE 3

* 1.2.1.4, table III, delete symbol "D" and footnote "4".

PAGE 4

* 2.2.1, Specification, delete:

"MIL-R-39005/5 - Resistors, Variable, Nonwire Wound (Adjustment Type, Lead Screw Actuated), Established Reliability, Style RJR28. INACTIVE FOR NEW DESIGN."

* 2.2.1, Standard, delete title "Electronic and Electrical Component Parts, Test Methods for" and substitute:

"Test Method Standard Electronic and Electrical Component Parts".

* 2.2.1, delete and substitute first parenthetical note:

"(Unless otherwise indicated, copies of the above specifications, standards, and handbooks are available from the Document Automation and Production Service, Building 4D (DPM-DODSSP), 700 Robbins Avenue, Philadelphia, PA 19111-5094)."

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T18:56Z
Check the source to verify that this is the current version before use.

PAGE 5

* 3.5.3, delete and substitute:

"3.5.3 Terminals. Terminals shall be as specified in table III. All terminals shall be fastened securely. Terminals shall be protected by a corrosion resistant metallic coating, and all terminals or exposed portions of insulated wire shall be treated to facilitate soldering."

PAGE 9

* 3.10, paragraph title change, delete and substitute:

Delete "Integrity of shaft (not applicable to style RJR32 and RJR50)" and substitute "Integrity of shaft (not applicable to style RJR50)".

PAGE 10

* 3.24, paragraph title change, delete and substitute:

Delete "Salt spray (corrosion)" and substitute "Salt atmosphere (corrosion)."

PAGE 14

* Table VII, Group IV Inspection column, title change, delete and substitute:

Delete "Salt spray (corrosion)" and substitute "Salt atmosphere (corrosion)."

PAGE 21

* 4.8.4, paragraph title change, delete and substitute:

Delete "Integrity of shaft (not applicable to style RJR32 and RJR50)" and substitute "Integrity of shaft (not applicable to style RJR50)".

PAGE 26

* Table XIII footnote 2, delete and substitute:

"2/ Not applicable in conformance inspection."

PAGE 27

* 4.8.19, paragraph title change, delete and substitute:

Delete "Salt spray (corrosion) (see 3.24)" and substitute "Salt atmosphere (corrosion) (see 3.24)."

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T18:56Z
Check the source to verify that this is the current version before use.

PAGE 30

* 4.8.25a, last sentence, delete and substitute:

"There shall be no circulation of air over the resistors other than that caused by the heat of the resistors."

PAGE 34

* 5.2, delete parenthetical note.

Custodians:
Army - CR
Navy - EC
Air Force - 11

Review activities:
Army - AR, AT, AV, CR4, MI
Navy - AS, MC, OS
Air Force - 19, 99

Preparing activity:
DLA - CC

(Project 5905-1673)

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T18:56Z
Check the source to verify that this is the current version before use.