MILITARY SPECIFICATION

RESISTORS, VARIABLE, NONWIRE-WOUND
(ADJUSTMENT TYPE, LEAD-SCREW ACTUATED),
ESTABLISHED RELIABILITY
STYLE RJR24

This amendment forms a part of MIL-R-39035/2E, dated 5 March 1987, and is approved for use by all Departments and Agencies of the Department of Defense.

PAGE 3

FIGURE 1, terminal type "W" and "X", delete in its entirety.

PAGE 4

FIGURE 1, delete terminal types "A" and "B" and substitute terminal types "W" and "X" respectively.

PAGE 6

TABLE I, delete and substitute:

"TABLE I. Nominal resistance values and maximum rated ac or dc working voltage.

Nominal resistance value	Maximum rated ac or dc working voltage per characteristics
	C, F, and H
Ohms	
10	2.23
20	3.1
50	5.0
100	7.0
200	10.0
500	15.8
1,000	22.3
2,000	31.6
5,000	50.0
10,000	70.7
20,000	100
25,000	111
50,000	158
Megohms	
0.10	223
0.20	300
0.25	300
0.50	300
1.00	300

"

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T18:57Z
Check the source to verify that this is the current version before use.

CONCLUDING MATERIAL

Custodians:
Army - ER
Navy - EC
Air Force - 85

Review activities:
Army - AR, MI
Navy - AS, OS
Air Force - 17, 99

User activities:
Army - AT, AV, ME
Navy - MC
Air Force - 19

Preparing activity:
Air Force - 85

Agent:
DLA - ES

(Project 5905-1133-2)

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T18:57Z
Check the source to verify that this is the current version before use.