INCH-POUND
MIL-PRF-39035/2F
AMENDMENT 1
31 October 1995

PERFORMANCE SPECIFICATION

RESISTORS, VARIABLE, NONWIRE-WOUND
(ADJUSTMENT TYPE, LEAD-SCREW ACTUATED)
ESTABLISHED RELIABILITY
STYLE RJR24

This amendment forms a part of MIL-PRF-39035/2F, dated 31 January 1994, and is approved for use by all Departments and Agencies of the Department of Defense.

PAGE 3 and 4

FIGURE 1, terminal types P, W, and X, side view, delete ".170 ±.025" and substitute ".017 ±.030" (three places).

PAGE 5

FIGURE 1, NOTES, add:

"8. Design of standoff is optional."

FIGURE 1, figure title, delete "RJR12" and substitute "RJR24".

CONCLUDING MATERIAL

Custodians:
Army - ER
Navy - EC
Air Force - 85

Review activities:
Army - AR, AT, AV, ME, MI
Navy - AS, MC, OS
Air Force - 17, 19, 99

Preparing activity:
DLA -ES

(Project 5905-1443)

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T18:57Z
Check the source to verify that this is the current version before use.