INCH-POUND

MIL-PRF-39035/2F
AMENDMENT 3
22 July 1997
SUPERSEDING
AMENDMENT 2
30 December 1995

PERFORMANCE SPECIFICATION

RESISTORS, VARIABLE, NONWIRE-WOUND
(ADJUSTMENT TYPE, LEAD-SCREW ACTUATED),
ESTABLISHED RELIABILITY
STYLE RJR24

This amendment forms a part of MIL-PRF-39035/2F, dated 31 January 1994, and is approved for use by all Departments and Agencies of the Department of Defense.

PAGE 3 and PAGE 4

FIGURE 1, terminal types P, W, and X, side view, delete ".017 ±.030" and substitute ".170 ±.030" (three places).

* FIGURE 1, terminal types P, W, and X, side view, add "SEE NOTE 9" to the .300 min dimension (three places).

PAGE 5

* FIGURE 1, notes, add:

"8. Design of standoff is optional.
"9. For terminal types P, W, and X, shorter lead lengths (.172 minimum) are available, and can be ordered though acquisition requirements. (see 6.2c)."

FIGURE 1, title, delete "RJR12" and substitute "RJR24".

* 6.2, acquisition requirements, add:

"c. Terminal lead lengths requirements (shorter lead lengths can be specified in the purchase order)."

The margins of this amendment are marked with an asterisk to indicate where changes (additions, modifications, corrections, deletions) from the previous amendment were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous amendment.

Custodians:
Army - CR
Navy - EC
Air Force - 85

Preparing activity:
DLA - CC

(Project 5905-1491)

Review activities:
Army - AR, AT, AV, CR4, MI
Navy - AS, MC, OS
Air Force - 17, 19, 99

DISTRIBUTION STATEMENT A Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T18:57Z
Check the source to verify that this is the current version before use.