INCH-POUND
MIL-PRF-39035/3E
w/AMENDMENT 1
20 October 2004
SUPERSEDING
MIL-PRF-39035/3E
6 June 2003

PERFORMANCE SPECIFICATION


RESISTORS, VARIABLE, NONWIRE-WOUND (ADJUSTMENT TYPE, LEAD-SCREW ACTUATED), NONESTABLISHED RELIABILITY, AND ESTABLISHED RELIABILITY STYLE RJR26

This specification is approved for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification covers the requirements for style RJR26, nonestablished reliability and established reliability, adjustment type, lead-screw actuated, nonwire-wound, variable resistors. This style is available in characteristic F and H.

1.2 Part or Identifying Number (PIN). Resistors covered by this specification must be identified by a PIN which must consist of a basis style of this specification and a coded number. The PIN must be in the following form:



2. APPLICABLE DOCUMENTS

2.1 General. The documents listed in this section are specified in sections 3 and 4 of this specification. This section does not include documents cited in other sections of this specification or recommended for additional information or as examples. While every effort has been made to ensure the completeness of this list, document users are cautioned that they must meet all specified requirements documents cited in sections 3 and 4 of this specification, whether or not they are listed.

Comments, suggestions, or questions on this document should be addressed to: Defense Supply Center, Columbus, ATTN: DSCC-VAT, Post Office Box 3990, Columbus, Ohio 43216-5000 or by email Resistor@dla.mil. Since contact information can change, you may want to verify the currency of this address information using the ASSIST Online database at http://assist.daps.dla.mil .

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T18:58Z
Check the source to verify that this is the current version before use.

2.2 Government documents.

2.2.1 Specifications, standards, and handbooks. The following specifications, standards, and handbooks form a part of this document to the extent specified herein. Unless otherwise specified, the issues of these documents are those cited in the solicitation or contract (see 6.2).

DEPARTMENT OF DEFENSE SPECIFICATION

MIL-PRF-39035 - Resistors, Variable, Nonwire-wound (Adjustment Type), Nonestablished Reliability, and Established Reliability, General Specification for.

(Copies of these documents are available online at http://assist.daps.dla.mil/quicksearch/ or http://assist.daps.dla.mil or from the Standardization Document Order Desk, 700 Robbins Avenue, Building 4D, Philadelphia, PA 19111-5094).

2.3 Order of precedence. In the event of a conflict between the text of this document and the references cited herein (except for related specification sheets), the text of this document takes precedence. Nothing in this document, however, supersedes applicable laws and regulations unless a specific exemption has been obtained.

3. REQUIREMENTS

3.1 General. The requirements for acquiring the product described herein shall consist of this document and MIL-PRF-39035.

3.2 Interface and physical dimension requirements. Resistors shall meet the interface and physical dimensions specified on figure 1.

3.3 Power rating. The power rating shall be 1/4 watt for characteristics F and H.

3.4 Terminals. Characteristics F and H are available in A-, B-, C-, P-, W-, and X- type terminals.

3.5 Nominal resistance value and maximum rated ac or dc working voltage. Nominal resistance values and maximum rated ac or dc working voltages shall be as specified in table I.

3.6 Actual effective electrical travel. Actual effective electrical travel shall be 10 turns minimum, and 25 turns maximum.

3.7 Operating torque. Operating torque shall be a maximum of 3 ounces-inches.

3.8 Maximum voltage. Maximum rated ac or dc working voltage shall be 200 volts.

4. VERIFICATION

4.1 Sampling and inspection. Sampling and inspection shall be in accordance with MIL-PRF-39035, and as specified herein.

4.2 Dielectric withstanding voltage. In the dielectric withstanding voltage test, the applied potential shall be 600 volts rms at atmospheric pressure, and 250 volts rms at reduced barometric pressure.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T18:58Z
Check the source to verify that this is the current version before use.


TABLE I. Nominal resistance value and maximum rated ac or dc working voltage.

Nominal resistance value	Maximum rated ac or dc working voltage per characteristics
	F and H
Ohms	
10	1.58
20	2.23
50	3.54
100	5.0
200	7.07
500	11.1
1,000	15.8
2,000	22.3
5,000	35.4
10,000	50.0
20,000	70.7
25,000	79.0
50,000	111.0
Megohms	
0.10	158
0.20	200
0.25	200
0.50	200
1.00	200


5. PACKAGING

5.1 Packaging. For acquisition purpose, the packaging requirements shall be as specified in the contract or order (see 6.2). When packaging of materiel is to be performed by DoD or in-house contractor personnel, these personnel need to contact the responsible packaging activity to ascertain packaging requirements. Packaging requirements are maintained by the Inventory Control Point's packaging activities within the Military Service or Defense Agency, or within the military services system commands. Packaging data retrieval is available from the managing Military Department's or Defense Agency's automated packaging files, CD-ROM products, or by contacting the responsible packaging activity.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T18:58Z
Check the source to verify that this is the current version before use.




TERMINAL TYPE A




TERMINAL TYPE B

FIGURE 1. Style RJR26 resistors.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T18:58Z
Check the source to verify that this is the current version before use.




TERMINAL TYPE C




TERMINAL TYPE P

FIGURE 1. Style RJR26 resistors - Continued.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T18:58Z
Check the source to verify that this is the current version before use.




TERMINAL TYPE P



TERMINAL TYPE W

FIGURE 1. Style RJR26 resistors - Continued.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T18:58Z
Check the source to verify that this is the current version before use.



SCHEMATIC DIAGRAM

Inches	mm	Inches	mm	Inches	mm	Inches	mm	Inches	mm
0.002	0.051	0.018	0.46	0.040	1.02	0.115	2.92	0.175	4.44
0.010	0.250	0.020	0.51	0.050	1.27	0.125	3.18	0.195	4.95
0.015	0.381	0.025	0.64	0.075	1.90	0.165	4.19	0.250	6.35
0.017	0.432	0.030	0.76	0.100	2.54	0.172	4.37	0.270	6.86

NOTES:
1. Dimensions are in inches.
2. Unless otherwise specified, tolerance is 0.005 (0.13 mm).
3. Metric equivalents are given for general information only.
4. The entire slot of the actuating screw must be above the surface of the unit.
5. The head of the lead screw actuator shall not extend beyond any edge of the surface upon which it is mounted.
6. Mounting means are by use of pins only.
7. Standoff shape and location is optional.

FIGURE 2. Style RJR26 resistors - Continued.

6. NOTES

(This section contains information of a general or explanatory nature that may be helpful, but not mandatory.)

6.1 Intended use. The notes specified in MIL-PRF-39035 are applicable to this specification.

6.2 Acquisition documents. Acquisition documents must specify the following:

a. Title, number, and date of this specification.

b. Issue of DoDISS to be cited in the solicitation, and if required, the specific issue of individual documents referenced (see 2.2.1).

c. Packaging requirements (see 5.1)

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T18:58Z
Check the source to verify that this is the current version before use.

6.3 Weight. The weight is .021 ounces (0.6 grams).

6.4 MIL-R-22097 substitution data. Resistors of this specification regardless of their failure rate designation are substitutes for resistors of the same resistance value, tolerance, terminal characteristic and resistance temperature characteristics specified in the inactivated specifications MIL-PRF-22097/5.

6.5 Amendment notations. The margins of this specification are marked with vertical lines to indicate where modifications from this amendment were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations.

Custodians:
Army - CR
Navy - EC
Air Force - 11
DLA - CC

Preparing activity:
DLA - CC

Review activities:
Army - AR, AT, AV, CR4, MI
Navy - AS, CG, MC, OS
Air Force - 19, 99

(Project 5905-2008)

NOTE: the activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at http://assist.daps.dla.mil.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T18:58Z
Check the source to verify that this is the current version before use.