FED. SUP CLASS
4730



PLUG, "O" RING BOSS

DASH NO.	NOMENCLATURE	M F-18866	TUBE O.D.
A4	BOSS PLUG		1/4
A5	BOSS PLUG		5/16
A6	BOSS PLUG		3/8
A8	BOSS PLUG		1/2
A10	BOSS PLUG		5/8
A12	BOSS PLUG		3/4

BORE DIA	.4)
	.003
	±.003
	±.004
	.391 ±.004
	.484±.004
	.609 ±.005

,J,K,L,M,N AND P

CANCELLED AFTER 7 MAY 1975
USE MIL-F-18866, SUPPLEMENT 1

NOTES:

1. ALL DIMENSIONS.
2. MATERIAL CADMIUM PLATED CARBON STEEL.
3. FITTINGS SHALL 7 & 8 AND TYPE IV, STYLES 8 & 10 OF MIL-F-18866 LOCKNUT AND CLINCHED WASHER IN ASSEMBLED FORM.
4. BOSS APPLICABLE TO ALL FITTINGS EXCEPT A,Q,R,S,T,U,V AND W.
5. THE R CONSISTS OF THE MS SHEET NUMBER PLUS THE DASH NUMBER. EXAMPLE -A4; A INDICATES "O"-RING BOSS PLUG AND 4 INDICATES TUBE SIZE IN 1/ INCREMENTS.
6. REFERENCED DOCUMENTS SHALL BE OF THE ISSUE IN EFFECT ON DATE OF INVITATIONS FOR BID.
7. FOR DESIGN FEATURE PURPOSES THIS STANDARD TAKES PRECEDENCE OVER PROCUREMENT DOCUMENTS REFERENCED HEREIN.
8. TUBE REDUCERS AND ADAPTERS SHALL CONFORM TO MS39323, MS39322, AND MS39324.

APPROVED 4 May 1967 REVISED (A) 7 MAY 1975

Review activity: WC
User activity: AT

This military standard is approved by the Mobility Equipment Command, Department of the Army and is mandatory for use by that activity. All other military activities are required to employ this standard where suitable.

P.A. ME Other Cust	TITLE FITTINGS: FLARED TUBE, 37-DEGREE, STEEL	MILITARY STANDARD MS39321 (ME)
PROCUREMENT SPECIFICATION MIL-F-18866	SUPERSEDES:	SHEET 1 OF 4

DD FORM 1 SEP 67 672-1 (Limited reproduction of this form is permitted. Previous editions of this form are obsolete.)

Source: https://assist.dla.mil - Downloaded: 2026-10-23T17:51Z
Check the source to verify that this is the current version before use.