MILITARY SPECIFICATION

CUTTER, CABLE, AERIAL TOW TARGET, MK VII

This specification has been approved by the Department of the Air Force and by the Navy Bureau of Aeronautics.

1. SCOPE

1.1 This specification covers one type of aerial tow target cable cutter, designated as the Cable Cutter MK VII, to be used for cutting snarled or tangled tow cable during attended towing operations from military aircraft.

2. APPLICABLE SPECIFICATIONS, STANDARDS, DRAWINGS, AND PUBLICATIONS

2.1 The following specifications, standards, and publication, of the issue in effect on date of invitation for bids, form a part of this specification:

SPECIFICATIONS

Federal

QQ-M-151	Metals; General Specification for Inspection of

Military

MIL-C-1511	Cable; Steel (Carbon) Flexible, Preformed
MIL-C-5765	Cable, Tow Target, Armored Steel
MIL-M-7911	Marking, Identification of Aeronautical Equipment, Assemblies, and Parts
MIL-P-116	Preservation, Method of
MIL-P-6064	Packaging of Lightweight Aircraft Accessories

STANDARDS

MIL-STD-129	Marking of Shipments
MS26506	Cutter - Cable, Aerial Tow Target, MK VII

PUBLICATIONS

Air Force-Navy Aeronautical Bulletin

No. 143	Specifications and Standards; Use of

(Copies of specifications, standards, and drawings required by contractors in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

3. REQUIREMENTS

3.1 Materials.- Materials shall conform to Specification QQ-M-151 and as listed on the applicable standard. Materials which are not covered by applicable specifications, or which are not specifically described herein, shall be of the best quality and suitable for the purpose intended.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T10:42Z
Check the source to verify that this is the current version before use.

3.1.1 Critical materials.- If the materials specified in this specification, applicable specifications, or standards for the production of the subject item are critical materials, as defined by the National Production Authority, the contractor shall list such materials and notify the procuring activity of its availability to the contractor. In case that materials are difficult to procure, the contractor shall also prescribe which critical or less critical material can be substituted without departing from, revising, or changing the original design and functioning of the subject item. No substitution of such material shall be permitted without prior written approval of the procuring activity.

3.1.2 Selection of materials.- Specifications and standards for all materials, parts, and Government certification and approval of processes and equipment, which are not specifically designated herein and which are necessary for the execution of this specification, shall be selected in accordance with ANA Bulletin No. 143.

3.2 Design and construction.-

3.2.1 General.- The cable cutter shall consist of an octagonal windplate with a formed-steel U-shaped body projecting from its center. The body shall contain a hardened steel cable cutting edge and a flat spring latch for holding the cable cutter on the cable. The cable cutter shall be fabricated in accordance with Standard MS26506.

3.2.2 Dimensions.- The cable cutter shall conform to the dimensions specified on Standard MS26506.

3.2.3 Performance.- The cable cutter shall be capable of cutting snarled or tangled 1/8-inch steel tow cable conforming to Specification MIL-C-1511 or MIL-C-5765, during aerial target towing operations.

3.3 Identification of product.- The cable cutter shall be marked for identification in accordance with Specification MIL-M-7911. The outer face of the octagonal plate shall contain the information presented below:

CUTTER, CABLE, AERIAL TOW TARGET, MK VII
Specification MIL-C-8614
Standard MS26506
Stock No. (USAF or Navy, as applicable)
Contract or Order No.
Manufacturer's name or trade-mark
US

3.4 Workmanship.- The workmanship shall conform with that required by the best commercial practice governing the quantity production of similar products.

4. SAMPLING, INSPECTION, AND TEST PROCEDURES

4.1 General.- All the tests required for the testing of cable cutters are classified as Inspection tests, for which necessary sampling techniques and methods of testing are specified in this section.

4.2 Tests.- No tests for the assembled cable cutter, other than the Physical characteristics test, (paragraph 4.3) shall be required unless deviations from the drawings indicated herein are requested by the contractor and approved by the procuring activity. If deviations are granted and incorporated, applicable tests shall be as specified by the procuring activity.

4.3 Physical characteristics test.- All cable cutters shall be subjected to a complete physical characteristics check at the contractor's plant by the Government Inspector to insure conformance with this specification and Standard MS26506 with respect to dimensions, materials, workmanship, and finish.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T10:42Z
Check the source to verify that this is the current version before use.

5. PREPARATION FOR DELIVERY

5.1 Application.- The requirements specified herein apply only to direct purchases by or direct shipments to the Government.

5.2 Preservation.- Each cable cutter shall be preserved in accordance with method I of Specification MIL-P-116, using a type P-1 preservative compound.

5.3 Packaging.- Each cable cutter shall be packaged in accordance with group I, type I, of Specification MIL-P-6064.

5.4 Packing.- Cable cutters shall be packed for overseas or domestic shipment, as applicable, in accordance with Specification MIL-P-6064. Twenty unit packages shall be contained within each shipping container.

5.5 Marking of shipments.- Interior packages and exterior shipping containers shall be marked in accordance with Standard MIL-STD-129. The nomenclature shall be as follows: Cutter, Cable, Aerial Tow Target, MK VII, Specification MIL-C-6614, Standard MS26506, Federal Stock No. * (if no FSN available, leave space therefor).

*Applicable data to be entered by the manufacturer.

6. NOTE.

6.1 Intended use.- The aerial tow target cable cutter is intended for use in flight during target towing operations when it becomes necessary or advisable to cut snarled or tangled tow cable at an appreciable distance from the towing airplane. If a target release or target becomes fouled or damaged, or if a snarl catcher is in use instead of a target release, it is necessary to sever the cable with the cable cutter in order to drop the target. The cable cutter travels down the tow cable and when it strikes an obstruction its cutting edge shears the cable, and the cable cutter drops off along with the other equipment. For best results, an airspeed of approximately 140 knots (IAS) should be maintained by the towing aircraft when using the cable cutting messenger.

6.2 Information required with bids.- Each bid shall be accompanied by a statement as to whether or not any exceptions are being taken to the requirements shown in the drawings and specifications. If exceptions are being taken or deviations are anticipated, alternative proposals shall be indicated in the statement and submitted therewith.

NOTICE: When Government drawings, specifications, or other data are used for any purpose other than in connection with a definitely related Government procurement operation, the United States Government thereby incurs no responsibility nor any obligation whatsoever; and the fact that the Government may have formulated, furnished, or in any way supplied the said drawings, specifications, or other data, is not to be regarded by implication or otherwise as in any manner licensing the holder or any other person or corporation, or conveying any rights or permission to manufacture, use, or sell any patented invention that may in any way be related thereto.

Custodians:
Navy - Bureau of Aeronautics
Air Force

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T10:42Z
Check the source to verify that this is the current version before use.

FOLD

DEPARTMENT OF THE NAVY

POSTAGE AND FEES PAID
NAVY DEPARTMENT

OFFICIAL BUSINESS

CHIEF, BUREAU OF NAVAL WEAPONS
ENGINEERING DIVISION
ATTN: CODE RREN-5
DEPARTMENT OF THE NAVY
WASHINGTON, D. C. 20360

FOLD

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T10:42Z
Check the source to verify that this is the current version before use.

SPECIFICATION ANALYSIS SHEET

Form Approved
Budget Bureau No. 119-R004

INSTRUCTIONS

This sheet is to be filled out by personnel either Government or contractor, involved in the use of the specification in procurement of products for ultimate use by the Department of Defense. This sheet is provided for obtaining information on the use of this specification which will insure that suitable products can be procured with a minimum amount of delay and at the least cost. Comments and the return of this form will be appreciated. Fold on lines on reverse side, staple in corner, and send to preparing activity *(as indicated on reverse hereof)*.

SPECIFICATION

ORGANIZATION *(Of submitter)* | CITY AND STATE

CONTRACT NO. | QUANTITY OF ITEMS PROCURED | DOLLAR AMOUNT $

MATERIAL PROCURED UNDER A

☐ DIRECT GOVERNMENT CONTRACT ☐ SUBCONTRACT

1. HAS ANY PART OF THE SPECIFICATION CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE?

A. GIVE PARAGRAPH NUMBER AND WORDING.

B. RECOMMENDATIONS FOR CORRECTING THE DEFICIENCIES.

2. COMMENTS ON ANY SPECIFICATION REQUIREMENT CONSIDERED TOO RIGID

3. IS THE SPECIFICATION RESTRICTIVE?

☐ YES ☐ NO IF "YES", IN WHAT WAY?

4. REMARKS *(Attach any pertinent data which may be of use in improving this specification. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity)*

SUBMITTED BY *(Printed or typed name and activity)* | DATE

DD FORM 1 APR 63 1426 REPLACES NAVSHIPS FORM 4863, WHICH IS OBSOLETE PLATE NO. 15419

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T10:42Z
Check the source to verify that this is the current version before use.