MIL-T-8619(Aer)
15 July 1953

MILITARY SPECIFICATION

TOWER; PARACHUTE DRYING

This specification has been approved by the Bureau of Aeronautics, Department of the Navy.

1. SCOPE AND CLASSIFICATION

1.1 Scope.- This specification covers one type of portable parachute drying tower.

2. APPLICABLE SPECIFICATIONS, OTHER PUBLICATIONS AND DRAWINGS

2.1 General.- The following specifications, publications and drawings of the issue in effect on the date of invitation for bids shall form a part of this specification.

SPECIFICATIONS

Military

MIL-A-140	Adhesive, Water Resistant, Waterproof Barrier - Material
JAN-P-105	Packaging and Packing for Overseas Shipment - Boxes, Wood, Cleated, Plywood
JAN-P-106	Packaging and Packing for Overseas Shipment - Boxes, Wood, Nailed
JAN-P-125	Packaging and Packing for Overseas Shipment - Barrier Materials, Waterproof, Flexible
JAN-P-139	Packaging and Packing for Overseas Shipment - Plywood, Container-Grade

Standards

MIL-STD-129	Marking of Shipments

DRAWINGS

Naval Aircraft Factory

501773	Parachute Drying Tower Assembly - Slip Joint Construction
605251	Frame - Structure Assembly - Parachute Drying Tower - Slip Joint Construction
605292	Cover Assembly - Parachute Drying Tower - Inner and Outer
605551	Crate, Packing - Parachute Drying Tower

2.2 Availability of Specifications, Publications and Drawings.-

2.2.1 When requesting specifications, publications, and drawings, refer to both title and number.

2.2.2 Copies of this specification and applicable specifications and drawings may be obtained upon application to the Commanding Officer, U.S. Naval Air Station, Johnsville, Pennsylvania, Attention: Technical Records Division.

2.2.3 Copies of the Navy Shipment Marking Handbook may be obtained upon application to the Bureau of Supplies and Accounts, Department of the Navy, Washington 25, D.C.

3. REQUIREMENTS

3.1 Materials.- Materials shall be as specified herein or as specified on applicable specifications and drawings. When materials are used which are not specifically designated, they shall be entirely suitable for the purpose intended.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T10:42Z
Check the source to verify that this is the current version before use.

3.1.1 AN or MS (Military Standard) Parts.- AN or MS parts shall be used wherever they are suitable for the purpose, and shall be identified on the drawing by their part numbers. Commercial utility parts such as screws, bolts, nuts, cotter pins, etc., may be used, provided they possess suitable properties and are replaceable by the AN or MS parts without alteration, and provided the corresponding AN or MS part numbers are referenced in the parts list and, if practicable, on the contractor's drawings. In the event there is no suitable corresponding AN or MS part in effect on date of invitation for bids, commercial parts may be used provided they conform to all requirements of this specification.

3.2 Design and Construction.- The parachute drying tower shall conform to NAF Drawing 501773. The tower shall consist essentially of a frame structure over which is supported two layers of canvas covering. Located at the bottom of the tower shall be a suitable opening to allow the entrance of a stream of warm air. The tower shall be capable of supporting parachutes suspended from pulleys at the top of the tower interior.

3.2.1 Frame.- The frame, conforming to Drawing No. 605251, shall be easily assembled or disassembled with the use of hand tools furnished with each drying tower.

3.2.2 Cover.- The tower frame cover shall consist of an inner and outer layer of canvas conforming in construction and material to Drawing No. 605292. The canvas layers shall be secured to the frame by means of a system of straps as shown on Drawing No. 605292. An inlet containing a butterfly valve shall be provided near the bottom of the tower cover to permit the injection and control of a warm air stream into the tower interior. A means for entering the drying tower shall be provided as shown on Drawing No. 605292.

3.2.2.1 Thermometer.- A thermometer, whose dial may be read on the outside of the drying tower, shall measure the temperature of the tower interior and shall be secured to the tower cover in accordance with Drawing No. 605292. The thermometer shall be calibrated from 25°F to 125°F.

3.3 Marking.- All markings shall be durable to withstand usage encountered in service.

3.3.1 Nameplate.- The outer canvas cover shall be legibly and permanently marked with the following information:

BUAER, U. S. NAVY
TOWER, PARACHUTE DRYING
Stock No.
NAF Part No. 501773-1
Contract No. _____ (or Order No. if Contract No. is not assigned)
Manufacturer's Serial No.
Manufacturer's Name or Trademark (omit address)

3.4 Accessories.- Furnished with each unassembled drying tower shall be a number of spare parts and hand tools to be used in the erection of the tower. These additional parts shall be in accordance with Drawing 501773 and furnished in quantities listed thereon.

3.5 Instructions.- The contractor shall furnish with each unassembled drying tower a printed copy of complete instructions for the erection and operation of the tower. The instructions shall be similar to those referred to on Drawing 501773.

3.6 Workmanship.- All details of workmanship shall be in accordance with high grade manufacturing practice covering this class of material.

4. SAMPLING, INSPECTION AND TEST PROCEDURES

4.1 General Policies and Instructions.-

4.1.1 Previous Approval.- Acceptance or approval of material during course of manufacture shall in no case be construed as a guaranty of the acceptance of the finished product.

4.1.2 Responsibility for Tests.- The contractor shall furnish all samples and shall be responsible for accomplishing the tests specified herein.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T10:42Z
Check the source to verify that this is the current version before use.

4.1.3 Supervision of Tests.- When inspection is conducted at the contractor's plant, all inspection and testing shall be under the supervision of the Inspector.

4.2 Sampling.-

4.2.1 Preproduction Test Samples.- Preproduction test samples shall consist of a completely assembled drying tower made up as a model of the towers to be made in production. Manufacture of any additional drying towers or parts on order shall be withheld until the preproduction model has received approval by the Bureau of Aeronautics.

4.2.2 Inspection Test Samples.- After approval of the preproduction test sample the Inspector shall select for inspection tests ten percent of the first lot of 50 towers on order or contract and two towers from each additional lot of 50 towers on the same order or contract.

4.3 Inspection.- Each drying tower on order shall be thoroughly examined to determine conformance to the dimensional and constructional requirement of the applicable manufacturing drawings and to any other requirements of this specification.

4.4 Tests.-

4.4.1 Preproduction Tests.- Preproduction testing is accomplished after an award of contract, on preproduction test samples which are representative of the production of the item, to determine that production meets all requirements of this specification including inspection test.

4.4.2 Inspection Test.- Inspection testing shall consist of the complete assembling of all inspection test sample towers. There shall be a proper fit between the members of the tower frame assembly and also of the tower cover when secured to the assembled tower frame.

4.5 Rejection and Retest.- Towers failing to meet the requirements of this specification shall be rejected. When one or more of the towers selected as representative of a certain lot fails to meet the requirements specified, the lot shall be rejected. Rejected towers shall not be resubmitted for inspection without furnishing full particulars, concerning previous rejection and measures taken to overcome the defects, to the Inspector.

5. PREPARATION FOR DELIVERY

5.1 Application.- The packaging, packing and marking requirements specified herein apply only to direct purchases by, or direct shipments to the Government.

5.2 Preservation.- No preservation is required.

5.3 Packaging.- The pipe and tubing sections, fittings and cable assemblies shall be grouped, prewrapped in heavy Kraft paper, and placed in the proper shipping container, as specified below, in a sequence so that parts needed first in the erection of the tower will be most accessible. Proper sequence shall be shown with the aid of numerical markings appearing on the "group packages." All parts other than tubing sections shall likewise be protected with Kraft paper wrapping prior to placement into the proper shipping container.

5.4 Packing.- Unless otherwise specified, all unassembled parachute drying towers, including accessories and spares, shall receive domestic packing. The unassembled parachute drying tower shall be distributed in one wooden container conforming to Drawing 605551. This wooden container shall include tubing, joints, cable assemblies, fabric parts, hold down stakes, guide lines, wood blocks, wrenches, sledge, butterfly valve, thermometer and spare parts.

5.4.1 Cushioning.- The contents of the shipping containers shall be secured by means of suitable internal framing, blocking, bracing, or cushioning so as to prevent movement of parts during shipment and storage, and in rough handling.

5.4.2 Domestic Packing.- Unless otherwise specified by the Procuring Activity, the wooden containers shall be so constructed to insure acceptance by common or other carrier for safe transportation at the lowest rate to the point of delivery. Except as specified herein, the container shall conform to the requirements of the Consolidated Freight Classification Rules in effect at the time of shipment. Containers shall be able to withstand storage, rehandling and reshipment without the necessity of repacking.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T10:42Z
Check the source to verify that this is the current version before use.

5.4.3 Overseas Packing.- Unless otherwise specified by the Procuring Activity, the unassembled parachute drying tower components shall be enclosed in containers conforming to Specification JAN-P-105 or JAN-P-106. Plywood, if used, shall be Type A or B, Condition I of Specification JAN-P-139. A sealed waterproof case-liner fabricated from materials conforming to Specification JAN-P-125, shall be used. The seams of the case-liner shall be sealed with adhesive conforming to Specification MIL-A-140.

5.5 Marking of Shipments.- Each container shall be durably and legibly marked in accordance with Standard MIL-STD-129. The nomenclature shall be as follows: Tower, Parachute Drying, Specification MIL-T-8619(Aer), NAF Assembly Part No. 501773-1.

6. NOTES

6.1 Intended Use.- Drying towers covered by this specification are intended to be used for drying all types of service parachutes.

6.2 Ordering Data.- Requisitions, contracts and orders shall state the quantity of drying towers required and whether overseas packing is desired (see Section 5).

NOTICE: When Government drawings, specifications, or other data are used for any purpose other than in connection with a definitely related Government procurement operation, the United States Government thereby incurs no responsibility nor any obligation whatsoever; and the fact that the Government may have formulated, furnished, or in any way supplied the said drawings, specifications, or other data is not to be regarded by implication or otherwise as in any manner licensing the holder or any other person or corporation, or conveying any rights or permission to manufacture, use, or sell any patented invention that may in any way be related thereto.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T10:42Z
Check the source to verify that this is the current version before use.

SPECIFICATION ANALYSIS SHEET

Form Approved
Budget Bureau No. 119-R004

INSTRUCTIONS

This sheet is to be filled out by personnel either Government or contractor involved in the use of the specification in procurement of products for ultimate use by the Department of Defense. This sheet is provided for obtaining information on the use of this specification which will insure that suitable products can be procured with a minimum amount of delay and at the least cost. Comments and the return of this form will be appreciated. Fold on lines on reverse side, staple in corner and send to preparing activity (as indicated on reverse hereof).

SPECIFICATION

ORGANIZATION (Of submitter)	CITY AND STATE

CONTRACT NO.	QUANTITY OF ITEMS PROCURED	DOLLAR AMOUNT
		$

MATERIAL PROCURED UNDER A

☐ DIRECT GOVERNMENT CONTRACT ☐ SUBCONTRACT

1. HAS ANY PART OF THE SPECIFICATION CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE?

A. GIVE PARAGRAPH NUMBER AND WORDING.

B. RECOMMENDATIONS FOR CORRECTING THE DEFICIENCIES.

2. COMMENTS ON ANY SPECIFICATION REQUIREMENT CONSIDERED TOO RIGID

3. IS THE SPECIFICATION RESTRICTIVE?

☐ YES ☐ NO IF "YES", IN WHAT WAY?

4. REMARKS (Attach any pertinent data which may be of use in improving this specification. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity)

SUBMITTED BY (Printed or typed name and activity)	DATE

DD, FORM 1 APR 63 1426 REPLACES NAVSHIPS FORM 4863, WHICH IS OBSOLETE C-8279

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T10:42Z
Check the source to verify that this is the current version before use.

FOLD

DEPARTMENT OF THE NAVY

POSTAGE AND FEES PAID
NAVY DEPARTMENT

OFFICIAL BUSINESS

CHIEF, BUREAU OF NAVAL WEAPONS
ENGINEERING DIVISION
ATTN: CODE RREN-5
DEPARTMENT OF THE NAVY
WASHINGTON, D. C. 20360

FOLD

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T10:42Z
Check the source to verify that this is the current version before use.