(METRIC)
A-A-156C
June 21, 1995
SUPERSEDING
A-A-156B
December 7, 1983

COMMERCIAL ITEM DESCRIPTION

BAG, PAPER (HARDWARE)

This Commercial Item Description has been approved by the General Services Administration/Federal Supply Service.

1. Scope. This description covers the requirements for self-opening paper bags of the sizes and weights of paper stock indicated in Table I.

2. Salient characteristics.

2.1. Construction.

The paper for hardware bags shall be kraft conforming to the applicable requirements in Table I herein. The seams shall bond the paper together throughout their area. The bags shall be supplied in the dimensions specified in Table I, with the tolerance of 6.4 mm (± 1/4") for face width and tuck width. The tolerance for bag length shall + unlimited, - 6.4 mm (1/4"). The bags, unless otherwise specified, shall be imprinted with the appropriate bag number, as shown in Table I, as part of the manufacturer's trademark or imprint.

Beneficial comments, recommendations, additions, deletions, clarifications, etc. and any data which may improve this document, should be sent to: General Services Administration, Federal Supply Service, 26 Federal Plaza, New York N.Y. 10278 ATTN: Engineering Branch (2FYEE).

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:05Z
Check the source to verify that this is the current version before use.

2.2. Physical requirements. Bags shall meet or exceed the physical requirements as specified in Table I:

Table I

Bag number	3	5	10	16	20	25
Basis weight [±5%] g/m^2 (lb, 24"x36"-500)	82 (50)	82 (50)	98 (60)	98 (60)	98 (60)	98 (60)
Bursting strength (minimum,points)	29	29	36	36	36	36
Tearing resistance, (MD,minimum,grams)	86	86	110	110	110	110
Face width, mm (inches)	120 (4-3/4)	127 (5)	159 (6-1/4)	208 (8-3/16)	208 (8-3/16)	208 (8-3/16)
Tuck width, mm (inches)	70 (2-3/4)	79 (3-1/8)	98 (3-7/8)	137 (5-3/8)	137 (5-3/8)	137 (5-3/8)
Bag length, mm (inches)	200 (7-7/8)	222 (8-3/4)	267 (10-1/2)	283 (11-1/8)	313 (12-5/16)	337 (13-1/4)

Basis weight, bursting strength, and tear resistance shall be determined in accordance with TAPPI methods T-410, T-403, and T-414, respectively.

2.3. Workmanship. Hardware bags shall be uniformly constructed, free from holes, tears, cuts, splits, or defects which might impair their appearance or serviceability.

3. Quality assurance:

3.1. Certification. The contractor shall certify and maintain substantiating evidence that the product offered meets the requirements of this Commercial Item Description/Specification, and that the product conforms to the producer's own drawings, specifications, standards, and quality assurance practices. The government reserves the right to require proof of such conformance prior to the first delivery and thereafter as may be otherwise provided for under the provisions of the contract.

3.2. Suppliers are encouraged to use quality control (QC) techniques that exhibit control over their processes, e.g. (Statistical Process Control SPC techniques), as defined in American National Standards Institute (ANSI) Z1.1, Z1.2 and Z1.3/American Society for Quality Control (ASQC) B.1, B.2 and B.3 that systematically reduce excess variations. Objective evidence shall be available that demonstrates overall measurement adequacy techniques and controls. These techniques will ensure quality levels equal to, or greater than, those cited in applicable technical document, or, herein.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:05Z
Check the source to verify that this is the current version before use.

End item inspection/testing may be used by the offeror or the Government representative, as a means to determine the effectiveness of the in process quality controls. In process controls shall not be substituted for end item performance testing.

For those characteristics for which there are no such controls, or for end item performance test, lot by lot sampling for inspection/test shall be required. Sampling shall be in accordance with (ANSI)/(ASQC) Z1.4. An inspection lot shall consist of all bags manufactured by the same process from the same components at the same time. The sample unit shall be one bag. The inspection level shall be S-2 with an AQL of 4.0 % defective for construction, dimensions, physical requirements and workmanship. The inspection level shall be S-1 with an AQL of 2.5 % defective for physical requirements.

The supplier must provide objective evidence (tests and inspection records) that the presented material meets the requirements of the sampling plan as indicated above.

4. Regulatory requirements. The contractor shall certify that the product offered shall include a minimum of 5% post-consumer recovered material, in accordance with Paragraph 23.403 of the Federal Acquisition Regulation (FAR). The Government reserves the right to require proof of such conformance prior to first delivery and thereafter as may be otherwise provided for under the provisions of the contract.

5. Packaging, Packing, and Marking: Shall be as specified in the contract or purchase order.

6. Referenced documents: The issues of the referenced documents in effect on the date of the solicitation for offers or request for proposals shall be used to determine conformance with the requirements of this Commercial Item Description.

6.1. Federal Regulations.

Federal Acquisition Regulation. Paragraph 23.403

Copies of the U.S. Code may be obtained through the Congressional Sales Office, U.S. Government Printing Office, Washington D.C., 20402.

6.2. Other publications.

ANSI/ASQC Z1.4 - American National Standards Institute (ANSI)/ American Society for Quality Control (ASQC), Sampling Procedures and Tables for Inspection by Attributes.

Available from: American Society for Quality Control, P.O. Box 3005, 611 E. Wisconsin Avenue, Milwaukee, WI 53201 4606.

6.3. TAPPI test methods are available from the Technical Association of the Pulp and Paper Industry, Technology Park, P.O. Box 105113, Atlanta, GA 30348.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:05Z
Check the source to verify that this is the current version before use.

7. Ordering data. Purchasers shall specify the following in the contract or purchase order.

(a). Title, number and date of this Commercial Item Description.
(b). Number and dimensions of the bag.
(c). Packaging, packing, and marking required.

MILITARY INTEREST:

NONE REGISTERED

PREPARING ACTIVITY:

GSA-FSS

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:05Z
Check the source to verify that this is the current version before use.