[METRIC]
A-A-1681B
February 22, 1994
SUPERSEDING
A-A-1681A
December 31, 1992

COMMERCIAL ITEM DESCRIPTION

VIEWER-PRINTER, PROJECTION, PHOTOGRAPHIC (READER/PRINTER, MICROFICHE)

The General Services Administration has authorized the use of this commercial item description.

This commercial item description covers desk top or console type reader/printers that will accommodate microfiche formats of 1:24 source document and COM format, and 1:42 and 1:48 COM format. They shall be of the following types, classes, groups and styles, as specified.

Type I - Electrostatic Printing
- Class 1 - Wet process with photoconductor coated paper and liquid toner.
- Class 2 - Dry process with plain paper and dry toner.
- Class 3 - Dry process with photoconductor coated paper and dry toner.

Style A - Single lens holder with 24x lens.
Style B - Single lens holder with 32x lens.
Style C - Single lens holder with 36X lens.
Style D - Dual lens holder with 24X and 32X lenses.
Style E - Dual lens holder with 24X and 36X lenses.
Style F - Dual lens holder with 24X and 42X lenses.
Style G - Dual lens holder with 24X and 48X lenses.
Style H - Single lens holder with 32X lens and an extra 24X interchangeable lens.
Style J - Single lens holder with 36X lens and an extra 24X interchangeable lens.

Salient characteristics.

General. Shall be designed specifically for desk top or console type use.

Unacceptable features. Portable readers characterized by features such as light weight, handles for transporting, battery operation, collapsible design, integral or separate carrying case, etc.

DISTRIBUTION STATEMENT A: Approved for public release; distribution is unlimited.

FSC 6730

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:15Z
Check the source to verify that this is the current version before use.

Lens interchangeability. Lens shall be operator interchangeable and easily installed.

Lamp. Rated average life of the lamp shall be not less than 500 hours and shall be easily accessible and replaceable without special tools.

Electrical characteristics. Machine shall operate on 120 volts, 60 Hz.

Power cord. The power cord shall be at least 1.8 meters (6 feet) long.

Frame format.
Lens magnification of 24X, the reader shall display no less than one frame of 98 frame format, vertically on the screen.
Lens magnifications of between 29X - 32X; 32.5X - 37X, respectively are all acceptable, provided the projected image is confined within available screen area and printed image is complete within the boundaries of the cut sheet of paper. The reader shall display no less than one frame of 208/270 frame format, vertically on the screen.

Zoom lens. A zoom lens with magnification ranges of 24X - 32X (Style D) and 24X -37X (Style E) may be substituted for the dual lens holder and lenses provided the projected and printed images meet the same aforementioned criteria.

Indexing system. The reader shall have a separate indexing system for 1:24 source document and COM fiche, and 1:42 and 1:48 COM fiche, as applicable.

Image rotation. 360 degree image rotation shall be available, as specified:

1) by carrier on single lens unit.
2) by carrier on dual lens unit.
3) on low magnification lens.
4) on high magnification lens.
5) on both high and low magnification lenses of the same unit.

Note: If image rotation system employed is by single carrier and the use of a double carrier automatically deletes the image rotation feature, indicate same by stating that image rotation is not available on a single lens and a dual lens unit with dual carrier. However, if the image rotation feature is not deleted from the dual carrier models (single and dual lenses) then there is no need for the aforementioned statement.

Paper size. Printers shall be either roll or sheet-fed. The rolls shall be at least 45.7 meters (150 feet) long.

Source: https://assist.dla.mil -- Downloaded: 202640-26T08:15Z
Check the source to verify that this is the current version before use.

Hopper. Hopper for sheet-fed units shall hold at least 100 sheets.

Paper handling. The unit shall be equipped to automatically move the paper from the print storage area through processing and deliver a finished print to the operator.

Exposure control. An exposure control with several settings shall be provided to produce optimum quality prints.

Blowback. The complete image of the print shall be a blowback of at least 69% of the 1:42, 67% of the 1:48 and 91% of the 1:24 microimages, respectively, as applicable.

Light shield. Front screen readers shall have light-absorbing black on all non-optical surfaces surrounding the screen. Rear screen shall have a fixed or detachable ambient light shield.

Glass flats. Automatic separating glass flats that accept either a standard 105mm x 148mm microfiche for a single fiche or two standard 105mm x 148mm microfiches will be supplied, as specified.

Indexing. Readers shall have a separate indexing system for 1:24 source document and COM fiche, 1:42 COM fiche, and 1:48 COM fiche as applicable.

Screen image. The screen shall indicate clearly the portion of the image that will be printed.

Print image. The print image shall be right reading and be positive (black image on white background) from negative fiche input of 4 to 9 mils thick.

Exposed print. The exposed and processed print shall be a reproduction of the image projected on the viewing surface. All data so projected must be legible and readable on the print. Image rotation shall be provided as necessary to meet this requirement.

Bi-modal feature. When specified, the printer shall be equipped with a bi-modal feature which will produce a positive print (black image on white background) from both a negative fiche input and a positive fiche input using a push-button or switch selection and appropriate toner or bi-modal kit or cartridge.

Masking. When specified, a masking feature or partial print feature shall be supplied. This will enable user to control the print area for print border removal or for a partial print size, consisting of many lines to as few as two lines.

Print preparation. Prints shall be prepared by a wet or dry process which may be electrostatic or thermal, as specified. Any

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:15Z
Check the source to verify that this is the current version before use.

surface dampness shall evaporate within a few seconds, after which it shall be possible to write on the print with pencil or pen.

Print time.
Type I - 18 seconds, max.

Operating temperature. Operating temperature shall be reached in less than 5 minutes.

Controls. Focus, tone and other operating or adjustment controls shall be readily accessible and identifiable.

Warning. Conspicuous warning signs shall be placed on or adjacent to areas or parts that may be of high voltage or other hazardous conditions.

Instruction. An instruction manual or card shall be furnished.

Accessories. A cleaning kit and appropriate dust cover shall be furnished with each unit.

Workmanship. The machine, including all parts and accessories shall be fabricated and finished in accordance with good workmanship standards and the machine shall be free from any defect which affects the appearance, durability or serviceability or which might cause personal injury.

Conformance. Shall provide acceptable proof of conformance with the requirements of the applicable safety standard(s) for the product by an organization approved by the Occupational Safety and Health Administration (OSHA) as a "Nationally Recognized Testing Laboratory" (NRTL). Acceptable proof of conformance includes a labelling, listing or certification of the product by an NRTL.

Quality Assurance Provisions

Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection and test requirements specified herein. Failure to meet all provisions of the requirements as specified, shall provide reason for rejection.

Regulatory requirements. In accordance with section 23.403 of the Federal Acquisition Regulations, the Government's policy is to acquire items composed of the highest percentage of recovered materials practicable, consistent with maintaining a satisfactory level of competition without adversely affecting performance requirements or exposing the supplier's employees to undue hazards from the recovered materials.

Source: https://assist.dla.mil -- Downloaded: 202610-26T08:15Z
Check the source to verify that this is the current version before use.

Metric products. Products manufactured to metric dimensions will be considered on an equal basis with those manufactured using inch-pound units, provided they fall within specified tolerances using conversion tables contained in the latest revision of FED-STD-376, and all other requirements of this Commercial Description are met.

If a product is manufactured to metric dimensions and those dimensions exceed the tolerances specified in the inch-pound units, a request shall be made to the contracting officer to determine if the product is acceptable.

The contracting officer has the option of accepting or rejecting the product.

Preservation, packaging, packing, labeling and marking. The preservation, packaging, packing, labeling and marking shall be as specified in the contract or purchase order.

Notes: Purchaser shall specify type, class, style and if applicable, group, bi-modal feature, dual carrier and image rotation.

Copies of FED-STD-376 may be obtained from the General Services Administration, Specifications Section (3 FBP-W), Suite 8100, 490 L'Enfant Plaza, SW, Washington, DC 20407.

PREPARING ACTIVITY

GSA - FSS

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:15Z
Check the source to verify that this is the current version before use.